HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: HALLIBURTON WELD A RESIN

Revision Date: 16-May-2013

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE

COMPANY/UNDERTAKING

Statement of Hazardous Nature Hazardous according to the criteria of NOHSC, Non-Dangerous Goods according to

the criteria of ADG.

Manufacturer/Supplier Halliburton Australia Pty. Ltd.

15 Marriott Road

Jandakot WA 6164 Australia

ACN Number: 009 000 775

Telephone Number: 61 (08) 9455 8300 Fax Number: 61 (08) 9455 5300

Product Emergency Telephone

Australia: 08-64244950

Papua New Guinea: 05 1 281 575 5000

NewZealand: 06-7559274

Fire, Police & Ambulance - Emergency Telephone

Australia: 000

Papua New Guinea: 000 New Zealand: 111

Identification of Substances or Preparation

Product Trade Name: HALLIBURTON WELD A RESIN

Synonyms: None
Chemical Family: Blend
UN Number: None
Dangerous Goods Class: None
Subsidiary Risk: None

Hazchem Code: None Allocated

Poisons Schedule: S5
Application: Resin

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	Australia NOHSC	New Zealand WES	ACGIH TLV-TWA
Aluminum	7429-90-5	30 - 60%	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 10 mg/m ³	TWA: 1 mg/m ³

2. COMPOSITION/INFORMATION ON INGREDIENTS								
Bisphenol A / Epichlorohydrin resin	25068-38-6	30 - 60%	Not applicable	Not applicable	Not applicable			
Calcium carbonate	471-34-1	10 - 30%	TWA: 10 mg/m ³	TWA: 10 mg/m ³	10 mg/m ³			
Butyl glycidyl ether	2426-08-6	1 - 5%	TWA: 25 ppm TWA: 133 mg/m ³	TWA: 25 ppm TWA: 133 mg/m ³	TWA: 3 ppm			
Crystalline silica, quartz	14808-60-7	0 - 1%	TWA: 0.1 mg/m ³	TWA: 0.2 mg/m ³	TWA: 0.025 mg/m ³			

Non-Hazardous Substance to Total of 100%

3. HAZARDS IDENTIFICATION

Hazard Overview

CAUTION! - ACUTE HEALTH HAZARD

May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May cause allergic skin reaction. May be harmful if swallowed.

DANGER! - CHRONIC HEALTH HAZARD

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Review the Material Safety Data Sheet (MSDS) for this product, which has been provided to your employer.

Risk Phrases

R43 May cause sensitization by skin contact.

R49 May cause cancer by inhalation. R68 Possible risk of irreversible effects. R36/38 Irritating to eyes and skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

HSNO Classification

6.3B Mildly irritating to the skin 6.4A Irritating to the eye 6.5B Contact sensitisers 6.6B Human mutagens 6.7A Known or presumed human carcinogens 6.8B Human reproductive or developmental toxicants 6.9B Harmful to human target organs or systems 9.1B Ecotoxic in the aquatic environment

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably

mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Wash with soap and water. Get medical attention if irritation persists.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water

for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek

medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Not Applicable

FIRE FIGHTING MEASURES

Suitable Extinguishing Media Carbon dioxide, dry chemical, foam.

not be used for safety reasons

Extinguishing media which must Water must not be used with open containers.

Special Exposure Hazards

Decomposition in fire may produce toxic gases. Contact with strong oxidizers may produce explosive mixtures. Hydrogen gas may be released on contact with

moisture, acids or alkalis.

Fire-Fighters

Special Protective Equipment for Full protective clothing and approved self-contained breathing apparatus required for

fire fighting personnel.

ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Avoid creating and breathing dust.

Environmental Precautionary

Measures

Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning /

Absorption

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate

methods for collection, storage and disposal.

HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Wash hands after use. Launder

> contaminated clothing before reuse. This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is

slippery when wet.

Storage Information Store away from acids. Store away from alkalis. Store away from oxidizers. Store in a

cool well ventilated area. Keep container closed when not in use. Store locked up. Use good housekeeping in storage and work areas to prevent accumulation of dust.

Close container when not in use.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use approved industrial ventilation and local exhaust as required to maintain

exposures below applicable exposure limits.

Respiratory Protection Wear a NIOSH certified, European Standard EN 149 (FFP2/FFP3), or equivalent

respirator when using this product.

Hand Protection Impervious rubber gloves. Nitrile gloves. Neoprene gloves. Butyl rubber gloves.

Wear clothing appropriate for the work environment. Dusty clothing should be Skin Protection

laundered before reuse. Use precautionary measures to avoid creating dust when

removing or laundering clothing.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid Color: Gray

Odor: Aromatic hydrocarbon

pH: Not Determined

Specific Gravity @ 20 C (Water=1): 1.81

Not Determined Density @ 20 C (kg/l): Bulk Density @ 20 C (kg/m³): Not Determined **Boiling Point/Range (C):** Not Determined Not Determined Freezing Point/Range (C): Pour Point/Range (C): Not Determined

Flash Point/Range (C): 93 **PMCC** Flash Point Method:

Autoignition Temperature (C): Not Determined Flammability Limits in Air - Lower (g/m³): Not Determined Flammability Limits in Air - Lower (%): Not Determined Flammability Limits in Air - Upper (g/m³): Not Determined Flammability Limits in Air - Upper (%): Not Determined Vapor Pressure @ 20 C (mmHg): Not Determined

Vapor Density (Air=1): >1 **Percent Volatiles:**

Evaporation Rate (Butyl Acetate=1): Not Determined Solubility in Water (g/100ml): Insoluble Not Determined Solubility in Solvents (g/100ml): Not Determined VOCs (g/l): Viscosity, Dynamic @ 20 C (centipoise): Not Determined

Viscosity, Kinematic @ 20 C (centistokes): Not Determined Partition Coefficient/n-Octanol/Water: Not Determined Molecular Weight (g/mole): Not Determined **Decomposition Temperature (C):** Not Determined

10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

Conditions to Avoid None anticipated

Incompatibility (Materials to

Avoid)

Strong oxidizers. Strong acids. Strong alkalis.

Hazardous Decomposition

Products

Hydrogen chloride. Aldehydes. Aluminum fumes. Butyl glycidyl ether. Carbon monoxide and carbon dioxide. Amorphous silica may transform at elevated

temperatures to tridymite (870 C) or cristobalite (1470 C).

Additional Guidelines Not Applicable

TOXICOLOGICAL INFORMATION 11.

Principle Route of Exposure Eye or skin contact, inhalation.

Sympotoms related to exposure

Inhalation

May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

Skin Contact May cause skin irritation. May cause an allergic skin reaction.

Eye Contact May cause eye irritation.

Ingestion Irritation of the mouth, throat, and stomach.

Aggravated Medical Conditions Individuals with respiratory disease, including but not limited to asthma and

bronchitis, or subject to eye irritation, should not be exposed to quartz dust.

Chronic Effects/Carcinogenicity

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

Other Information

For further information consult "Adverse Effects of Crystalline Silica Exposure" published by the American Thoracic Society Medical Section of the American Lung Association, American Journal of Respiratory and Critical Care Medicine, Volume 155, pages 761-768 (1997).

Toxicity Tests

Oral Toxicity: Not determined

Dermal Toxicity: Not determined

Inhalation Toxicity: Not determined

Primary Irritation Effect: Not determined

HALLIBURTON WELD A RESIN Page 5 of 7 Carcinogenicity Not determined

Genotoxicity: Not determined

Reproductive /

Not determined

Developmental Toxicity:

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability Not determined

Bio-accumulation Not determined

Ecotoxicological Information

Acute Fish Toxicity: Not determined Acute Crustaceans Toxicity: Not determined Acute Algae Toxicity: Not determined

Chemical Fate Information Not determined

Other Information Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal MethodDisposal should be made in accordance with federal, state, and local regulations.

Incineration recommended in approved incinerator according to federal, state, and local regulations. Substance should NOT be deposited into a sewage facility.

Contaminated Packaging Follow all applicable national or local regulations. Contaminated packaging may be

disposed of by: rendering packaging incapable of containing any substance, or treating packaging to remove residual contents, or treating packaging to make sure the residual contents are no longer hazardous, or by disposing of packaging into

commercial waste collection.

14. TRANSPORT INFORMATION

Land Transportation

ADR

Not restricted

Air Transportation

ICAO/IATA

Not restricted

Sea Transportation

IMDG

Not restricted

Other Transportation Information

Labels: None

REGULATORY INFORMATION

Chemical Inventories

Australian AICS Inventory New Zealand Inventory of

Chemicals

US TSCA Inventory EINECS Inventory

All components listed on inventory or are exempt. All components listed on inventory or are exempt.

All components listed on inventory or are exempt.

This product, and all its components, complies with EINECS

Classification Т - Toxic.

Χi - Irritant.

- Dangerous For The Environment. N

Risk Phrases R43 May cause sensitization by skin contact.

> R49 May cause cancer by inhalation. R68 Possible risk of irreversible effects. R36/38 Irritating to eyes and skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety Phrases S2 Keep out of reach of children.

S28 After contact with skin, wash immediately with plenty of water

S61 Avoid release to the environment. Refer to special instructions/Safety data

sheets

S37/39 Wear suitable gloves and eye/face protection.

OTHER INFORMATION 16.

The following sections have been revised since the last issue of this SDS

Not applicable

Contact

Australian Poisons Information Centre

24 Hour Service: - 13 11 26

Police or Fire Brigade: - 000 (exchange): - 1100

New Zealand National Poisons Centre

0800 764 766

Additional Information For additional information on the use of this product, contact your local Halliburton

representative.

For questions about the Safety Data Sheet for this or other Halliburton products,

contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement This information is furnished without warranty, expressed or implied, as to accuracy

or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of

the user.

END OF MSDS

HALLIBURTON WELD A RESIN Page 7 of 7