# **HALLIBURTON**

# **MATERIAL SAFETY DATA SHEET**

Product Trade Name: HALLIBURTON WELD A RESIN

Revision Date: 16-May-2013

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: HALLIBURTON WELD A RESIN

Synonyms: None Chemical Family: Blend Application: Resin

Manufacturer/Supplier Halliburton Energy Services

P.O. Box 1431

Duncan, Oklahoma 73536-0431

Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Aluminum	7429-90-5	30 - 60%	TWA: 1 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>
Bisphenol A / Epichlorohydrin	25068-38-6	30 - 60%	Not applicable	Not applicable
resin				
Calcium carbonate	471-34-1	10 - 30%	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>
Butyl glycidyl ether	2426-08-6	1 - 5%	TWA: 3 ppm	50 ppm
Crystalline silica, quartz	14808-60-7	0 - 1%	TWA: 0.025 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
				%SiO2 + 2

#### 3. HAZARDS IDENTIFICATION

Hazard Overview CAUTION! - ACUTE HEALTH HAZARD

May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May cause allergic skin reaction. May be harmful if swallowed.

**DANGER! - CHRONIC HEALTH HAZARD** 

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Review the Material Safety Data Sheet (MSDS) for this product, which has been provided to your employer.

# **FIRST AID MEASURES**

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably

mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Wash with soap and water. Get medical attention if irritation persists.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water

for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek

medical attention. Never give anything by mouth to an unconscious person.

**Notes to Physician** Not Applicable

# FIRE FIGHTING MEASURES

200 Flash Point/Range (F): Flash Point/Range (C): 93 **PMCC** Flash Point Method:

**Autoignition Temperature (F):** Not Determined **Autoignition Temperature (C):** Not Determined Flammability Limits in Air - Lower (%): Not Determined Not Determined Flammability Limits in Air - Upper (%):

Fire Extinguishing Media Carbon Dioxide, Dry Chemicals, Foam.

**Special Exposure Hazards** Decomposition in fire may produce toxic gases. Contact with strong oxidizers may

produce explosive mixtures. Hydrogen gas may be released on contact with

moisture, acids or alkalis.

Fire-Fighters

Special Protective Equipment for Full protective clothing and approved self-contained breathing apparatus required for

fire fighting personnel.

**NFPA Ratings:** Health 1, Flammability 1, Reactivity 0 **HMIS Ratings:** Health 1\*, Flammability 1, Reactivity 0

# ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Avoid creating and breathing dust.

**Environmental Precautionary** 

Measures

Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning /

**Absorption** 

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate

methods for collection, storage and disposal.

#### HANDLING AND STORAGE

**Handling Precautions** Avoid contact with eyes, skin, or clothing. Wash hands after use. Launder

contaminated clothing before reuse. This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is

slippery when wet.

# **Storage Information**

Store away from acids. Store away from alkalis. Store away from oxidizers. Store in a cool well ventilated area. Keep container closed when not in use. Store locked up. Use good housekeeping in storage and work areas to prevent accumulation of dust.

Close container when not in use.

# **EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Engineering Controls** Use approved industrial ventilation and local exhaust as required to maintain

exposures below applicable exposure limits.

**Respiratory Protection** Wear a NIOSH certified, European Standard EN 149 (FFP2/FFP3), or equivalent

respirator when using this product.

**Hand Protection** Impervious rubber gloves. Nitrile gloves. Neoprene gloves. Butyl rubber gloves.

Wear clothing appropriate for the work environment. Dusty clothing should be **Skin Protection** 

laundered before reuse. Use precautionary measures to avoid creating dust when

removing or laundering clothing.

Chemical goggles; also wear a face shield if splashing hazard exists. **Eye Protection** 

**Other Precautions** Eyewash fountains and safety showers must be easily accessible.

# PHYSICAL AND CHEMICAL PROPERTIES

Solid **Physical State:** Color: Gray

Odor: Aromatic hydrocarbon

pH: Not Determined

1.81 Specific Gravity @ 20 C (Water=1):

Density @ 20 C (lbs./gallon): Not Determined

Bulk Density @ 20 C (lbs/ft3): 15.1

**Boiling Point/Range (F):** Not Determined **Boiling Point/Range (C):** Not Determined Not Determined Freezing Point/Range (F): Freezing Point/Range (C): Not Determined Vapor Pressure @ 20 C (mmHg): Not Determined

Vapor Density (Air=1): >1 0 **Percent Volatiles:** 

Not Determined **Evaporation Rate (Butyl Acetate=1):** Insoluble

Solubility in Water (g/100ml):

Solubility in Solvents (g/100ml): Not Determined VOCs (lbs./gallon): Not Determined Viscosity, Dynamic @ 20 C (centipoise): Not Determined Viscosity, Kinematic @ 20 C (centistokes): Not Determined **Partition Coefficient/n-Octanol/Water:** Not Determined Molecular Weight (g/mole): Not Determined

# 10. STABILITY AND REACTIVITY

**Stability Data:** Stable

**Hazardous Polymerization:** Will Not Occur

**Conditions to Avoid** None anticipated

Incompatibility (Materials to

Avoid)

Strong oxidizers. Strong acids. Strong alkalis.

HALLIBURTON WELD A RESIN Page 3 of 7

**Hazardous Decomposition** 

**Products** 

Hydrogen chloride. Aldehydes. Aluminum fumes. Butyl glycidyl ether. Carbon monoxide and carbon dioxide. Amorphous silica may transform at elevated

temperatures to tridymite (870 C) or cristobalite (1470 C).

Additional Guidelines

Not Applicable

## 11. TOXICOLOGICAL INFORMATION

**Principle Route of Exposure** 

Eye or skin contact, inhalation.

Sympotoms related to exposure Inhalation

May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

**Skin Contact** 

May cause skin irritation. May cause an allergic skin reaction.

**Eye Contact** 

May cause eye irritation.

Ingestion

Irritation of the mouth, throat, and stomach.

**Aggravated Medical Conditions** 

Individuals with respiratory disease, including but not limited to asthma and bronchitis, or subject to eye irritation, should not be exposed to guartz dust.

**Chronic Effects/Carcinogenicity** 

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

Other Information For further information consult "Adverse Effects of Crystalline Silica Exposure"

published by the American Thoracic Society Medical Section of the American Lung Association, American Journal of Respiratory and Critical Care Medicine, Volume

155, pages 761-768 (1997).

**Toxicity Tests** 

Oral Toxicity: Not determined

**Dermal Toxicity:** Not determined

Inhalation Toxicity: Not determined

**Primary Irritation Effect:** Not determined

Carcinogenicity Not determined

Genotoxicity: Not determined

Reproductive /

**Developmental Toxicity:** 

Not determined

#### 12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability Not determined

Bio-accumulation Not determined

# **Ecotoxicological Information**

Acute Fish Toxicity: Not determined Acute Crustaceans Toxicity: Not determined Acute Algae Toxicity: Not determined

Chemical Fate Information Not determined

Other Information Not applicable

# 13. DISPOSAL CONSIDERATIONS

**Disposal Method**Disposal should be made in accordance with federal, state, and local regulations.

Incineration recommended in approved incinerator according to federal, state, and local regulations. Substance should NOT be deposited into a sewage facility.

**Contaminated Packaging** Follow all applicable national or local regulations. Contaminated packaging may be

disposed of by: rendering packaging incapable of containing any substance, or treating packaging to remove residual contents, or treating packaging to make sure the residual contents are no longer hazardous, or by disposing of packaging into

commercial waste collection.

# 14. TRANSPORT INFORMATION

# **Land Transportation**

DOT

Not restricted

HALLIBURTON WELD A RESIN Page 5 of 7

#### **Canadian TDG**

Not restricted

**ADR** 

Not restricted

# **Air Transportation**

ICAO/IATA

Not restricted

# Sea Transportation

**IMDG** 

Not restricted

# Other Transportation Information

Labels: None

#### REGULATORY INFORMATION

#### **US Regulations**

**US TSCA Inventory** All components listed on inventory or are exempt.

**EPA SARA Title III Extremely** 

**Hazardous Substances** 

Not applicable

**EPA SARA (311,312) Hazard** 

Class

Acute Health Hazard Chronic Health Hazard

This product contains toxic chemical(s) listed below which is(are) subject to the **EPA SARA (313) Chemicals** 

reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372:

Aluminum//7429-90-5

**EPA CERCLA/Superfund Reportable Spill Quantity** 

MA Right-to-Know Law

Not applicable.

**EPA RCRA Hazardous Waste** 

Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste as

defined by the US EPA.

The California Proposition 65 regulations apply to this product. **California Proposition 65** 

NJ Right-to-Know Law One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

**Canadian DSL Inventory** All components listed on inventory or are exempt.

**WHMIS Hazard Class** D2B Toxic Materials

D2A Very Toxic Materials

One or more components listed.

Crystalline silica

HALLIBURTON WELD A RESIN Page 6 of 7

# 16. OTHER INFORMATION

# The following sections have been revised since the last issue of this SDS Not applicable

**Additional Information** 

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products,

contact Chemical Compliance at 1-580-251-4335.

**Disclaimer Statement**This information is furnished without warranty, expressed or implied, as to accuracy

or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of

the user.

\*\*\*END OF MSDS\*\*\*