



# MATERIAL SAFETY DATA SHEET

Page 1 of 7

## HE120 - ALUMINUM ROOF PAINT

1. Product And Company Identification			
<b>Supplier</b> HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716  Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com		<b>Manufacturer</b> HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716  Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	
<b>Supplier Emergency Contacts &amp; Phone Number</b> CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666		<b>Manufacturer Emergency Contacts &amp; Phone Number</b> CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	
 <b>Issue Date:</b> 06/24/2014  <b>Product Name:</b> HE120 - ALUMINUM ROOF PAINT <b>Product Code:</b> HE120			
2. Composition/Information On Ingredients			
Ingredient Name		CAS Number	Percent Of Total Weight
1,2,4-trimethylbenzene		95-63-6	1 - 5
aluminum		7429-90-5	15 - 25
aromatic petroleum distillates		64742-95-6	1 - 5
petroleum asphalt		8052-42-4	30 - 50
stoddard solvent		8052-41-3	20 - 40
xylene		1330-20-7	1 - 5
EMERGENCY OVERVIEW			
<b>CAUTION! Combustible Liquid. Central nervous system depressant. Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Causes skin irritation.</b>			
<b>Appearance/Odor:</b> Silvery Brown Liquid, mild petroleum solvent odor			
3. Hazards Identification			
<b>Primary Routes(s) Of Entry</b> Inhalation			
<b>Eye Hazards</b> May cause eye irritation (burning, tearing, redness or swelling).			
<b>Skin Hazards</b> May cause skin irritation and contact dermatitis upon prolonged contact.			
<b>Ingestion Hazards</b> May be harmful if swallowed.			



## HE120 - ALUMINUM ROOF PAINT

### 3. Hazards Identification - Continued

#### **Inhalation Hazards**

Exposure to vapors may cause respiratory tract irritation. Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.

#### **Chronic/Carcinogenicity Effects**

None of the ingredients of this product comprising over 0.1% are classified as carcinogenic according to OSHA, National Toxicology Program (NTP), International Agency for Research on Cancer (IARC) or the American Conference of Governmental Industrial Hygienists (ACGIH).

### 4. First Aid Measures

#### **Eye**

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

#### **Skin**

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

#### **Ingestion**

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim. Call a physician or poison control center immediately.

#### **Inhalation**

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.

#### **Note To Physician**

Aspiration of liquid into the lungs during swallowing or vomiting can cause lung inflammation, serious lung damage and even death from chemical pneumonitis.

### 5. Fire Fighting Measures

**Flash Point:** 105 °F 40.5 °C

**Flash Point Method:** Setaflash

**Flammability Class:** Class II

**Lower Explosive Limit:** 0.9

**Upper Explosive Limit:** 6.0

#### **Fire And Explosion Hazards**

Combustible Liquid. Vapors are heavier than air and may spread long distances and ignite. Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

#### **Extinguishing Media**

Chemical foam, carbon dioxide (CO<sub>2</sub>), or dry chemical. Do not use direct stream of water.

#### **Fire Fighting Instructions**

Firefighters should wear self-contained breathing apparatus and full protective gear.

### 6. Accidental Release Measures

Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect and dispose in accordance with applicable regulations. Avoid runoff to waterways and sewers. For large spills, contain runoff and recover by pumping with explosion proof equipment.



## HE120 - ALUMINUM ROOF PAINT

## 7. Handling And Storage

**Handling And Storage Precautions**

Keep away from ignition sources. Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Do not handle or store near heat, sparks, flame, strong oxidants or strong acids. Use only with adequate ventilation.

## 8. Exposure Controls/Personal Protection

**Engineering Controls**

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

**Eye/Face Protection**

Chemical splash goggles or faceshield over safety glasses or goggles recommended.

**Skin Protection**

Use with chemical-protective gloves to prevent skin contact.

**Respiratory Protection**

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

**Ingredient(s) - Exposure Limits**

1,2,4-trimethylbenzene

ACGIH TLV-TWA 25 ppm

aluminum

ACGIH TLV-TWA 10 mg/m<sup>3</sup>

OSHA PEL-TWA 15 mg/m<sup>3</sup> (total dust)

OSHA PEL-TWA 5 mg/m<sup>3</sup> (respirable dust)

aromatic petroleum distillates

OSHA PEL-TWA 500 ppm

petroleum asphalt

ACGIH TLV-TWA 0.5 mg/m<sup>3</sup> (inhalable fraction, as benzene-soluble aerosol)

stoddard solvent

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 500 ppm

xylene

ACGIH TLV-STEL 150 ppm

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 100 ppm

## 9. Physical And Chemical Properties

**Appearance**

Silvery Brown Liquid

**Odor**

Mild petroleum solvent odor

**Chemical Type:** Mixture

**Physical State:** Liquid

## HE120 - ALUMINUM ROOF PAINT

### 9. Physical And Chemical Properties - Continued

#### **Odor - Continued**

**Boiling Point:** 300-400 °F 149-204 °C

**Specific Gravity:** 0.96

**Percent Volatiles:** <60

**Vapor Pressure:** 2 @68°F

**Vapor Density:** >1

**pH Factor:** not applicable

**Solubility:** insoluble in water

**Evaporation Rate:** <1

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

#### **Incompatible Materials**

Avoid contact with strong oxidizing agents and acids.

#### **Hazardous Decomposition Products**

Toxic and irritating gases, vapors or fumes of aluminum, carbon monoxide (CO), carbon dioxide (CO2).

### 11. Toxicological Information

#### **Chronic/Carcinogenicity**

None of the ingredients present in this product, at concentrations equal to or greater than 0.1%, have been determined to be carcinogenic by IARC, NTP, OSHA, or ACGIH.

#### **Miscellaneous Toxicological Information**

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

#### **Ingredient(s) - Toxicological Data**

1,2,4-trimethylbenzene

LD50 (oral, rat): 5000 mg/kg

LC50 (rat): 18 g/m3 (4-hour exposure)

aromatic petroleum distillates

LD50 (oral, rat): 2900 mg/kg

LD50 (oral, rat): 8400 mg/kg

stoddard solvent

oral-rat LD50: >5000 mg/kg

dermal-rabbit LD50: >3000 mg/kg

inhal-rat LC50: >5500 mg/m3 (880 ppm)

inhal-rat LC50: >1300 ppm

xylene

LD50 (oral, rat): 5400 mg/kg

LD50 (dermal, rabbit): 12180 mg/kg

LC50 (rat): 6350 ppm (4-hour exposure)

### 12. Ecological Information

No specific information available.

### HE120 - ALUMINUM ROOF PAINT

#### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

#### 14. Transport Information

Ground or Water Domestic Voyage

Not restricted if shipped in containers < 450L (119 gallons)

Restricted if shipped in containers > 450L (119 gallons)

US NA1993, Combustible liquid, n.o.s., (Petroleum Distillates mixture), Combustible liquid, III

Canada UN1999, Tars liquid, 3, III

Unless departs > flash point:

Both UN3256, Elevated Temperature liquid, flammable, n.o.s., (Petroleum Distillates mixture), 3, III

IMDG UN1999, Tars liquid, 3, III

IATA UN1999, Tars liquid, 3, III

#### DOT (Pictograms)



#### 15. Regulatory Information

##### U.S. Regulatory Information

Asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.

##### SARA Hazard Classes

Acute Health Hazard

##### Ingredient(s) - U.S. Regulatory Information

1,2,4-trimethylbenzene

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical  
aluminum

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical  
xylene

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

##### Ingredient(s) - State Regulations

1,2,4-trimethylbenzene

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

aluminum

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

### HE120 - ALUMINUM ROOF PAINT

#### 15. Regulatory Information - Continued

##### **Ingredient(s) - State Regulations - Continued**

Pennsylvania - Workplace Hazard  
 Pennsylvania - Environmental Hazard  
 Massachusetts - Hazardous Substance  
 New York City - Hazardous Substance  
 aromatic petroleum distillates  
 New Jersey - Workplace Hazard  
 Pennsylvania - Workplace Hazard  
 petroleum asphalt  
 New Jersey - Workplace Hazard  
 Pennsylvania - Workplace Hazard  
 Massachusetts - Hazardous Substance  
 New York City - Hazardous Substance  
 stoddard solvent  
 New Jersey - Workplace Hazard  
 Pennsylvania - Workplace Hazard  
 Massachusetts - Hazardous Substance  
 New York City - Hazardous Substance  
 xylene  
 New Jersey - Workplace Hazard  
 New Jersey - Environmental Hazard  
 New Jersey - Special Hazard  
 Pennsylvania - Workplace Hazard  
 Pennsylvania - Environmental Hazard  
 Massachusetts - Hazardous Substance  
 New York City - Hazardous Substance

##### **Canadian Regulatory Information**

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: B3 - Combustible Liquid, D2B - Toxic


##### **Ingredient(s) - Canadian Regulatory Information**

1,2,4-trimethylbenzene  
 WHMIS - Ingredient Disclosure List  
 stoddard solvent  
 WHMIS - Ingredient Disclosure List

##### **WHMIS - Canada (Pictograms)**



### HE120 - ALUMINUM ROOF PAINT

NFPA	HMIS
	HEALTH <input type="text" value="2"/>
	FLAMMABILITY <input type="text" value="2"/>
	REACTIVITY <input type="text" value="1"/>
	PERSONAL PROTECTION <input type="text"/>

#### 16. Other Information

##### Revision/Preparer Information

This MSDS Supersedes A Previous MSDS Dated: 02/24/2011

##### Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).