

MATERIAL SAFETY DATA SHEET

Product Trade Name: HYDRO-PLUG

Revision Date: 09-Dec-2013

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Statement of Hazardous Nature Hazardous according to the criteria of NOHSC, Non-Dangerous Goods according to the criteria of ADG.

Manufacturer/Supplier Halliburton/Baroid Australia Pty. Ltd.
15 Marriott Road
Jandakot
WA 6164
Australia

ACN Number: 009 000 775
Telephone Number: 61 (08) 9455 8300
Fax Number: 61 (08) 9455 5300

Product Emergency Telephone

Australia: 08-64244950
Papua New Guinea: 05 1 281 575 5000
New Zealand: 06-7559274

Fire, Police & Ambulance - Emergency Telephone

Australia: 000
Papua New Guinea: 000
New Zealand: 111

Identification of Substances or Preparation

Product Trade Name: HYDRO-PLUG
Synonyms: None
Chemical Family: Blend
UN Number: None
Dangerous Goods Class: None
Subsidiary Risk: None
Hazchem Code: None Allocated
Poisons Schedule: None Allocated
Application: Loss Circulation Material

Prepared By Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. HAZARDS IDENTIFICATION

Statement of Hazardous Nature Hazardous according to the criteria of NOHSC, Non-Dangerous Goods according to the criteria of ADG.

Hazard Overview

CAUTION! - ACUTE HEALTH HAZARD

May cause eye and respiratory irritation.

DANGER! - CHRONIC HEALTH HAZARD

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Review the Material Safety Data Sheet (MSDS) for this product, which has been provided to your employer.

Classification

T - Toxic.

Risk Phrases

R49 May cause cancer by inhalation.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Safety Phrases

S22 Do not breathe dust.

HSNO Classification

Not Determined

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	Australia NOHSC	New Zealand	ACGIH TLV-TWA
			WES	WES	
Mica	12001-26-2	10 - 30%	TWA: 2.5 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³
Crystalline silica, quartz	14808-60-7	0 - 1%	TWA: 0.1 mg/m ³	TWA: 0.2 mg/m ³	TWA: 0.025 mg/m ³

Non-Hazardous Substance to Total of 100%

4. FIRST AID MEASURES

Inhalation

If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.

Skin

Wash with soap and water. Get medical attention if irritation persists.

Eyes

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

Ingestion

Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician

Not Applicable

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

All standard fire fighting media

Extinguishing media which must not be used for safety reasons

None known.

Special Exposure Hazards Flammable dust when in finely divided and highly suspended state.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Avoid creating and breathing dust.

Environmental Precautionary Measures None known.

Procedure for Cleaning / Absorption Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate methods for collection, storage and disposal.

7. HANDLING AND STORAGE

Handling Precautions Avoid dust accumulations. This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is slippery when wet.

Storage Information Use good housekeeping in storage and work areas to prevent accumulation of dust. Close container when not in use. Store away from oxidizers. Store in a dry location. Keep from heat, sparks, and open flames. Product has a shelf life of 36 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use approved industrial ventilation and local exhaust as required to maintain exposures below applicable exposure limits.

Respiratory Protection Wear a NIOSH certified, European Standard EN 149 (FFP2/FFP3), or equivalent respirator when using this product.

Hand Protection Normal work gloves.

Skin Protection Wear clothing appropriate for the work environment. Dusty clothing should be laundered before reuse. Use precautionary measures to avoid creating dust when removing or laundering clothing.

Eye Protection Wear safety glasses or goggles to protect against exposure.

Other Precautions None known.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid
Color: Dark gray
Odor: Odorless

pH:	8 - 9
Specific Gravity @ 20 C (Water=1):	2.0
Density @ 20 C (kg/l):	Not Determined
Bulk Density @ 20 C (kg/M3):	Not Determined
Boiling Point/Range (C):	Not Determined
Freezing Point/Range (C):	Not Determined
Pour Point/Range (C):	Not Determined
Flash Point/Range (C):	Not Determined
Flash Point Method:	Closed cup
Autoignition Temperature (C):	Not Determined
Flammability Limits in Air - Lower (g/m ³):	Not Determined
Flammability Limits in Air - Lower (%):	Not Determined
Flammability Limits in Air - Upper (g/m ³):	Not Determined
Flammability Limits in Air - Upper (%):	Not Determined
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	Not Determined
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Slightly soluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (g/l):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined
Decomposition Temperature (C):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	None known.
Incompatibility (Materials to Avoid)	Strong acids. Strong alkalis.
Hazardous Decomposition Products	Carbon monoxide and carbon dioxide. Amorphous silica may transform at elevated temperatures to tridymite (870 C) or cristobalite (1470 C).
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

Symptoms related to exposure

Acute Toxicity Inhalation

May cause mild respiratory irritation. Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

Eye Contact
Skin Contact
Ingestion

May cause mild eye irritation.
 May cause mild skin irritation.
 May cause mild gastric distress.

Chronic Effects/Carcinogenicity

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Mica	12001-26-2	> 15000 mg/kg (Rat)	No data available	No data available
Crystalline silica, quartz	14808-60-7	500 mg/kg (Rat)	No data available	No data available

12. ECOLOGICAL INFORMATION

Ecotoxicological Information

Ecotoxicity Product

Acute Fish Toxicity: Not determined
Acute Crustaceans Toxicity: Not determined
Acute Algae Toxicity: Not determined

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Mica	12001-26-2	No information available	No information available	No information available	EC50: > 10,000 mg/l (Daphnia magna)
Crystalline silica, quartz	14808-60-7	No information available	No information available	No information available	No information available

12.2 Persistence and degradability

The methods for determining biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

Does not bioaccumulate

12.4 Mobility in soil

No information available

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

13. DISPOSAL CONSIDERATIONS

Disposal Method Bury in a licensed landfill according to federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

ADR
Not restricted

Air Transportation

ICAO/IATA
Not restricted

Sea Transportation

IMDG
Not restricted

Other Transportation Information

Labels: None

15. REGULATORY INFORMATION

Chemical Inventories

Australian AICS Inventory All components listed on inventory or are exempt.
New Zealand Inventory of Chemicals This product does not comply with NZIOC

US TSCA Inventory All components listed on inventory or are exempt.
EINECS Inventory This product, and all its components, complies with EINECS

Classification T - Toxic.

Risk Phrases R49 May cause cancer by inhalation.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Safety Phrases S22 Do not breathe dust.

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS
Not applicable

Contact

Australian Poisons Information Centre

24 Hour Service: - 13 11 26

Police or Fire Brigade: - 000 (exchange): - 1100

New Zealand National Poisons Centre

0800 764 766

Additional Information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****