

W W HENRY CO -- ACOUSTICAL TILE ADHESIVE, 137 -- 8040-00N004072

=====
Product Identification
=====

Product ID:ACOUSTICAL TILE ADHESIVE, 137

MSDS Date:06/07/1988

FSC:8040

NIIN:00N004072

Status Code:A

MSDS Number: CHSFZ

=== Responsible Party ===

Company Name:W W HENRY CO

Address:5608 SOTO ST

City:HUNTINGTON PARK

State:CA

ZIP:90255

Country:US

Info Phone Num:213-583-4961

Emergency Phone Num:213-583-4961

CAGE:EO927

=== Contractor Identification ===

Company Name:HENRY W W CO

Box:3001

City:LANCASTER

State:PA

ZIP:17604

Country:US

Phone:717-396-2328;717-396-2935

CAGE:11761

Company Name:W W HENRY CO

Address:5608 SOTO ST

City:HUNTINGTON PARK

State:CA

ZIP:90255-5000

Country:US

Phone:213-583-4961

CAGE:EO927

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL ALCOHOL; (DENATURED ETHANOL). VP:40 @ 66F.

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 2-3%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM

Ingred Name:TOLUENE (SARA 313) (CERCLA). VP:37 @ 86F.

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 2-3%

OSHA PEL:200 PPM

ACGIH TLV:50 PPM, S

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA 313). VP:32 @ 68F.

CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5-10%
OSHA PEL:400 PPM
ACGIH TLV:400 PPM;500 STEL

Ingred Name:VOLATILE ORGANIC COMPOUNDS: 136-137 G/L.
RTECS #:9999999VO

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:HDCHS, DIZZ, EYE, NOSE, THROAT & LUNG
DISTRESS FROM VAPS. INHAL OF HIGH CONCS MAY ASPHYXIATE. RPTS HAVE
ASSOC RPTD & PRLNG OCCUP OVEREXP TO SOLVS W/PERM BRAIN & NERV SYS
DMG. INTENTIONAL MISUSE BY DEL IB CONC & INHALING CONTENTS MAY BE
HARMFUL/FATAL. NO LONG TERM LAB TESTS TO DETERMINE CHRONIC EFTS.
(EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HLTH HAZ:SKIN IRRIT & DERM MAY DEVELOP FROM
PRLNG CONT W/SKIN. NOTE:TOLUENE APPEARS ON THE NAVY LIST OF OCCUP
CHEM REPRO HAZARDS. SEEK CONSULTATION FROM APPROPRIATE HEALTH
PROFESSIONALS CONCERNING LAT EST HAZARD LIST INFO & SAFE HANDLING &
EXPOSURE INFO .
Medical Cond Aggravated by Exposure:CURRENT ANEMIA, RESPIRATORY TRACT
OR LIVER AILMENTS & SKIN CONDITIONS.

=====
===== First Aid Measures =====

First Aid:INGEST:CALL MD IMMEDIATELY . INHAL:MOVE PERSON TO FRESH AIR &
APPLY ARTF RESP IF NEEDED. CALL MD IMMEDIATELY. EYES:FLUSH W/PLENTY
OF WATER FOR AT LEAST 15 MINUTES. SKIN:WASH THOROUGHLY W/SOAP &
WATER OR HAND CLEANER.

=====
===== Fire Fighting Measures =====

Flash Point:2F,-17C
Lower Limits:1%
Extinguishing Media:FOAM, CO*2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT .
Unusual Fire/Explosion Hazard:FLAMMABILITY CLASS-OSHA:1B. VAPS ARE
FLAMM IF ALLOWED TO COLLECT & CONCENTRATE. CLSD CNTNRS MAY DEVELOP
EXCESSIVE PRESS & ERUPT WHEN EXPOS TO EXTREME HEAT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE OR EXTINGUISH ALL SOURCES OF IGNITION
IN AREA, INCLUDING EQUIPMENT WHICH MAY SPARK. SCOOP MATERIAL INTO
APPROVED DOT CONTAINER. REMOVE TO SAFE PLACE WHERE MATERIAL CAN
DRY.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, FLAMES & ALL SOURCES OF IGNITION. KEEP OUT OF REACH OF CHILDREN. USE ONLY AS DIRECTED ON LABEL.

Other Precautions:CLOSED CONTAINER AFTER EACH USE. DO NOT RE-USE CONTAINER. AVOID SKIN & EYE CONTACT. FIRE PREVENTION:KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME & ALL OTHER SOURCES OF IGNITION DURING USE & UNTIL ALL VAPOR S ARE GONE. DO NOT SMOKE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:PROPER VENTILATION NORMALLY SUFFICIENT IF EYE WATERING, HEADACHES OR DIZZINESS ARE EXPERIENCED, INCREASE FRESH AIR SUPPLY, WEAR NIOSH APPROVED RESPIRATORY EQUIPMENT OR LEAVE THE AREA.

Ventilation:FLAMM VAPS MAY IGNITE. ADEQ VENT IS ESSNTL TO PVNT BUILDUP OF VAPS TO LEL/FLAMM CONC. OPEN ALL WINDOWS & DOORS & (SUPDAT)

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA .

Work Hygienic Practices:WASH SKIN THOROUGHLY W/SOAP & WATER OR HAND CLEANER.

Supplemental Safety and Health

VENT:UTILIZE OTHER FIRE-SAFE MEANS TO ASSURE FRESH AIR ENTRY & EXHAUST DURING USE & UNTIL ALL VAPORS ARE GONE. A SOLVENT & RESIN ODOR MAY BE NOTED UNTIL ADHESIVE DRIES. AVOID SKIN & EYE CONTACT.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>150F,>66C

Vapor Pres:SEE INGS

Vapor Density:HVR/AIR

Spec Gravity:1.32

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:15-20

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN.

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME & ALL OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products:NONE KNOWN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS . DISPOSE OF I/A/W LOCAL DISPOSAL REGULATIONS. DO NOT FLUSH ADHESIVE DOWN DRAINS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.