



MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Hook-It

Manufacturer:

Federal Mogul Corporation
26555 Northwestern Highway
Southfield, MI 48033

MSDS# BH-128

24hr Emerg # (Infotrac): 1-800-535-5053

International: 001-352-323-3500

Non-Emerg #: 248-354-9844

SECTION 2: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Bentley-Harris Hook-It is a lightweight, damage resistant sleeving with a unique hoop and loop self-closing feature that eliminates spot taping and does not require an open end for installation. The sleeving permits easy access for inspection, rework or replacement of components. Used to bundle, protect and dress wire and hose assemblies, Hook-It provides cut-through and abrasion protection. It is highly flexible and readily conforms to irregular shapes and contours. It does not trap heat or moisture.

This information provides the minimum criteria for safe usage and handling of this product. Companies using this product should develop their own occupational health program to protect employees from injury or adverse health effects.

Ingredient	CAS No.	% Weight	OSHA PEL	ACGIH TLV
Polyester Monofilament	None Established	69	None Established	None Established
Polyester fill yarn	None Established	<1	None Established	None Established
Hook and loop closure (Velcro)	None Established	30	None Established	None Established

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Shipped material is not considered hazardous, but operations (e.g., overheating, burning, machining, abrading, or riveting) that can create airborne dust should be avoided.

POTENTIAL HEALTH EFFECTS

Inhalation: Dust from abnormal abrasion and/or vapors caused by heating to greater than 300°C may cause respiratory irritation.

Skin: Molten material can cause thermal burns.

Eye: Dust particles may cause irritation.

Ingestion: Not a probable route of entry.

POTENTIAL HEALTH EFFECTS (continued)**Carcinogenicity:**

	COMPONENT
	NTP
	IARC
	OSHA
Polyester Monofilament	No No No
Polyester fill yarn	No No No
Hook and loop closure (Velcro)	No No No

Symptoms and Effects of Exposure to Selected Individual Components**Exposure Hazards:** None known**SECTION 4: FIRST AID MEASURES**

Inhalation:	Move to fresh air. If irritation persists, seek medical attention.
Eye Contact:	Rinse thoroughly with ample amounts of water. If irritation persists, seek medical attention.
Skin Contact:	Wash thoroughly with soap and water. If molten material falls on skin, do not attempt to remove the material from the skin; cool immediately with water. Seek medical attention.
Ingestion:	Not a probable route of entry. Seek medical attention.

SECTION 5: FIRE FIGHTING MEASURES

This product is inherently flame resistant, but may ignite at temperatures exceeding 600°C in an oxygen-enriched atmosphere.

Flashpoint: N/A **LEL:** N/A **UEL:** N/A **Autoignition Temperature:** N/A

Extinguishing Media: Use media suitable for surrounding fire.

Unusual Fire and Explosion Hazards: None

Special Fire-Fighting Procedure: Wear self-contained breathing apparatus when extinguishing. Hazardous decomposition products are generated in fire conditions.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Scrap monofilament may present a slipping hazard, use good housekeeping practices. If dust is generated during machining, abrading or riveting, remove dust by vacuuming or wet-mopping or place in an airtight polyethylene bag. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust from surfaces.

SECTION 7: HANDLING AND STORAGE

Store in a cool, dry place. Shipping and storage may result in accumulation of dust in shipping containers. If this occurs while shipping product, remove dust by vacuuming or wet-mopping or place in an airtight polyethylene bag. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust from surfaces.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Protection: Any operation which may produce dust, including machining, grinding, riveting, or abrading this product, should be adequately exhausted to prevent inhalation of dust.

Respiratory Protection: Use a NIOSH-approved respirator if there is a potential for exposure to exceed applicable PELs or TLVs. (See 29 CFR 1910.134, OSHA Respiratory Protection Standard.)

Skin Protection: If skin irritation occurs, gloves and other protective garments may be worn. It is recommended to wash hands after working with material.

Eyes: Wear safety glasses or goggles, as necessary, if dust exposure is possible.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	N/A	Vapor Pressure:	N/A
Melting Point:	256°C	Vapor Density (air = 1):	N/A
pH:	N/A	% Volatile:	N/A
Specific Gravity:	1.54 g/cc	Evaporation Rate:	N/A
Water Solubility:	Insoluble	Color, Form and Odor:	Black, solid and odorless

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and storage conditions.

Incompatibility (Materials/Conditions to Avoid): Strong bases

Hazardous Polymerization: Will not polymerize

Decomposition Products: Thermal decomposition will start at temperatures above 300° C producing such by-products as carbon monoxide with trace amounts of esters, alcohols, acids and acetaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

Inhalation: Refer to Section 3

Skin: Refer to Section 3
Eye: Refer to Section 3
Ingestion: Refer to Section 3
Acute: None known
Chronic: None known

SECTION 12: ECOLOGICAL INFORMATION

N/A

SECTION 13: DISPOSAL CONSIDERATIONS

Federal and state law regulates disposal of scrap material or dust as solid waste; disposal must be in accordance with federal and state laws. Contact local regulatory agencies for guidance.

SECTION 14: TRANSPORTATION INFORMATION

Proper Shipping Name: Not regulated
Hazard Class: None
Identification Number: None
Packing Group: N/A
Shipping Label: None
Additional Marking Requirement: None

SECTION 15: REGULATORY INFORMATION

U.S. TSCA: All chemicals used in the manufacture of this product are listed on the U.S. Toxic Substances Control Act (TSCA) Inventory

California Proposition 65: This product does not contain ingredients known to the State of California to cause cancer, birth defects or other reproductive effects.

SARA Title III – Section 313 Supplier Notification: This product does not contain chemicals subject to SARA Title III/CERCLA “reportable quantities” (RQs) and/or “threshold planning quantities” (TPQs) and/or are classified as “Toxic Chemicals” under the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and 40 CFR 372.

RCRA Hazardous Waste Code: Not Available

CERCLA Hazardous Substances: Not Available

OSHA: Not Available

WHMIS Classification: Not Available

SECTION 16: OTHER INFORMATION

Abbreviations:

CAS No.:	Chemical Abstract Services Number
OSHA PEL:	U.S. Occupational Safety and Health Administration Permissible Exposure Limit
ACGIH TLV:	American Conference of Governmental Industrial Hygienists Threshold Limit Value (2004)
N/A:	Not Applicable
IARC:	International Agency for Research on Cancer
NTP:	National Toxicology Program
NIOSH:	National Institute of Occupational Safety and Health
HEPA:	High-efficiency particulate air

The information and recommendations stated above are taken from sources believed to be accurate as of the date of this revision. Federal-Mogul makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability, including direct, incidental or consequential damages for any reliance thereof.

This MSDS should not be used as a complete or accurate summary of the content of this product. For specific information on brand names, manufacturers, or quantities, please refer to product specification documents, wherever available.