

SAFETY DATA SHEET

ZepInc

I D Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : I D Red Liquid 55GL
Material number : 00000000000057085

Manufacturer or supplier's details

Company : Zep Inc.
Address : 1310 Seaboard Industrial Blvd., NW
Atlanta, GA 30318
Telephone : 404-352-1680

Emergency telephone numbers

For SDS Information	: Compliance Services 1-877-428-9937
For a Medical Emergency	: 877-541-2016 Toll Free - All Calls Recorded
For a Transportation Emergency	: CHEMTREC: 800-424-9300 - All Calls Recorded. In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Degreaser
Vehicle Maintenance

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	clear
Odour	hydrocarbon-like

GHS Classification

Flammable liquids : Category 2
Skin irritation : Category 2
Specific target organ toxicity -
single exposure : Category 1
Specific target organ toxicity -
single exposure : Category 3 (Central nervous system)
Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

ID Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

H370 Causes damage to organs.

Precautionary statements

: **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P307 + P311 IF exposed: Call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 70 - < 90
propan-2-ol	67-63-0	>= 5 - < 10
heptane	142-82-5	>= 1 - < 5
methanol	67-56-1	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

ID Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
Remove contaminated clothing and shoes.
Wash contaminated clothing before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
Keep eye wide open while rinsing.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Effects are dependent on exposure (dose, concentration, contact time).
Effects are immediate and delayed.
Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat.
Symptoms may include irritation, redness, pain, and rash.
Causes damage to organs.
Causes skin irritation.
May cause drowsiness or dizziness.
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

ID Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

Hazardous combustion products	: Carbon dioxide (CO ₂) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation hood. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	: No smoking.

ID Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.
 Do not freeze.

Storage temperature : 5 - 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		ST	500 ppm 1,225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z-1
		TWA	400 ppm 980 mg/m ³	OSHA P0
		STEL	500 ppm 1,225 mg/m ³	OSHA P0
		PEL	400 ppm 980 mg/m ³	CAL PEL
		STEL	500 ppm 1,225 mg/m ³	CAL PEL
		heptane	142-82-5	TWA
C	440 ppm 1,800 mg/m ³			NIOSH REL
TWA	500 ppm 2,000 mg/m ³			OSHA Z-1
TWA	400 ppm 1,600 mg/m ³			OSHA P0
STEL	500 ppm 2,000 mg/m ³			OSHA P0
PEL	400 ppm 1,600 mg/m ³			CAL PEL
STEL	500 ppm 2,000 mg/m ³			CAL PEL
methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm	NIOSH REL

SAFETY DATA SHEET



ID Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

			260 mg/m3	
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
		TWA	200 ppm 260 mg/m3	OSHA P0
		C	1,000 ppm	CAL PEL
		PEL	200 ppm 260 mg/m3	CAL PEL
		STEL	250 ppm 325 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves
Remarks : Skin should be washed after contact. For prolonged or repeated contact use protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Ensure that eyewash stations and safety showers are close to the workstation location.
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures

: Wear suitable protective equipment.

SAFETY DATA SHEET

I D Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

When using do not eat, drink or smoke.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point : 64 °C

Flash point : -18 °C
Method: TCC

Evaporation rate : No data available
No data available

Upper explosion limit : 11.6 %(V)

Lower explosion limit : 1.2 %(V)

Vapour pressure : 178.65 hPa (20 °C)

Relative vapour density : No data available

Density : 0.7 g/cm³

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : insoluble

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

I D Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION**Potential Health Effects**

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat. Symptoms may include irritation, redness, pain, and rash.

Carcinogenicity:

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity**Product:**

Acute oral toxicity	: Acute toxicity estimate : 3,217 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate : 102.52 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method

SAFETY DATA SHEET



I D Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

propan-2-ol:
Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg
Method: Calculation method

heptane:
Acute inhalation toxicity : LC50 Rat: 103 mg/l
Exposure time: 4 h

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Naphtha (petroleum), hydrotreated light:
propan-2-ol:
heptane:
methanol:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

SAFETY DATA SHEET



I D Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

heptane :
Partition coefficient: n-octanol/water : log Pow: 5

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life., May cause long lasting harmful effects to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with

SAFETY DATA SHEET



I D Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
UN1993, Flammable liquids, n.o.s., (HEPTANE, ISOPROPANOL), 3, II

Transportation Regulation: IMDG (Vessel):
UN1993, FLAMMABLE LIQUID, N.O.S., (HEPTANE, ISOPROPANOL), 3, II

Transportation Regulation: IATA (Cargo Air):
UN1993, Flammable liquid, n.o.s., (HEPTANE, ISOPROPANOL), 3, II

Transportation Regulation: IATA (Passenger Air):
UN1993, Flammable liquid, n.o.s., (HEPTANE, ISOPROPANOL), 3, II

Transportation Regulation: TDG (Canada):
UN1993, FLAMMABLE LIQUID, N.O.S., (HEPTANE, ISOPROPANOL), 3, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
methanol	67-56-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SAFETY DATA SHEET



I D Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:
 methanol 67-56-1 2.9342 %

California Prop 65 WARNING! This product contains a chemical known to the State of California to cause cancer.
 benzene 71-43-2
 WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
 methanol 67-56-1
 toluene 108-88-3
 benzene 71-43-2

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory
DSL All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms :



Signal word : **Danger:**
 Hazard statements : Highly flammable liquid and vapour. May be fatal if sw allowed and enters airways.
 Causes skin irritation. May cause drowsiness or dizziness. Causes damage to aquatic life.

I D Red Liquid 55GL

Version 4.1

Revision Date 02/08/2017

Print Date 08/18/2017

Precautionary statements :

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF exposed: Call a POISON CENTER or doctor/physician. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	4.1
Revision Date:	02/08/2017
Print Date:	08/18/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes.

This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.