SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.

W. F. Taylor Co., Inc.

11545 Pacific Avenue Fontana, CA 92337-8228 951/360-6677

CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: IVC 2037 FLEX TECH FIBERGLASS BACKED VINYL SHEET PS ADHESIVE

ITEM NUMBER: 2037-04-IVC

ITEM DESCRIPTION: IVC 2037 Flec Tech Fiberglass Backed Sheet Vinyl Adh 1-Qrt

PRODUCT DESCRIPTION: LATEX BASED ADHESIVE

CHEMICAL FAMILY: ACRYLIC LATEX, RESIN BLEND

REVISION DATE: 02/26/14 REVIEW DATE: / PRINT DATE:07/21/14 PRINT TIME:13:50

MANUFACTURED FOR: IVC US INC.

101 IVC DRIVE

DALTON, GA 30721

UNITED STATES

PHONE NO.: (706) 529-2600

www.ivcgroup.us

HMIS HAZARD RATING

LEAST: 0 HEALTH: 1
SLIGHT: 1 FLAMMABLE: 0
MODERATE: 2 REACTIVITY: 0

HIGH: 3
EXTREME: 4

PREPARED BY: ROBERT DDAMULIRA PREEMPTS PREVIOUS MSDS SHEETS

SECTION II HAZARDOUS INGREDIENTS

SECTION III PHYSICAL DATA

 ${\tt Hazard} \hspace{1.5cm} {\tt CAS} \ \# \hspace{1.5cm} {\tt WT/Wt} \ \$ \ {\tt Less} \ {\tt Than}$

NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS

BOILING POINT: 212 DEGREES F
LBS / GAL: 8.4 - 8.6
EVAPORATION RATE: SAME AS WATER
VAPOR DENSITY: SAME AS WATER.
PERCENT VOLATILE: 48 -50 (BY WEIGHT)

COLOR: OFF WHITE

ODOR: NIL

VOC, g/l less water, less exempt solvent: 0 (calculated)

SECTION IV FIRE AND EXPLOSION HAZARD DATA

(Continued) Page 2

PRODUCT NAME: IVC 2037 FLEX TECH FIBERGLASS BACKED VINYL SHEET PS ADHESIVE

ITEM NUMBER: 2037-04-IVC

ITEM DESCRIPTION: IVC 2037 Flec Tech Fiberglass Backed Sheet Vinyl Adh 1-Qrt

REVISION DATE: 02/26/14 REVIEW DATE: / / PRINT DATE:07/21/14 PRINT TIME:13:50

FLASH POINT, PENSKY-MARTIN C.C.: NA

AUTO IGNITION TEMPERATURE, DEGREES F: NA

FLAMMABLE LIMITS IN AIR (% BY VOLUME): LEL: NA UEL: NA

EXTINGUISHING MEDIA:

(X) WATER SPRAY (X) CARBON DIOXIDE () OTHER

(X) FOAM (X) DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: USE SELF CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN

SECTION V HEALTH HAZARD IDENTIFICATION

SYMPTOMS OF OVER EXPOSURE:

INHALATION: MAY CAUSE SLIGHT IRRITATION TO THE UPPER RESPIRATORY TRACT.

EYES: VAPOR MAY CAUSE IRRITATION.

SKIN: MAY CAUSE SLIGHT SKIN IRRITATION.

INGESTION: NOT A LIKELY ROUTE OF ENTRY UNDER PROPER HANDLING CONDITIONS. MAY CAUSE VOMITING. SYMPTOMS MAY BE SAME AS INHALATION.

HEALTH EFFECTS OR RISK FROM EXPOSURE:

ACUTE: INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTACT WITH EYES AND SKIN MAY

RESULT TO IRRITATION. INGESTION MAY RESULT TO GASTRIC DISTURBANCES.

CHRONIC: NOT KNOWN

SECTION VI FIRST AID PROCEDURES

FIRST AID PROCEDURES:

EYES CONTACT: WASH WITH WATER AT LEAST 15 MINUTES. IF IRRITATIONS PERSISTS, SEEK MEDICAL

SKIN CONTACT: REMOVE FROM SKIN AND WASH WITH SOAP AND WATER. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. ADMINISTER OXYGEN, IF NECESSARY. SEEK MEDICAL ATTENTION.

INGESTION: IF SWALLOWED, CALL PHYSICIAN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN

SECTION VII HANDLING AND STORAGE

KEEP OUT OF THE REACH OF CHILDREN. DO NOT INDUCE VOMITING IF INGESTED.PROTECT FROM EXTREME TEMPERATURE CONDITIONS. AVOID BREATHING BUILDUP OF VAPORS. USE WITH ADEQUATE VENTILATION.

SECTION VIII SPECIAL PROTECTION INFORMATION

(Continued) Page 3

PRODUCT NAME: IVC 2037 FLEX TECH FIBERGLASS BACKED VINYL SHEET PS ADHESIVE

ITEM NUMBER: 2037-04-IVC

ITEM DESCRIPTION: IVC 2037 Flec Tech Fiberglass Backed Sheet Vinyl Adh 1-Qrt

REVISION DATE: 02/26/14 REVIEW DATE: / / PRINT DATE:07/21/14 PRINT TIME:13:50

VENTILATION AND ENGINEERING CONTROLS: USE LOCAL EXHAUST. DO NOT USE CLOSED

AIR-CIRCULATING SYSTEM. OPEN WINDOWS AND DOORS IF NECESSARY.

RESPIRATORY PROTECTION: NIOSH RESPIRATOR IF NEEDED.

CLOTHING: CHEMICAL RESISTANT GLOVES, APRON, COVERALLS, AND BOOTS AS NECESSARY TO PREVENT

CONTACT.

EYE PROTECTION: CHEMICAL GOGGLES OR FACE SHIELD

OTHER CLOTHING AND EQUIPMENT: IF CLOTHING BECOMES CONTAMINATED, REMOVE AND CLEAN BEFORE

REWEARING.

WORK PRACTICES, HYGIENIC PRACTICES: FOLLOW LABEL INSTRUCTIONS.

PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: USE GOGGLES AND GLOVES

WHEN CLEANING ADHESIVE FROM EQUIPMENT. MAINTAIN PROPER VENTILATION.

SECTION IX SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED

KEEP OUT OF SEWER SYSTEMS TO PREVENT BLOCKAGE DUE TO POLYMER DEPOSITS. USE ABSORBENT MATERIAL TO COLLECT AND/OR SCRAPE UP EXCESS AND PLACE INTO CLOSED DOT APPROVED CONTAINERS FOR DISPOSAL.

SECTION X STABILITY AND REACTIVITY DATA

STABILITY: STABLE

FREEZE THAW STABILITY: UP TO 5 CYCLES AT 10 DEGREES F

CONDITIONS TO AVOID: KEEP AWAY FROM EXTREME TEMPERATURE CONDITIONS.

INCOMPATIBILTY-MATERIALS TO AVOID: OXIDIZING MATERIALS

HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): OXIDES OF CARBON, WATER

AND ORGANIC COMPOUNDS OF UNKNOWN STRUCTURE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION XI TOXICOLOGICAL PROPERTIES

NOT AVAILABLE

SECTION XII ECOLOGICAL INFORMATION

NOT AVAILABLE

SECTION XIII DISPOSAL CONSIDERATION

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS

SECTION XIV: TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: NOT APPLICABLE PROPER HAZARD CLASS: NOT HAZARDOUS

HAZARD CODE: NOT HAZARDOUS

SECTION XV REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD(29CFR 1910.1200) HAZARD CLASS(ES): NONE

SARA TITLE III SECTION 312 HAZARD CLASS: NONE

EPA SARA TITLE III SECTION 313: NONE

SECTION XVI OTHER INFORMATION

(Continued) Page 4

PRODUCT NAME: IVC 2037 FLEX TECH FIBERGLASS BACKED VINYL SHEET PS ADHESIVE ITEM NUMBER: 2037-04-IVC

2037-04-IVC

ITEM DESCRIPTION: IVC 2037 Flec Tech Fiberglass Backed Sheet Vinyl Adh 1-Qrt

REVISION DATE: 02/26/14 REVIEW DATE: / / PRINT DATE:07/21/14 PRINT TIME:13:50

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.