

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S. Department of Labor

Occupation Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY

INSTA-SHINE (120450)

*Note: Blank spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.*

Section I

D.O.T. Hazard Class: CONSUMER COMMODITY ORM-D

Manufacturer's Name

Beaver Research Company

Emergency Telephone Number

1-800-255-3924 (Chem-Tel)

Address (Number, Street, City, State, and ZIP Code)

3700 E. Kilgore Road Portage, MI 49002

Telephone Number For Information

1-800-544-0133

HMIS RATING: (Based on Aerosol Concentrate): 0-Minimal; 1-Slight;
2-Moderate; 3-Serious; 4-Extreme

Date Prepared

01/29/01

HEALTH 0 REACTIVITY 0

Signature of Preparer (optional)

FIRE1 PERSONAL PROTECTION: A

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	PEL	TWA/ TLV	Other Limits Recommended	% (optional)
Food Grade Mineral Oil (8042-47-5)	N/E	N/E	--	10-20
Citrus Terpene (5989-27-5)	N/E	N/E	--	01-05
Liquified Petroleum Gas (68476-85-7)	1000ppm	1000ppm	--	10-20

Section III - Physical/Chemical Characteristics

Boiling Point	~158°F	Specific Gravity (H2O = 1) @75°F:	0.960
Vapor Pressure (mm Hg) (psig @70°F):	60	Total VOC %	~18%
Vapor Density (AIR = 1)	>1	Evaporation Rate (Butyl Acetate = 1)	N/A

Solubility in Water

pH: 11.0

Complete

Appearance and Odor

White Jel Liquid with Citrus Scent

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
None to Boiling (158°F)	Flammable Spray	NA	NA

Extinguishing Media

Foam, CO2, Dry Media

Special Fire Fighting Procedures

Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

Unusual Fire and Explosion Hazards

Exposure to temperatures above 120°F may cause bursting.

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid	None
	Stable	X		

Incompatibility (Materials to Avoid)

Avoid contact with strong oxidizing agents.

Hazardous Decomposition or Byproducts

Carbon Dioxide, Carbon Monoxide

Hazardous	May Occur		Conditions to Avoid	None
Polymerization	Will Not Occur	X		

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	Yes	Yes

Health Hazards (Acute and Chronic)

Eyes: May cause slight irritation but does not injure eye tissue.

Skin: Frequent or prolonged skin contact may cause irritation.

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea, and other central nervous system effects.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis. Minimal toxicity.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Signs and Symptoms of Exposure

See above "Health Hazards".

Medical Conditions Generally Aggravated by Exposure

N/A

Emergency and First Aid Procedure

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **Skin:** Wash with soap and water. If irritation persists seek medical attention. **Inhalation:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **Ingestion:** Do not induce vomiting. Seek medical attention immediately.

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. Keep sparks, heat sources, and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbant material in accordance with Federal, State and local laws.

Waste Disposal Method

Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State, and local authorities for approved procedures.

Precautions to be Taken in Handling and Storage

KEEP OUT OF THE REACH OF CHILDREN. For Industrial & Institutional Use Only. Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120°F. NFPA Code 30B Rating: Level 2 Aerosol.

Other Precautions

N/A

Section VIII - Control Measures

Respiratory Protection (Specify Type)

None needed for proper use in accordance with label directions.

Ventilation	Local Exhaust	Yes	Special	N.A.
	Mechanical(General)	N.A.	Other	N.A.

Protective Gloves

None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made.

Other Protective Clothing or Equipment

Eye Protection: None needed unless it is anticipated that a splash or sprayback will occur, then wear safety glasses or chemical proof goggles.

Work/Hygienic Practices

No smoking.

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

Forms by WindowChem Software (707)864-0845