**FILE NO.:** 239709



# **INTEGRITY WHITE GEL**

### **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: Integrity White Gel MANUFACTURER: International Nail Manufacturers (inm)

CHEMICAL NAME: N/A DIVISION: Nail Cartel, Inc.

CHEMICAL FAMILY: UV Gels ADDRESS: 1221 N. Lakeview Ave.

 PRODUCT USE:
 Nail Gel
 PHONE:
 714-779-9892

 EMERGENCY PHONE:
 Info-Trac
 1-352-323-3500
 FAX:
 714-779-9971

MSDS DATE: 4/16/2010 PREPARED BY: Tonja Byers

#### **SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/ OSHA	%
Polyurethane Acrylate Oligomer	Exempt	N/E	Di-Hema Trimethylhexyl Dibarbamate*	N/E	N/E	Not Listed	60-70
Tripropylene Glycol Diacrylate Esters (TPGDA)	42978-66-5	256-032-2	N/E	N/E	N/E	Not Listed	20-30
Hydroxycyclohexyl phenyl ketone	947-19-3	213-426-9	Hydroxycyclohexyl phenyl ketone	N/E	N/E	Not Listed	2-6
Silicon Dioxide	60676-86-0	262-373-8	Silica	N/E	N/E	Not Listed	2-6
Benzophenone	119-61-9	204-337-6	Benzophenone	N/E	N/E	Not Listed	1-3
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI 60725	N/E	N/E	Not Listed	0-1
Titanium Dioxide	13463-67-7	236-675-5	Titanium Dioxide	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	3/no/no	0-1
N/E-None Established N/R-Not Reviewed	N/DA-No Dat N/A-Not Appli			_			

Hazard Symbols: Xi Risk Phrases: R22, R36/38, R43 Safety Phrases: S18, S24/25, S36/37, S38

#### **SECTION 3: HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This information is based on finding from related or similar materials.

- May Be Slightly Toxic.
- May cause moderate skin injury (reddening & swelling).
- May cause chemical burn in eye.

#### Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: No specific information available.

Eyes: No specific information available. Contains materials that essentially nonirritating, but contact may cause slight

transient irritation.

Skin: No specific information available. Contains materials that may cause moderate skin injury (reddening and

swelling) and/or sensitizations. Prolonged contact may cause blister formation (burns). Since irritation may not

occur immediately, contact can go unnoticed.

**Ingestion:** No specific information available. Contains materials that may be practically nontoxic.

Inhalation: No specific information available. Low volatility makes vapor inhalation unlikely. Aerosol can be irritating. Sub-Chronic Effects: No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime

skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section 11, Toxicological Information for Details

### **SECTION 4: FIRST AID MEASURES**

First Aid for Eye: Flush with plenty of water for 15 minutes and seek medical attention.

First Aid for Skin: Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

**First Aid for Ingestion:** If appreciable quantities are swallowed, seek medical attention.

PAGE 1 OF 5

FILE NO.: 239709



## INTEGRITY WHITE GEL

First Aid for Inhalation: In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing

has stopped, administer artificial respiration and seek medical attention.

#### **SECTION 5: FIRE-FIGHTING MEASURES**

Flash Point (°F/°C)	Flammable Limit (vol %)	Auto-ignition Temperature (vol %)
>212°F/100°C	No Data	No Data

Method:

Extinguishing Media: Use carbon dioxide or dry chemical for small fires, aqueous foam or water for large fires. Fire Fighting Instructions: Remove all ignition sources. Wear self-contained breathing apparatus and complete personal

protective equipment when entering confined areas where potential for exposure to vapors or

products of combustion exists.

Unusual Hazards:

High temperatures and fire conditions may cause rapid and uncontrolled polymerization

which can

result in explosions and the violent runture of storage vessels or containers. Avoid the use of a

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill or Release Procedures Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detergent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer!! US Regulations (CERCLA) require reporting spills and releases to soil, water, and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washing from entering waterways.

#### **SECTION 7: HANDLING AND STORAGE**

Handling: Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged

exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of an increased penetration potential. When handling gel for product use, do not heat above 100°F/38°C or disassociation of silica in product may occur. Material is UV

light sensitive, avoid prolonged exposure to light/heat.

Storage: Store in a cool place, away from heat and light. Store at temperatures below 100°F/38°C.

Explosion Hazard: High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the

violent rupture of storage vessels or containers.

#### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

Engineering Controls: Local exhaust recommended to control exposure which may result from operations generating aerosols and hot

operations generating vapors.

\*-NIOSH Exposure limits for silicone Dioxide=6mg/m³ TWA, 3000 mg/m³ IDLH

**Personal Protective Equipment** 

General: To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard

assessment in accordance with OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than

PVC

Eye/Face Protection: Wear chemical splash goggles. Contact lenses should not be worn.

Skin Protection: Wear impervious gloves (Butyl rubber, Neoprene, and/or Nitrile).

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be

permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29CFR1910.134, or European Standard EN149.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**FILE NO.:** 239709



## **INTEGRITY WHITE GEL**

Appearance	Odor & Odor Threshold	pН	Specific Gravity	Viscosity	% Volatile
White, high viscous	Characteristic acrylate odor	N/A	(H2O=1): 1.15	N/DA	By Volume : <0.5
liquid					

Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure	Vapor Density	Evaporation Rate	Ignition	Solubility in Water (20°C)
N/A	N/A	N/A	(mm Hg) @ 20°C:<0.01	No Data	No Data	No Data	Insoluble

Flash Point (°F/°C)	Flammable Limit (vol %)	Auto-ignition Temperature (vol %)
>212°F/100°C Setaflash	No Data	No Data

## **SECTION 10: STABILITY AND REACTIVITY**

Stability: Normally Stable

#### **Hazardous Decomposition Products:**

Fumes produced when heated to decomposition may include:

Carbon monoxide, carbon dioxide.

Incompatibility (Materials to Avoid)

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust, and string bases.

Hazardous Polymerization: May occur—Uncontrolled polymerization may cause rapid evolution of Heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

Conditions to Avoid: Storage >100°F, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation-Skin	Irritation-Eye
No information available	No information available	No information available	No information available	No information available
Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers.				
Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.				

Sensitization	Mutagenicity	Sub-Chronic Toxicity
N/DA	N/DA	N/DA

### **SECTION 12: ECOLOGICAL INFORMATION**

#### **Ecotoxicological Information**

Acute Toxicity to Fish	Acute Toxicity to Invertibrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

#### Chemical Fate Information

One micar rate information		
Biodegradability	N/DA	
Chemical Oxygen Demand	N/DA	

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations. Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

## **SECTION 14: TRANSPORT INFORMATION**

DOT (49 CFR 172)	
DO: (10 01 11 11 2)	

**FILE NO.:** 239709



# **INTEGRITY WHITE GEL**

Proper Shipping Name:	Non-Regulated Material
Identification #	N/A
Marine Pollutant:	No
Special Provisions:	N/A
Emergency Response Guidebook (ERG) #	N/A
IATA (DRG)	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Packaging Instructions:	
Emergency Response Guidance (ICAO) #:	
IMO (IMDG)	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number	N/A
Special Provisions & Stowage/Segregation	None
Emergency Schedule (EmS) #:	
Other Information	Flash point >100°C

# SECTION 15: REGULATORY INFORMATION

## **US Federal Regulations**

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP and ODS's), as defined by the U.S. Clean Air Act:	
	Benzophenone (SOCMI Chemical)	
Olean Water Act Bulletin Belletent		
Clean Water Act: Priority Pollutant	Pollutant This product contains no chemicals listed under the U.S. Clean Water Act Priority Pollutant List.	
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and/or other applications as an	
	indirect food additive.	
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard.	
	Its hazards are:	
	Immediate (acute) health hazard.	
	Delayed (chronic) health hazard.	
	Reactive hazard.	
RCRA		
110111	This product is not considered to be a hazardous waste under RCRA (40 CRF 261)	
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Section 302 as extremely hazardous substances.	
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 304 as extremely hazardous chemical for	
	emergency release notification ("CERLA" List).	
SARA Title III: Section 311-312	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated	
	under Section 311-312 (40 CFR 370). Its hazards are:	
	Immediate (acute) health hazard.	
	Delayed (chronic) health hazard.	
	Reactive hazard.	
SARA Title III: Section 313	This product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the	
SARA TILIE III. SECLIOII 313	, , , , , , , , , , , , , , , , , , , ,	
T004 0 41 0 41 1 4	Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.	
TSCA Section 8 (b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA	
	premanufacture notification requirements.	
TSCA Significant New Use Rule:	None of the chemicals listed have a SNUR under TSCA.	

### **State Regulations**

CA Right-to-Know Law:	Silicon Dioxide CAS# 7631-86-9
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Titanium Dioxide CAS # 13463-67-7, Silicon Dioxide CAS# 7631-86-9
NJ Right-to-Know Law:	Titanium Dioxide CAS # 13463-67-7, Silicon Dioxide CAS# 7631-86-9
PA Right-to-Know Law:	Titanium Dioxide CAS # 13463-67-7, Silicon Dioxide CAS# 7631-86-9
FL Right-to-Know Law:	Titanium Dioxide CAS # 13463-67-7, Silicon Dioxide CAS# 7631-86-9
MN Right-to-Know Law:	Benzophenone CAS# 119-61-9, Titanium Dioxide CAS# 13463-67-7, Silicon Dioxide CAS# 7631-86-9

## SECTION 15: REGULATORY INFORMATION-cont.

**FILE NO.:** 239709



# **INTEGRITY WHITE GEL**

## **International Regulations**

CDSL: Canadian Inventory (on Canadian Transitional List

Titanium dioxide CAS# 13463-67-7 is on the DSL List. WHMIS = n/da Benzophenone CAS# 11-61-9 is on the DSL List. WHMIS = n/da

Hydroxycyclohexyl phenyl ketone CAS#947-19-3 is on the DSL List. WHMIS = n/da Tripropylene Glycol Diacrylate Esters (TPGDA) CAS# 42978-66-5 is on the DSL List. WHMIS=n/da Silicon dioxide CAS# 60676-86-0 is on the DSL List. WHMIS = n/da

**EINECS: European Inventory** 

#### **Integrity Colored Gel-Pluto:**


- HAZARD SYMBOLS: Xi: Irritant
- RISK PHRASES: R22: Harmful if swallowed, R36/38: Irritating to eyes and skin, R43: May cause sensitization by skin contact
- SAFETY PHRASES: \$18: Handle and open container with care, \$24/25: avoid contact with skin and eyes, \$36/37: Wear suitable protective clothing and gloves, \$38: in case of insufficient ventilation, wear suitable respirator equipment.


# SECTION 16: OTHER INFORMATION

OSHA PEL for nuisance dust:

15mg/m³ (total dust) 5mg/m³ (respirable dust)

ACGIH PEL for nuisance dust: 10 mg/m<sup>3</sup>





**DISCLAIMER:** The information presented herin was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers' intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage, or expense arising out of any way connected with the handling, storage, use, or disposal of this product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (800) 535-5053.