



MATERIAL SAFETY DATA SHEET

Version Number: 1

Preparation date: 2008-03-06

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: JACKHAMMER Baseboard and Buildup Stripper
MSDS #: MS0400131
Product Code: 4966777
Recommended use: Industrial/Institutional. Floor care.

Manufacturer, importer, supplier:

US Headquarters
The Butcher Company
8310 16th St.
Sturtevant, Wisconsin 53177-0902
Phone: 1-800-225-9475
MSDS Internet Address:
www.thebutchercompany.com

Emergency telephone number: 1-800-228-5635 (Prosar); 1-651-917-6133 (Int'l Prosar); 01-800-710-3400 (México)

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

- DANGER
- CORROSIVE
- CAUSES SKIN AND EYE BURNS
- HARMFUL OR FATAL IF SWALLOWED

Principle routes of exposure:

Eye contact. Skin contact. Inhalation.

Eye contact:

Corrosive. Causes permanent eye damage, including blindness.

Skin contact:

Corrosive. Causes permanent damage.

Inhalation:

May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion:

Corrosive. Causes burns to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous ingredients**

Ingredient(s)	CAS #	Weight %
Benzyl alcohol	100-51-6	0.1 - 1.5%
2-butoxyethanol	111-76-2	1 - 5%
Diethylene glycol butyl ether	112-34-5	1 - 5%
Potassium hydroxide	1310-58-3	1 - 5%
Monoethanolamine	141-43-5	1 - 5%
Isobutane	75-28-5	3 - 7%

4. FIRST AID MEASURES**Eye contact:**

Immediately flush eyes with running water for 15-20 minutes, keeping eyelids open. Get medical attention immediately.

Skin contact:

Immediately flush with plenty of water for 15-20 minutes. Get medical attention immediately.

Inhalation:

If breathing is affected, remove to fresh air. Get medical attention immediately.

Ingestion:

If swallowed, rinse mouth. Give a cupful of water or milk. THEN IMMEDIATELY CONTACT A PHYSICIAN OR POISON CENTER. DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Aggravated Medical Conditions:

Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Use dry chemical, CO₂, water spray or "alcohol" foam.

Extinguishing media which must not be used for safety reasons:

No information available

Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Specific hazards: Aerosol product - Containers may rocket or explode in heat of fire. NFPA 30B Level 1 Aerosol .

Unusual hazards: Corrosive material (See sections 8 and 10).

Specific methods: Aerosol Product - Containers may rocket or explode in heat of fire. Use water spray to keep fire-exposed containers cool.

NFPA

Health: 3

Flammability: 4

Instability: 0

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Put on appropriate personal protective equipment (see Section 8.).

Environmental precautions and clean-up methods:

No information available

7. HANDLING AND STORAGE

Handling:

Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage:

Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection:

Chemical-splash goggles.

Hand protection:

Chemical-resistant gloves

Skin and body protection:

Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear.

Respiratory protection:

In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice

Ingredient(s)	ACGIH	OSHA	Mexico
2-butoxyethanol	20 ppm (TWA)	Skin 240 mg/m ³ (TWA) 50 ppm (TWA)	75 ppm (STEL) 360 mg/m ³ (STEL) 26 ppm (TWA) 120 mg/m ³ (TWA)
Potassium hydroxide	2 mg/m ³ (Ceiling)		
Monoethanolamine	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m ³ (TWA)	6 ppm (STEL) 15 mg/m ³ (STEL) 3 ppm (TWA) 8 mg/m ³ (TWA)
Isobutane	1000 ppm (TWA)		


HMIS

Health 3

Fire Hazard 4

Reactivity 0

Personal protective equipment



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Aerosol

Color: Clear White

pH: 13.0

Specific gravity: 0.99

Bulk density: No information available

Evaporation Rate: No information available

Solubility: completely soluble

Solubility in other solvents: No information available

Partition coefficient (n-octanol/water): No information available

Appearance: Aerosol

Odor: Solvent

Dilution pH: No information available.

Density: 8.24 lbs/gal

Vapor density: No information available

Viscosity: No information available

VOC: 10.75% *

Boiling point/range:	Not determined
Melting point/range:	Not determined
Flash point:	<20 (Propellant) ^{°F} <-7 ^{°C}
Decomposition temperature:	Not determined
Autoignition temperature:	No information available
Elemental Phosphorus:	0.11 %P

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Stability:	The product is stable
Polymerization:	Hazardous polymerization does not occur
Materials to avoid:	Acids. Metals.
Conditions to avoid:	Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products:	None reasonably foreseeable.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients

Ingredient(s)	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
Benzyl alcohol	1230	2000 mg/kg	8.8 mg/L (4 h)
2-butoxyethanol	470	220 mg/kg	2.21 mg/L (4 h); 450 ppm (4 h)
Diethylene glycol butyl ether	4500	=2700 mg/kg	Not available
Potassium hydroxide	275	Not available	Not available
Monoethanolamine	1720	1 mL/kg	Not available
Isobutane	Not available	Not available	=658 mg/L (4 h)

Acute toxicity: Corrosive Oral LD50 estimated to be between 2000 - 3000 mg/kg Dermal LD50 estimated to be > 2000 mg/kg

Chronic toxicity: None known

Specific effects

Carcinogenic effects:	None known
Mutagenic effects:	None known
Reproductive toxicity:	None known
Target organ effects:	None known

12. ECOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION**Environmental Information:** No data available**13. DISPOSAL CONSIDERATIONS****Waste from residues / unused products:**

Dispose of according to all federal, state and local applicable regulations

14. TRANSPORT INFORMATION**DOT/TDG:** Please refer to the Bill of Lading/receiving documents for up to date shipping information**15. REGULATORY INFORMATION****International Inventories**

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations**California Proposition 65:** This product is not subject to the reporting requirements under California's Proposition 65**STATE RIGHT TO KNOW**

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Benzyl alcohol	100-51-6	X	X	X	-
2-butoxyethanol	111-76-2	X	X	X	X
Diethylene glycol butyl ether	112-34-5	-	X	X	-
Potassium hydroxide	1310-58-3	X	X	X	X
Monoethanolamine	141-43-5	X	X	X	X
Water	7732-18-5	-	-	-	-
Ethoxylated secondary alcohol	84133-50-6	-	-	-	-
Isobutane	75-28-5	X	X	X	-

CERCLA/ SARA

Ingredient(s)	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
2-butoxyethanol 111-76-2	1 - 5%			X
Diethylene glycol butyl ether 112-34-5	1 - 5%			X
Potassium hydroxide 1310-58-3	1 - 5%	1000		

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Diethylene glycol butyl ether 112-34-5	X		

SARA 311/312 Hazard Categories

Immediate: X
Delayed: -
Fire: X
Reactivity: -
Sudden Release of Pressure: X

Canada**WHMIS hazard class:** E Corrosive material , A Compressed gases.**16. OTHER INFORMATION****Reason for revision:** Not applicable**Prepared by:** NAPRAC

Additional advice:

None

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.