

SAFETY DATA SHEET

Revision Date: 02-May-2017 Revision Number: 1

PRODUCT AND COMPANY IDENTIFICATION

Product Name AURA WATERBORNE EXTERIOR LOW LUSTRE FINISH BASE 2

Product Code K6342X Alternate Product Code K6342X

Product Class WATER THINNED PAINT

Color All Recommended use Paint

Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited

8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.com

Manufacturer

Benjamin Moore & Co.

101 Paragon Drive Montvale, NJ 07645 Phone: 855-724-6802 www.benjaminmoore.com **Emergency Telephone Number(s)**

CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin sensitization	Category 1A
Carcinogenicity	Category 2

Label elements

Warning

Hazard statements

May cause an allergic skin reaction Suspected of causing cancer

Revision Date: 02-May-2017



Appearance liquid Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves

Precautionary Statements - Response

If exposed or concerned get medical attention **Skin**

If on skin wash with plenty of soap and water
If skin irritation or rash occurs get medical attention
Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

Other hazards

May cause allergic skin reaction

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Titanium dioxide	13463-67-7	10 - 30%
Nepheline syenite	37244-96-5	5 - 10%
Barium sulfate	7727-43-7	1 - 5%
Kaolin	1332-58-7	1 - 5%
Kaolin, calcined	92704-41-1	1 - 5%
Zinc oxide	1314-13-2	1 - 5%
Hexanedioic acid, dihydrazide	1071-93-8	0.25 - 0.5%
Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester	41556-26-7	0.25 - 0.5%
Sodium C14-C16 olefin sulfonate	68439-57-6	0.25 - 0.5%
Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-	330-54-1	0.1 - 0.25%
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimeth ylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegah ydroxy-	104810-48-2	0.1 - 0.25%

4. FIRST AID MEASURES

General Advice No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15

minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.

Revision Date: 02-May-2017

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of

water. Consult a physician if necessary.

Most Important Symptoms/Effects May cause allergic skin reaction.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective Equipment And Precautions For

Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

Flash Point Data

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Not applicable

Not applicable

Flammability Limits In Air

Lower Explosion LimitNot applicableUpper Explosion LimitNot applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

K6342X - AURA WATERBORNE EXTERIOR LOW **LUSTRE FINISH BASE 2**

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental Precautions See Section 12 for additional Ecological Information.

Soak up with inert absorbent material. Sweep up and **Methods For Clean-Up**

shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 02-May-2017

ventilation, wear suitable respiratory equipment.

Keep container tightly closed. Keep out of the reach of Storage

children.

No information available **Incompatible Materials**

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

No exposure limits have been established for this product.

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
Titanium dioxide	10 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m ³ - TWA	10 mg/m³ - TWA	10 mg/m ³ - TWAEV
			3 mg/m³ - TWA		
Nepheline syenite	N/E	N/E	N/E	10 mg/m³ - TWA	N/E
Barium sulfate	5 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m ³ - TWA	10 mg/m³ - TWA	10 mg/m ³ - TWAEV
			3 mg/m³ - TWA		5 mg/m³ - TWAEV
Kaolin	2 mg/m³ - TWA	5 mg/m³ - TWAEV			
Zinc oxide	2 mg/m³ - TWA	10 mg/m ³ - TWAEV			
	10 mg/m ³ - STEL	5 mg/m³ - TWAEV			
					10 mg/m ³ - STEV
Urea,	10 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m ³ - TWA	10 mg/m³ - TWA	10 mg/m ³ - TWAEV
N-(3,4-dichlorophenyl)-N,N-di					
methyl-					

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Skin Protection Respiratory Protection

Safety glasses with side-shields.

Protective gloves and impervious clothing.

In case of insufficient ventilation wear suitable respiratory

equipment.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash

Revision Date: 02-May-2017

thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 11.1 - 11.2

 Specific Gravity
 1.33 - 1.35

pH No information available Viscosity (cps) No information available

Solubility
No information available
Water Solubility
No information available
Evaporation Rate
No information available

Vapor PressureNo information availableVapor DensityNo information available

 Wt. % Solids
 55 - 65

 Vol. % Solids
 40 - 50

 Wt. % Volatiles
 35 - 45

 Vol. % Volatiles
 50 - 60

VOC Regulatory Limit (g/L) < 50
Boiling Point (°F) 212
Boiling Point (°C) 100
Freezing Point (°F) 32
Freezing Point (°C) 0

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Flammability (solid, gas)

Upper Explosion Limit

Lower Explosion Limit

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)

Autoignition Temperature (°C)

Decomposition Temperature (°F)

Decomposition Temperature (°C)

No information available

10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions To Avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility Of Hazardous Reactions None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

K6342X - AURA WATERBORNE EXTERIOR LOW LUSTRE FINISH BASE 2

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Information on toxicological effects

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation

Skin contact Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

Revision Date: 02-May-2017

Inhalation May cause irritation of respiratory tract.

Ingestion Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Sensitization: May cause an allergic skin reaction.

Neurological Effects No information available. **Mutagenic Effects** No information available. **Reproductive Effects** No information available. **Developmental Effects** No information available. **Target Organ Effects** No information available. No information available. STOT - single exposure STOT - repeated exposure No information available. Other adverse effects No information available. **Aspiration Hazard** No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 10189 mg/kg ATEmix (inhalation-dust/mist) 42.7 mg/L

Component

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)

Barium sulfate

LD50 Oral: > 5,000 g/kg (Rat) vendor data

Kaolin

LD50 Oral: > 5000 mg/kg (Rat)

Kaolin, calcined

LD50 Oral: > 5000 mg/kg (Rat) vendor data

Zinc oxide

LD50 Oral: 5000 mg/kg (Rat)

LC50 Inhalation (Dust): > 5700 mg/m³ (Rat, 4 hr.)

Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester

Sensitization:

May cause sensitization by skin contact

Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-

LD50 Oral: 1017 mg/kg (Rat) LD50 Dermal: > 5000 mg/kg (Rat)

K6342X - AURA WATERBORNE EXTERIOR LOW LUSTRE FINISH BASE 2

Poly(oxy-1,2-ethanediyl),

.alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-

Sensitization:

May cause sensitization by skin contact

Revision Date: 02-May-2017

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP
	2B - Possible Human Carcinogen	
Titanium dioxide	_	

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

K6342X - AURA WATERBORNE EXTERIOR LOW LUSTRE FINISH BASE 2

<u>Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-</u> LC50: 3.5 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 02-May-2017

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States

PSL: Canada

Yes - All components are listed or exempt.

No - Not all of the components are listed.

One or more component is listed on NDSL.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

 Chemical Name
 CAS-No
 Weight % (max)
 NPRI Parts 1- 4

 Zinc oxide
 1314-13-2
 1 - 5%
 Listed

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

Revision Date: 02-May-2017

16. OTHER INFORMATION

HMIS -Health: 1* Flammability: 0 Reactivity: 0 PPE: -

HMIS Leaend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked questions-questions posees-eng.php.

Product Stewardship Department Prepared By

> Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

855-724-6802

02-May-2017 **Revision Date:** Not available **Reason For Revision**

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET