



KEL-TACK

MATERIAL SAFETY DATA SHEET

MSDS-5-030

20000 176th Street NW
Big Lake, MN 55309
TOLL FREE PHONE:
1.800.328.7720

Emergency Phone: CHEMTREC 1.800.424.9300, INTERNATIONAL (202)483.7616

SECTION I - PRODUCT IDENTIFICATION.

Product Name: **KELTACK**
Product Use: **SUNDRY EMBALMING**
Chemical Family: **N/A**
Whmis Classification: **NOT REGULATED**
TDG Hazard Class: **NOT REGULATED**

SECTION II - HAZARDOUS INGREDIENTS

<u>Ingredients</u>	<u>Cas#</u>	<u>wt.%</u>	<u>LC50</u> (Rat.lhl)	<u>LD50</u> (Rat.oral)	<u>LD50</u> (rbt.skin)
Paraffin Oil	8012-95-1	80	n/a	n/a	n/a

SECTION III - PHYSICAL DATA

Boiling Point:	n/a	Specific Gravity (H2O=1):	n/a
Vapour Pressure (mm hg):	n/a	Volatile %:	n/a
Vapour Density (air=1):	n/a	Evaporation Rate (BuAe=1):	n/a
Solubility in water:	n/a	Ph:	n/a
Coeff. water/oil dist:	n/a	Freezing Point:	49 C
Appearance & odour:	purple, soft sticky wax, mild odour	Odour Threshold:	n/a

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability: **YES** Combustible solid
Flash Point: 193C
Upper Explosion Limit: n/a
Lower Explosion Limit: n/a
Auto Ignition Temp: 245C
Hazardous Combustion Products: none
Explosion Data: none
Rate of Burning: n/a
Explosive Power: none
Sensitivity to Static Discharge: n/a
Means of Extinction: Carbon dioxide, dry chemical, water spray.
Special Fire Fighting Procedures: Wear self-contained breathing apparatus and complete personal protective equipment.

SECTION V - REACTIVITY DATA

Stability: stable
Incompatibility: Strong oxidizing agents.
Hazardous Polymerization: Will not occur
Conditions to Avoid: Keep away from heat, sparks and flames
Hazardous Decomposition: Carbon dioxide

SECTION VI - TOXICOLOGICAL PROPERTIES

*****OCCUPATIONAL EXPOSURE LIMITS*****

Exposure Limit: Paraffin Oil (TLV-C) n/a (TLV-STEL) 10 mg/m³
(TLV-TWA) 5 mg/m³

Inhalation: May cause irritation or injury.

Eye Contact: Causes irritation.

Skin: May cause irritation.

Ingestion: n/a.

SECTION VII - FIRST AID

Inhalation: Move victim to fresh air, contact physician.

Eye Contact: Flush eyes with lukewarm water. If irritation persists, obtain medical attention immediately.

Skin Contact: Wash contaminated skin. If irritation persists contact physician.

Ingestion: Do not induce vomiting. Have victim drink large amounts of water. Contact physician immediately.

SECTION VIII - PREVENTIVE MEASURES

Spill and Leak Procedures: Use absorbent material and place in closed pail.

Waste Disposal: None.

****Personal Protective Equipment****

Respiratory protection: None required.

Protective Gloves: Neoprene or latex recommended.

Eye Protection: Chemical safety goggles should be worn to prevent eye contact.

Other Protective equipment: None.

Ventilation: Local exhaust.

****Storage and Handling****

Handling: Do not store below 5C or above 49C.

Storage: The hazard potential of this material is relatively low. General ventilation is usually sufficient.

SECTION IX - ADDITIONAL INFORMATION

Abbreviations:	TLV:	Threshold Limit Values	STEL:	Short-term Exp. Level
	TWA:	8 hr Time-Weighted Average		
	ACGIH:	American Conference of Governmental Industrial Hygienists 1993-94		
	OSHA:	Occupational Safety and Health Administration		
	N/A:	Not Available		

SECTION X - PREPARATION INFORMATION

Date: May 9