



# Lubegard Kooler Kleen Transmission Flush

## Safety Data Sheet

According to OSHA HazCom 2012

Date of issue: March 14, 2014

Revision date: February 13, 2018

Version: 1.2

## SAFETY DATA SHEET

### 1. Product and Company Identification

**Product Name:** Kooler Kleen Transmission Flush

**Product Code:** 19001, 19009, 19111

**Product Type:** Aerosol

**Product Use:** Transmission Flush

**Manufacturer:** International Lubricants, Inc.

**Address:** 7930 Occidental Ave S

Seattle, WA 98108

Phone: (206) 762-5343

**Emergency Phone** Chemtel: (800) 255-3924  
(813) 248-0585

**NOTE:** The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

### 2. Hazard Identification

#### Classification of substance or mixture:

Extremely Flammable Aerosol	Category 1
Gases under pressure	Compressed gas
Aspiration hazard	Category 1
Eye Irritation	Category 2A
STOT – Single Exposure	Category 3 (Central Nervous System)

#### GHS Label elements:

##### Pictograms



**Signal Word:** Danger

#### Hazard Statement(s)

H222 Extremely Flammable Aerosol  
H280 Gases under pressure; may explode if heated  
H304 May be fatal if swallowed and enters airways



# Lubegard Kooler Kleen Transmission Flush

## Safety Data Sheet

According to OSHA HazCom 2012

Date of issue: March 14, 2014

Revision date: February 13, 2018

Version: 1.2

- H319 Causes serious eye irritation
- H336 May cause drowsiness or dizziness

### Precautionary Statements:

#### Prevention

- P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing fume/mist/vapours/spray
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated place.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

- P301+P310 If Swallowed: Immediately call a poison Center/doctor/physician
- P331 Do not induce vomiting
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a poison center/doctor if you feel unwell.
- P305+P351  
+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep canter tightly closed.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F
- P501 Dispose of contents/container in accordance with local/regional regulations.

### 3. Composition information on ingredients

Ingredients	CAS #	Percent
Light Distillate	64742-47-8	60-80%
Stoddard Solvent	8052-41-3	10-20%
Isopropanol	67-63-0	7-13%
Carbon Dioxide	124-38-9	1-5%
Dimethylpolysiloxane	63148-62-9	<0.1%

### 4. First Aid Measures

#### Eye Contact:

Immediately flush with warm water for 15 minutes. Keep eye wide open while rinsing. If irritation persist seek medical attention.



# Lubegard Kooler Kleen Transmission Flush

## Safety Data Sheet

According to OSHA HazCom 2012

Date of issue: March 14, 2014

Revision date: February 13, 2018

Version: 1.2

### **Skin Contact:**

Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.

### **Inhalation:**

Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.

### **Ingestion:**

Do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

## **5. Fire Fighting Measures**

**Flash Point:** Flash point of propellant <0 degrees F.

### **Flammable limits in air, % by volume:**

**Upper: Unknown**

**Lower: Unknown**

### **Extinguishing Media:**

Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

### **Unusual Fire & Explosion Hazards:**

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.

### **Special Fire Fighting Procedures:**

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

## **6. Accidental Release Measures**

### **Spill or Leak Instructions**

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas.



# Lubegard Kooler Kleen Transmission Flush

## Safety Data Sheet

According to OSHA HazCom 2012

Date of issue: March 14, 2014

Revision date: February 13, 2018

Version: 1.2

Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

## 7. Handling and Storage

### Handling:

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

### Storage:

Store in a cool, dry area, away form heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

## 8. Exposure Controls / Personal Protection

### Protective Equipment:

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

### Engineering Controls:

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

### Respiratory Protection:

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above 1000 ppm, an approved self-contained breathing apparatus or airline respirator with full face-piece is required

### Other Suggested Equipment:

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

### Discretion Advised:

We. take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.



# Lubegard Kooler Kleen Transmission Flush

## Safety Data Sheet

According to OSHA HazCom 2012

Date of issue: March 14, 2014

Revision date: February 13, 2018

Version: 1.2

### Exposure guidelines:

Ingredients	CAS #	Exposure Limits
Light Distillate	64742-47-8	Supplier (TWA) 100 ppm 8h (1)
Stoddard Solvent	8052-41-3	ACGIH (TLV) 100 ppm 8h OSHA PEL (TWA) 500 ppm 8h
Isopropanol	67-63-0	ACGIH (TWA) 200 ppm OSHA Z-1 (TWA) 400 ppm
Carbon Dioxide	124-38-9	ACGIH (TWA) 9000 mg/m <sup>3</sup> 10 h OSHA PEL (TWA) 9000 mg/m <sup>3</sup> 8h
Dimethylpolysiloxane	63148-62-9	NE

(1) Supplier Recommended

## 9. Physical and Chemical Properties

**Appearance:** Clear mist as dispensed from aerosol can.

**Evaporation Rate:** Ether = 1 Slower

**PH:** NA

**Initial Boiling point and boiling range:** NE

**Flammability:** NA

**Vapor density** >1 (Air=1)

**Relative density** NE

**Partition coefficient:** NE

**Decomposition temperature:** NE

**Flammable limits in air, % by volume:**

**Upper:**NE

**Lower:**NE

**Odor:** Ether like

**Melting/Freezing point:** NE

**Flash Point:** Flash point of propellant <0°F

**Vapor pressure:** >30 psi

**Solubility:** negligible

**Auto-ignition temperature:** NE

**Viscosity:** NA

## 10. Stability and Reactivity

**Stability:** Stable

**Conditions to Avoid:** Heat, spark, and open flame

**Incompatibility:** Strong-Oxidizing Agents

**Hazardous Decomposition:** Combustion will produce Carbon Monoxide, Carbon Dioxide and nitrogen-oxygen compounds.

**Hazardous Polymerization:** Will not occur

## 11. Toxicological Information

### Component Toxicological Information:

#### Acute oral toxicity

Light Distillate

LD50 Rat >5000mg/k



# Lubegard Kooler Kleen Transmission Flush

## Safety Data Sheet

According to OSHA HazCom 2012

Date of issue: March 14, 2014

Revision date: February 13, 2018

Version: 1.2

Dimethylpolysiloxane	LD50 Rat >5,000 mg/k
Isopropanol	LD50 Rat >5,500 mg/kg
<b>Acute inhalation toxicity</b>	
Light Distillate	LC50 Rat > 6.8 mg/l 4h
Isopropanol	LC50 Rat >10,000 ppm 6h
<b>Acute dermal toxicity</b>	
Light Distillate	LD50 Rabbit 2000-4000 mg/k
Dimethylpolysiloxane	LD50 Rat >2,000 mg/kg
Isopropanol	LD50 Rabbit > 12,800 mg/kg

## 12. Ecological Information

### Isopropanol:

Toxicity to fish LC 50 (pimephales promelas (fatheadminnow)): 9,640 mg/l Exposure 96h  
Toxicity to daphania and  
Other aquatic invertebrates EC50 (Daphnia magna (water flea)): . 10,000 mg/l exposure 24h

No other data

## 13. Disposal Considerations

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

## 14. Transport Information

Aerosols (limited quantity),  
Class 2.1, ERG 126

AIR (IATA)  
Aerosols (limited quantity),  
Class 2.1, ERG 126, UN No. 1950  
Vessel

Aerosol (Limited Quantity), Class 2.1, UN No 1950

## 15. Regulatory Information

### Environmental Regulations



# Lubegard Kooler Kleen Transmission Flush

## Safety Data Sheet

According to OSHA HazCom 2012

Date of issue: March 14, 2014

Revision date: February 13, 2018

Version: 1.2

### SARA 302/304:

None

### SARA 311/312:

Immediate ( x ) Delayed ( ) Fire ( x ) Reactive ( ) Sudden Release of Pressure ( x )

### Section 313

This product contains: None reportable

### California Prop 65

None

All the chemicals used in this product are TSCA listed.

Check with your local regulators to be sure all local regulations are met.

## 16. Other Information

**Hazard ratings** This information is intended solely for the use of individuals trained in the NFPA and/or HMIS systems.

**NFPA:** Level 3 Aerosol

**HMIS:** Health: 2 Flammability: 4 Reactivity: 0

**RATING:** 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

### Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.