

SAFETY DATA SHEET

1263

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name LESS THAN 100 PPM (MOISTURE), BALANCE OXYGEN

Synonym(s) 1263 - SDS NUMBER • PRODUCT CODE: 292 • SPECIAL GAS MIXTURE

1.2 Uses and uses advised against

Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS

1.3 Details of the supplier of the product

Supplier name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA

Telephone 131 262, (02) 8874 4400

Fax 132 427 (24 hours)

Website http://www.boc.com.au

1.4 Emergency telephone number(s)

Emergency 1800 653 572 (24/7) (Australia only)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

GHS classification(s) Oxidizing Gases: Category 1

Gases Under Pressure: Compressed gas

2.2 Label elements

Signal word DANGER

Pictogram(s)





Hazard statement(s)

H270 May cause or intensify fire; oxidizer.

H280 Contains gas under pressure; may explode if heated.

Prevention statement(s)

P220 Keep/Store away from clothing/incompatible materials/combustible materials.

P244 Keep reduction valves free from grease and oil.

Response statement(s)

P370 + P376 In case of fire: Stop leak if safe to do so.

Storage statement(s)

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal statement(s)

None allocated.



SDS Date: 13 May 2015

PRODUCT NAME LESS THAN 100 PPM (MOISTURE), BALANCE OXYGEN

2.3 Other hazards

No information provided.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content (v/v)
OXYGEN	7782-44-7	231-956-9	Remainder
MOISTURE	-	-	<0.01%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Adverse effects not expected from this product. Eye

If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. For advice, contact a Inhalation

Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin Adverse effects not expected from this product.

Due to product form and application, ingestion is considered unlikely. Ingestion

First aid facilities No information provided.

4.2 Most important symptoms and effects, both acute and delayed

Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty and convulsion.

4.3 Immediate medical attention and special treatment needed

Treatment for hyperoxia.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use water fog to cool containers from protected area.

5.2 Special hazards arising from the substance or mixture

Non flammable - oxidising agent. Supports combustion and may cause fire/explosion in contact with incompatible substances, strong acids, reducing agents, combustibles and flammables. Materials which burn in air, will burn more vigorously in oxygen enriched atmospheres.

5.3 Advice for firefighters

Temperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be activated. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot. Remove cool cylinders from the path of the fire if safe to do so. Ensure working area is well ventilated before re-use. Notify the manufacturer that you will be returning a faulty cylinder. Residual product will be disposed of when the cylinder is returned.

5.4 Hazchem code

2S

2 Fine Water Spray.

S Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Dilute spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use Personal Protective Equipment (PPE) as detailed in Section 8 of the SDS.

6.2 Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.3 Methods of cleaning up

Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.

Page 2 of 6

ChemAlert.

SDS Date: 13 May 2015

PRODUCT NAME LESS THAN 100 PPM (MOISTURE), BALANCE OXYGEN

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

7.2 Conditions for safe storage, including any incompatibilities

Do not store near sources of ignition or incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

No exposure standards have been entered for this product.

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls No special precautions are normally required when handling this product.

PPE

Eye / Face Wear safety glasses. Hands Wear leather gloves. **Body** Wear safety boots.

Respiratory Not required under normal conditions of use.







9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

COLOURLESS GAS Appearance Odour **ODOURLESS Flammability** NON FLAMMABLE Flash point NOT RELEVANT **Boiling point** -183°C (Oxygen) **Melting point** NOT AVAILABLE **Evaporation rate** NOT APPLICABLE pН NOT APPLICABLE Vapour density 1.105 (Oxygen) (Air = 1) Specific gravity **NOT APPLICABLE** Solubility (water) 0.032 cm³/cm³ (Oxygen) Vapour pressure **NOT AVAILABLE Upper explosion limit NOT RELEVANT** Lower explosion limit **NOT RELEVANT Partition coefficient NOT AVAILABLE Autoignition temperature NOT AVAILABLE** Decomposition temperature **NOT AVAILABLE**

> SDS Date: 13 May 2015 Page 3 of 6



PRODUCT NAME LESS THAN 100 PPM (MOISTURE), BALANCE OXYGEN

9.1 Information on basic physical and chemical properties

NOT AVAILABLE **Viscosity Explosive properties** NOT AVAILABLE **Oxidising properties** OXIDISING GAS **NOT AVAILABLE Odour threshold**

9.2 Other information

Critical temperature -118.6°C (Oxygen) Cylinder pressure (when full) 13,000 kPa @ 15°C

% Volatiles 100 %

Critical pressure 5,043 kPa (Oxygen)

10. STABILITY AND REACTIVITY

10.1 Reactivity

Unreactive under normal conditions.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Combustible materials such as oil and grease can spontaneously ignite at low temperatures in oxygen enriched atmospheres. Materials which burn in air, will burn more vigorously in oxygen enriched atmospheres.

10.6 Hazardous decomposition products

This material will not decompose to form hazardous products other than that already present.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Based on available data, the classification criteria are not met. Acute toxicity

Not classified as a skin irritant. Skin Not classified as an eye irritant. Eve

Not classified as causing skin or respiratory sensitisation. Sensitization

Not classified as a mutagen. Mutagenicity Carcinogenicity Not classified as a carcinogen. Not classified as a reproductive toxin. Reproductive

STOT - single Not classified as causing organ effects from single exposure.

exposure

STOT - repeated exposure

Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty

Page 4 of 6

and convulsion.

Aspiration Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No ecological damage caused by this product.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

ChemAlert.

SDS Date: 13 May 2015

PRODUCT NAME LESS THAN 100 PPM (MOISTURE), BALANCE OXYGEN

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE





	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)	
14.1 UN Number	3156	3156	3156	
14.2 Proper Shipping Name	COMPRESSED GAS, OXIDIZING, N.O.S. (CONTAINS OXYGEN)	COMPRESSED GAS, OXIDIZING, N.O.S. (CONTAINS OXYGEN)	COMPRESSED GAS, OXIDIZING, N.O.S. (CONTAINS OXYGEN)	
14.3 Transport hazard classes	2.2, 5.1	2.2, 5.1	2.2, 5.1	
14.4 Packing Group	None Allocated	None Allocated	None Allocated	

14.5 Environmental hazards No information provided

14.6 Special precautions for user

 Hazchem code
 2S

 GTEPG
 2B1

 EMS
 F-C, S-W

Other information Ensure cylinder is separated from driver and foodstuffs. Refer to Commonwealth, State and Territory

Dangerous Goods Legislation which contain requirements which affect gas storage and transport.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the

Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Page 5 of 6

Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous

Substances [NOHSC: 1008(2004)].

Hazard codes O Oxidising

Risk phrases R8 Contact with combustible material may cause fire.

Safety phrases S2 Keep out of reach of children.

S17 Keep away from combustible material.

Inventory listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

ChemAlert.

SDS Date: 13 May 2015

16. OTHER INFORMATION

Additional information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS# Chemical Abstract Service number - used to uniquely identify chemical compounds

Central Nervous System **CNS**

EC No. EC No - European Community Number

Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous **EMS**

Goods)

GHS Globally Harmonized System

Group Text Emergency Procedure Guide **GTEPG** International Agency for Research on Cancer IARC

Lethal Concentration, 50% / Median Lethal Concentration LC50

Lethal Dose, 50% / Median Lethal Dose LD50

mg/m³ Milligrams per Cubic Metre OEL Occupational Exposure Limit

pΗ relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure) STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia TLV Threshold Limit Value **TWA** Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au.

[End of SDS]

ChemAlert.

SDS Date: 13 May 2015