

---

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

---

### 1.1 Product identifier

**Product name** LESS THAN 50% CARBON DIOXIDE BALANCE ARGON  
**Synonym(s)** 1197 - SDS NUMBER • PRODUCT CODE: 285, 288 • SAM31023 - MATERIAL NUMBER • SPECIAL GAS MIXTURE

### 1.2 Uses and uses advised against

**Use(s)** CALIBRATION • INDUSTRIAL APPLICATIONS

### 1.3 Details of the supplier of the product

**Supplier name** BOC LIMITED (AUSTRALIA)  
**Address** 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA  
**Telephone** 131 262, (02) 8874 4400  
**Fax** 132 427 (24 hours)  
**Website** <http://www.boc.com.au>

### 1.4 Emergency telephone number(s)

**Emergency** 1800 653 572 (24/7) (Australia only)

---

## 2. HAZARDS IDENTIFICATION

---

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

**GHS classification(s)** Gases Under Pressure: Compressed gas

### 2.2 Label elements

**Signal word** WARNING

**Pictogram(s)**



**Hazard statement(s)**

H280 Contains gas under pressure; may explode if heated.

**Prevention statement(s)**

None allocated.

**Response statement(s)**

None allocated.

**Storage statement(s)**

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

**Disposal statement(s)**

None allocated.

### 2.3 Other hazards

Asphyxiant. Effects are proportional to oxygen displacement.

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

#### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content (v/v)
ARGON	7440-37-1	231-147-0	>50%
CARBON DIOXIDE	124-38-9	204-696-9	<50%

### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

<b>Eye</b>	None required.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.
<b>Skin</b>	None required.
<b>Ingestion</b>	Due to product form and application, ingestion is considered unlikely.
<b>First aid facilities</b>	No information provided.

#### 4.2 Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation. Low concentrations of CO2 cause increased respiration and headache.

#### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

#### 5.1 Extinguishing media

Use water fog to cool containers from protected area.

#### 5.2 Special hazards arising from the substance or mixture

Non flammable.

#### 5.3 Advice for firefighters

Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Do not approach cylinders or containers suspected of being hot.

#### 5.4 Hazchem code

2TE	
2	Fine Water Spray.
T	Wear full fire kit and breathing apparatus. Dilute spill and run-off.
E	Evacuation of people in and around the immediate vicinity of the incident should be considered.

### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use Personal Protective Equipment (PPE) as detailed in Section 8 of the SDS.

#### 6.2 Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

#### 6.3 Methods of cleaning up

Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.

#### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

### 7.2 Conditions for safe storage, including any incompatibilities

Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

### 7.3 Specific end use(s)

No information provided.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Argon	SWA (AUS)	Asphyxiant			
Carbon dioxide	SWA (AUS)	5000	9000	30000	54000
Carbon dioxide in coal mines	SWA (AUS)	12500	22500	30000	54000

#### Biological limits

No biological limit values have been entered for this product.

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

#### PPE

- Eye / Face** Wear safety glasses.
- Hands** Wear leather gloves.
- Body** Wear safety boots.
- Respiratory** Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	COLOURLESS GAS
Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT APPLICABLE
pH	NOT APPLICABLE
Vapour density	NOT AVAILABLE
Specific gravity	NOT APPLICABLE
Solubility (water)	0.759 cm <sup>3</sup> /cm <sup>3</sup> (Carbon dioxide)
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE

**9.1 Information on basic physical and chemical properties**

<b>Autoignition temperature</b>	NOT AVAILABLE
<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT AVAILABLE
<b>Explosive properties</b>	NOT AVAILABLE
<b>Oxidising properties</b>	NOT AVAILABLE
<b>Odour threshold</b>	NOT AVAILABLE

**9.2 Other information**

<b>% Volatiles</b>	100 %
<b>Cylinder pressure (when full)</b>	13000 kPa @ 15°C

**10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

Carefully review all information provided in sections 10.2 to 10.6.

**10.2 Chemical stability**

Stable under recommended conditions of storage.

**10.3 Possibility of hazardous reactions**

Polymerization will not occur.

**10.4 Conditions to avoid**

Avoid contact with incompatible substances.

**10.5 Incompatible materials**

Moist carbon dioxide is corrosive, hence acid resistant materials are required (e.g. stainless steel). Certain properties of some plastics and rubbers may be affected by carbon dioxide (i.e. embrittlement, leaching of plasticisers, etc). Dust of aluminium, chrome, manganese may ignite then explode when heated in carbon dioxide. Incompatible with acrylaldehyde, aziridine, metal acetylides, sodium peroxide.

**10.6 Hazardous decomposition products**

This material will not decompose to form hazardous products other than that already present.

**11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Acute toxicity**

**Information available for the product:**

Based on available data, the classification criteria are not met. Low concentrations of carbon dioxide cause increased respiration and headache.

**Information available for the ingredient(s):**

Ingredient	Oral Toxicity (LD50)	Dermal Toxicity (LD50)	Inhalation Toxicity (LC50)
CARBON DIOXIDE	--	--	470000 ppm/30M (rat)

<b>Skin</b>	Not classified as a skin irritant.
<b>Eye</b>	Not classified as an eye irritant.
<b>Sensitisation</b>	Not classified as causing skin or respiratory sensitisation.
<b>Mutagenicity</b>	Not classified as a mutagen.
<b>Carcinogenicity</b>	Not classified as a carcinogen.
<b>Reproductive</b>	Not classified as a reproductive toxin.
<b>STOT – single exposure</b>	Asphyxiant. Effects are proportional to oxygen displacement. Over exposure may result in dizziness, drowsiness, weakness, fatigue, breathing difficulties and unconsciousness.
<b>STOT – repeated exposure</b>	Not classified as causing organ damage from repeated exposure.
<b>Aspiration</b>	Not classified as causing aspiration.

**12. ECOLOGICAL INFORMATION**

**PRODUCT NAME LESS THAN 50% CARBON DIOXIDE BALANCE ARGON****12.1 Toxicity**

No information provided.

**12.2 Persistence and degradability**

No information provided.

**12.3 Bioaccumulative potential**

No information provided.

**12.4 Mobility in soil**

No information provided.

**12.5 Other adverse effects**

When discharged to the atmosphere, carbon dioxide may contribute to the greenhouse effect.

**13. DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods****Waste disposal** Cylinders should be returned to the manufacturer or supplier for disposal of contents.**Legislation** Dispose of in accordance with relevant local legislation.**14. TRANSPORT INFORMATION**

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	1956	1956	1956
<b>14.2 Proper Shipping Name</b>	COMPRESSED GAS, N.O.S. (Contains Argon and Carbon Dioxide)	COMPRESSED GAS, N.O.S. (Contains Argon and Carbon Dioxide)	COMPRESSED GAS, N.O.S. (Contains Argon and Carbon Dioxide)
<b>14.3 Transport Hazard Class</b>	2.2	2.2	2.2
<b>14.4 Packing Group</b>	None Allocated	None Allocated	None Allocated

**14.5 Environmental hazards** No information provided**14.6 Special precautions for user****Hazchem code** 2TE**GTEPG** 2C1**EMS** F-C, S-V**Other information** Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.**15. REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Poison schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).**Classifications** Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

**Hazard codes** None allocated.

**PRODUCT NAME LESS THAN 50% CARBON DIOXIDE BALANCE ARGON**

<b>Risk phrases</b>	None allocated.
<b>Safety phrases</b>	None allocated.
<b>Inventory listing(s)</b>	<b>AUSTRALIA: AICS (Australian Inventory of Chemical Substances)</b> All components are listed on AICS, or are exempt.

---

**16. OTHER INFORMATION**

---

**Additional information** The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**PRODUCT NAME LESS THAN 50% CARBON DIOXIDE BALANCE ARGON**

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmt.com.au](http://www.rmt.com.au).

**[ End of SDS ]**