

LEX CPF=21^A

Lowered Exposure Glutaraldehyde Based Arterial Fluid with Entrone and AD-P

LEX is a lowered exposure glutaraldehyde arterial fluid which contains Entrone for achieving penetration to the point of complete saturation and AD-P for control of aldehyde action to obtain better diffusion and improvement of cosmetic effect. In addition, there are advanced buffers, modifiers and control agents to further enhance the embalming action of LEX. This results in an improved firming action and fluid distribution. LEX has a superior sanitizing action due to the glutaraldehyde present. LEX is recommended for all normal embalming situations. LEX is not recommended in cases of advanced decomposition.

PH-A¹	BETA CO-INJECT	LEX ^B		ALOF	TRISAN⁴	ALOE FACTOR ⁵		
		MODERATE FIRMNESS	DEFINITE ² FIRMNESS	ALOE FACTOR³	ADD FOR EXTRA FIRMNESS	ADD TO RESTORE MOISTURE CON- TENT		
3-4	8-10	8-10	11-13	1-2	2-4	4-8		
→ → MIX IN THIS ORDER → → DILUTE TO ONE GALLON								

Notes:

- A A value assigned to all Champion fluids ranking them on the basis of preservative ability using recommended dilutions in normal cases. The Champion Preservative Factor is not index but can equal it in certain fluids. It is derived from the total chemical composition of each fluid and results of extensive field research. The Champion Preservative Factor can be used by the embalmer to predict the reactivity, preservative value and firming action of Champion fluids.
- B Add Champion Coloro Dyes as needed to achieve desired cosmetic effect.
- 1 For proper water conditioning and pH balance to maximize fluid efficiency (if using soft water reduce amount to 2-3 ozs.)
- 2 These are recommended amounts for normal cases. Additional amounts of fluid will be needed for cases with higher aldehyde demand such as cancer, renal and liver diseases with their complications, institutional cases and other wasting diseases, delayed embalming cases, edema and bodies subjected to extensive drug therapy.
- 3 Humectant to control aldehyde action and prevent dehydration during embalming. Use in all non-lanolin based fluids. Do not use in cases of moisture retention (edema, etc.).
- 4 For increased aldehyde action of fluid with improved rigidity and preservation. (Increases preservative factor of fluid without inducing dehydration or other unwanted effects.)
- 5 For maximum rehydration of tissues. Restores moisture in cases of dehydration or emaciation. Use in last 1 to 1-1/2 gallons of solution with intermittent or restricted drainage.

BEFORE USING, READ MATERIAL SAFETY DATA SHEET.
FOR PROFESSIONAL EMBALMING USE ONLY.

MATERIAL SAFETY DATA SHEET

THE CHAMPION COMPANY

400 Harrison Street Springfield, Ohio 45505

EMERGENCY TELEPHONE NO. (937) 324-5681

CHEMTREC: (800) 424-9300 (Spill, Leak, Fire, Exposure or Accident)

HAZARD RATING

Health 2 Fire 2 Reactivity 0 Special 0

I. PRODUCT INFORMATION

General Type:

Embalming Fluid

Trade Name:

LEX

II. HAZARDOUS INGREDIENTS

		OSHA PEL	ACGIH TLV
MATERIAL (CAS)	<u>%</u>	TWA/STEL (15)	TWA/STEL (15)
Formaldehyde (50-00-0)	7	.75ppm/2ppm	.3ppm (ceiling)
Possible Carcinogen: NTP, IARG	0		
Glutaraldehyde (111-30-8)	6	.2ppm (ceiling)	.05ppm (ceiling)
Phenol (108-95-2)	. 1	5ppm/NONE	5ppm/NONE
Isopropanol (67-63-0)	11	400ppm/NONE	200ppm/400ppm

III. PHYSICAL DATA

Boiling Point Specific Gravity 190° F+ 0.988 Freezing Point Vapor Pressure

N/A UNKNOWN

Vapor Density Percent Volatiles 1 12 Solubility in Water Evaporation Rate COMPLETE

ercent volatiles I

(Butyl Acetate = 1)

Appearance and Odor

Reddish solution with mild pleasant odor.

IV. FIRE AND EXPLOSION HAZARD DATA

Flash Point

Flammable Limits In Air

Extinguishing Media

Special Fire Fighting

Procedures

Unusual Fire and Explosion Hazard

>150° F (COC) Combustible Liquid

Lower 6.7 Upper 72

Foam, Dry Chemical, Carbon Dioxide, Water Spray

Wear self-contained breathing apparatus, cool container with water

spray.

V. HEALTH HAZARD DATA

Threshold Limit Value

See Part II

Effects of Overexposure

If swallowed may cause burns, nausea, vomiting, diarrhea, blindness or death. Skin contact may cause burns, dermatitis or serious skin injury. Eye contact may cause burns, inflammation, eye injury or blindness. Inhalation may cause burning of throat and lungs, difficult breathing and collapse, liver damage, nerve damage or blindness. Can be absorbed through skin.

Emergency and First Aid

Procedures

Contact physician immediately. If swallowed do not induce vomiting, give milk or water and get medical attention. If unconscious - give nothing. If eye or skin contact - flush with water for 15 minutes. Remove contaminated clothing, get medical attention. If inhaled - remove to fresh air, give artificial respiration. If not breathing, get medical attention.

VI. REACTIVITY DATA

Stability

Conditions to Avoid Incompatibilities

Hazardous Decomposition Products

Hazardous Polymerization

Product is stable

Sparks, heat and open flames

Strong acids and alkalis

At high temperatures may release carbon monoxide or carbon dioxide

Will not occur

VII. SPILL OR LEAK PROCEDURES

If Material is Spilled Neutralize with sodium sulfite solution and flush to sewer with

large quantity of water - if allowed. Mop up with dry, non-reactive absorbent and dispose of as solid waste as allowed.

Waste Disposal Method Flush to chemical sewer, incinerate, dispose in sanitary landfill - if

allowed or flush to waste treatment system - if allowed.

VIII. SPECIAL PROTECTION INFORMATION

Respiratory Protection Unnecessary if area is adequately ventilated - use organic vapor mask

if necessary.

Local Ventilation Preferred

Mechanical VentilationAcceptable if necessarySpecial VentilationNot normally requiredOther VentilationNot normally required

Protective Gloves Impervious vinyl or rubber type
Eye Protection Coverall goggles or full face shield

Other Protective Equipment Safety shower, eye wash and full protective clothing is required.

IX. SPECIAL PRECAUTIONS

Maintain adequate ventilation and engineering controls to insure exposure levels below OSHA limits. Avoid prolonged inhalation or contact with skin or eyes.

Keep bottles tightly capped. Keep away from heat and flames. Store in cool, dry, well-ventilated area.

The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.

Date August 1, 2010