



## SAFETY DATA SHEET

# LPS 2 INDUSTRIAL-STRENGTH LUBRICANT(AEROSOL SPRAY)

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

**PRODUCT NAME:** LPS 2 INDUSTRIAL-STRENGTH LUBRICANT(AEROSOL SPRAY)  
**PART No.:** M02400  
**SUPPLIER:** Ambersil Ltd.  
Castlefield Industrial Estate, Wylds Rd, Bridgwater, Somerset, UK, TA6 4DD  
**TEL:** +44 (0)1278 424200  
**FAX:** +44 (0)1278 425644  
**EMERGENCY TELEPHONE(S):** +44 (0) 1278 424200

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	EINECS No.	CAS No.	CONTENTS	SYMBOL	RISK (R No.)
ODOURLESS KEROSENE	265-149-8	64742-47-8	60-100 %	Xn	65
CARBON DIOXIDE	204-696-9	124-38-9	1-5	NC	Not classified.

The full text for all R-phrases are shown in section 16.

**COMPOSITION COMMENTS:** Risk phrases in this section apply only to individual constituents and not the finished preparation.

### 3 HAZARDS IDENTIFICATION

Extremely flammable.

### 4 FIRST AID MEASURES

**INHALATION:** If inhaled, provide fresh air. Seek medical attention if irritation persists.  
**INGESTION:** DO NOT induce vomiting. Seek medical attention immediately and show this safety data sheet.  
**SKIN:** Wash affected area with soap and water. If irritation persists seek medical attention.  
**EYES:** In case of contact with eyes, rinse with water until irritation subsides. If irritation persists, seek medical attention.

# LPS 2 INDUSTRIAL-STRENGTH LUBRICANT(AEROSOL SPRAY)

## 5 FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Powder, foam or CO<sub>2</sub>. Do not use a water jet.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Oxides of carbon, noxious fumes.

**PROTECTIVE MEASURES IN FIRE:**

In the event of fire protect against exploding cans. Water spray may be used to cool aerosol cans.

## 6 ACCIDENTAL RELEASE MEASURES

**PRECAUTIONS TO PROTECT ENVIRONMENT:**

Do not allow entry into drains or watercourses. If this occurs inform the local authorities at once.

**SPILL CLEANUP METHODS:**

This product is a hermetically sealed pressurised aerosol unit and accidental spillage is unlikely. If can is ruptured, allow contents to discharge in situ, whilst removing all ignition sources from the area and ensuring maximum ventilation. Use an absorbent material, eg sand, to mop up residues. See section 13 'Disposal Considerations'.

## 7 HANDLING AND STORAGE

**USAGE PRECAUTIONS:**

Do not spray on a naked flame or any incandescent material.

**STORAGE PRECAUTIONS:**

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. It is recommended that aerosols are stored in their own location away from bulk flammable liquids and packaging materials. Store in a cool, dry place away from heat and ignition sources.

## 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME	CAS No	STD	LT EXP (8 hrs)	ST EXP (15 min)
ODOURLESS KEROSENE	64742-47-8	OES.	1000 mg/m <sup>3</sup>	
CARBON DIOXIDE	124-38-9	OES.	5000 ppm	15000 ppm

**INGREDIENT COMMENTS:** OES = Occupational Exposure Standard.

**PROCESS CONTROL MEASURES:**

Exposure to this material may be controlled in a number of ways. The measures appropriate for a particular worksite depend on how the material is used and on the potential for exposure. Use of the basic principles of Industrial Hygiene will enable this material to be used safely.

**VENTILATION:**

No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

**HYGIENIC WORK ROUTINES:**

**PERSONAL PROTECTION:** Wear personal protective equipment appropriate to the task.

# LPS 2 INDUSTRIAL-STRENGTH LUBRICANT(AEROSOL SPRAY)

## 9 PHYSICAL AND CHEMICAL PROPERTIES

<b>APPEARANCE:</b>	Liquid.	<b>COLOUR:</b>	Amber.
<b>ODOUR/TASTE:</b>	Faint.		
<b>SOLUBILITY DESCRIPTION:</b>	Insoluble in water.		
<b>BOILING POINT (°C):</b>	177 @ 760mmHg		
<b>SPECIFIC GRAVITY (Water=1):</b>	0.84 @ 20 °C	<b>VAPOUR DENSITY (air=1):</b>	>1
<b>VAPOUR PRESSURE:</b>	<1mmHg @ 20 °C	<b>EVAPORATION RATE:</b>	<0.1(BuAc=1)
<b>VISCOSITY:</b>	5 cSt @ 21 °C	<b>FLASH POINT (°C):</b>	79
<b>FLASH POINT METHOD:</b>	PM Closed cup.		

## 10 STABILITY AND REACTIVITY

<b>STABILITY:</b>	There are no known stability problems associated with this product when stored and used under the conditions recommended.
<b>MATERIALS TO AVOID:</b>	Strong oxidizing agents.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	Combustion will generate: smoke, possibly thick and choking, resulting in zero visibility. Combustion may also generate: oxides of sulphur.

## 11 TOXICOLOGICAL INFORMATION

<b>HEALTH HAZARDS, GENERAL:</b>	An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this product. Health hazards associated with aerosols are considered to be limited due to their hermetically sealed nature.
<b>INHALATION:</b>	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.
<b>INGESTION:</b>	Harmful: small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause lung damage.
<b>SKIN:</b>	May cause defatting of the skin, but is not classified as an irritant.
<b>EYES:</b>	Irritating to eyes.

## 12 ECOLOGICAL INFORMATION

<b>ENVIRONMENTAL HAZARDS:</b>	An ecotoxicity study of this product has not been conducted. However, this product contains no substances which are classified as dangerous for the environment.
-------------------------------	--

## 13 DISPOSAL CONSIDERATIONS

<b>DISPOSAL METHODS:</b>	Recycle empty containers if facilities are available. Dispose of in accordance with local authority recommendations.
--------------------------	--

# LPS 2 INDUSTRIAL-STRENGTH LUBRICANT(AEROSOL SPRAY)

## 14 TRANSPORT INFORMATION

### ROAD:

**UN No:** 1950  
**HAZARD CLASS (ADR):** Class 2: Gases; Compressed, liquefied or dissolved under pressure.  
**ADR CLASS No:** 5A  
**PROPER SHIPPING NAME I:** AEROSOLS

### RAIL:

### SEA:

**UN SEA:** 1950  
**SEA TRANSPORT CLASS No:** 2.2

### AIR:

**UN AIR:** 1950  
**AIR TRANSPORT CLASS No:** 2.1

## 15 REGULATORY INFORMATION

### LABEL FOR SUPPLY:



EXTREMELY FLAMMABLE

**RISK PHRASES:** R-12 Extremely flammable.  
**SAFETY PHRASES:** S-16 Keep away from sources of ignition - No Smoking.  
S-51 Use only in well ventilated areas.

### UK REGULATORY REFERENCES:

Chemicals (Hazard Information & Packaging) Regulations.

## 16 OTHER INFORMATION

### USER NOTES:

The purpose of the above information is to describe this product only in terms of Health and Safety requirements. The information given therefore, should not be construed as guaranteeing specific properties or specification. Customers should satisfy themselves as to the suitability and completeness of this information for their own particular use, bearing in mind any other Health and Safety legislation or regulations. The information and recommendations in this publication are to the best of our knowledge reliable. However, nothing herein is construed as a warranty or representation. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

### INFORMATION SOURCES:

British Aerosol Manufacturers Association Code of Practice.  
HSE EH40 Occupational Exposure Limits.  
Suppliers health & safety data sheets.

# LPS 2 INDUSTRIAL-STRENGTH LUBRICANT(AEROSOL SPRAY)

**REVISION DATE:** 23.01.03

**REVISION No. /REPLACES SDS ISSUED:**

1

**R-PHRASES (Full Text):**

Not classified.

R-65

Harmful: may cause lung damage if swallowed.

**DATE:**

25.10.00