Material Safety Data Sheet



1. Product and company identification

Historic MSDS #: #65297-US06 US12 US13

Code #65297-US06 US12 US13 CA01

Product use Engine Oils.

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

Manufacturer BP Lubricants USA Inc.

1500 Valley Road Wayne, NJ 07470

Telephone: (973) 633-2200 Telecopier: (973) 633-7475

EMERGENCY HEALTH

INFORMATION:

1 (800) 447-8735

Outside the US: +1 703-527-3887 (CHEMTREC)

EMERGENCY SPILL INFORMATION:

1 (800) 424-9300 CHEMTREC (USA)

OTHER PRODUCT

1 (866) 4 BP - MSDS

INFORMATION

(866-427-6737 Toll Free - North America)

email: bpcares@bp.com

2. Hazards identification

Physical state

Color

Clear

Emergency overview AUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

Frolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash

thoroughly after handling.

Potential health effects

Eyes May cause eye irritation.

Skin May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation

and/or dermatitis.

Inhalation May cause respiratory tract irritation.

Ingestion Ingestion may cause gastrointestinal irritation and diarrhea.

See toxicological information (Section 11)

Product name Castrol Tection Extra 15W-40 (CJ-4)

Product code

Product code

Product code

Version 5 Date of issue 05/28/2012. Format US Language ENGLISH

(US) (ENGLISH)

3. Composition/information on ingredients

Ingredient name CAS # %

Base oil - highly refinedVaries85 - 90Zinc alkyl dithiophosphate84605-29-81 - 5Base oil - highly refinedVaries0.1 - 1

4. First aid measures

medical attention if symptoms occur.

Skin contact Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes.

Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if

symptoms occur.

Inhalation Inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion ont induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. If potentially dangerous quantities of this material have been

swallowed, call a physician immediately. Get medical attention if symptoms occur.

5. Fire-fighting measures

Fire/explosion hazards

in a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable Use an extinguishing agent suitable for the surrounding fire.

Not suitable To not use water jet.

Fire-fighting procedures Fromptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

No action shall be taken involving any personal risk or without suitable training.

Hazardous combustion

products

Combustion products may include the following:

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Protective clothing (fire) Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal

protective equipment (see Section 8).

Environmental precautions

Noid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers,

waterways, soil or air).

Methods for cleaning up

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Product code

195297-US06 US12 US13 CA01 Page: 2/6

Version 5 Date of issue 05/28/2012.

Format US

Language ENGLISH

(US) (ENGLISH)

7. Handling and storage

Handling

Fut on appropriate personal protective equipment (see Section 8). Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

Storage

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see Section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Other information

Sulfur compounds in this material may decompose when heated to release hydrogen sulfide gas which may accumulate to potentially lethal concentrations in enclosed air spaces. Vapor concentrations of hydrogen sulfide above 50 ppm, or prolonged exposure at lower concentrations, may saturate human odor perceptions so that the smell of gas may not be apparent. Exposure to concentrations of hydrogen sulfide vapor above 500 ppm may cause rapid death. Do not rely on the sense of smell to detect hydrogen sulfide.

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name Occupational exposure limits

Base oil - highly refined ACGIH (United States).

TWA: 5 mg/m3 8 hours. Form: Mineral oil, mist

OSHA (United States).

TWA: 5 mg/m³ 8 hours. Form: Mineral oil, mist

Base oil - highly refined ACGIH (United States).

TWA: 5 mg/m³ 8 hours. Form: Mineral oil, mist

OSHA (United States).

TWA: 5 mg/m³ 8 hours. Form: Mineral oil, mist

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Some states may enforce more stringent exposure limits.

Control Measures

Se only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Personal protection

Eyes

Woid contact with eyes. Safety glasses with side shields or chemical goggles.

Skin and body

void contact with skin and clothing. Wear suitable protective clothing.

Respiratory

Se adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.

Hands

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.

Product code

455297-US06 US12 US13 CA01 Page: 3/6

Version 5 Date of issue 05/28/2012. Format US

Language ENGLISH

(US)

(ENGLISH)

9. Physical and chemical properties

Liquid. **Physical state C**lear Color

Flash point Closed cup: >200°C (>392°F) [Pensky-Martens.]

0.88 Specific gravity

Kinematic: 116 mm²/s (116 cSt) at 40°C **Viscosity**

Kinematic: 15.5 mm²/s (15.5 cSt) at 100°C

Solubility insoluble in water.

10. Stability and reactivity

Stability and reactivity The product is stable.

Possibility of hazardous

reactions

void all possible sources of ignition (spark or flame).

Conditions to avoid Incompatibility with various substances

Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition

products

This product may release hydrogen sulfide (H₂S) if it is heated to high temperatures.

Inder normal conditions of storage and use, hazardous reactions will not occur.

Hazardous polymerization

Inder normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Other Toxicity Data **USED ENGINE OILS**

> Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

Contains low concentration of zinc alkyl dithiophosphate (ZDDP). Concentration is not expected to Other information

cause eye or skin irritation.

Potential chronic health effects

Carcinogenicity No known significant effects or critical hazards.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

Persistence/degradability **B**iodegradable

Mobility pillages may penetrate the soil causing ground water contamination.

This product is not expected to bioaccumulate through food chains in the environment. **Bioaccumulative potential**

Other ecological Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired. information

13. Disposal considerations

Date of issue 05/28/2012.

Waste information

Version 5

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied

Language ENGLISH

455297-US06 US12 US13 CA01 Page: 4/6 **Product code**

(US) (ENGLISH)

Format US

containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

15. Regulatory information

U.S. Federal Regulations

United States inventory (TSCA 8b)

MI components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: No products were found.

SARA 302/304/31 1/312 Hazardous Chemicals. No products were round.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Castrol Tection

Extra 15W-40 (CJ-4): Immediate (acute) health hazard

SARA 313

Form R - Reporting

requirements

Product name CAS number Concentration

Zinc alkyl dithiophosphate 84605-29-8 0.825 - 1.6335

Supplier notification Zinc alkyl dithiophosphate

Zinc alkyl dithiophosphate 84605-29-8 0.825 - 1.6335

CERCLA Sections
102a/103 Hazardous
102a/103 Hazardous
Substances (40 CFR

DERCLA: Hazardous substances.: Benzene: 10 lbs. (4.54 kg); Arsenic: 1 lb. (0.454 kg); Cadmium (Non-pyrophoric): 10 lbs. (4.54 kg); lead: 10 lbs. (4.54 kg); Zinc alkyl dithiophosphate;

Part 302.4): State regulations

Hazardous Substances

Massachusetts

Wone of the components are listed.

Substances

New Jersey Hazardous
Substances

The following components are listed: MINERAL OIL (UNTREATED and MILDLY TREATED);
ZINC compounds; MINERAL OIL (UNTREATED and MILDLY TREATED)

California Prop. 65 WARNING: This product contains a chemical known to the State of California to cause cancer.

Arsenic

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Cadmium (Non-pyrophoric); lead; Benzene

Other regulations

REACH Status For the REACH status of this product please consult your company contact, as identified in

Section 1.

(PICCS)

Product name Castrol Tection Extra 15W-40 (CJ-4)

Product code

Product code

Product code

Version 5 Date of issue 05/28/2012. Format US Language ENGLISH (US) (ENGLISH)

16. Other information

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

HMIS® Rating: Health

Flammability 7

Physical 70 Hazard

Personal protection

National Fire Protection

Association (U.S.A.)



History

Date of issue 05/28/2012.

Date of previous issue 10/07/2009.

Prepared by Product Stewardship

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

 Product name
 €astrol Tection Extra 15W-40 (CJ-4)
 Product code
 €5297-US06 US12 US13 CA01
 Page: 6/6

 Version 5
 Date of issue 05/28/2012.
 Format US
 Language ENGLISH

 (US)
 (ENGLISH)