STROKE FC-W 10W30 4M



1. IDENTIFICATION

1.1. PRODUCT IDENTIFIER USED ON LABEL:

Finished Product Item Number	Customer Item Number	LABEL DESCRIPTION ACTUAL	BRAND
Y10W30FC12	LUB10W30FC12	YAMALUBE MARINE PERFORMANCE FOUR STROKE FC-W 10W30 4M	YAMALUBE
Y10W30FC04	LUB10W30FC04	YAMALUBE MARINE PERFORMANCE FOUR STROKE FC-W 10W30 4M	YAMALUBE
Y10W30FC55	LUB10W30FC55	YAMALUBE MARINE PERFORMANCE FOUR STROKE FC-W 10W30 4M	YAMALUBE

- 1.1.1. Distributed by Yamaha Motor Corporation U.S.A.
- 1.2. OTHER MEANS OF IDENTIFICATION:
 - 1.2.1. 10W30 LOW PHOSPHOROUS ENGINE OIL
- 1.3. RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE;
 - 1.3.1. PETROLEUM LUBRICATING OIL
 - 1.3.2. NO OTHER USES RECOMMENDED
- 1.4. NAME, ADDRESS, AND TELEPHONE NUMBER OF THE CHEMICAL MANUFACTURE R, IMPORTER, OR OTHER RESPONSIBLE PARTY:
 - 1.4.1.

Spectrum Lubricants Corporation

500 Industrial Park Drive Selmer, TN 38375-3276 United States of America

Product Information

MSDS Requests: (800) 264-6457 or +17316454972 Technical Information: (800) 264-6457 or +17316454972 General Information: vswedley@spectrumcorporation.com

1.5. EMERGENCY PHONE NUMBER:

1.5.1.

Emergency Response

STROKE FC-W 10W30 4M

North America: CHEMTREC (800) 424-9300 after 5:00pm CST Or +17035273887

Health Emergency

USA: (800) 264-6457 or +17316454972

2. HAZARD(S) IDENTIFICATION

- 2.1. CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) of §1910.1200:
 - 2.1.1. Acute Inhalation Category 4
 - 2.1.2. Skin Sensitizer Category 1
- 2.2. Signal Word:
 - 2.2.1. Warning
- 2.3. **Symbol:**



- 2.4. Hazard Statements:
 - 2.4.1. Harmful if Inhaled.
 - 2.4.2. May cause an allergic skin reaction.
- 2.5. Precautionary Statements:
 - 2.5.1. Prevention:
 - 2.5.1.1. Avoid breathing mists or spray.
 - 2.5.1.2. Use only outdoors or in a well-ventilated area.
 - 2.5.1.3. Contaminated work clothing must not be allowed out of workplace.
 - 2.5.1.4. Wear protective gloves.
 - 2.5.2. Response:
 - 2.5.2.1. If inhaled: Remove person to fresh air and keep comfortable for breathing.
 - 2.5.2.2. Call a poison center/doctor if you feel unwell.
 - 2.5.2.3. If on skin wash with plenty of water
 - 2.5.2.4. I skin irritation or rash occurs: get medical advice/attention.
 - 2.5.2.5. Wash contaminated clothing before reuse.
 - 2.5.3. Disposal:
 - 2.5.3.1. Dispose of contents/container in accordance with local/regional/national/international regulations (to be specified).

3. Composition/information on ingredients

3.1. The chemical name and concentration (exact percentage) or concentration ranges of all ingredients which are classified as health hazards in accordance with paragraph (d) of §1910.1200

3.1.1.

STROKE FC-W 10W30 4M

COMPONENTS	CAS Number	EU Number	Concentration
			(%)
Solvent-dewaxed heavy paraffinic distillates (petroleum)	64742-65-0	265-169-7	15-30
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	265-157-1	50-75

4. FIRST AID MEASURES

4.1.

Skin:	Wash skin with plenty of soap and warm water. Wash clothing before re-use.		
Eye:	If splashed into eyes flush eyes with clear water for several minutes.		
Inhalation:	Remove person to fresh air and keep comfortable for breathing. Call a poison		
	center/doctor if you feel unwell		
Ingestion:	If ingested, do not induce vomiting. Call a physician.		

5. FIRE FIGHTING MEASURES

- 5.1. Flash Point: 430°F (221.11°C)
- 5.2. Protective Equipment/Fire Fighting Instructions:
 - 5.2.1. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.
- 5.3. Extinguishing Media:
 - 5.3.1. Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.
- 5.4. Special Firefighting Procedures:
 - 5.4.1. Cool exposed containers with water spray.
- 5.5. Unusual Fire and Explosion Hazards:
 - 5.5.1. Pressure increase in over heated closed containers. Cool containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

6.1. Spill Procedures:

- 6.1.1. Remove ignition sources. Recover Liquid. Add absorbent to spill area. Ventilate confined spaces. Advise authorities if product enters sewers, etc.
- 6.2. Waste Disposal:

STROKE FC-W 10W30 4M

6.2.1. Assure conformity with applicable disposal regulations. Dispose of absorbed material at approved waste site

6.3. Precautionary Measures:

- 6.3.1. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Wash thoroughly after handling.
- 6.3.2. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

7. HANDLING AND STORAGE

7.1. HANDLING

7.1.1. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum re-conditioner or disposed of properly.

7.2. STORAGE

7.2.1. Keep container closed when not in use. Do not store with strong oxidizing agents. Do not store at elevated temperatures.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1. Component Exposure Limits:

8.1.1. SYNTHETIC ENGINE OIL 5mg/m3 (oil mist) ACGIH TLV OSHA PEL

COMPONENTS	ACGIH TLV	OSHA PEL
Solvent-dewaxed heavy paraffinic	5mg/m³ (oil	5mg/m³ (oil
distillates (petroleum)	mist) TWA	mist) TWA
Petroleum distillates, hydrotreated heavy	5mg/m³ (oil	5mg/m³ (oil
paraffinic	mist) TWA	mist) TWA

8.2. Engineering Controls:

8.2.1. Ventilate as needed to comply with exposure limit

8.3. Eye Protection:

8.3.1. Use goggles/face shield to avoid eye contact

8.4. Glove Protection:

8.4.1. Use impervious gloves to avoid repeated/prolonged skin contact.

8.5. Work/Hygienic Practices:

8.5.1. If clothing becomes contaminated, change to fresh clean clothing. Do not wear until thoroughly laundered.

SAFETY DATA SHEET — YAMALUBE MARINE PERFORMANCE FOUR STROKE FC-W 10W30 4M

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Appearance/Odor:	Amber liquid with mild hydrocarbon odor.	9.2. Odor Threshold:	No data available
9.3. pH:	No data available	9.4. Boiling Point:	Wide range
9.5. Melting Point:	No data available	9.6. Solubility (H ₂ 0):	Negligible
9.7. Specific Gravity:	0.8761 @ 15.6°C	9.8. Density:	7.3 lbs/gal
9.9. Octanol/H ₂ 0 Coeff.:	No data available	9.10. Evaporation Rate (BUAC=1):	<1
9.11. Molecular Weight:	No data available	9.12. Decompostion Temp:	No data available
9.13. Auto Ignition:	No data available	9.14. Lower Flammability Limit:	No data available
9.15. Flash Point:	430°F (221.11°C)	9.16. Upper Flammability Limit:	No data available
9.17. Vapor Density (Air=1):	>1	9.18. Vapor Pressure:	<1mmHg @ 20°C
9.19. VOC :	Nill	9.20. Flammability Class:	Not classified
9.21. Viscosity @ 40°C	82cSt (82 mm²/s)	9.22. Viscosity @ 100°C	12.1cSt (12.1 mm²/s)

10.STABILITY AND REACTIVITY

10.1. Reactivity:

10.1.1. Material does not pose a significant reactivity hazard.

10.2. Chemical Stability:

10.2.1. Stable

10.3. Incompatibility/Conditions to avoid:

10.3.1. Avoid strong oxidants

10.4. Possibility of Hazardous Reactions:

10.4.1. Will not undergo hazardous polymerization.

10.5. Hazardous Decomposition Products:

10.5.1. Partial burning produces fumes, smoke and carbon monoxide

11. TOXICOLOGY INFORMATION

STROKE FC-W 10W30 4M

11.1. Likely Routes of Exposure:

11.1.1. Ingestion, Inhalation, Eye contact, Skin contact.

11.2. Acute Effects:

- 11.2.1. Inhalation: Harmful if inhaled. May cause respiratory irritation.
- 11.2.2. Eye Contact: Causes serious eye irritation.
- 11.2.3. Skin Contact: Causes Skin irritation.
- 11.2.4. Ingestion: Expected to be low ingestion hazard.

11.3. Component Data/ Analysis

COMPONENTS	Oral (LD50) (Rat)	Inhalation (LC50) (Rat)	Dermal (LD50) (Rabbit)
Solvent-dewaxed heavy paraffinic distillates (petroleum)	>5000 mg/kg	2.18 mg/l (4hr)	>2000 mg/kg
Petroleum distillates, hydrotreated heavy paraffinic	>5000 mg/kg	2.18 mg/l (4hr)	>2000 mg/kg

11.4. Sensitization:

11.4.1. None known.

11.5. Carcinogenicity:

11.5.1. None greater than 0.1%.

11.6. Mutagenicity:

11.6.1. None known.

11.7. Reproductive Toxicity:

11.7.1. None known.

11.8. Teratogenicity:

11.8.1. None known.

12.ECOLOGICAL INFORMATION

12.1. Ecotoxicity

12.1.1. An environmental fate analysis is not available for this specific product. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

12.2. Environmental Fate

12.2.1. Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. Also, the coating action associated with petroleum and petroleum products can be harmful or fatal to aquatic life and waterfowl.

13. DISPOSAL CONSIDERATIONS

13.1. Waste Disposal:

STROKE FC-W 10W30 4M

13.1.1. Assure conformity with applicable disposal regulations. Dispose of absorbed material at approved waste site.

14.TRANSPORTATION INFORMATION

The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside of the United States.

14.1. ROAD AND RAIL

14.1.1. DOT: NOT REGULATED

14.2. **VESSEL**

14.2.1. IMDG: NOT REGULATED

14.3. AIR

14.3.1. IATA: NOT REGULATED

15.REGULATORY INFORMATION

15.1. TSCA Inventory

15.1.1. This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.

15.2. SARA 302/304 Emergency Planning and Notification

15.2.1. No components were identified.

15.3. SARA 311/312 Hazard Identification

15.3.1. Acute (Immediate) Health Hazard

15.4. SARA 313 Toxic Chemical Notification and Release Reporting

15.4.1.: No components were identified.

15.5. **CERCLA**

15.5.1. No components were identified.

15.6. Clean Water Act (CWA)

15.6.1. This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

15.7. California Proposition 65:

15.7.1. The product contains chemicals known to the state of California to cause cancer, birth defects, or any other reproductive harm.

15.8. New Jersey Right-to-Know Label

15.8.1. Petroleum Oil

15.8.2. <1% Zinc alkyl dithiophosphate

16.OTHER INFORMATION

16.1.

HAZARD RANKINGS				
HMIS		NFPA		
HEALTH HAZARD	1	HEALTH HAZARD	1	

SAFETY DATA SHEET — YAMALUBE MARINE PERFORMANCE FOUR STROKE FC-W 10W30 4M

FIRE HAZARD	1	FIRE HAZARD	1
PHYSICAL HAZARD	0	INSTABILITY/REACTIVITY	0
Personal Protection	В		

16.2. **Date of preparation:** 12/18/2013 16.3. **MANUFACTURER DISCLAIMER:**

16.3.1. The data presented herein is based upon tests and information, which we believe to be reliable.

However, users should make their own investigations to determine the suitability of the information for their particular purpose.