Liquid WHENCH

SAFETY DATA SHEET

1. Identification

Product identifier Liquid Wrench White Lithium Grease

Other means of identification

SDS number L616

 Part No.
 L616, L616/4

 Tariff code
 2710.19.4000

Recommended use Grease
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name

Address

RSC Chemical Solutions
600 Radiator Road
Indian Trail, NC 28079

United States

Telephone Customer Service: (704) 821-7643

Technical: (704) 821-7643

Website www.rscbrands.com E-mail sds@rscbrands.com

Emergency phone number Emergency Telephone: (303) 623-5716

Emergency Contact: RMPDC (877) 740-5015

2. Hazard(s) identification

Physical hazards Flammable aerosols Classification not possible

Health hazardsAcute toxicity, oralCategory 4Skin corrosion/irritationCategory 2

Serious eye damage/eye irritation Category 2

Category 2

Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Contains gas under pressure; may explode if heated. Harmful if swallowed. May be fatal if

swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause

drowsiness or dizziness.

Precautionary statement

Prevention Avoid breathing gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this

product. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. Wear

protective gloves.

Response If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If

on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin

irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Material name: Liquid Wrench White Lithium Grease L616, L616/4 Version #: 06 Revision date: 02-12-2019 Issue date: 04-29-2015

Disposal

Hazard(s) not otherwise classified (HNOC)

Supplemental information

Dispose of contents/container in accordance with local/regional/national/international regulations. Combustible.

54.97% of the mixture consists of component(s) of unknown acute oral toxicity. % of the mixture consists of component(s) of unknown acute dermal toxicity. 26.73, 15% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 26.73, 15% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-(2-butoxyéthoxy) Éthanol		112-34-5	20 - < 30
Distillates (petroleum), Hydrotreated Light	Hydrotreated light distillates (petroleum)	64742-47-8	20 - < 30
Stoddard Solvent And/or Solvent Naphtha (petroleum), Medium Aliphatic And/or Hydrotreated Naphtha, Heavy	(8052-41-3 and/or 64742-88-7 and /or 64742-48-9)	Trade Secret	20 - < 30
Distillates (petroleum), Hydrotreated Heavy Naphthenic		64742-52-5	10 - < 20
Carbon Dioxide		124-38-9	1 - < 3
Corrosion Inhibitor		Mixture	1 - < 3
Zinc Oxide		1314-13-2	< 0.3
Other components below reportable	e levels		3 - < 5

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim medical attention and special under observation. Symptoms may be delayed.

Treatment needed

General informationEnsure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).

Unsuitable extinguishing production of the provided product of the product of the provided product

Specific hazards arising from During fire, gases hazardous to health may be formed. **the chemical**

Special protective equipment Self-contained breathing apparatus and full protective clothing must be worn in case of fire. and precautions for firefighters

Fire fighting equipment/instructionsCool containers exposed to heat with water spray and remove container, if no risk is involved.
Containers should be cooled with water to prevent vapor pressure build up.

Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible. No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not taste or swallow. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage. including any incompatibilities

Level 2 Aerosol.

Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)	US.	OSHA Table Z-	1 Limits for Air	r Contaminants ((29 CFR 1910.1000)
---	-----	----------------------	------------------	------------------	--------------------

Туре	Value	Form
PEL	9000 mg/m3	
	5000 ppm	
PEL	5 mg/m3	Mist.
	2000 mg/m3	
	500 ppm	
PEL	400 mg/m3	
	100 ppm	
PEL	5 mg/m3	Respirable fraction.
	5 mg/m3	Fume.
	15 mg/m3	Total dust.
	PEL PEL	PEL 9000 mg/m3 5000 ppm 5 mg/m3 2000 mg/m3 500 ppm 400 mg/m3 100 ppm PEL 100 ppm 5 mg/m3 5 mg/m3 5 mg/m3

Material name: Liquid Wrench White Lithium Grease

SDS US L616, L616/4 Version #: 06 Revision date: 02-12-2019 Issue date: 04-29-2015

Components	Туре	Value	Form
2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Zinc Oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	Form
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
Zinc Oxide (CAS 1314-13-2)	Ceiling	15 mg/m3	Dust.
	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Fume.
		5 mg/m3	Dust.
ogical limit values	No biological exposure limits noted for	or the ingredient(s).	
ropriate engineering trols	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to mair exposure limits have not been estable eyewash station and safety shower.	air changes per hour) should pplicable, use process enclosi tain airborne levels below reco	ures, local exhaust ventilation ommended exposure limits.
vidual protection measures	s, such as personal protective equipn	ent	
Eye/face protection	Face shield is recommended. Wear industrial settings only.	safety glasses with side shields	s (or goggles). Applicable fo

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Applicable for industrial settings only.

Wear appropriate chemical resistant clothing. Applicable for industrial settings only. Other

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an **Respiratory protection**

air-supplied respirator. Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded. Dust & vapor respirator. Applicable for industrial settings only.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene When using do not smoke. Keep away from food and drink. Always observe good personal

hygiene measures, such as washing after handling the material and before eating, drinking, and/or considerations

smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas. **Form** Aerosol. Color Not available. Odor Not available.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -90.58 °F (-68.1 °C) estimated Initial boiling point and boiling 314.6 °F (157 °C) estimated

range

Flash point 104.0 °F (40.0 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

0.7 % estimated

Flammability limit - upper

(%)

5 % estimated

Explosive limit - lower (%)

Explosive limit - upper (%)

Not available.

Not available.

Vapor pressure 0.174 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 229 °F (109.44 °C) estimated

Decomposition temperature Not available. **Viscosity** < 200 cps

Other information

Density 7.33 lbs/gal estimated

Explosive properties Not explosive.

Flame extension None Flammability (flash back) No

Heat of combustion (NFPA

30B)

24.97 kJ/g estimated

Oxidizing properties

Percent volatile

Specific gravity

VOC

Not oxidizing.

24.43 % estimated

0.88 estimated

0 % w/w

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or

vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components Species Test Results

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Acute Dermal

LD50 Rabbit 2700 mg/kg

Oral

LD50 Rat 4500 mg/kg

Stoddard Solvent And/or Solvent Naphtha (petroleum), Medium Aliphatic And/or Hydrotreated Naphtha, Heavy

<u>Acute</u>

Dermal *Liquid*

LD50 Rabbit > 2000 mg/kg

Oral Liquid

LD50 Rat > 5000 mg/kg

Zinc Oxide (CAS 1314-13-2)

<u>Acute</u>

Inhalation

LC50 Mouse > 5.7 mg/l, 4 Hours

Oral

LD50 Rat > 5 g/kg

Skin corrosion/irritation

Serious eye damage/eye

Causes serious eye irritation.

Causes skin irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) 1300 mg/l, 96 hours

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours
Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

Zinc Oxide (CAS 1314-13-2)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 2246 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-(2-butoxyéthoxy) Éthanol 0.56

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number Not available.

UN proper shipping name

Transport hazard class(es)

Consumer Commodity

Class ORM-D

Subsidiary risk

Packing group Not available.

Environmental hazards

Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions 306
Packaging non bulk 302, 304
Packaging bulk 302, 314, 315

IATA

UN number UN1950

UN proper shipping name Aerosols, non-flammable

SDS US

Transport hazard class(es)

2.2 Class Subsidiary risk

Not available. Packing group

Environmental hazards

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN1950 **UN number** Aerosols **UN** proper shipping name

Transport hazard class(es)

2.2 Class Subsidiary risk

Packing group Not available.

Environmental hazards

Marine pollutant No F-D, S-U **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5) Listed. Zinc Oxide (CAS 1314-13-2) Listed.

Not applicable.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
2-(2-butoxyéthoxy) Éthanol	112-34-5	20 - < 30	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

California Proposition 65



WARNING: This product can expose you to Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

04-29-2015 Issue date **Revision date** 02-12-2019

Version # 06

Health: 3* **HMIS®** ratings Flammability: 1

Physical hazard: 0

Health: 2 NFPA ratings

Flammability: 1 Instability: 0

NFPA ratings



The information provided in this Safety Data Sheet is correct to the best of our knowledge, Disclaimer

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

This document has undergone significant changes and should be reviewed in its entirety. **Revision information**

Material name: Liquid Wrench White Lithium Grease

SDS US

Yes