

1. IDENTIFICATION:

PRODUCT NAME: LUBRI-BOND 220 AEROSOL HMIS CODES H F R P

PRODUCT CODE: PLB220AEMSDS 2*4 1 G

PRODUCT USE .: Low Friction Coating

Manufacturer:

EVERLUBE PRODUCTS
100 COOPER CIRCLE
PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300

INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800

NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR

DATE PREPARED: 10/27/2015

2. HAZARDS INDENTIFICATION



CLASSIFICATION:

Serious Eye Damage/Eye Irritation - Category 2
Flammable Aerosol - Category 1
Acute Toxicity Oral - Category 4
Aquatic Acute - Category 3
Aspiration Hazard - Category 1
Carcinogenicity - Category 2
Gas Under Pressure - Compressed gas
Reproductive Toxicity - Catetory 1
Skin Irritation Category - 2
Specific target organ toxicity, repeated exposure - Category 2
Specific target organ toxicity, single exposure - Category 3

SIGNAL WORD:

DANGER

HAZARDS STATEMENTS:

H222-Extremely flammable aerosol

H229-Pressurized container, may burst if heated

H304-May be fatal if swallowed and enters airways

H315-Causes skin irritation

H319-Causes serious eye irritation

H351-Suspected of causing cancer

H360-May damage fertility or the unborn child.

H373-May cause damage to organs through prolonged or repeated exposure.

H402-Harmful to aquatic life

PRECAUTIONARY STATEMENTS:

P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking

P211-Do not spray on an open flame or other ignition source.

P251-Pressurized container: Do not pierce or burn, even after use.

P280-Wear protective gloves/eye protection/face protection.



SAFETY DATA SHEET

P403-P233-P410-P412-Store in a well ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 122°F/50°C.

P501-Dispose of contents/container in accordance with local/regional/national/regulation.

3. COMPOSITION/INFORMATION ON INGREDIENTS	CAS#	% BY WT.
DIMETHYL ETHER	115-10-6	55 - 60%
LC50 (inhalation, rat) = $164,000$ ppm for 4 hour		
TOLUENE	108-88-3	15% - 20%
OSHA PEL 200.00 PPM-TWA		
OSHA PEL 300.000 PPM-CEILING		
OSHA VPEL 100.000 PPM-TWA OSHA VPEL 150.000 PPM-STEL (SKIN)		
ACGIH TLV 50.000 PPM-TWA (SKIN)		
ACGIH TLV 30.000 FPM-STEL (SKIN)		
LD 50 ORAL RAT: 2.6 g/kg		
LC 50 INHALATION RAT: 8000 PPM; 4 h		
LD 50 DERMAL RABBIT: 12,124 mg/kg		
LC50 FISH 7.63 mg/l 96 h		
EC50 INVERTEBRATES 8 mg/l 24 h		
EC50 ALGAE 10 mg/l 24h		
CYCLOHEXANONE	108-94-1	5% - 10%
ACGIH TLV 20 PPM TWA		
ACGIH TLV 50 PPM STEL		
NIOSH REL 100 mg/m3		
NOISH REL 25 PPM		
OSHA Z-1 200 mg/m3 PEL		
OSHA Z-1 50 PPM LD50 ORAL 1535 mg/kg (RAT)		
LD50 OKAL 1333 mg/kg (KAI) LD50 SKIN 948 mg/kg (rabbit)		
LC50 INHALATION: 8000ppm 4H (rat)		
LD50 ORAL 1400 mg/kg (mouse)		
LC50 FATHEAD MINNOW 481-578 mg/l 96 hr		
LC50 DAPHNIA 800 mg/l 24 hr		
METHYL ETHYL KETONE	78-93-3	0% - 5%
ACGIH TLV: 200 ppm		
OSHA/ACGIH STEL: 300 ppm		
OSHA TWA 200 ppm		
LD50 ORAL 3400.0 mg/kg (RATS)		
DC50 VAPORS 2000 PPM (RATS)		
LD50 SKIN 12600 mg/kg (RABBITS)		
LC50 FISH 100 mg/l 96 hr EC50 DAPHNIA >100 mg/l 48 hr		
EC50 BAPHNIA >100 mg/1 40 mg		
LEAD PHOSPHITE	12141-20-	7 0% - 5%
ACGIH TLV-TWA: 0.15 mg/m3 (8 hrs), as Pb	12111 20	
BLV: 50 mmg/100g blood		
OSHA PEL: 0.05 mg/m3, AS Pb		
ANTIMONY TRIOXIDE	1309-64-4	0% - 5%
ACGIH PEL-TWA: 0.5 mg/m3 as Sb		
ACGIH TLV TWA: 0.5 mg/m3 as Sb		
NOISH REL 0.5 mg/m3		
IDL: 50 mg/m3 as Sb		
>34,600 mg/kg Acute Oral (rat)		
3,250 mg/kg Acute Intraperitoneal (rat)		
172 mg/kg Acute Intraperitoneal (mouse) ETHYL BENZENE	100-41-4	0% - 5%
TILL DUNGUINE	TOO 41-4	U 0 U 0



ACGIH: 20 ppm TWA

OSHA 100 ppm TWA; 435 mg/m3 TWA OSHA 125 ppm STEL; 545 mg/m3 STEL NIOSH 100 ppm TWA; 435 mg/m3 TWA NIOSH 125 ppm STEL; 545 mg/m3 STEL

LD50 ORAL: 3500 mg/kg (rat)

LC50 Inhalation 17.2 mg/l 4h (rat) LD50 Dermal 15354 mg/kg (rabbit) LC50 FISH: 11.0-18.0 mg/l 96 hr

EC50 ALGAE 4.6 mg/l 72 hr

EC50 DAPHNIA 18.-2.5 mg/l 48 hr

4. First Aid Measures

Eves:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

Skin:

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used. Consult a doctor if irritation persists.

Ingestion:

Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.

Inhalation:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

5. Fire Fighting Measures

Flammable Properties:

Flash Point Liquid (Degree F): 15.8 F Flash Point Method TOC Flash Point Propellant..... -42.0 F

Explosive Limits:

Upper explosive limit: 27.0% Lower explosive limit: 1%

Hazardous Combustion Products:

Oxides of Carbon, Aldehydes, Antimony fumes, Hydrogen Peroxide and their compounds

Extinguishing Media:

CO2, foam, dry chemical or halon

Firefighting Procedures:

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

In case of fire, toxic fumes of lead oxide may be emitted.

6. Accidental Release Measures

Small Spill:

Eliminate all sources of ignition, provide ventilation, contain spill,



and absorb with inert absorbent.

Issue warning "Flammable". Isolate the hazard area and restrict access.

Handle as highly flammable liquid.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Prevent the spill or wash from entering sewers or watercourses.

Large Spill:

Remove by mechanical means and place in containers.

Use only non-sparking tools and equipment.

Environmental Precautions:

Prevent product or wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

7. Handling and Storage

Handling:

Maintain good personal hygiene. Avoid breathing processing vapors. Avoid prolonged or repeated skin contact. Wash skin with soap and water after handling. Wash contaminated clothing before re-use.

Storage:

Storage of individual cans should be done in an area below 120F, away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantiies, compliance with NFPA 30B (Manufacture and Storage of Aerosol products) is recommneded.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

None known

Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment.

For personal entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere. Make-up air should always be supplied to balance air exhausted.

Prevent the product or the wash waters from entering the water system or sewers.

Personal Protective Equipment:

EVERLUBE PRODUCTS SAFETY DATA SHEET



Respiratory Protection:

In case of inadequate ventilation, wear respirator protection. Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.

9. Physical and Chemical Properties

Flammability (solid, gas)....: Extremely Flammable Aerosol

Boiling Point 175 F

Melting/Freezing Point: None known

VOC....: 652 grams/liter

Flash Point Liquid.....: 15.8 F
Flash Point Propellant....: -42.0 F
Vapor Pressure 61.30 psig

Vapor Density 2.410 g/cc Maximum

Solubility in Water: Insoluble Density..... 7.4 lb/gl

Evaporation Rate Data not available.

Explosive Limits:

Upper Explosive Limit: 27.0% Lower Explosive Limit: 1% Specific Gravity: .8887

PH Not Applicable.

Volatile (% by Weight).....: 85%

Appearance and Odor Gray/Black liquid, organic solvent odor

Odor Threshold: None known Viscosity None known

Partition Coefficient:....: Data not available Decomposition Temperature ...: Data not available

Autoignition temperature....: 759.2 F

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

Stable under normal conditions.

Incompatibility:

Oxidizers, Strong Acids or Alkalies.

Hazardous Decomposition Products:

Irritating and/or toxic fumes including the following may be released: Oxides of Carbon, Aldehydes, Antimony fumes, Hydrogen Peroxide and their compounds

Hazardous Polymerization:

Will not occur.



11. Toxicological Information

Acute Toxicity Values:

Mixture, see section 3 - Hazardous Ingredients

Germ Cell Mutagenicity:

None of the ingredients are know or suspected of causing genetic defects.

Chronic/Carcinogenicity:

IARC (International Agency for Research of Cancer): Group 2B-Possibly carcinogenic to humans

NTP (National Toxicology Program): Not listed as a carcinogen

Reproductive Toxicity:

Product contains chemical(s) that may damage fertility or the unborn child

STOT-single exposure:

If inhaled may cause drawsiness or dizziness

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard:

Aspiration Hazard - Category 1

Routes of Exposure:

Skin contact, skin absorption, eye contact, inhalation

12. Ecological Information

Environmental Fate:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

Environmental Toxicity:

Data not available

Persistence and Degradability:

Data not available

Bioaccumulative Potential:

Data not available

Mobility in Soil

Data not available

Other Adverse Effects:

None known

13. Disposal Considerations

Disposal Methods:



Dispose of contents/container to: A licensed waste disposal facility. Do not attempt to combust waste on-site. DO NOT INCINERATE - CONTENTS UNDER PRESSURE.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

UN Number:

UN 1950

UN Shipping Name:

Aerosol, Flammable

Transport Hazard Class:

Class 2.1



Packing Group:

Not Applicable

ENVIRONMENTAL HAZARDS:

Marine Pollutant:

May be harmful to aquatic life.

Special Precautions for User:

None known

15. Regulatory Information

U.S. Federal Regulations:

OSHA:

OSHA Regulated

TSCA:

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE EXTINCT FROM REQUIREMENTS

CERCLA: SARA Hazard Category:

Section 313:

IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313 THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE ARE NO REPORTABLE COMPONENTS.

COMPONENT CAS # % BY WT.

FRANK DODD SECTION 1502:

ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT MINERALS ACT).



State Regulations:

California Prop 65:

This product contains a chemical known to the State of California to cause cancer.

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Regulations:

WHMIS Classification:

A, B5, D1B, D2A, D2B

CEPA (Canadian Environmental Protection Act)

ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

EINECS (European Inventory of Existing Chemical List)

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

16. Other Information

DATE OF PREPARATION: 10/27/2015

KEY/LEGEND:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: International Carriage of Dangerous Goods by Road

RID: International Carriage of Dangerous Goods by Rail

CAS: Chemical Abstracts Service

CERCLA: Comprehensive Environmental Response, Compensation, & Liability

Act

DOT: Department of Transportation

HMIS: Hazardous Materials Identification System IATA: International Air Transport Association ICAO: International Civil Aviation Organization

IDL: Immediately Dangerous to Life

IMDG: International Maritime Dangerous Goods

IMO: International Maritime Organization

LC: Lethal Concentration

LD: Lethal Dose

NIOSH: National Institute for Occupational Safety & Health

OSHA: Occupational Safety & Health Administration

PPM: Parts Per Million

REL: Recommended Exposure Limit

SARA: Superfund Amendments and Reauthorization Act

STEL: Short-term Exposure Limits

STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value

TSCA: Toxic Substances Control Act

TWA: Time Weighted Average

VOC: Volatile Organic Compounds

WHMIS: Workplace Hazardous Materials Information System

Manufacturer Disclaimer:

LUBRI-BOND 220 AEROSOl Page 9 of 9



TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABLITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL

www.everlubeproducts.com