

1. Identification

Product identifier Motor Medic Diesel Fuel Conditioner with Cetane Boost

Other means of identification

SDS number M6749
Part No. M6749
Tariff code 3811.19.0000

Recommended use Diesel Fuel Additive


Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name RSC Chemical Solutions
Address 600 Radiator Road
 Indian Trail, NC 28079
 United States
Telephone Customer Service: (704) 821-7643
 Technical: (704) 684-1811
Website www.rscbrands.com
E-mail sds@rscbrands.com
Emergency phone number Emergency Telephone: (303) 623-5716
 Emergency Contact: RMPDC (877-740-5015)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, dermal	Category 4
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	

Hazard statement	Flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. Causes eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	4.9% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 4.9% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha (petroleum), Hydrotreated Heavy		64742-48-9	20 - < 30
Solvent Naphtha (petroleum), Medium Aliph.		64742-88-7	20 - < 30
Stoddard Solvent		8052-41-3	20 - < 30
1,2,4-Trimethylbenzene		95-63-6	1 - < 3
BENZENE, DIMETHYL		1330-20-7	1 - < 3
NAPHTHALENE		91-20-3	1 - < 3
Nonane		111-84-2	1 - < 3
Trimethylbenzene		25551-13-7	1 - < 3
BENZENE, METHYL-		108-88-3	< 1
BENZENE,1-METHYLETHYL-		98-82-8	< 1
ETHYLBENZENE		100-41-4	< 1
HEXANE		110-54-3	< 1
BENZENE		71-43-2	< 0.2
Other components below reportable levels			10 - < 20

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
BENZENE (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
BENZENE, DIMETHYL (CAS 1330-20-7)	PEL	435 mg/m3
BENZENE, 1-METHYLETHYL- (CAS 98-82-8)	PEL	100 ppm
		245 mg/m3
ETHYLBENZENE (CAS 100-41-4)	PEL	50 ppm
		435 mg/m3
HEXANE (CAS 110-54-3)	PEL	100 ppm
		1800 mg/m3
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)	PEL	500 ppm
		400 mg/m3
NAPHTHALENE (CAS 91-20-3)	PEL	100 ppm
		50 mg/m3
Stoddard Solvent (CAS 8052-41-3)	PEL	10 ppm
		2900 mg/m3
		500 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
BENZENE (CAS 71-43-2)	Ceiling	25 ppm
	TWA	10 ppm
BENZENE, METHYL- (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
BENZENE (CAS 71-43-2)	STEL	2.5 ppm	
	TWA	0.5 ppm	
BENZENE, DIMETHYL (CAS 1330-20-7)	STEL	150 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
BENZENE, METHYL- (CAS 108-88-3)	TWA	100 ppm	Non-aerosol.
BENZENE, 1-METHYLETHYL- (CAS 98-82-8)	TWA	20 ppm	
ETHYLBENZENE (CAS 100-41-4)	TWA	50 ppm	
HEXANE (CAS 110-54-3)	TWA	20 ppm	
NAPHTHALENE (CAS 91-20-3)	TWA	50 ppm	
Nonane (CAS 111-84-2)	TWA	10 ppm	
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)	TWA	200 ppm	
Stoddard Solvent (CAS 8052-41-3)	TWA	200 mg/m3	
Trimethylbenzene (CAS 25551-13-7)	TWA	100 ppm	
	TWA	25 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3
BENZENE (CAS 71-43-2)	STEL	25 ppm
	TWA	1 ppm
BENZENE, METHYL- (CAS 108-88-3)	STEL	0.1 ppm
		560 mg/m3
	TWA	150 ppm
		375 mg/m3
BENZENE, 1-METHYLETHYL- (CAS 98-82-8)	TWA	100 ppm
		245 mg/m3
ETHYLBENZENE (CAS 100-41-4)	STEL	50 ppm
		545 mg/m3
	TWA	125 ppm
		435 mg/m3
HEXANE (CAS 110-54-3)	TWA	100 ppm
		180 mg/m3
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)	TWA	50 ppm
		400 mg/m3
NAPHTHALENE (CAS 91-20-3)	STEL	100 ppm
		75 mg/m3
	TWA	15 ppm
		50 mg/m3
Nonane (CAS 111-84-2)	TWA	10 ppm
		1050 mg/m3
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)	TWA	200 ppm
Stoddard Solvent (CAS 8052-41-3)	TWA	100 mg/m3
	Ceiling	1800 mg/m3
	TWA	350 mg/m3

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
BENZENE (CAS 71-43-2)	25 µg/g	S-Phenylmercapturic acid	Creatinine in urine	*
BENZENE, DIMETHYL (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
BENZENE, METHYL- (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
HEXANE (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

BENZENE (CAS 71-43-2)	Can be absorbed through the skin.
BENZENE, METHYL- (CAS 108-88-3)	Can be absorbed through the skin.
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Can be absorbed through the skin.
HEXANE (CAS 110-54-3)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BENZENE, METHYL- (CAS 108-88-3)	Skin designation applies.
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Skin designation applies.

US - Tennessee OELs: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Can be absorbed through the skin.
--------------------------------------	-----------------------------------

US ACGIH Threshold Limit Values: Skin designation

BENZENE (CAS 71-43-2)	Can be absorbed through the skin.
HEXANE (CAS 110-54-3)	Can be absorbed through the skin.
NAPHTHALENE (CAS 91-20-3)	Can be absorbed through the skin.
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)	Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Can be absorbed through the skin.
--------------------------------------	-----------------------------------

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Can be absorbed through the skin.
--------------------------------------	-----------------------------------

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection wear safety glasses with side shields (or goggles)

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Liquid.
Physical state	Liquid.
Form	Liquid.
Color	Orange/Brown
Odor	Pungent.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-94 °F (-70 °C) estimated
Initial boiling point and boiling range	314.6 °F (157 °C) estimated
Flash point	112.0 °F (44.4 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.7 % estimated
Flammability limit - upper (%)	6 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.29 hPa estimated
Vapor density	Not available.
Relative density	1.44
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	229 °F (109.44 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	6.88 lbs/gal
Explosive properties	Not explosive.
Flammability class	Flammable IC estimated
Moisture	< 0.5 %
Oxidizing properties	Not oxidizing.
Percent volatile	3.91 % estimated
Specific gravity	0.83
VOC (Weight %)	72.76 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Harmful in contact with skin. Causes skin irritation.
Eye contact	Causes eye irritation.
Ingestion	Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics	Headache. May cause drowsiness and dizziness. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.
---	---

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Harmful if inhaled. Harmful in contact with skin. Narcotic effects.
-----------------------	---

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 3160 mg/kg
Inhalation		
LC50	Rat	> 2000 ppm, 48 Hours
Oral		
LD50	Rat	6 g/kg
BENZENE (CAS 71-43-2)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	9980 ppm
	Rat	10000 ppm, 7 Hours
Oral		
LD50	Mouse	4700 mg/kg
	Rat	3306 mg/kg
BENZENE, DIMETHYL (CAS 1330-20-7)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 43 g/kg
Inhalation		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
Oral		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg
BENZENE, METHYL- (CAS 108-88-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12124 mg/kg 14.1 ml/kg
Inhalation		
LC50	Mouse	5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours

Components	Species	Test Results
		12200 ppm, 2 Hours
		8000 ppm, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
BENZENE,1-METHYLETHYL- (CAS 98-82-8)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	2000 ppm, 7 Hours
		24.7 mg/l, 2 Hours
	Rat	8000 ppm, 4 Hours
Oral		
LD50	Rat	1400 mg/kg
ETHYLBENZENE (CAS 100-41-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	17800 mg/kg
Oral		
LD50	Rat	3500 mg/kg
HEXANE (CAS 110-54-3)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	48000 ppm, 4 Hours
Oral		
LD50	Rat	24 mg/kg
	Wistar rat	49 mg/kg
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)		
<u>Acute</u>		
Inhalation		
LC50	Rat	61 mg/l, 4 Hours
Oral		
LD50	Rat	> 25 ml/kg
NAPHTHALENE (CAS 91-20-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2 g/kg
	Rat	> 20 g/kg
Oral		
LD50	Guinea pig	1200 mg/kg
	Rat	490 mg/kg
Nonane (CAS 111-84-2)		
<u>Acute</u>		
Inhalation		
LC50	Rat	3200 ppm, 4 Hours
Trimethylbenzene (CAS 25551-13-7)		
<u>Acute</u>		
Oral		
LD50	Rat	8970 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE (CAS 71-43-2)	1 Carcinogenic to humans.
BENZENE, DIMETHYL (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
BENZENE, METHYL- (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	2B Possibly carcinogenic to humans.
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
NAPHTHALENE (CAS 91-20-3)	2B Possibly carcinogenic to humans.
Stoddard Solvent (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

BENZENE (CAS 71-43-2)	Cancer
-----------------------	--------

US. National Toxicology Program (NTP) Report on Carcinogens

BENZENE (CAS 71-43-2)	Known To Be Human Carcinogen.
NAPHTHALENE (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	7.19 - 8.28 mg/l, 96 hours
BENZENE (CAS 71-43-2)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	8.76 - 15.6 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	7.2 - 11.7 mg/l, 96 hours
BENZENE, DIMETHYL (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours
BENZENE, METHYL- (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
BENZENE,1-METHYLETHYL- (CAS 98-82-8)			
Aquatic			
Crustacea	EC50	Brine shrimp (Artemia sp.)	3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.7 mg/l, 96 hours

Components		Species	Test Results
ETHYLBENZENE (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
HEXANE (CAS 110-54-3)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/l, 96 hours
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
NAPHTHALENE (CAS 91-20-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (Oncorhynchus gorbuscha)	1.11 - 1.68 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

BENZENE	2.13
BENZENE, DIMETHYL	3.12 - 3.2
BENZENE, METHYL-	2.73
BENZENE, 1-METHYLETHYL-	3.66
ETHYLBENZENE	3.15
HEXANE	3.9
NAPHTHALENE	3.3
Nonane	5.46
Stoddard Solvent	3.16 - 7.15

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1223
UN proper shipping name	Kerosene, solution (Solvent Naphtha (petroleum), Medium Aliph.), MARINE POLLUTANT
Transport hazard class(es)	
Class	3

Subsidiary risk	-
Label(s)	3
Packing group	III
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	144, B1, IB3, T2, TP2
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242

IATA

UN number	UN1223
UN proper shipping name	Kerosene solution (Solvent Naphtha (petroleum), Medium Aliph.)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	Yes
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (ALIPHATIC HYDROCARBON SOLVENT), MARINE POLLUTANT
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Nonane (CAS 111-84-2)

1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE (CAS 71-43-2)

Listed.

BENZENE, DIMETHYL (CAS 1330-20-7)

Listed.

BENZENE, METHYL- (CAS 108-88-3)

Listed.

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Listed.

ETHYLBENZENE (CAS 100-41-4)

Listed.

HEXANE (CAS 110-54-3)

Listed.

NAPHTHALENE (CAS 91-20-3)

Listed.

Nonane (CAS 111-84-2)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

BENZENE (CAS 71-43-2)

Cancer

Central nervous system

Blood

Aspiration

Skin

Eye

respiratory tract irritation

Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-Trimethylbenzene	95-63-6	1 - < 3
BENZENE, DIMETHYL	1330-20-7	1 - < 3
NAPHTHALENE	91-20-3	1 - < 3
BENZENE, METHYL-	108-88-3	< 1
BENZENE,1-METHYLETHYL-	98-82-8	< 1
ETHYLBENZENE	100-41-4	< 1
HEXANE	110-54-3	< 1
BENZENE	71-43-2	< 0.2

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE (CAS 71-43-2)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, METHYL- (CAS 108-88-3)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

BENZENE, METHYL- (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

BENZENE, METHYL- (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

BENZENE, METHYL- (CAS 108-88-3) 594

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE (CAS 71-43-2)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, METHYL- (CAS 108-88-3)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)
NAPHTHALENE (CAS 91-20-3)
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)
Stoddard Solvent (CAS 8052-41-3)
Trimethylbenzene (CAS 25551-13-7)

US. Massachusetts RTK - Substance List

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE (CAS 71-43-2)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, METHYL- (CAS 108-88-3)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)
NAPHTHALENE (CAS 91-20-3)
Nonane (CAS 111-84-2)
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)
Stoddard Solvent (CAS 8052-41-3)
Trimethylbenzene (CAS 25551-13-7)

US. New Jersey Worker and Community Right-to-Know Act

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE (CAS 71-43-2)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, METHYL- (CAS 108-88-3)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)
NAPHTHALENE (CAS 91-20-3)
Nonane (CAS 111-84-2)

Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)
Stoddard Solvent (CAS 8052-41-3)
Trimethylbenzene (CAS 25551-13-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE (CAS 71-43-2)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, METHYL- (CAS 108-88-3)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)
NAPHTHALENE (CAS 91-20-3)
Nonane (CAS 111-84-2)
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)
Stoddard Solvent (CAS 8052-41-3)
Trimethylbenzene (CAS 25551-13-7)

US. Rhode Island RTK

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE (CAS 71-43-2)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, METHYL- (CAS 108-88-3)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
NAPHTHALENE (CAS 91-20-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2)	Listed: February 27, 1987
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Listed: April 6, 2010
ETHYLBENZENE (CAS 100-41-4)	Listed: June 11, 2004
NAPHTHALENE (CAS 91-20-3)	Listed: April 19, 2002

US - California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2)	Listed: December 26, 1997
BENZENE, METHYL- (CAS 108-88-3)	Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

BENZENE, METHYL- (CAS 108-88-3)	Listed: August 7, 2009
---------------------------------	------------------------

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2)	Listed: December 26, 1997
-----------------------	---------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 01-20-2016
Version # 01
HMIS® ratings Health: 2*
Flammability: 3
Physical hazard: 0

NFPA ratings Health: 2
Flammability: 3
Instability: 0

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.