MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

Refer to supplier

Product name: MASTERS HEAVY DUTY FLAME PROTECTOR PAD

Product use: Protector Pad

Supplier name and address: Manufacturer name and address:

G.F. THOMPSON CO. LTD.
620 Steven Court, Unit #11
Newmarket, Ontario

L3Y 6Z2

Emergency Tel. #: WHMIS CLASS: N/A

Mon – Fri, 7:30 am to 5:00 pm EST 905-898-2557 800-499-3673 (toll free) **24 hr Emergency Tel:**

905-252-4793

SECTION II - HAZARDOUS INGREDIENTS

Material CAS# % OSHA PEL ACGIH TLV

Carbon and
Graphite Felt

100 N/E N/E

SECTION III - PHYSICAL DATA

Boiling Point: N/A
Vapour Pressure (mm Hg): N/A
Vapour Density (Air=1): N/A
Solubility in Water: Negligible
Specific Gravity (Water=1): N/A
Percent Volatile by Volume %: N/A

Evaporation Rate (Butyl Acetate=1): N/A Appearance/Odour: Black Felt: Negligible Odour

Fibre Density (g/cc): 1.4

SECTION IV - FIRE AND EXPLOSION DATA

Flash point (Method): N/A Upper flammable limit %: N/A Lower flammable limit %: N/A

Extinguishing Media: Water, difficult to ignite **Special Fire Fighting Procedures:** None

Unusual Fire and Explosion Hazards: Incinerating can generate airborne fibres which may cause

electrical malfunctions.

N/A - Not Applicable N/E - None Established

SECTION V – HEALTH DATA

Primary RoutesInhalation?Skin?Ingestion?Eyes?Of ExposureYesUnlikelyYes

Effects of Overexposure: Fibres may cause mechanical irritation to the eyes and skin. No significant inhalation hazards have been identified. If fibres are generated and ventilation is inadequate, use NIOSH/MSHA approved respirator.

Carcinogenicity NTP - No I ARC - No OSHA - No

SECTION VI-EMERGENCY AND FIRST AID PROCEDURES

For overexposure to graphite felt fibres:

Eyes: Flush with water for at least 15 minutes. Seek medical attention if irritation develops or persists. Always wear appropriate eye protection.

Lungs: Remove to fresh air. Seek medical attention if breathing becomes difficult.

Skin: Wash affected area thoroughly with mild soap and water. Gloves and/or protective skin creams may be helpful. Seek medical attention if irritation develops or persists.

SECTION VII – REACTIVITY DATA

Stability: Stable Conditions to Avoid: N/A

Incompatibility (Materials to Avoid): N/A Hazardous Decomposition Products: None

Hazardous Polymerization: Will not occur

SECTION VIII – SPILL AND LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Vacuum or sweep up spills taking care not to generate airborne fibres which can cause electrical malfunctions.

Waste disposal method: Incinerating can generate airborne fibres. Waste fibres should be bagged or containerized and buried in landfill where permitted according to local, Provincial and Federal regulations.

SECTION IX – SPECIAL PROTECTION INFORMATION

Respiratory Protection: NIOSH/MSHA approved respirator if airborne fibres are generated

Ventilation Requirements:

Local Exhaust: Yes. If fibres are generated **Special:** N/A

Mechanical (general): As necessary to minimize fibres Protective Gloves: Yes

Eye Protection: Safety Glasses with side shields, goggles or face shield.

Other Protective Clothing or Equipment: Long Sleeved clothing. Eye wash station.

OFFICAL V. OFFICAL PRODUCTIONS

SECTION X – SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing: Graphite fibres are electrically conductive and ay cause short circuits which may result in damage to or malfunction of electrical equipment. All forms of electrical equipment, enclosures and circuits in or near areas where fibres are used should be properly protected against infiltration of or contact with airborne particles or fibres.

Other precautions: Wash work clothes separately from other clothes.

Prepared by: G.F. THOMPSON CO. LTD.

Telephone #: 905-898-2557

Preparation date: December 1, 2012
