U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Shipbuilding,			ng (29 CFR 1915, 1916, 1917)	ing, =	- 11	
		SEC1	TION I			
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.					
SPARTAN CHEMICAL COMPANY, INC.			419/531-5551			
ADDRESS (Number, Street, City, State, and ZIP Co. 110 North Westwood Avenue, To.	ode) 1 edo	Ohio	43607			
CHEMICAL NAME AND SYNONYMS n/		, 01.20	TRADE NAME AND SYN MLD BOWL CLEANS	ONYMS		
CHEMICAL FAMILY n/a			FORMULA n/a			
			20/			
SECTION	111 -	HAZAF	RDOUS INGREDIENTS	1 1 2		1
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COA	ATINGS	%	TLV (Units)
PIGMENTS			BASE METAL			i ja
CATALYST			ALLOYS			
VEHICLE		<u>*</u> , =	METALLIC COATINGS			
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX			
ADDITIVES			OTHERS		4 1	
OTHERS	-				-	
HAZARDOUS MIXTURE	S OF (OTHER LIC	QUIDS, SOLIDS, OR GASES		%	TLV (Units)
n-alkyl (C ₁₄ -50%; C ₁₂ -40%;	C ₁₆	-10%) d	imethyl benzyl ammonium	chloride.	05	10
phosphoric acid						
•					25	

SEC	TION	VIII - P	HYSICAL DATA			
BOILING POINT (°F.)	210	0-212	SPECIFIC GRAVITY (H2O=1)		1.140	
VAPOR PRESSURE (mm Hg.)		33	PERCENT, VOLATILE BY VOLUME (%)		99	
VAPOR DENSITY (AIR=1)	unl	known	EVAPORATION RATE (less than 1	
SOLUBILITY IN WATER	con	mplete			LIM	11 +
APPEARANCE AND ODOR pink, nonvis	scous	s, phos	phoric acid based bowl c	leaner	-	
	FIRE		XPLOSION HAZARD DATA			11-1
FLASH POINT (Method used) none			FLAMMABLE LIMITS	Lel		Uel
EXTINGUISHING MEDIA n/a	1					
SPECIAL FIRE FIGHTING PROCEDURES	none	3				
4						
UNUSUAL FIRE AND EXPLOSION HAZARDS		none	*			

		ECTION	11/ 45	LTH HAZARD [ΛΛΤΛ			
THRESHOLD LIMIT	VALUE ,		· V · NEA	LITITIAZANUL	/A 1 A			
EFFECTS OF OVER	n/a							
	acid	l wi	ll irrita	te skin	<u> </u>			
EXTERNAL: In attention. teaspoon or milk or raw	Avoid contact nore of magne	ures Cidenta W/foo Sia, C	al contac d. INTER halk or s	t, flush w/pl NAL: call ph mall pieces o	enty of water and get medical ysician immediately. Drink a f soap, softened w/water in			
		SECTIO	ON VI - R	EACTIVITY DA	TA			
STABILITY	UNSTABLE		CONDITIONS TO AVOID					
	STABLE	Use only on vitreous to			collets and urinals			
INCOMPATABILITY	l	<u> </u>	<u> </u>					
HAZARDOUS DECO	MPOSITION PRODU	n/a						
			n/a	CONDITIONS TO	AVOID			
HAZARDOUS POLYMERIZATION	MAY OCCU	R	do not store near explosives or article					
, JET MERIZATION	WILL NOT	WILL NOT OCCUR		bearing yellow DOT labels				
flush w/wate waste disposal waste as above	METHOD	mal sa	nitary se	wer				
-g.*			SPECIAL P	ROTECTION IN	FORMATION			
RESPIRATORY PRO	TECTION (Specify 1	ype)						
VENTILATION	LOCAL EXHAUST				SPECIAL			
	MECHANICAL (G	eneral)		-	OTHER			
PROTECTIVE GLOV	recommende	ed.		EYE PROTECTION	recommended			
OTHER PROTECTIV	E EQUIPMENT	othing	special					
COSCOLITIONS TO				CIAL PRECAUT	TIONS			
n/a OTHER PRECAUTIO		Deing AN	S STOKING					

PAGE (2) GPO 930-540 Form OSHA-20 Rev. May 72