# SAFETY DATA SHEET



Date of issue/Date of revision 17 September 2016

Version 5

# **Section 1. Identification**

Product name : MOSAIC ULTRA SATIN RED BASE T50215

Product code : 00365087

Other means of : Not available.

identification

Product type : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against

: Not applicable.

Manufacturer : PPG Industries. Inc.

One PPG Place

Pittsburgh, PA 15272

**Emergency telephone** 

number

: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)

**Technical Phone Number** : 1-800-441-9695 (8:00 am to 5:00 pm EST)

## Section 2. Hazards identification

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available

for employees and other users of this product.

Classification of the substance or mixture

: Not classified.

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 34.9%

**GHS label elements** 

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

Prevention : Not applicable.

Response : Not applicable.

United States Page: 1/11

Date of issue 17 September 2016Version 5

Product name MOSAIC ULTRA SATIN RED BASE T50215

### Section 2. Hazards identification

Photosensitive agents: In case of accidental eve contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes. In case of accidental skin contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin.

**Storage** : Not applicable. **Disposal** : Not applicable.

Supplemental label

elements

: Sanding and grinding dusts may be harmful if inhaled. Emits toxic fumes when heated.

Hazards not otherwise

classified

None known.

# Section 3. Composition/information on ingredients

Substance/mixture Mixture

: MOSAIC ULTRA SATIN RED BASE T50215 **Product name** 

Ingredient name	%	CAS number
	≥5.0 - ≤10 ≥1.0 - ≤5.0	7727-43-7 6535-46-2

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### **Description of necessary first aid measures**

**Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice. In case of accidental eve contact, avoid concurrent exposure to the sun or other

sources of UV light which may increase the sensitivity of the eyes.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognized skin cleanser. Do NOT use solvents or thinners.

In case of accidental skin contact, avoid concurrent exposure to the sun or other

sources of UV light which may increase the sensitivity of skin.

: If swallowed, seek medical advice immediately and show this container or label. Keep Ingestion

person warm and at rest. Do NOT induce vomiting.

**United States** Page: 2/11

Date of issue 17 September 2016 Version 5

**Product name MOSAIC ULTRA SATIN RED BASE T50215** 

### Section 4. First aid measures

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

#### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

. .

Unsuitable extinguishing

media

: None known.

# Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

# Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

: Use an extinguishing agent suitable for the surrounding fire.

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides

halogenated compounds metal oxide/oxides

# Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

# Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

United States Page: 3/11

Date of issue 17 September 2016Version 5

Product name MOSAIC ULTRA SATIN RED BASE T50215

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### **Precautions for safe handling**

Protective measures Special precautions

- : Put on appropriate personal protective equipment (see Section 8).
- : If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

United States Page: 4/11

## Section 8. Exposure controls/personal protection

### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
parium sulfate	ACGIH TLV (United States, 3/2015).  TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction  OSHA PEL (United States, 2/2013).  TWA: 5 mg/m³ 8 hours. Form: Respirable fraction  TWA: 15 mg/m³ 8 hours. Form: Total dust
3-hydroxy-N-(o-tolyl)-4-[(2,4,5-trichlorophenyl)azo]naphthalene- 2-carboxamide	ACGIH TLV (United States).  TWA: 10 mg/m³

#### Key to abbreviations

Α	= Acceptable Maximum Peak	S	<ul> <li>Potential skin absorption</li> </ul>
ACGIH	= American Conference of Governmental Industrial Hygienists.	SR	<ul> <li>Respiratory sensitization</li> </ul>
С	= Ceiling Limit	SS	<ul> <li>Skin sensitization</li> </ul>
F	= Fume	STEL	= Short term Exposure limit values
IPEL	= Internal Permissible Exposure Limit	TD	= Total dust
OSHA	<ul> <li>Occupational Safety and Health Administration.</li> </ul>	TLV	= Threshold Limit Value
R	= Respirable	TWA	= Time Weighted Average

### Consult local authorities for acceptable exposure limits.

= OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

# Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

# Appropriate engineering controls

**Environmental exposure** controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection
Skin protection
Hand protection

: Safety glasses with side shields.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Gloves : polyethylene

United States Page: 5/11

Date of issue 17 September 2016 Version 5

Product name MOSAIC ULTRA SATIN RED BASE T50215

## Section 8. Exposure controls/personal protection

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.
Color : Various

Odor : Characteristic.
Odor threshold : Not available.

**pH** : 8.5

Melting point: Not available.Boiling point: 100°C (212°F)

Flash point : Closed cup: Not applicable. [Product does not sustain combustion.]

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Flammability (solid, gas) : Not available.

Lower and upper explosive : Upper: 0%

(flammable) limits

Evaporation rate

: 0.05 (butyl acetate = 1)

**Vapor pressure** : 3.3 kPa (25 mm Hg) [room temperature]

Vapor density : Not available.

Relative density : 1.16 Density ( lbs / gal ) : 9.68

**Solubility** : Partially soluble in the following materials: cold water.

Partition coefficient: n-

octanol/water

: Not available.

Viscosity : Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)

**Volatility** : 64% (v/v), 55.578% (w/w)

% Solid. (w/w) : 44.422

United States Page: 6/11

Date of issue 17 September 2016Version 5

**Product name MOSAIC ULTRA SATIN RED BASE T50215** 

## Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** 

: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Decomposition products may include the following materials: carbon monoxide, carbon

dioxide, smoke, oxides of nitrogen.

# **Section 11. Toxicological information**

### **Information on toxicological effects**

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
7-hydroxy-N-(o-tolyl)-4-[(2,4, 5-trichlorophenyl)azo] naphthalene-2-carboxamide	LD50 Oral	Rat	5.1 g/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

**Irritation/Corrosion** 

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

**Skin** : There are no data available on the mixture itself.

**Respiratory**: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Carcinogenicity

**Conclusion/Summary**: There are no data available on the mixture itself.

Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

United States Page: 7/11

Date of issue 17 September 2016Version 5

Product name MOSAIC ULTRA SATIN RED BASE T50215

## Section 11. Toxicological information

### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

Target organs : Contains material which may cause damage to the following organs: lungs, upper

respiratory tract, eyes.

### **Aspiration hazard**

Not available.

### Information on the likely routes of exposure

#### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Conclusion/Summary**: There are no data available on the mixture itself. Acrylate components of the mixture

have irritating properties. Prolonged or repeated contact with skin or mucous

membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure

and eye contact.

**Short term exposure** 

Potential immediate : There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

**Potential immediate**: There are no data available on the mixture itself.

effects

**Potential delayed effects**: There are no data available on the mixture itself.

Potential chronic health effects

General: No known significant effects or critical hazards.Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.

United States Page: 8/11

Date of issue 17 September 2016Version 5

**Product name MOSAIC ULTRA SATIN RED BASE T50215** 

## Section 11. Toxicological information

**Developmental effects** 

: No known significant effects or critical hazards.

**Fertility effects** 

Not available.

: No known significant effects or critical hazards.

## Section 12. Ecological information

### **Toxicity**

Not available.

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Not available.

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

Not available.

## Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# 14. Transport information

United States Page: 9/11

Date of issue 17 September 2016Version 5

### **Product name MOSAIC ULTRA SATIN RED BASE T50215**

## 14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
<b>Environmental hazards</b>	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

**DOT** : None identified. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

# Section 15. Regulatory information

### **United States**

**United States inventory (TSCA 8b)**: All components are listed or exempted.

#### **SARA 302/304**

**SARA 304 RQ** : Not applicable. **Composition/information on ingredients** 

No products were found.

### **SARA 311/312**

Classification : Not applicable. Composition/information on ingredients

Name	hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
3-hydroxy-N-(o-tolyl)-4-[(2,4, 5-trichlorophenyl)azo]naphthalene- 2-carboxamide	Yes.	No.	No.	No.	No.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

**United States** Page: 10/11

Date of issue 17 September 2016Version 5

Product name MOSAIC ULTRA SATIN RED BASE T50215

### Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 1 Flammability: 0 Physical hazards: 0

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health: 1 Flammability: 0 Instability: 0

Date of previous issue : 5/1/2016
Organization that prepared : EHS

the MSDS

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 11/11