

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Pressure Seal

Section I

Manufacturer's Name MYERS TIRE SUPPLY	Emergency Telephone Number None
Address (Number, Street, City, State, and ZIP Code) P. O. Box B, Professional Arts Bldg. Suite C Chambersburg, Pa. 17201	Telephone Number for Information 800-233-7086 Date Prepared April 1, 1990 Signature of Preparer (optional)

Section II - Hazardous Ingredients / Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Propylene Glycol CAS #57-55-6	NA	NA	NA	2
Ethylene Glycol Normal Butyl Ether CAS 111-76-2	50 ppm 240 mg/m ³	25 ppm 120 mg/m ³	None	2

DOT Classification - NA - Non Hazardous

UN # - NA- Non Hazardous

VOC - 52 gm. per lite

Section III - Physical / Chemical Characteristics

Boiling Point	212F - 100C	Specific Gravity (H2O = 1)	1.05
Vapor Pressure (mm Hg.)	26.5 at 25C - 77 F	Melting Point	Not Applicable
Vapor Density (Air = 1)	Not Applicable	Evaporation Rate (Butyl Acetate = 1)	More than 1
Solubility in Water	Dilutable		

Appearance and Odor Creamy texture, slight alcohol odor.

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) None Wet, Dry film 400F	Flammable Limits	LEL Not applicable	UEL Not Applicable
Extinguishing Media	Water, Dry Chemical, Co2, Alcohol Foam		
Special Fire Fighting Procedures	None		
Unusual Fire and Explosion Hazards	None		

NA - Not Applicable

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid	Excessive temperature extremes.
	Stable	X		

Incompatibility (Materials to Avoid) Strong oxidizers, chromic anhydrite, lead perchlorate, perchlorate acids.

Hazardous Decomposition or By products Thermal dcomposition may produce carbon monoxide & or carbon dioxide, less than 0.1% acrylate monomer.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhilation? X	Skin? No	Ingestion? X
--------------------	------------------	-------------	-----------------

Health Hazards (Acute and Chronic) Avoid exceeding PEL and TLV limits. If ingested call a physician & or transport to medical facility.

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? No
------------------	------------	------------------------	-----------------------

Signs and Symptoms of Exposure
 Inhilation - nausea or dizziness.
 Ingestion - irritation to digestive track.

Medical Conditions Generally Aggravated by Exposure Not Known

Emergency and First Aid Procedures Wash skin and eyes for ten minutes with copious amount of water. If ingested call a physician and or transport to medical facility.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled Flush spilled material into suitable retaining area or containers with large quantity of water. Small amounts of spilled material may be absorbed into an appropriate absorbant. Keep out of drains, sewers and waterways.

Waste Disposal Method Observe local, State and Federal regulations.

Precautions to Be Taken in Handling and Storing Keep containers in a cool and dry area. Use and store this product with adequate ventilation. (See Section IV) Keep product containers closed when not in use. Avoid subjecting this product to extreme temperature variations and freezing and shocking the emulsion with large quantities of chemicals.
 Other Precautions Careful handling practices should be exercised and unnecessary exposure avoided. Do not wear saturated clothing or shoes.

Section VIII - Control Measures

Respiratory Protection (Specify Type) Use in well ventilated area. Confined area conditions may warrant exhaust system.

Ventilation	Local Exhaust	Special	None
	If required to stay below PEL & TLV limits. Mechanical (General)	Other	None

Protective Gloves	Usually not required.	Eye Protection	Eye bath should be available. Safety Glasses with out side shields.
-------------------	-----------------------	----------------	--

Other Protective Clothing or Equipment Usually not required.

Work / Hygienic Practices Careful handling practices should be exercised and unnecessary exposure avoided. Do not wear saturated clothing or shoes.

NA - Not Applicable