

MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: MSS 20 Standard Gloss Seam Sealer

MCS 32 Commercial Seam Sealer MCS 42 Commercial Seam Sealer MCT-20 Seam Sealer Kit, 2 oz. Tube

Chemical Name: Vinyl Adhesive

Product Use/Class: Vinyl adhesive/seam sealer

Company Information: Mannington Mills, Inc.

P.O. Box 30 - Route 45 75 Mannington Mills Road Salem, New Jersey 08079

Phone Numbers: General: (856) 935-3000

Product Emergency: (866) 359-5602 Spill Response: (800) 424-9300

Effective Date: January 2, 2009 Supersedes Date: June 20, 2003

Reason for Revision: Update

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Weight %	Exposure Guidelines				
			ACGIH - TLV		OSHA - PEL		Other
			TWA	STEL	TWA	Ceiling	Other
Tetrahydrofuran	109-99-9	N/A	200 ppm	N/A	N/A	N/A	
Cyclohexanone	108-94-1	N/A	50 ppm	N/A	N/A	N/A	

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Form: Clear, colorless liquid

Color: Clear

Odor: Solvent odor

WARNING STATEMENTS

This material is flammable. Avoid breathing vapor.

POTENTIAL HEALTH EFFECTS

Primary Routes of Exposure

Eye Contact: Vapors may irritate eyes and mucus membranes.

Skin Contact: Contact with skin may cause irritation, possible rash or reddening upon contact. May cause allergic reaction or skin desensitization.

Inhalation: Inhalation of high vapor concentrations may have results ranging from dizziness, headaches, shortness of breath, muscular weakness to unconsciousness.

Ingestion: May be toxic if ingested in large amounts. May cause throat irritation, gastrointestinal discomfort, and vomiting.

Chronic: N/A

Other: Effects of Overexposure - Inhalation of high vapor concentrations may have results ranging from dizziness and headaches to unconsciousness. Prolonged or repeated liquid contact with the skin will dry and de-fat skin, leading to dermatitis.

Refer to Section 11 for toxicological information.

SECTION 4 - FIRST AID MEASURES

If in Eyes: Flush eyes with water for 15-20 minutes. Seek medical attention.

If on Skin: Wash skin thoroughly with soap and water.

If Inhaled: Move victim to fresh air. If unconscious, seek medical attention at once.

If Swallowed: Do not induce vomiting. Seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 6 Deg F

Lower Explosive Limit (LEL) %: Tetrahydrofuran 2.0% Cyclohexanone 1.1% **Upper Explosive Limit (UEL)** %: Tetrahydrofuran 11.8% Cyclohexanone 12.75%

Auto-Ignition Temperature: N.A.

OSHA Flammability Classification: N.A.

Hazardous Products of Combustion: See Section 10

Extinguishing Media: N.A.

Unusual Fire and Explosion Hazards: Flammable material

Fire Fighting Equipment: Use foam, carbon dioxide, or dry chemical fire fighting apparatus. **Miscellaneous Advice:** Solvent vapors can travel to an ignition source and flash back. Vapors can form explosive mixtures with air. Containers may vent, rupture, or burst at temperatures of 130 Deg F or over. Water spray may be used to keep closed containers cool to prevent pressure build-up. Firefighters should wear self-contained breathing apparatus and use equipment to protect against venting or bursting of containers. Avoid breathing vapors.

Refer to Section 10 for additional information.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Remove all possible sources of ignition.

Methods for Clean-up: Transfer to a suitable container using non-sparking tools.

Refer to Section 13 for disposal information.

Refer to Sections 14 and 15 for reportable quantity information.

SECTION 7 - HANDLING AND STORAGE

Handling: Use only in a well ventilated area.

Storage: Close containers after use. Store in a dry environment away from any sources of ignition. Keep from prolonged freezing for optimum performance. Acceptable storage temperature range is 35-95 deg F.

Consult the Mannington Professional Installation Handbook for additional information on handling and storage.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use adequate ventilation, local exhaust at point of use.

Respiratory Protection: Use NIOSH/MSHA approved air purifying respiration with combination

dust/mist filter and organic vapor cartridge if ventilation is not present.

Eye Protection: Chemical safety glasses.

Hand and Skin Protection: Use gloves if in contact with skin.

Other Protective Equipment:

Hygienic Practices: Always wash hands before eating, smoking or using toilet facilities. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, colorless liquid Water Solubility: Essentially insoluble

Volatiles (Wt. %): 92% **Physical State:** Liquid

Melting Point: VOC (calculated): Approx. 741 grams/liter **Boiling Point:** 151 deg F

Vapor Pressure: Tetrahydrofuran 143 mm Hg

Cyclohexanone 3.95 mm Hg

Evaporation Rate: Slower than ether Density:

Vapor Density: Heavier than water pH:

Specific Gravity: 0.92 (*Water* = 1.0) **Decomposition Temperature:**

SECTION 10 - STABILITY AND REACTIVITY

Conditions to Avoid: Sources of ignition, high temperatures. **Materials to Avoid:** Strong oxidizing agents and select amines.

Stability: Stable

Hazardous Reactions: N.A.

Hazardous Polymerization: Will not occur

Hazardous Decomposition Products: Thermal decomposition in the presence of air may yield

carbon monoxide, carbon dioxide, and/or oxides of nitrogen.

SECTION 11 - TOXICOLOGICAL INFORMATION

Product LD50 (Oral): N.A. Product LD50 (Dermal): N.A.

Product LC50: N.A.

Immediate (Acute) Effects: N.A.

Delayed (Subchronic & Chronic) Effects: Overexposure may cause irritation to eyes, skin, throat,

lungs, and nose.

SECTION 12 - ECOLOGICAL INFORMATION

Product produces slight toxicity to aquatic life. Insufficient data exists to evaluate the effect on plants, birds, or land animals.

SECTION 13 - DISPOSAL CONSIDERATIONS

US EPA RCRA Status: N.A.
Disposal Considerations: N.A.
Disposal Method: See below

Miscellaneous: Disposal should be done in accordance with all local, state and federal

(40 CFR Part 261) regulations. Be aware that state and local

requirements differ widely depending on location and may in many

cases be different from federal rules.

SECTION 14 - TRANSPORT INFORMATION

The information provided in this section is for information only. Please apply the appropriate regulations to properly classify your shipment for transport.

DOT Proper Shipping Name: N.A.
DOT Hazard Class: ORM-D
DOT UN/NA Number: N.A.
Packing Group: N.A.
Emergency Response Guide Number: N.A.

Other: DOT Consumer Commodity

SECTION 15 - REGULATORY INFORMATION

U.S. Federal Regulations: N.A. SARA Section 313: None Toxic Substances Control Act: N.A.

Inventory Status: N.A. Export Notification: N.A.

Other: California Proposition 65 - Tetrahydrofuran, CAS Number 109-99-9

SECTION 16 - OTHER INFORMATION

Hazard Ratings	Health	Fire	Reactivity	Additional Information
Suggested NFPA Rating	2	3	0	
Suggested HMIS Rating				

Disclaimer:

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date of hereof, the company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will the company be responsible for damages of any nature whatsoever resulting from the use of or reliance upon Information. NO REPRESENTATIONS OR WARRANTIES, ETHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

Legend:

N.E. - Not Established

N.A. - Not Available

N/A - Not Applicable

C - Ceiling (Exposure Levels)

PEL - Permissible Exposure Limits

OEL - Occupational Exposure Limit

TSCA - Toxic Substances Control Act

NFPA - National Fire Protection Association

TLV - Exposure Limits Developed by ACCIH

MSHA - Mine Safety and Health Administration

NIOSH - National Institute for Occupational Safety

OSHA - Occupational Safety and Health Administration

HAZCOM - Hazard Communication Standard (29CFR1910.1200)

ACGIH - American Conference of Government Industrial Hygienists

CERCLA - Comprehensive Environmental Response, Comprehensive and Liability Act

S - Skin

ppm - Parts per Million

° F. - Degrees Fahrenheit

° C. - Degrees Centigrade

STEL - Short-Term Exposure Limit

CIH - Certified Industrial Hygienist

TWA - Time Weighted Average