

# White Sands Hair Care, Inc.

27631 La Paz Road, Suite G  
Laguna Niguel, CA 92677  
949-206-1300

## Material Safety Data Sheet

(Complies with ANSI Z400.1-1998)

Product Name:	Infinity Finish Spray, 55% VOC (10.0 oz.)	<b>MSDS #</b> <b>WHI001-PR988</b> Issued: 5/5/04
Product Code:	WHI34000	

### Section 1. Chemical Product and Company Identification

Product Name:		Infinity Finish Spray, 55% VOC (10.0 oz.)		
Product Code:		WHI34000		
Product Class:		Aerosol Hair Spray		
<b><i>For further information contact:</i></b>				
White Sands Hair Care		Mon-Fri	Telephone:	949-206-1300 8 am to 5 pm PT
27631 La Paz Road, Suite G			Fax:	949-206-1313
Laguna Niguel, CA 92677			Web Site:	<a href="http://www.whitesandsproducts.com">www.whitesandsproducts.com</a>
<b><i>For Chemical Emergencies:</i></b>				
Spill, Leak, Fire or Accident		Telephone	1 800 424 9300	North America
Call CHEMTREC			1 703 527 3886	Others

### Section 2. Composition and Information on Ingredients

Hazardous Components:	CAS #	Vapor Pressure	Weight %	ACGIH TLV		OSHA PEL		Units
				TWA	STEL	TWA	STEL	
Specially Denatured Alcohol	64-17-5	44 mmHg@ 68 °F	≤55	1000		1000		ppm
Ethane, 1,1 Difluoro	75-37-6	64 psig@ 70 °F	≤45	N/E		N/E		ppm
NE = not established for this material.								
** = Components marked								

### Section 3. Hazard Identification

<b>Emergency Overview:</b>	<b>Warning: Flammable. Contents under pressure. Container may burst if heated.</b> Do not place in hot water, or near radiators, stoves or other sources of heat. Do not puncture or incinerate container or store at temperature over 120 °F. Do not use in presence
<b>Potential Health Effects:</b>	
<b>Eye contact:</b>	Contact may cause mild eye irritation including stinging, watering, and redness.
<b>Skin contact:</b>	Practically non-irritating to skin. Prolonged or repeated contact may result in defatting and drying to the skin which may result in skin irritation and dermatitis.
<b>Inhalation:</b>	Contains asphyxiant gases. Intentional inhalation of gases may cause headache, fatigue, weakness, mental confusion, mood disturbances, and decreased coordination and judgment. Severe overexposure may produce more serious symptoms, including coma and death
<b>Ingestion:</b>	No harmful or chronic effects are expected to occur from a single accidental ingestion. Intentional and continuous ingestion can cause serious effects on liver and kidney. Contains denatured alcohol.
<b>Chronic Effects:</b>	None when used as directed.

### Section 4. First Aid Measures

<b>Eye:</b>	Flush or rinse eye with tempered water while holding eyelid open. Remove contact lenses, if worn. If irritation or redness
-------------	--

	persists seek medical attention.
<b>Skin:</b>	Clean affected area(s) thoroughly by washing with mild soap and water, pat dry. If irritation or redness develops and persists, seek medical attention.
<b>Inhalation:</b>	If breathing difficulties develop, move victim away from source of exposure and into fresh air, give oxygen as necessary. Seek immediate medical attention.
<b>Ingestion:</b>	DO NOT induce vomiting. Have a conscious person drink two glasses of water. Seek medical attention.

## Section 5. Fire Fighting Measures

<b>Flammability Classification:</b>	<b>Flammable pursuant to CFR 16, Ch II Subchapter C, part 1500.45.</b>
<b>Aerosol Level</b>	<b>Aerosol Level 2</b> (REF: to NFPA 30B, Section 1-7 of August 6, 1998). <i>Code for the Manufacture and Storage of Aerosol Products.</i>
<b>Unusual Fire &amp; Explosion Hazards:</b>	Aerosols may burst at temperatures above 120 °F. Contents under pressure. Cool uninvolved containers to prevent possible bursting.
<b>Extinguishing Media:</b>	Use extinguishing agent suitable for type of surrounding fire.
<b>Fire Fighting Instructions:</b>	The use of self-contained breathing apparatus is recommended for fire fighters. <b>Fight fire upwind</b> . Containers exposed to intense heat from fires must be cooled with water to prevent vapor pressure buildup which could result in container rupture. Keep cont

## Section 6. Accidental Release Measures

**Large Spills:**  
Keep sources of ignition and hot metal surfaces isolated from spill. Stay upwind and away from spill/release. Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Wear appropriate prot

## Section 7. Handling and Storage.

<b>Handling:</b>	Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if likelihood of eye contact. Wash unintentional residue with soap and water.
<b>Storage:</b>	Store aerosol containers in cool, dry, well-ventilated areas away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from any incompatible material (see section 10). Protect container(s) against physical damage. To avoid unintention

## Section 8. Exposure Controls / Personal Protection

<b>Engineering Controls:</b>	A well ventilated room with adequate air circulation. Use local and general exhaust ventilation to effectively remove and prevent buildup of vapors/mist generated from the handling of this product.
<b>Respiratory:</b>	If used with adequate ventilation, no protective equipment is necessary.
<b>Skin:</b>	Not required based on the hazard of the material.
<b>Eye/Face:</b>	While contact with this material is not expected to cause appreciable irritation, the use of approved eye protection to safeguard against potential eye contact is considered good practice.
<b>Other Protective Equipment:</b>	A source of clean water should be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

## Section 9. Physical and Chemical Properties.

<b>Concentrate Only:</b>	<b>Finish Product:</b>
<b>Appearance:</b>	<b>Vapor Pressure:</b>
Clear liquid with fragrance/alcohol smell	55 - 65 psig @ 70 °F
<b>Boiling Range:</b>	
< 100 °F (38 °C)	
<b>Flash Point:</b>	
Not Applicable	

<i>Specific Gravity:</i>	0.815 (water=1)
<i>pH:</i>	Not Applicable
<i>Weight per Gallon:</i>	6.8 #/gal
<i>Solubility (water):</i>	soluble

#### Section 10. Stability and Reactivity

<i>Chemical Stability:</i>	Stable under normal conditions of storage and handling.
<i>Conditions to Avoid:</i>	High temperatures, above 120 °F, open flames and sparks.
<i>Incompatible Materials</i>	Avoid contact with strong oxidizing and reducing agents. Strong acids and bases. (Household Ammonia, Drain Openers etc.)
<i>Hazardous Decomposition</i>	Combustion may produce carbon monoxide, carbon dioxide and other unidentified organic compounds.
<i>Products:</i>	
<i>Hazardous Polymerization:</i>	Will not occur.

#### Section 11. Toxicological Information

No definitive information found on carcinogenicity, mutagenicity, target organs or developmental toxicity.

#### Section 12. Ecological Information

Not found

#### Section 13. Disposal Considerations

Along with properly characterizing all waste materials, consult state and local regulations regarding the proper disposal of this material.

#### Section 14. Transport Information

<b>1. DOT (Ground)</b>	
Shipping Name:	Consumer Commodity
Hazard Class:	ORM-D
<b>2. IMDG (Overseas)</b>	
Shipping Name:	Aerosols
Class:	2
UN No.:	1950
<b>3. IATA (Air)</b>	
Shipping Name:	Consumer Commodity
Class:	9
ID No.:	ID8000
Label:	Miscellaneous Dangerous Goods Class 9
Packaging Instructions:	910

#### Section 15. Regulatory Information

*Toxic Chemicals List under SARA Section 313 of the Title III and 40 CFR Part 372.*

None

*Chemicals under California Proposition 65*

None

*Flammability Classification 16 CFR, Ch II Subch. C, Part 1500.45*

Flammable

*Code of Manufacture and Storage of Aerosol Products NFPA 30B*

Aerosol Level 2

**Section 16. Documentary Information**

Issue Date: 05/05/04  
Revised: New  
Product Code: WHI34000

***Disclaimer of Expressed and Implied Warranties.***

The information in this document is believed to be correct as of the date issued. ***HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF***