

# MATERIAL SAFETY DATA SHEET

---

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### 2. Product Identification

Product Name: ProGuard Steam Cylinder Oil 680  
Product Number: 11313  
Synonyms: Petroleum Based Lubricant, Steam Cylinder Oil  
Chemical Name: Petroleum based lubricant

### Company Identification

Lyden Oil Company  
3711 LeHarps Road  
Youngstown, Ohio 44515 USA  
1-330-792-1100 (For product information) 1-800-362-9410  
(For emergencies)  
1-800-728-2482 or 1-703-527-3887 (CHEMTREC)

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### COMPONENT LISTING:

Chemical Name	Amount	CAS Number
RESIDUAL OIL, SOLVENT REFINED AND DEWAXED	80.0 - 90.0 %	64742-65-0
POLYBUTENE	10.0 - 15.0 %	9003-29-6
ADDITIVES	< 5.0 %	MIXTURE

(See Section 8 for exposure guidelines)

(See Section 15 for regulatory information)

### HAZARDS DISCLOSURE

This product contains no known hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

As defined under Sara 311 and 312, this product contains no known hazardous materials.

### 3. HAZARDS IDENTIFICATION

#### \*\*\*\*\* EMERGENCY OVERVIEW \*\*\*\*\*

- \* \*
- \* **Not expected to cause a severe emergency hazard.** \*
- \* \*

**HMIS Rating -** **Health: 1**

**Flammability: 1**  
**Reactivity: 0**

**NFPA Rating -** **Health: 0**

**Flammability: 1**  
**Reactivity: 0**  
**Special Hazard: N/A**

### POTENTIAL HEALTH EFFECTS

#### **EYE:**

Contact may cause eye irritation and redness.

#### **SKIN:**

Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

#### **INHALATION:**

Inhalation of vapors or mist may be mildly irritating to the nose, throat, and respiratory tract.

#### **INGESTION:**

Small amounts swallowed during normal handling operations are not likely to cause injury.

#### **CHRONIC EFFECTS:**

No adverse effects have been documented in humans as a result of chronic exposure.

#### **CARCINOGENICITY INFORMATION:**

Based on OSHA 1910.1200 and IARC study requirements, this product does not require labeling.

## 4. FIRST AID MEASURES

### **EYE CONTACT FIRST AID:**

Flush eye with water for 15 minutes.

Get medical attention if irritation develops or persists.

### **SKIN CONTACT FIRST AID:**

Wash skin with soap and water.

Thoroughly wash (or discard) clothing and shoes before reuse.

### **INHALATION FIRST AID:**

Remove to fresh air.

If not breathing, give artificial respiration.

### **INGESTION FIRST AID:**

If vomiting should occur spontaneously, keep airway clear.

### **NOTES TO PHYSICIAN:**

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

### **FLAMMABLE PROPERTIES**

COC Flash Point: 271.1 C (520.0 F)

Autoignition Temperature: N/A

### **FLAMMABLE LIMITS IN AIR**

LEL: 0.9 %

UEL: 7 %

### **EXTINGUISHING MEDIA:**

Carbon dioxide, foam, or dry powder. Water may be used to cool below flash point.

### **FIRE FIGHTING INSTRUCTIONS:**

As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

### **COMBUSTION PRODUCTS:**

Fumes, smoke and carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

## 6. ACCIDENTAL RELEASE MEASURES

### **SAFEGUARDS (PERSONNEL):**

Wear appropriate personal protective equipment.

### **INITIAL CONTAINMENT:**

Absorb spills with inert material.

### **LARGE SPILLS PROCEDURE:**

Contain spilled material.

Large spillage should be dammed-off and pumped into containers.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

### **SMALL SPILLS PROCEDURE:**

Clean up area by absorbent material.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

## 7. HANDLING AND STORAGE

### **HANDLING (PERSONNEL):**

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Wash hands thoroughly after handling.

### **HANDLING (PHYSICAL ASPECTS):**

Store in a cool dry area.

Keep container closed to avoid contamination.

### **STORAGE PRECAUTIONS:**

Keep container closed when not in use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### ENGINEERING CONTROLS:

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical ventilation to maintain exposure below PEL/TLV (s).

### EYE / FACE PROTECTION REQUIREMENTS:

Where contact with this material is likely, eye protection is recommended.

### SKIN PROTECTION REQUIREMENTS:

When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material.

### RESPIRATORY PROTECTION REQUIREMENTS:

When there is potential for airborne exposures in excess of applicable limits, wear NIOSH/MSHA approved respiratory protection.

### EXPOSURE GUIDELINES:

No Information Available.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

FORM	: Liquid
COLOR	: Dark Amber
ODOR	: Mild fatty odor
BOILING POINT	: >315 C
VAPOR PRESSURE	: <0.1 mm Hg @ 20 C
VAPOR DENSITY	: >2 (Air = 1)
SOLUBILITY IN WATER ....	: Nil
SPECIFIC GRAVITY	: 0.96 (Water = 1)
PH	: N/A
% VOLATILES	: Negligible %
VISCOSITY	: 680 cSt @ 40 C
EVAPORATION RATE	: Not established

## 10. STABILITY AND REACTIVITY

### STABILITY:

Stable.

### POLYMERIZATION:

Hazardous polymerization will not occur.

### INCOMPATIBILITY WITH OTHER MATERIALS:

Avoid contact with strong oxidizing agents.

---

**DECOMPOSITION:**

In the case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

**CONDITIONS TO AVOID:**

Sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

**EYE EFFECTS:**

Minimal irritation on contact.

**SKIN EFFECTS:**

Practically non-toxic if absorbed. May cause mild irritation with prolonged and repeated exposure.

**ACUTE ORAL EFFECTS:**

Tests on similar materials indicate low order of acute oral toxicity.

**ACUTE INHALATION EFFECTS:**

Low acute toxicity expected on inhalation.

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL HAZARDS:**

Ecotoxicological Information: No specific aquatic data available for this product.

## 13. DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:**

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

Do not flush to surface water or sanitary sewer system.

---

#### **CONTAINER DISPOSAL:**

Empty drums should be completely drained, properly bunged and promptly shipped to the supplier or a drum reconditioner.

All other containers should be disposed of in an environmentally safe manner.

### **14. TRANSPORTATION INFORMATION**

PRODUCT LABEL	: ProGuard Steam Cylinder Oil 680
D.O.T. SHIPPING NAME	: Not regulated by DOT
TECHNICAL SHIPPING NAME	: N/A
D.O.T. HAZARD CLASS	: N/A
UN NUMBER	: N/A
D.O.T. LABEL	: N/A
D.O.T. PLACARD	: N/A
BULK CLASS	: N/A
PACKAGE CLASS	: N/A

### **15. REGULATORY INFORMATION**

#### **REGULATORY LISTS SEARCHED:**

01 = CANADIAN DISCLOSURE LIST	02 = SARA Title III - Section 313
03 = CERCLA HAZARDOUS SUBSTANCES	04 = Clean Air Act - Section 112
05 = TITLE V	06 = CA Proposition 65
07 = SC TOXIC AIR POLLUTANTS LIST	

#### **MISCELLANEOUS INFORMATION:**

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA).

### **16. OTHER INFORMATION**

APPROVED BY	: Mark Falappi
TITLE	: Lubrication Engineer
APPROVAL DATE	: 10-17-08
SUPERCEDES DATE ...: New	
RTN NUMBER	: 00011313 (Official Copy)

**Disclaimer of Express or Implied Warranties** The information on this MSDS was obtained from sources we believe to be reliable. However, this information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and beyond our knowledge. For this and other reasons, Lyden Oil does not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable. Lyden Oil Company, Inc. believes this information is accurate but not all-inclusive in all circumstances. It is the responsibility of the user to determine suitability of the material for their purposes. No warranty, expressed or implied, is given.