

Search

GO

MSDS : SLIP PLATE AEROSOL (W/O 1,1,1-TRI)

CAS :

NAME : *** proprietary ***

SUPERIOR GRAPHITE CO -- SLIP PLATE AEROSOL (W/O 1,1,1-TRI)

Material Safety Data Sheet

MSDS Num: BYTYX

MSDS NAME: SLIP PLATE AEROSOL (W/O 1,1,1-TRI)

Responsible Party

Name: SUPERIOR GRAPHITE CO

Address: 120 SOUTH RIVERSIDE PLAZA

City: CHICAGO IL 60606

Info Phone: 312-559-2999

Emergency Phone Number: 502-885-7186

Preparer's Name: GEORGE RUSSELL

Proprietary Ind: Y

Published: Y

Contractor Summary

Name: SUPERIOR GRAPHITE CO.

Address: 10 S RIVERSIDE PLAZA

City: CHICAGO IL 60606-3913

Phone: 312-559-2999/502-885-7186

Ingredients

Name: *** PROPRIETARY ***

Health Hazards Data

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: NO

Ingestion: YES

Carcinogenicity Inds - NTP: YES

IARC: YES

OSHA: NO

Effects of Exposure: ACUTE: EYES, SKIN & RESP SYSTEM IRRIT. NARCOTIC IN HIGH CONCS. SEV OVEREXP MAY CAUSE DMG TO BLOOD. INHAL: RESP IRRIT, DIZZ, HDCH, NAUS, FATG, DROWS, IMPAIRED COORD, CNS DEPRESS/HEART ARRHYTH. SKIN: CO NT MAY DRY SKIN; PRLNGD CONT MAY CAUSE IRRIT. CAN NOT BE EASILY ABSORB THRU SKIN. SOLV ACTION CAN DRY &(EFTS OF OVEREXP)

Explanation Of Carcinogenicity: USERS OF THE "L" VERSION OF CONSULT THE "LR" VERSION INGREDIENT 10.

Signs And Symptoms Of Overexposure: HLTH HAZ: DEFAT SKIN CAUSING SKIN TO CRACK, LEADING TO DERM. EYES: LIQ/VAP CAN CAUSE MOD TO SEV IRRIT. CHRONIC: REPORTS HAVE ASSOC RPTD/PRLNGD OCCUP EXPOS TO SOLVS W/PERM BRAIN & NERVOUS SYS & OTHER I NTERNAL ORGAN DMG. NOTE: TOLUENE APPEARS ON NAVY LISTING OF OCCUP CHEM REPRO HAZS. SEEK CONSULT FROM APPROP(SUPDAT)

Medical Cond Aggravated By Exposure: LIVER & KIDNEY DISEASE, ANEMIA,

CORONARY DISEASE OR RHYTHM DISORDERS OF THE HEART.

First Aid: INGEST: DO NOT INDUCE VOMITING. SEEK MED ATTN. SKIN: REMOVE CONTAMINATED CLOTHING & WASH BEFORE REUSE. WIPE OFF WITH TOWEL. WASH WITH SOAP & WATER. GET MED ATTN IF IRRITATION DEVELOPS. INHAL: REMOVE TO FRESH AIR. ADMIN O₂ IF NEEDED. APPLY ARTIF RESPIRATOR IF BREATHING HAS STOPPED. GET MED ATTN. EYES: FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES & SEEK MED ATTN.

=====
Handling and Disposal

=====
Spill Release Procedures: AVOID BREATHING VAPORS. VENTILATE AREA, REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL & PLACE IN CLOSED CONTAINERS FOR DISPOSAL.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Handling And Storage Precautions: STORE & USE IN COOL, DRY, WELL-VENTILATED AREAS. DO NOT STORE >120°F. DO NOT PUNCTURE/INCINERATE CANS. DO NOT STICK PIN, NAIL/ANY OTHER SHARP OBJECT

Other Precautions: SMALL PRESSURE CONTAINERS OF FLAMMABLE PRODUCTS MAY BE STORED IN AREAS SUITABLE FOR ORDINARY COMBUSTION WITH RESPECT TO CONSTRUCTION, DRAINAGE, CONTROL OF IGNITION SOURCES & VENTS EXCEPT THAT THEY SHOULD NOT BE STORED IN BASEMENTS.

=====
Fire and Explosion Hazard Information

=====
Extinguishing Media: FOAM, ALCOHOL FOAM, CO₂, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (F.P.N.). WATER SPRAY MAY BE INEFFECTIVE. WATER EXPLODES WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLE (SUPPLEMENTAL DATA)

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE FROM INTERNAL PRESSURE BUILD-UP WHEN EXPOSED TO EXTREME HEAT & DISCHARGE CONTENTS. VAPOR ACCUMULATION CAN FLASH/EXPLODE IF IGNITED. OVEREXPOSURE TO (SUPPLEMENTAL DATA)

=====
Control Measures

=====
Respiratory Protection: NONE UNDER NORMAL USE. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE NIOSH/MSHA APPROVED CHEMICAL/MECHANICAL FILTER DESIGNED TO REMOVE COMBINATION OF PARTICLES & VAPOR. IN CONFINED AREAS, USE NIOSH/MSHA APPROVED AIR LINE TYPE RESPIRATOR/HOOD, SCBA IS REQUIRED FOR

Ventilation: LOCAL EXHAUST REQUIRED. MECHANICAL REQUIRED.

Protective Gloves: SOLVENT RESISTANT GLOVES.

Eye Protection: ANSI APPROVED CHEMICAL WORKERS GOGGLES (F.P.N.).

Other Protective Equipment: EMERGENCY EYE WASH AND DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA (F.P.N.).

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health: USERS OF THE "L" VERSION OF THIS DOCUMENT SHOULD CONSULT THE "LR" VERSION FOR FURTHER INFORMATION (F.P.N.). FIRE FIGHTING PROCEDURE: ARE PREPARED FOR EXPLOSION HAZARD: DECOMPOSITION PRODUCTS MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION. EFFECTS OF OVEREXPOSURE: HEALTH PROFESSIONALS CONCERNING LATEST HAZARD LIST INFORMATION & SAFE HANDLING & EXPOSURE INFORMATION (F.P.N.).

=====
Physical/Chemical Properties

=====
Solubility in Water: SLIGHT

Appearance and Odor: AEROSOL PRODUCT.

=====
Reactivity Data

=====
Stability Indicator: YES

Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.

Materials To Avoid: STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products: MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION, FUMES MAY CONTAIN CARBON MONOXIDE.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT.

=====
Toxicological Information

=====
=====
Ecological Information
=====

=====
=====
MSDS Transport Information
=====

=====
=====
Regulatory Information
=====

=====
=====
Other Information
=====

=====
=====
HAZCOM Label
=====

MSDS NAME: SLIP PLATE AEROSOL (W/O 1,1,1-TRI)

Company: SUPERIOR GRAPHITE CO.

Street: 10 S RIVERSIDE PLAZA

City: CHICAGO IL

Zipcode: 60606-3913

Health Emergency Phone: 502-885-7186

Label Required IND: Y

Date Of Label Review: 08/22/1995

Status Code: C

Label Date: 08/22/1995

Origination Code: G

Chronic Hazard IND: Y

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: WARNING

Respiratory Protection IND: YES

Health Hazard: Moderate

Contact Hazard: Moderate

Fire Hazard: None

Reactivity Hazard: None

Hazard And Precautions: ACUTE: EYES, SKIN AND RESPIRATORY SYSTEM IRRITATION. NARCOTIC IN HIGH CONCENTRATIONS. SEVERE OVEREXPOSURE MAY CAUSE DAMAGE TO BLOOD. INHALATION: RESPIRATORY IRRITATION, DIZZINESS, HEADACHE, NAUSEA, FATIGUE, DROWSINESS, IMPAIRED COORDINATION, CENTRAL NERVOUS SYSTEM DEPRESSION OR HEART ARRHYTHMIA. SKIN: CONTACT MAY CAUSE DRY SKIN; PROLONGED CONTACT MAY CAUSE IRRITATION. CAN NOT BE EASILY ABSORBED TH ROUGH SKIN. SOLVENT ACTION CAN DRY AND DEFAT CAUSING CRACKING AND DERMATITIS. EYES: LIQUID OR VAPOR CAN CAUSE MODERATE TO SEVERE IRRITATION. CHRONIC: CANCER HAZARD. CONTAINS MATERIAL WHICH IS LISTED A S AN ANIMAL LUNG CARCINOGEN(FP N).

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.

*** END OF RECORD ***

[Search More](#)



ALL PAGES On Chemical Property IN THIS GROUP

NAME	CAS
<u>0.35% PENTANE AND 19% OXYGEN IN NITROGEN</u>	109-66-0 7782-44-7 7727-37-9
<u>KENTEK K3</u>	9002-88-4 1333-86-4 41741-86-0 471-34-1 68611-44-9 1309-37-1 1304-28-5 1313-99-1 1314-13-2
<u>152 DEVELOPER PREMIX, 78-6969-8614-6</u>	7439-89-6 25213-39-2 58353-09-6 39382-25-7 1333-86-4 9003-07-0 8005-02-5
<u>PATCHING PLASTER, READY MIX RTV142, SILICONE SEALANT SPECIALTY HAND CLEANER</u>	64742-46-7 9004-82-4 8002-33-3 61789-40-0
<u>AFBC</u>	8001-54-5 112-34-5
<u>FLEETWELD 35C, AWSE6011</u>	65996-61-4 1344-09-8 13463-67-7 1309-48-4 7439-96-5 14808-60-7 1317-65-3 7439-89-6 584-08-7 7439-89-6
<u>SUPERBONDER 496 INSTANT ADHESIVE, 49661</u>	137-05-3 9011-14-7 123-31-9
<u>MIL-H-17672 D (2) GR 2075-T-H,A 0940 CARBON DIOXIDE, SOLID TECTYL 802A RM 320A CHRISTO-LUBE MCG 1002 OIL CHLORINE REAGENT #3</u>	64742-54-7 124-38-9
<u>CHLORINE REAGENT</u>	1310-73-2 88-14-2 7732-18-5 10102-17-7
<u>CHLORINE REAGENT #2</u>	1310-73-2 9005-84-9 881-49-8 7732-18-5 7681-11-0
<u>3M BRAND M-2950 CHEM-PAC FIXER</u>	50-21-5 7732-18-5 7732-18-5 7772-98-7

3M BRAND M-2950 CHEM-PAC WASH ADDITIVE

7775-19-1
64-19-7
10043-67-1
7757-83-7
107-21-1
7732-18-5
64-02-8
107-21-1
9002-93-1

CARPET PROTECTOR CONCENTRATE, 61-5000-0262-3
WELD-ON P-70 PRIME FOR PVC AND CPVC PASTIC PIPE
QUICK METAL PRESS FIT REPAIR, 66010

81-07-2
24448-20-2
27813-02-1
39382-25-7
112945-52-5
9003-20-7
80-15-9
67-56-1
13463-67-7
114-83-0
613-48-9
110-16-7

DARATHENE AEROSOL, 5037
ZINC 95 AEROSOL, 5028
AC 4368

TYPE 252 DEVELOPER PREMIX, 78-6969-5974-7

9003-07-0
8005-02-5
7439-89-6
25767-47-9
58353-09-6
1333-86-4

LOK-TITE STAIN SEALER (037159) (I)
2059 MONOLEX PENETRATING OIL & LUBRICANT
RUST VETO 4214-HF, 214215

8008-20-6
91-20-3
68526-77-2
64742-54-7
95-63-6
7440-39-3

TRI-MATIC, 0095
ZEREX ANTIFREEZE, NVS 547278
AIRCAIR PROTEX EXTRA, 53-XXX-500
XEROX XT-18 TONER
20401, DERUSTO BARBEQUE & STOVE BLACK (SUPDAT)
GLID-GUARD ALKYD INDUSTRIAL ENAMEL - WHITE, 4550
11067-2, 7651184, REAR VIEW MIRROR (SUPDAT)

71-55-6
13395-16-9
868-77-9
79-10-7
80-15-9
102-82-9
2530-85-0
1332-37-2
1317-61-9
7440-38-2
7440-43-9
7439-92-1
7440-41-7
1333-82-0

COPPERAS RED IRON OXIDE

FG RED
SELFLOC 2250

BJ INK CARTRIDGE BC-40, F45-0151-400/500

WEATHERBAN 606-NF WHITE SEALANT

SODIUM SILICATE N

235B2968, BAR RUST 235 MULTI PURPOSE EPOXY (SUPDAT) 1333-86-4
112945-52-5
25068-38-6
64742-95-6
14807-96-6
110-43-0
12001-26-2
71-36-3
13463-67-7

WELDON 2705 PVC PIPE CEMENT

109-99-9
78-93-3
108-94-1

U-418 QUICK CURE PRIMERLESS ADHESIVE

LATEX BASE DRYLOK MASONRY WATERPROOFER, 651

TRAFFIC PAINT-LCF YELLOW, 7312

64742-88-7
108-88-3
64742-89-8

SLIP PLATE AEROSOL (W/O 1,1,1-TRI)

MINT NI-712

BENZOIC ACID TECH, 05019

65-85-0

Free MSDS Search (Providing 250,000+ Material Properties)
Chemcas.com| Ads link:todaystock.net
Last modified: 05/01/2023 11:12:15