

**NOTE: MSDS SHEET FOR MYERS #31596 LUBE USED IN THE
6/5/08 Myers Manufactured # 31599 Hub Kit**

00006474	MATERIAL SAFETY DATA SHEET				Page 1
K-G PACKAGING 8001 KEELE STREET, P.O BOX 89 CONCORD; L4K 1Y8; ONTARIO					
PRODUCT: 1515-01-005 76215 TEFLON DRY LUBRICANT 11OZ (311G)					
  					
Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION					
MANUFACTURER	K-G PACKAGING INC. 8001 KEELE STREET P.O. BOX 89 ONTARIO CANADA L4K 1Y8 CANUTEC EMERGENCY #:1-613-996-6666(24HR)				
PRODUCT NAME.....	1515-01-005 76215 TEFLON DRY LUBRICANT 11OZ (311G)				
CHEMICAL FAMILY.....	ACRYLIC BASED COATING.				
MOLECULAR WEIGHT.....	NOT APPLICABLE.				
CHEMICAL FORMULA.....	MIXTURE.				
TRADE NAMES & SYNONYMS.....	1515-01-005 76215 TEFLON DRY LUBRICANT 11OZ (311G)				
PRODUCT USES.....	DRY LUBRICANT WITH TEFLON.				
FORMULA/LAB BOOK #.....	F 01-046.				
Section 02: COMPOSITION/INFORMATION INGREDIENTS					
Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route,Species	LC/50 Route,Species
ACETONE	30-60	750 ppm	67-64-1	>9750 mg/kg ORAL - RAT	>16,000 ppm (4 hr) INHAL - RAT
TOLUENE	10-30	50 ppm	108-88-3	5000 mg/kg ORAL - RAT	8000 ppm (4 hr) INHAL - RAT
PTFE DISPERSION	1-5	N.A.	9002-84-0	NOT AVAILABLE	NOT AVAILABLE
ISOBUTANE	7-15	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT
PROPANE	10-30	1000 ppm	74-98-6	NOT APPLICABLE	NOT AVAILABLE
Section 03: HAZARDS IDENTIFICATION					
ROUTE OF ENTRY: INGESTION.....	MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.				
INHALATION.....	INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE ASPHYXIANT.				
EYE CONTACT.....	MAY CAUSE IRRITATION.				
SKIN ABSORPTION.....	NO DATA AVAILABLE FOR THIS PRODUCT MIXTURE.				
SKIN CONTACT.....	MAY CAUSE IRRITATION.				
EFFECTS OF ACUTE EXPOSURE.....	DIZZINESS, NAUSEA, IRRITATION TO SKIN & EYES.				
EFFECTS OF CHRONIC EXPOSURE.....	SOLVENTS MAY CAUSE DEFATTING DERMATITIS				
EXPOSURE LIMIT OF MATERIAL.....	SEE SECTION 2.				
Section 04: FIRST AID MEASURES					
EMERGENCY FIRST AID PROCEDURE	IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.				
Section 05: FIRE FIGHTING MEASURES					
AUTO IGNITION TEMPERATURE (°C).....	465-480.				
SPECIAL PROCEDURES.....	WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.				
FLAMMABILITY.....	EXTREMELY FLAMMABLE.				
IF YES, UNDER WHICH CONDITIONS?.....	EXCESSIVE HEAT, SPARKS AND OPEN FLAME.				
EXTINGUISHING MEDIA.....	WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.				
FLASH POINT (C), TAG CLOSED CUP.....	LOWEST KNOWN VALUE IS ACETONE @ -18C.				
UPPER FLAMMABLE LIMIT.....	12.8.				
(% BY VOLUME)					
LOWER FLAMMABLE LIMIT.....	1.				
(% BY VOLUME)					
EXPLOSION DATA					
SENSITIVITY TO STATIC DISCHARGE.....	NOT APPLICABLE.				
SENSITIVITY TO IMPACT.....	NOT APPLICABLE.				
HAZARDOUS COMBUSTION PRODUCTS.....	HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.				
AEROSOL FLAME PROJECTION					

PRODUCT: 1515-01-005 76215 TEFLON DRY LUBRICANT 11OZ (311G)**Section 05: FIRE FIGHTING MEASURES**

CLASSIFIED AS:..... >15cm BUT <100cm.
FLASHBACK..... NONE.

Section 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL..... REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.

Section 07: HANDLING AND STORAGE

STORAGE NEEDS..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.
ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS).
HANDLING PROCEDURES AND EQUIPMENT..... STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.
SYNERGISTIC MATERIALS..... NONE KNOWN.

Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

GLOVES/ TYPE..... WEAR CHEMICAL RESISTANT GLOVES.
RESPIRATORY/TYPE..... IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED.
EYE/TYPE..... SAFETY GLASSES.
FOOTWEAR/TYPE..... NOT NORMALLY REQUIRED.
OTHER/TYPE..... NOT REQUIRED.

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... AEROSOL.
APPEARANCE..... CLOUDY, WHITE.
ODOR..... AROMATIC ODOR.
ODOR THRESHOLD..... NOT AVAILABLE.
VAPOUR PRESSURE(PSIG)-AEROSOL..... 65-75.
@ 20 C
BOILING POINT (°C)(CONC)..... 57-111.
EVAPORATION RATE..... GREATER THAN 1.
n-BUTYL ACETATE = 1
VAPOUR DENSITY (AIR=1)..... GREATER THAN 1.
(BY WEIGHT)
SOLUBILITY IN WATER g/L (20°C)..... NOT AVAILABLE.
pH..... NOT APPLICABLE.
SPECIFIC GRAVITY (LIQUID)..... 0.82-0.86.
COEFFICIENT OF WATER/OIL DIST..... NOT AVAILABLE.
FREEZING POINT: (°C)..... NOT AVAILABLE.
AEROSOL PERCENT VOLATILE..... 95-99.
(BY WEIGHT)
SPECIFIC GRAVITY (AEROSOL)..... 0.68 - 0.72.

Section 10: STABILITY AND REACTIVITY

HAZARDOUS PRODUCTS OF DECOMPOSITION..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
CHEMICAL STABILITY:
YES..... UNDER NORMAL CONDITIONS.
NO, WHICH CONDITIONS?..... NOT APPLICABLE.
COMPATIBILITY WITH OTHER SUBSTANCES:
NO, WHICH ONES?..... STRONG OXIDIZING AGENTS.
REACTIVITY CONDITIONS?..... NOT APPLICABLE.
HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

Section 11: TOXICOLOGICAL INFORMATION

REPRODUCTIVE EFFECTS..... TOLUENE - PROLONGED AND REPEATED EXPOSURE OF PREGNANT ANIMALS TO TOLUENE (LEVELS GREATER THAN APPROXIMATELY 1500 ppm) HAS BEEN REPORTED TO CAUSE ADVERSE FETAL DEVELOPMENTAL EFFECTS.
IRRITANCY OF MATERIAL..... SKIN/EYE IRRITANT.
SENSITIZING CAPABILITY OF MATERIAL..... UNKNOWN.
CARCINOGENICITY OF MATERIAL..... NONE KNOWN.
MUTAGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE MUTAGENIC EFFECTS ARE ANTICIPATED.
TERATOGENICITY..... NONE KNOWN.

Section 12: ECOLOGICAL CONSIDERATIONS

ENVIRONMENTAL..... NOT AVAILABLE.

PRODUCT: 1515-01-005 76215 TEFLON DRY LUBRICANT 11OZ (311G)

Section 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL..... DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

Section 14: TRANSPORTATION INFORMATION

T.D.G. CLASSIFICATION..... CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1).
D.O.T. CLASSIFICATION..... CONSUMER COMMODITY, ORM-D.

Section 15: REGULATORY INFORMATION

CANADIAN REGULATIONS:

WHMIS CLASSIFICATION..... A,B5,D2A,D2B.
CNFC SECTION 3.3.5..... LEVEL 3.

CEPA (Canadian Environmental Protection Act) LEVEL 3.
ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED.

U.S. REGULATIONS:

HMIS RATING HEALTH..... 2 MODERATE HAZARD.

HMIS RATING FLAMMABILITY..... 4 SEVERE HAZARD.

HMIS RATING REACTIVITY..... 1 SLIGHT HAZARD.
HMIS RATING PERSONAL PROTECTION..... 1 SLIGHT HAZARD.

HMIS RATING PERSONAL PROTECTION..... B.
NEPA SCORE 202 LEVEL 3

NFPA CODE 30B..... LEVEL 3.
SARA 313 INFORMATION:..... THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

108-88-3 TOLUENE

CALIFORNIA PROPOSITION 65:..... THE FOLLOWING

STATE OF CALIFORNIA PROP 65.....
THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986:
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA

TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

1. PRODUCT IDENTIFICATION: PRODUCT NAME: **CHLORINE BIRYL BIS(2-CHLOROPHENYL) NITRO**
CAS #: **100-50-4** CHEMICAL NAME: **CHLORINE BIRYL BIS(2-CHLOROPHENYL) NITRO**

100% TOLUENE 100% TOLUENE *108-88-3

TSCA (Toxic Substances Control Act)..... ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY

VOC (wt/wt%)
IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING.
55.69

Section 16: OTHER INFORMATION

NOTICE FROM KG PACKAGING INC THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY K-G PACKAGING INC. FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. K-G PACKAGING INC. ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

PREPARED BY..... ANY OTHER MATERIAL
PREPARATION DATE TECHNICAL SERVICES
May29/06