

Material Safety Data Sheet

Myers Order Nos. 46058, 46059

Date prepared: April 5, 2001

Section 1: Chemical Product and Company Information

Manufacturer: Myers Tire Supply
1293 South Main Street
Akron, OH 44309

Information Telephone: (717) 264-5819 (General Information)

Emergency Telephone: (800) 233-7086 (International Marketing Offices)

Product name: Concentrate Tire Paint
Product description: Styrene Acrylate Latex Based Paint
C.A.S. Number No classification- mixture.

Section 2: Composition/ Information on Ingredients

<u>Ingredients</u>	<u>CAS</u>	<u>Weight Percentage Range</u>
Water	7732-18-5	45-55
Acrylate polymer	Proprietary	20-30
Carbon Black	01333-86-4	12-20
Propylene glycol	57-55-6	1-3
Residual styrene	100-42-5	<25ppm

Section 3: Hazards Identification

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Contact with eyes may cause irritation and possible permanent damage to eye tissue.

SKIN CONTACT: Frequent or prolonged contact may cause irritation, dermatitis, or redness.

INHALATION: High vapor concentrations may be irritating to the eyes and respiratory tract, may cause headaches, dizziness, or drowsiness.

INGESTION: Ingestion of this product may cause abdominal discomfort, nausea, cramps, and other related symptoms.

Section 4: First Aid Measures

EYE CONTACT: Flush eyes with copious amounts of water until irritation subsides. If irritation persists, get medical attention.

SKIN CONTACT: Wash with large amounts of water, use soap if available.

INHALATION: Remove affected victim from exposure and bring them into fresh air.

INGESTION: If swallowed DO NOT induce vomiting. Keep at rest. Seek prompt medical attention.

Section 5: Fire-Fighting Measures

Flashpoint: >300F

Flammable limits in air: Not established

Autoignition temperature: Not established

NFPA Rating: **H 1 F 1 R 0**

Extinguishing Media:

Use water fog, foam or dry chemical extinguishing media.

Fire Fighting:

Use water spray to cool fire exposed surfaces and to protect personnel.

Firefighters should be equipped with self-contained breathing apparatus and turn out gear.

No unusual decomposition products are produced under fire conditions.

Section 6: Accidental Release Measures

Contain spill. Absorb product on inert material, shovel into appropriate container, and dispose with in accordance with local, state, and federal regulations. Prevent material from entering waterways. See section 8 for personal protective equipment while cleaning up the spill.

Section 7: Storage and Handling

Keep container closed when not in use. Handle and open containers with care. Store in a cool, well-ventilated place away from excessive heat or freezing conditions.

Avoid contact with skin and eyes.

Empty containers should not be reused unless thoroughly cleaned of product residues.

Protect from freezing!

Section 8: Exposure Controls/ Personal Protection

Always use in a well-ventilated area.

Personal Protective Equipment

Protective gloves should be worn to prevent prolonged or repeated skin contact. **Chemical goggles or Safety glasses with side shields** should be worn to prevent eye contact with spills or splashes.

Section 9: Physical and Chemical Properties

Specific Gravity (Water=1)	1.07-1.09
Solubility in water (%)	>95%
Viscosity	20K-50K centipoises (#4 @ 6 rpm; Brookfield)
Odor	Characteristic ammonia
Appearance	Black liquid, pudding-like consistency
Weight solids (%)	40.1-40.3
Volume solids (%)	35.4-35.6
pH	9-10.5
VOC	0.33 lbs/gl solids @ 105° C 0.19 lbs/gl liquid @ 105° C < 4 ppm @ 40° C (ambient temperature)

Section 10: Stability and Reactivity

Stability: Stable.

Hazardous Polymerization: Will not occur.

Incompatible Materials: Strong oxidizers.

Hazardous Decomposition: May produce harmful vapors upon combustion.

Section 11: Toxicological Information

Please refer to Section 3 of this MSDS for available information on the potential health effects of this product.

Section 12: Ecological Information

No specific ecological data is available for this product. Refer to section 6 of this MSDS for information regarding accidental releases.

Section 13: Disposal Considerations

Follow federal, state, and local regulations. Do not flush to drain or storm sewer.

Section 14: Transport Information

Freight Description:

Liquid latex paint, NOI, NMFC 149980 sub 2
This product is non-hazardous and non-regulated by DOT.

Section 15: Regulatory Information

TSCA: This product's components are listed on the EPA's TSCA Inventory or are exempt from notification requirements.

SARA 311 Categories:

Immediate (Acute) Health Effects: Yes (See section 3 for details)

Delayed (Chronic) Health Effects: None determined

Fire Hazard: No

Sudden Release of Pressure Hazard: No

Section 16: Other Information

Hazardous Materials Identification System Ratings:

H 1 F 0 R 0 PP