

Material Safety Data Sheet

A490 SKID Penetrant/Lubricant

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: SKID Penetrant/Lubricant
Product Code: A490
Version Date: 01/12/09
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS #	ACGIH TLV	Exposure Limits OSHA PEL	OTHER
Petroleum hydrocarbon	1330-20-7	100 ppm	Not established	Not established
Hydrocarbon propellant	68-476-86-8	800 ppm	Not established	Not established
NJ Trade Secret Registry	#80100382-5007P	Not established	Not established	Not established
Petroleum hydrocarbon	64741-89-5	5 mg/m3 (oil mist)	Not established	Not established
NJ Trade Secret Registry	#80100382-5139P	Not established	Not established	Not established

3. HAZARDS IDENTIFICATION

POTENTIAL ACUTE [single or short term] HEALTH EFFECTS OF OVEREXPOSURE

Eye : Can cause severe eye irritation.

Skin : Skin contact may cause irritation. Symptoms may include redness, discomfort, drying and cracking, or rash. Prolonged or repeated exposure may dry the skin. Liquid may cause frostbite. Prolonged or repeated contact with liquid can cause irritation and dermatitis. Can cause severe irritation.

Ingestion : This product may be harmful or fatal if swallowed.

Inhalation : Breathing small amounts during handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits. Symptoms of exposure may include: initial Central Nervous System excitation (euphoria, exhilaration, light-headedness) followed by CNS depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other CNS effects, such as confusion, impaired coordination, coma, and death. May cause nausea, vomiting, coughing and pulmonary irritation.

POTENTIAL CHRONIC [long term] HEALTH EFFECTS OF OVEREXPOSURE:

General Effects: This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. The relevance of these findings to humans is uncertain. Excessive exposure may cause lung injury. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible kidney effects. mild, reversible liver effects. nervous system effects. liver abnormalities. respiratory tract damage (nose, throat, and airways). kidney damage.

Cancer Information: A component(s) of this product is listed as a known carcinogen to humans by International Agency for Research on Cancer (IARC), the American Conference of Governmental Industrial Hygienists (ACGIH), the US National Toxicology Program (NTP) and with OSHA.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Skin contact may aggravate an existing dermatitis.

HMIS® III* HAZARDOUS WARNINGS:

Health: 2 Flammability: 4 Physical: 1 Personal Protective Equipment: See Section 8

* See www.paint.org/hmis or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.

Ingestion: If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Do not induce vomiting. Have victim drink 8 to 10 ounces of water to dilute the material in the stomach. Contact a physician, medical facility, or poison control center immediately. Aspiration into the lungs can cause serious damage.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep the victim warm and quiet. Seek immediate medical attention.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; auditory system; arrhythmias (irregular heartbeats);

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.

Fire Fighting Instructions: Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area. Do not direct a solid stream of water or foam into hot burning pools, this may cause frothing and increase fire intensity.

Aerosol Flame Projection Test: Extremely flammable aerosol, as determined by ASTM D 3065-94. Do not use near ignition sources such as sparks or open flames.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. Wear appropriate clothing.

7. HANDLING AND STORAGE

Handling: Do not use near ignition sources. Use with adequate ventilation. Avoid prolonged or repeated contact with skin. This material can be harmful or irritating. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Avoid prolonged or repeated breathing of vapor. Wash hands thoroughly after handling. Use bonding and grounding when transferring quantities of material.

Storage: Keep away from heat, sparks and flame. Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 120 degrees F. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Empty container may contain residues which are hazardous.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated in "Section 2" of this MSDS (from known, suspected or apparent adverse effects). Ventilation is required to maintain operator exposure below published exposure limits. Local exhaust should be used in areas where exposure limits may be exceeded.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.

Respiratory Protection: A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Vapor Density:	[air = 1] 1.74
Appearance:	Clear with yellow tint	Evaporation Rate:	0.02-0.1 (n-Butyl acetate = 1)
Odor:	Petroleum	Solubility in Water:	Negligible; 0-1%
Specific Gravity:	0.78 (H ₂ O=1)	Boiling Point:	Not applicable°F
Vapor Pressure:	38.00 PSIG @ 70°F	pH:	Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Conditions to Avoid: Avoid contact with: Strong oxidizing agents. Strong acids. Strong bases. Open flames and high temperatures.

Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons. Polymer fragments. Carbon Monoxide.

11. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

12. TRANSPORTATION INFORMATION

Agency	Proper Shipping name	UN Number	Hazard Class	Packing Group
DOT	Consumer commodity	Not applicable	ORM-D	Not applicable
IATA	Consumer commodity	Not applicable	9	Not applicable

13. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.

Ethyl benzene	100-41-4	1- 10	Prop65 Cancer
Benzene	71-43-2	0.001- 0.01	Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.

Toluene	108-88-3	0.1- 1	Prop65 Birth Defects
Benzene	71-43-2	0.001- 0.01	Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.