

# Material Safety Data Sheet



**SECTION 1 PRODUCT AND COMPANY IDENTIFICATION**

## CHEVRON and TEXACO PREMIUM UNLEADED GASOLINES

**Product Use:** Fuel

**Product Number(s):** CPS201019 [See Section 16 for Additional Product Numbers]

**Synonyms:** Calco Premium Gasoline, Chevron Premium Unleaded Gasoline, Chevron Supreme Plus Unleaded Gasoline, Chevron Supreme Unleaded Gasoline, Gasolines, Automotive, Texaco Power Premium Unleaded Gasoline

**Company Identification**

Chevron Products Company  
Marketing, MSDS Coordinator  
6001 Bollinger Canyon Road  
San Ramon, CA 94583  
United States of America

**Transportation Emergency Response**

CHEMTREC: (800) 424-9300 or (703) 527-3887

**Health Emergency**

Chevron Emergency Information Center: Located in the USA. International collect calls accepted. (800) 231-0623 or (510) 231-0623

**Product Information**

MSDS Requests: <http://www.chevron.com/contact>  
Technical Information: (510) 242-5357

SPECIAL NOTES: This MSDS applies to: all motor gasoline.

**SECTION 2 HAZARDS IDENTIFICATION**

\*\*\*\*\*

**EMERGENCY OVERVIEW**

- EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE
- HARMFUL OR FATAL IF SWALLOWED - MAY CAUSE LUNG DAMAGE IF SWALLOWED
- MAY CAUSE RESPIRATORY TRACT IRRITATION IF INHALED
- MAY CAUSE DIZZINESS, DROWSINESS AND REDUCED ALERTNESS
- CAUSES SKIN IRRITATION
- KEEP OUT OF REACH OF CHILDREN
- MAY CAUSE CANCER BASED ON ANIMAL DATA
- TOXIC TO AQUATIC ORGANISMS. MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT

\*\*\*\*\*

**IMMEDIATE HEALTH EFFECTS**

**Eye:** Not expected to cause prolonged or significant eye irritation.

**Skin:** Contact with the skin causes irritation. Skin contact may cause drying or defatting of the skin. Contact with the skin is not expected to cause an allergic skin response. Symptoms may include pain, itching, discoloration, swelling, and blistering. Not expected to be harmful to internal organs if absorbed through the skin.

**Ingestion:** Because of its low viscosity, this material can directly enter the lungs, if swallowed, or if subsequently vomited. Once in the lungs it is very difficult to remove and can cause severe injury or death.

**Inhalation:** The vapor or fumes from this material may cause respiratory irritation. Symptoms of respiratory irritation may include coughing and difficulty breathing. Excessive or prolonged breathing of this material may cause central nervous system effects. Central nervous system effects may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion, or disorientation. At extreme exposures, central nervous system effects may include respiratory depression, tremors or convulsions, loss of consciousness, coma or death.

**DELAYED OR OTHER HEALTH EFFECTS:**

**Reproduction and Birth Defects:** This material is not expected to cause birth defects or other harm to the developing fetus based on animal data.

**Cancer:** Prolonged or repeated exposure to this material may cause cancer. Contains naphthalene, which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) by the International Agency for Research on Cancer (IARC). Gasoline has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) by the International Agency for Research on Cancer (IARC).

Contains benzene, which has been classified as a carcinogen by the National Toxicology Program (NTP) and a Group 1 carcinogen (carcinogenic to humans) by the International Agency for Research on Cancer (IARC).

Contains ethylbenzene which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) by the International Agency for Research on Cancer (IARC).

Whole gasoline exhaust has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) by the International Agency for Research on Cancer (IARC).

Contains benzene, which has been classified as an A1 Group Confirmed Human Carcinogen by the American Conference of Governmental Industrial Hygienists (ACGIH).

See Section 11 for additional information. Risk depends on duration and level of exposure.

**SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS**

COMPONENTS	CAS NUMBER	AMOUNT
Gasoline	86290-81-5	100 %vol/vol
Benzene	71-43-2	0.1 - 4.9 %vol/vol
Toluene (methylbenzene)	108-88-3	1 - 35 %vol/vol
Ethyl benzene	100-41-4	0.1 - 3 %vol/vol
Xylene (contains o-, m-, & p- xylene isomers in varying amounts)	1330-20-7	1 - 15 %vol/vol
Butane	106-97-8	1 - 12 %vol/vol
Heptane	142-82-5	1 - 4 %vol/vol
Hexane	110-54-3	1 - 5 %vol/vol
Cyclohexane	110-82-7	1 - 3 %vol/vol
Methylcyclohexane	108-87-2	1 - 2 %vol/vol
Pentane, 2,2,4-trimethyl- (Isooctane)	540-84-1	1 - 13 %vol/vol
Naphthalene	91-20-3	0.1 - 2 %vol/vol
Ethanol	64-17-5	0 - 10 %vol/vol
Methyl tert-butyl ether (MTBE)	1634-04-4	<= 0.1 %vol/vol

Information on ingredients that are considered Controlled Products and/or that appear on the WHMIS Ingredient Disclosure List (IDL) is provided as required by the Canadian Hazardous Products Act (HPA, Sections 13 and 14). Ingredients considered hazardous under the OSHA Hazard Communication Standard, 29 CFR 1910.1200, are also listed. See Section 15 for additional regulatory information.

#### SECTION 4 FIRST AID MEASURES

**Eye:** No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

**Skin:** Wash skin with water immediately and remove contaminated clothing and shoes. Get medical attention if any symptoms develop. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

**Ingestion:** If swallowed, get immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

**Inhalation:** Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if breathing difficulties continue or if any other symptoms develop.

**Note to Physicians:** Ingestion of this product or subsequent vomiting may result in aspiration of light hydrocarbon liquid, which may cause pneumonitis.

#### SECTION 5 FIRE FIGHTING MEASURES

See Section 7 for proper handling and storage.

##### FLAMMABLE PROPERTIES:

**Flashpoint:** (Tagliabue Closed Cup ASTM D56) < -45 °C (< -49 °F)

**Autoignition:** > 280 °C (> 536 °F)

**Flammability (Explosive) Limits (% by volume in air):** Lower: 1.4 Upper: 7.6 (Typical)

**EXTINGUISHING MEDIA:** Dry Chemical, CO<sub>2</sub>, AFFF Foam or alcohol resistant foam if >15% volume polar solvents (oxygenates).

##### PROTECTION OF FIRE FIGHTERS:

**Fire Fighting Instructions:** Use water spray to cool fire-exposed containers and to protect personnel. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

**Combustion Products:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

#### SECTION 6 ACCIDENTAL RELEASE MEASURES

**Protective Measures:** Eliminate all sources of ignition in the vicinity of the spill or released vapor. If this material is released into the work area, evacuate the area immediately. Monitor area with combustible gas indicator.

**Spill Management:** Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. All equipment used when handling the product must be grounded. A vapor suppressing foam may be used to reduce vapors. Use clean non-sparking tools to collect absorbed material. Where feasible and appropriate, remove contaminated soil. Place contaminated

materials in disposable containers and dispose of in a manner consistent with applicable regulations.  
**Reporting:** Report spills to local authorities as appropriate or required.

## SECTION 7 HANDLING AND STORAGE

**Precautionary Measures:** Do not get in eyes, on skin, or on clothing. This product presents an extreme fire hazard. Liquid very quickly evaporates, even at low temperatures, and forms vapor (fumes) which can catch fire and burn with explosive violence. Invisible vapor spreads easily and can be set on fire by many sources such as pilot lights, welding equipment, and electrical motors and switches. Do not taste or swallow. Do not breathe vapor or fumes. Never siphon gasoline by mouth. Do not store in open or unlabeled containers. **READ AND OBSERVE ALL PRECAUTIONS ON PRODUCT LABEL.** Keep out of the reach of children. Wash thoroughly after handling.

**General Handling Information:** Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

**Static Hazard:** Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids', National Fire Protection Association (NFPA 77, 'Recommended Practice on Static Electricity', and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents'. Improper filling of portable gasoline containers creates danger of fire. Only dispense gasoline into approved and properly labeled gasoline containers. Always place portable containers on the ground. Be sure pump nozzle is in contact with the container while filling. Do not use a nozzle's lock-open device. Do not fill portable containers that are inside a vehicle or truck/trailer bed.

**General Storage Information:** DO NOT USE OR STORE near heat, sparks, flames, or hot surfaces . USE AND STORE ONLY IN WELL VENTILATED AREA. Keep container closed when not in use.

**Container Warnings:** Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

## SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

### ENGINEERING CONTROLS:

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits.

### PERSONAL PROTECTIVE EQUIPMENT

**Eye/Face Protection:** No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

**Skin Protection:** Wear protective clothing to prevent skin contact. Selection of protective clothing may include gloves, apron, boots, and complete facial protection depending on operations conducted. Suggested materials for protective gloves include: Chlorinated Polyethylene (or Chlorosulfonated Polyethylene), Nitrile Rubber, Polyurethane, Viton.

**Respiratory Protection:** Determine if airborne concentrations are below the recommended occupational exposure limits for jurisdiction of use. If airborne concentrations are above the acceptable limits, wear an approved respirator that provides adequate protection from this material, such as: Air-Purifying Respirator for Organic Vapors.

When used as a fuel, this material can produce carbon monoxide in the exhaust. Determine if airborne concentrations are below the occupational exposure limit for carbon monoxide. If not, wear an approved positive-pressure air-supplying respirator.

Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

**Occupational Exposure Limits:**

Component	Country/ Agency	TWA	STEL	Ceiling	Notation
Benzene	ACGIH	.5 ppm (weight)	2.5 ppm (weight)	--	Skin A1 Skin
Benzene	CVX	1 ppm (weight)	5 ppm (weight)	--	--
Butane	ACGIH	1000 ppm (weight)	--	--	--
Cyclohexane	ACGIH	100 ppm (weight)	--	--	--
Ethanol	ACGIH	1000 ppm (weight)	--	--	A4 A3
Ethyl benzene	ACGIH	20 ppm (weight)	125 ppm (weight)	--	A3
Gasoline	ACGIH	300 ppm (weight)	500 ppm (weight)	--	A3
Heptane	ACGIH	400 ppm (weight)	500 ppm (weight)	--	--
Hexane	ACGIH	50 ppm (weight)	--	--	Skin
Methyl tert-butyl ether (MTBE)	ACGIH	50 ppm (weight)	--	--	A3
Methyl tert-butyl ether (MTBE)	CVX	--	50 ppm	--	--
Methylcyclohexane	ACGIH	400 ppm (weight)	--	--	--
Naphthalene	ACGIH	10 ppm (weight)	15 ppm (weight)	--	Skin
Pentane, 2,2,4-trimethyl- (Isooctane)	ACGIH	300 ppm (weight)	--	--	--
Toluene (methylbenzene)	ACGIH	50 ppm (weight)	--	--	Skin A4
Xylene (contains o-, m-, & p- xylene isomers in varying amounts)	ACGIH	100 ppm (weight)	150 ppm (weight)	--	A4

NOTE ON OCCUPATIONAL EXPOSURE LIMITS: Consult local authorities for acceptable provincial values

in Canada. Consult the Canadian Standards Association Standard 94.4-2002 Selection, Use and Care of Respirators.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

**Attention:** the data below are typical values and do not constitute a specification.

**Color:** Colorless to yellow

**Physical State:** Liquid

**Odor:** Petroleum odor

**pH:** Not Applicable

**Vapor Pressure:** 5 psi - 15 psi (Typical) @ 37.8 °C (100 °F)

**Vapor Density (Air = 1):** 3 - 4 (Typical)

**Boiling Point:** 37.8°C (100°F) - 204.4°C (400°F) (Typical)

**Solubility:** Insoluble in water; miscible with most organic solvents.

**Freezing Point:** Not Applicable

**Melting Point:** Not Applicable

**Specific Gravity:** 0.7 g/ml - 0.8 g/ml @ 15.6°C (60.1°F) (Typical)

**Viscosity:** <1 SUS @ 37.8°C (100°F)

**Evaporation Rate:** No data available

**Odor Threshold:** No data available

**Coefficient of Water/Oil Distribution:** No data available

## SECTION 10 STABILITY AND REACTIVITY

**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Incompatibility With Other Materials:** May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

**Hazardous Decomposition Products:** None known (None expected)

**Hazardous Polymerization:** Hazardous polymerization will not occur.

**Sensitivity to Mechanical Impact:** No.

## SECTION 11 TOXICOLOGICAL INFORMATION

### IMMEDIATE HEALTH EFFECTS

**Eye Irritation:** The eye irritation hazard is based on evaluation of data for similar materials or product components.

**Skin Irritation:** For a 4-hour exposure, the Primary Irritation Index (PII) in rabbits is: 4.8/8.0.

**Skin Sensitization:** This material did not cause skin sensitization reactions in a Buehler guinea pig test.

**Acute Dermal Toxicity:** LD50: >3.75g/kg (rabbit).

**Acute Oral Toxicity:** LD50: >5 ml/kg (rat)

**Acute Inhalation Toxicity:** 4 hour(s) LD50: >20000mg/m<sup>3</sup> (rat). **Subchronic Effects:** Exposure of rats for 13 weeks (6 hr/day for 5 days/week) to the light ends of gasoline (up to 20,000 mg/m<sup>3</sup>) resulted in minimal responses of toxicity. There were no indications of neurotoxicity based morphological, functional and biochemical indices. There was also no evidence of immunotoxicity in the rats. However, when rats were exposed to gasoline vapor containing ethanol up to 20,000 mg/m<sup>3</sup> there was evidence of both humoral immune suppression and mild astrogliosis. **Reproduction and Birth Defects:** Exposure of rats to the light ends of gasoline at up to 20,000 mg/m<sup>3</sup> had generally no impact upon reproductive abilities and did not cause birth defects. **Genetic Toxicity:** Gasoline was not mutagenic, with or without activation, in the Ames assay (Salmonella typhimurium), Saccharomyces cerevisiae, or mouse lymphoma assays. In addition, point mutations were not induced in human lymphocytes. Gasoline was not mutagenic when

tested in the mouse dominant lethal assay. Administration of gasoline to rats did not cause chromosomal aberrations in their bone marrow cells. Inhalation exposure of rats to the light ends of gasoline caused increased sister chromatid exchange in their peripheral white blood cells but did not cause an increase in micronucleated red blood cells in their bone marrow.

**ADDITIONAL TOXICOLOGY INFORMATION:**

Gasolines are highly volatile and can produce significant concentrations of vapor at ambient temperatures. Gasoline vapor is heavier than air and at high concentrations may accumulate in confined spaces to present both safety and health hazards. When vapor exposures are low, or short duration and infrequent, such as during refueling and tanker loading/unloading, neither total hydrocarbon nor components such as benzene are likely to result in any adverse health effects. In situations such as accidents or spills where exposure to gasoline vapor is potentially high, attention should be paid to potential toxic effects of specific components. Information about specific components in gasoline can be found in Sections 2/3, 8 and 15 of this MSDS. More detailed information on the health hazard of specific gasoline components can be obtained calling the Chevron Emergency Information Center (see Section 1 for phone numbers).

Pathological misuse of solvents and gasoline, involving repeated and prolonged exposure to high concentrations of vapor is a significant exposure on which there are many reports in the medical literature. As with other solvents, persistent abuse involving repeated and prolonged exposures to high concentrations of vapor has been reported to result in central nervous system damage and eventually, death. In a study in which ten human volunteers were exposed for 30 minutes to approximately 200, 500 or 1000 ppm concentrations of gasoline vapor, irritation of the eyes was the only significant effect observed, based on both subjective and objective assessments.

Lifetime inhalation of wholly vaporized unleaded gasoline at 2056 ppm has caused increased liver tumors in female mice and kidney cancer in male rats. In their 1988 review of carcinogenic risk from gasoline, The International Agency for Research on Cancer (IARC) noted that, because published epidemiology studies did not include any exposure data, only occupations where gasoline exposure may have occurred were reviewed. These included gasoline service station attendants and automobile mechanics. IARC also noted that there was no opportunity to separate effects of combustion products from those of gasoline itself. Although IARC allocated gasoline a final overall classification of Group 2B, i.e. possibly carcinogenic to humans, this was based on limited evidence in experimental animals plus supporting evidence including the presence in gasoline of benzene. The actual evidence for carcinogenicity in humans was considered inadequate.

To explore the health effects of workers potentially exposed to gasoline vapors in the marketing and distribution sectors of the petroleum industry, the American Petroleum Institute sponsored a cohort mortality study (Publication 4555), a nested case-control study (Publication 4551), and an exposure assessment study (Publication 4552). Histories of exposure to gasoline were reconstructed for cohort of more than 18,000 employees from four companies for the time period between 1946 and 1985. The results of the cohort mortality study indicated that there was no increased mortality from either kidney cancer or leukemia among marketing and marine distribution employees who were exposed to gasoline in the petroleum industry, when compared to the general population. More importantly, based on internal comparisons, there was no association between mortality from kidney cancer or leukemia and various indices of gasoline exposure. In particular, neither duration of employment, duration of exposure, age at first exposure, year of first exposure, job category, cumulative exposure, frequency of peak exposure, nor average intensity of exposure had any effect on kidney cancer or leukemia mortality. The results of the nested case-control study confirmed the findings of the original cohort study. That is, exposure to gasoline at the levels experienced by this cohort of distribution workers is not a significant risk factor for leukemia (all cell types), acute myeloid leukemia, kidney cancer or multiple myeloma.

**SECTION 12 ECOLOGICAL INFORMATION**

**ECOTOXICITY**

- 48 hour(s) LC50: 3.0 mg/l (Daphnia magna)
- 96 hour(s) LC50: 2.7 mg/l (Oncorhynchus mykiss)
- 96 hour(s) LC50: 8.3 mg/l (Cyprinodon variegatus)

96 hour(s) LC50: 1.8 mg/l (Mysidopsis bahia)

This material is expected to be toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment. Gasoline studies have been conducted in the laboratory under a variety of test conditions with a range of fish and invertebrate species. An even more extensive database is available on the aquatic toxicity of individual aromatic constituents. The majority of published studies do not identify the type of gasoline evaluated, or even provide distinguishing characteristics such as aromatic content or presence of lead alkyls. As a result, comparison of results among studies using open and closed vessels, different ages and species of test animals and different gasoline types, is difficult.

The bulk of the available literature on gasoline relates to the environmental impact of monoaromatic (BTEX) and diaromatic (naphthalene, methylnaphthalenes) constituents. In general, non-oxygenated gasoline exhibits some short-term toxicity to freshwater and marine organisms, especially under closed vessel or flow-through exposure conditions in the laboratory. The components which are the most prominent in the water soluble fraction and cause aquatic toxicity, are also highly volatile and can be readily biodegraded by microorganisms.

The ecotoxicity hazard is based on an evaluation of data for the components or a similar material.

### ENVIRONMENTAL FATE

**Ready Biodegradability:** This material is expected to be readily biodegradable. Following spillage, the more volatile components of gasoline will be rapidly lost, with concurrent dissolution of these and other constituents into the water. Factors such as local environmental conditions (temperature, wind, mixing or wave action, soil type, etc), photo-oxidation, biodegradation and adsorption onto suspended sediments, can contribute to the weathering of spilled gasoline.

The aqueous solubility of non-oxygenated unleaded gasoline, based on analysis of benzene, toluene, ethylbenzene+xylenes and naphthalene, is reported to be 112 mg/l. Solubility data on individual gasoline constituents also available.

The biodegradability of this material is based on an evaluation of data for the components or a similar material.

### SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by USEPA under RCRA (40CFR261), Environment Canada, or other State, Provincial, and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

### SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

**TC Shipping Description:** UN1203 GASOLINE, 3, II, MARINE POLLUTANT (GASOLINE)

**IMO/IMDG Shipping Description:** UN1203, GASOLINE, 3, II, FLASH POINT SEE SECTION 5 OR 9, MARINE POLLUTANT (GASOLINE)

**ICAO/IATA Shipping Description:** UN1203, GASOLINE, 3, II

**DOT Shipping Description:** UN1203, GASOLINE, 3, II; **OPTIONAL DISCLOSURE:** UN1203, GASOLINE, 3, II, MARINE POLLUTANT (GASOLINE)

**SECTION 15 REGULATORY INFORMATION**

**REGULATORY LISTS SEARCHED:**

- 01-1=IARC Group 1
- 01-2A=IARC Group 2A
- 01-2B=IARC Group 2B
- 35=WHMIS IDL

The following components of this material are found on the regulatory lists indicated.

Benzene	01-1, 35
Butane	35
Cyclohexane	35
Ethanol	01-1, 35
Ethyl benzene	01-2B, 35
Gasoline	01-2B
Heptane	35
Hexane	35
Methylcyclohexane	35
Naphthalene	01-2B, 35
Pentane, 2,2,4-trimethyl- (Isooctane)	35
Toluene (methylbenzene)	35
Xylene (contains o-, m-, & p- xylene isomers in varying amounts)	35

**CHEMICAL INVENTORIES:**

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), PICCS (Philippines), TSCA (United States).

**WHMIS CLASSIFICATION:**

- Class B, Division 2: Flammable Liquids
- Class D, Division 2, Subdivision A: Very Toxic Material - Carcinogenicity
- Class D, Division 2, Subdivision B: Toxic Material - Skin or Eye Irritation

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations. (See Hazardous Products Act (HPA), R.S.C. 1985, c.H-3,s.2).

**MSDS PREPARATION:**

This Material Safety Data Sheet has been prepared by the Toxicology and Health Risk Assessment Unit, ERTC, P.O. Box 1627, Richmond, CA 94804, (888)676-6183.

**Revision Date:** MARCH 05, 2014

**SECTION 16 OTHER INFORMATION**

**HMIS RATINGS:** Health: 2\* Flammability: 3 Reactivity: 0

**Additional Product Number(s):** CPS201024, CPS201050, CPS201051, CPS201058, CPS201060, CPS201061, CPS201066, CPS201068, CPS201069, CPS201071, CPS201072, CPS201078, CPS201081, CPS201084, CPS201085, CPS201088, CPS201091, CPS201092, CPS201094, CPS201096, CPS201097, CPS201098, CPS201101, CPS201103, CPS201114, CPS201117, CPS201193, CPS201213, CPS201214, CPS201215, CPS201233, CPS201234, CPS201235, CPS201263, CPS201264, CPS201265, CPS201274, CPS201275, CPS201276, CPS201283, CPS201284, CPS201285, CPS201293, CPS201294, CPS201295, CPS201853, CPS201854, CPS201861, CPS201862, CPS201863, CPS204006, CPS204007, CPS204008, CPS204009, CPS204014, CPS204015, CPS204026, CPS204027, CPS204050, CPS204051, CPS204074, CPS204075, CPS204092, CPS204093, CPS204108, CPS204109, CPS204120, CPS204121, CPS204144, CPS204145, CPS204168, CPS204169, CPS204192, CPS204193, CPS204204, CPS204205, CPS204211, CPS204216, CPS204217, CPS204228, CPS204229, CPS204252, CPS204253, CPS204276, CPS204277, CPS204294, CPS204295, CPS204327, CPS204328, CPS204329, CPS204351, CPS204353, CPS204355, CPS204357, CPS204362, CPS204363, CPS204368, CPS204369, CPS204374, CPS204375, CPS204380, CPS204381, CPS204386, CPS204387, CPS204392, CPS204393, CPS204398, CPS204399, CPS204404, CPS204405, CPS204410, CPS204411, CPS204416, CPS204417, CPS204422, CPS204423, CPS204428, CPS204429, CPS204434, CPS204435, CPS204440, CPS204441, CPS204443, CPS204447, CPS204451, CPS204455, CPS204459, CPS204463, CPS204470, CPS204471, CPS204488, CPS204489, CPS204506, CPS204507, CPS204524, CPS204525, CPS204542, CPS204543, CPS204560, CPS204561, CPS204578, CPS204579, CPS204596, CPS204597, CPS204614, CPS204615, CPS204632, CPS204633, CPS204650, CPS204651, CPS204668, CPS204669, CPS204683, CPS204694, CPS204695, CPS204700, CPS204701, CPS204706, CPS204707, CPS204712, CPS204713, CPS204725, CPS204726, CPS204731, CPS204732, CPS204741, CPS241766

**REVISION STATEMENT:** This revision updates the following sections of this Material Safety Data Sheet:

14

**ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:**

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
	CAS - Chemical Abstract Service Number
ACGIH - American Conference of Governmental Industrial Hygienists	IMO/IMDG - International Maritime Dangerous Goods Code
API - American Petroleum Institute	MSDS - Material Safety Data Sheet
CVX - Chevron	NFPA - National Fire Protection Association (USA)
DOT - Department of Transportation (USA)	NTP - National Toxicology Program (USA)
IARC - International Agency for Research on Cancer	OSHA - Occupational Safety and Health Administration

**The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.**