

MORTON PAINT COMPANY

U.S. CHEMICAL & PLASTICS
An Alco Industries Company
600 Nova Drive SE
Massillon, OH 44646
PH 330-830-6000 - FAX 330-830-6005

For Chemical Emergency

CHEMTREC: 1-800-424-9300

=====

SECTION I - IDENTIFICATION OF PRODUCT

=====

PRODUCT NAME: Sprayable Urethane Truck Bed Liner Activator - Part B
PRODUCT CODE: (999623), 1435-1, 1435-4, 1435-12
SYNONYM/CROSS REFERENCE: Hardener and Activator for Paints
SCHEDULE B NUMBER: 3815.90.0000-0

=====

=====

SECTION II - HAZARDOUS INGREDIENTS

=====

INGREDIENTS	WGT%	CAS #	TLV/PEL
Hexamethylene Diisocyanate	<0.35 %	822-06-0	AGCIH TLV 0.005 ppm
Polyisocyanate Blend	99-100%	3779-63-3 28182-81-2	N/E

=====

=====

SECTION III - PHYSICAL DATA

=====

APPEARANCE: Viscous, clear to straw-colored liquid
SPECIFIC GRAVITY: 1.15
VAPOR PRESSURE (mmHG): N/Av
BOILING POINT: 248-410F
VAPOR DENSITY: * Heavier than Air 5
EVAPORATION RATE (Ethyl Ether = 1): Slower than Ethyl Ether
VOLATILES BY WEIGHT: Nil
SOLUBILITY IN WATER: Miscible
VOC (Less water and exempt): Grams/Liter = <12
Lbs/Gallon = <0.10

=====

=====

SECTION IV - FIRE AND EXPLOSION DATA

=====

FLASH POINT: 365°F/185°C Seta Flash Closed cup
LOWER FLAMMABLE LIMIT %: N/E
UPPER FLAMMABLE LIMIT %: N/E
FIRE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam
SPECIAL FIRE FIGHTING PROCEDURES: Fight like a fuel oil fire. Cool fire exposed containers with water spray. Firefighter should wear OSHA/NIOSH approved self-contained breathing apparatus.
UNUSUAL FIRE AND EXPLOSION HAZARD: Closed containers exposed to high temperatures, such as fire conditions may rupture.

SECTION V - HEALTH HAZARD/TOXICOLOGICAL PROPERTIES

OVEREXPOSURE EFFECTS:

ACUTE EFFECTS:

EYES: Contact with eyes can cause irritation, redness, tearing, blurred vision, and/or swelling.

SKIN: Contact with skin can cause irritation, (minor itching, burning and/or redness), Dermatitis, defatting may be readily absorbed through the skin.

INHALATION: Inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and/or asphyxiation. Aspiration of material into lungs may result in chemical pneumonitis which can be fatal. May be toxic.

INGESTION: Ingestion can cause gastrointestinal irritation, nausea, vomiting, diarrhea.

CHRONIC EFFECTS:

Overexposure to this material has apparently been known to cause the following effects in lab animals: liver, kidney, lung, blood, and central nervous system damage. May cause skin and/or respiratory sensitization.

CARCINOGEN: YES _____ NO X

TERATOGEN: YES _____ NO X

MUTAGEN: YES _____ NO X

ISOCYANATES/DIISOCYANATES

Aliphatic Polyisocyanate or Polymeric Isophorone Diisocyanate or Polyisocyanate:

Repeated exposure may cause allergic skin rash, itching, swelling. Repeated overexposure to Isocyanates may cause lung injury, including a decrease in lung function, which may be permanent. Overexposure may cause asthma-like reactions with shortness of breath, wheezing, cough which may be permanent or permanent lung sensitization. This effect may be delayed for several hours after exposure. Individuals with preexisting lung disease, asthma or breathing difficulties may have increased susceptibility to the toxicity of excessive exposure.

1,6 Hexamethylene Diisocyanate:

May cause temporary upper respiratory and/or lung irritation with cough, difficult breathing, or shortness of breath. Overexposure may cause asthma-like reactions with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Prolonged skin contact may cause chemical burns. Liquid splashes in the eye may result in chemical burns. Individuals with preexisting lung disease, asthma or breathing difficulties may have increased susceptibility to the toxicity of excessive exposures.

PRIMARY ROUTES OF EXPOSURE: Inhalation, skin

FIRST AID:

INHALATION: If inhaled, remove victim from exposure to a well-ventilated area. Make them comfortably warm, but not hot. Use oxygen or artificial respiration as required. Consult a physician.

SKIN: For skin contact, wash promptly with soap and excess water.

EYES: For eye contact, flush promptly with excess water for at least fifteen minutes. Consult a physician.

INGESTION: If ingested, do not induce vomiting. Give victim a glass of water. Call a physician immediately.

SECTION V I - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Open flames, sparks, heat, electrical and static discharge. Because of the potential for release of HDI monomer, temperatures in excess of 196°F (90°C) are not recommended when curing coatings containing this product.

INCOMPATIBILITY MATERIALS TO AVOID: Strong acids, alkalis, oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide and Carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VII - SPILL AND DISPOSAL PROCEDURE

SPILLS, LEAK OR RELEASE: Ventilate area. Remove all possible sources of ignition. Avoid prolonged breathing of vapor. Contain spill with inert absorbent. Pour decontamination fluid over spill. Typical decontamination solutions are: 20% Tergitol TMN10, 80% water or 0-10% Ammonia, 2-5% detergent, balance water. For large spills, it may be necessary to use a respirator to keep exposure levels below TLV/PEL limits.

WASTE DISPOSAL: Dispose of in accordance with local, state, and federal regulations.

SECTION VIII - PROTECTION INFORMATION

RESPIRATORY PROTECTION: If component TLV limits are exceeded, use NIOSH/MSHA approved respirator to remove vapors. Use an air-supplied respirator if necessary. For isocyanates, use TC-10C positive pressure supplied respirator or equivalent.

VENTILATION: Use adequate ventilation in volume and pattern to keep TLV/PEL below recommended levels. Explosion-proof ventilation may be necessary.

PROTECTIVE GLOVES: To prevent prolonged exposure use rubber gloves; solvents may be absorbed through the skin

EYE PROTECTION: Safety Glasses or goggles with splash guards or side shields.

OTHER PROTECTIVE EQUIPMENT: Wear protective clothing as required to prevent skin contact.

SECTION IX - HANDLING AND STORAGE PRECAUTIONS

STORAGE AND HANDLING: Use with adequate ventilation. Avoid contact with eyes and skin. Avoid breathing vapors. Do not store the product above 100°F/38°C. Do not flame, cut, braze weld or melt empty containers. Keep the product away from heat, open flame, and other sources of ignition. Avoid contact with strong acids, alkalis, and oxidizers.

SECTION X - ADDITIONAL INFORMATION

SHIPPING INFORMATION: Please comply with DOT regulations in USA

HMIS RATING:

Health	2	4 = Extreme
Fire	1	3 = High
Reactivity	1	2 = Moderate
		1 = Slight
		0 = Insignificant

Personal Protection - See Section VIII

CALIFORNIA PROPOSITION 65:

Trace amounts of some chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be present in this product.

SECTION 313 SUPPLIER NOTIFICATION:

This product contains the following toxic chemicals subject to the reporting requirements of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

CHEMICAL NAME	CAS	% BY WGT
Not Applicable		

THIS INFORMATION MUST BE INCLUDED IN ALL MSDS's THAT ARE COPIED AND DISTRIBUTED FOR THIS CHEMICAL

=====

ABBREVIATIONS

=====

IARC = International Agency for Research on Cancer
ACGIH = American Conference of Governmental Industrial Hygienists
NIOSH = National Institute of Occupational Safety and Health
TLV = Threshold Limit Value
PEL = Permissible Emission Level
DOT = Department of Transportation
NTP = National Toxicology Program
N/AV = Not Available
N/AP = Not Applicable
N/E = Not Established
N/D = Not Determined

PREPARED BY: **MORTON PAINT COMPANY**
U S Chemical & Plastics
Alco Industries Companies
600 NOVA DRIVE SE
MASSILLON, OH 44646

TELEPHONE NBR 330-830-6000
FAX NBR 330-830-6005

DATE REVIEWED: January 10, 2011
DATE REVISED: February 24, 2010
REVISION: Review

The information in the Material Safety Data Sheet has been compiled from our experience and from data presented in various technical publications. It is the user's responsibility to determine the suitability of this information for the adoption of the safety precautions as may be necessary. We reserve the right to revise Material Safety Data Sheets from time to time as new technical information becomes available. The user has the responsibility to contact the Company to make sure that the MSDS is the latest one issued.