MATERIAL SAFETY DATA SHEET

Effective Date: March 2011

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Heat-Shrinkable Tubing Chemical Name: Not Applicable, mixture

HSTT, HSTTV, HSTTA, & HSTTRA CAS #: Not applicable, mixture

HSTTVA, HSTT4A, HST, HSTTT

DOT Proper Shipping Name: Not regulated **Control Division**: Panduit Corporation

DOT Identification No.: Not regulated16530 163rd St.**DOT Hazard Classification**: Not regulatedLockport, IL 60441

Telephone (815) 836-1800

EMERGENCY TELEPHONE NUMBERS:

24-Hour Emergency Information (US): 800-535-5053 (InfoTrac) 24-Hour Emergency Information (International): 352-323-3500

NON-EMERGENCY HEALTH/SAFETY INFORMATION:

CHEMICAL FAMILY: Not Applicable.

PRODUCT USE: Typical uses of heat-shrinkable polymeric products include primary electrical

insulation, EMI/RFI shielding, cable jacketing and repair, strain relief, waterproofing, cable/pipe identification, corrosion protection, environmental/mechanical protection, and cable joining, splicing, and

termination in commercial and military/aerospace electronic applications.

This product may contain a hazardous substance or preparation that is regulated under US-OSHA; CAN-WHMIS; IOSH; ISO; UK-CHIP; or EU Directives (67/548/EEC-Dangerous Substance Labeling, 98/24/EC-Chemical Agents at Work, 99/45/EC-Preparation Labeling, 2001/58/EC-MSDS Content, and 1907/2006/EC-REACH). A MSDS/SDS is required for this product because when used as recommended or intended under ordinary conditions, it may present a health and safety exposure or other hazard.

Section 2: Hazards Identification

Emergency Overview:

In common with most organic materials, thermal degradation and combustion byproducts may be toxic and should not be inhaled. Thermal degradation is not significant at temperatures achieved during proper installation, as directed by product installation guides. At temperatures higher than those recommended for proper installation, most significantly if the product burns, the thermal degradation and combustion byproducts will depend on the base polymer used, and additives, if any may include, but are not limited to carbon monoxide, carbon dioxide, organic acids, aldehydes (including formaldehyde), acetic acid,

low molecular weight hydrocarbons, silicon dioxide, hydrogen chloride, hydrogen fluoride, hydrogen bromide, vinyl acetate, ammonia, hydrogen cyanide, antimony, fluoro-olefins, phosphine and oxides of nitrogen, phosphorus and sulfur.

POTENTIAL HEALTH EFFECTS:

Proper installation of this product creates no known acute or chronic health hazards.

ACUTE HEALTH HAZARDS:

EYES: Contact with molten material may cause thermal burns.

SKIN: This product is not expected to be a skin irritant. Contact with the molten

material may cause thermal burns. No harmful effects are expected from skin

absorption of this product.

INGESTION: Ingestion of this product is highly unlikely. There is insufficient information

available on this material to predict the effects from ingestion.

INHALATION: In common with most organic materials, thermal degradation and combustion

byproducts may be toxic and should not be inhaled. (See Comments below and the Thermal Degradation and Combustion Byproducts Section for more specific

information.)

CHRONIC HEALTH HAZARDS:

None of the ingredients to which users may be exposed and which are present at equal to or greater than 0.1% of the product, are listed by OSHA, NTP, or IARC as suspect carcinogens.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Overheating the product to charring or burning may produce vapors that may cause eye, skin, nose and throat irritation. Persons with pre-existing eye, skin, or respiratory disorders (e.g., asthma conditions) may be more susceptible to the effects of these vapors.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS (Chemical/Common Names): CAS No.: % by Wt EC No:

Not applicable Not Established Not determined

Not applicable – This product is a manufactured article. Heat-Shrinkable Polymeric Products are not hazardous during proper installation, but the heat-shrinkable tubing may emit hazardous thermal decomposition and combustion byproducts if overheated to degradation. See "Thermal Degradation and Combustion Byproduct" section of this MSDS for more specific information. Base polymer materials

include polyethylene and olefin copolymers. Heat-shrinkable products may be coated with or used in conjunction with adhesives/mastics, which are based on olefin copolymers or polyamides.

SECTION 4: FIRST AID MEASURES

EYE CONTACT: If eye irritation occurs, flush with clean water for 15 minutes while holding eyelids apart. Seek medical attention.

SKIN CONTACT: First aid is normally not required. After handling product, it is good work practice to wash your hands. If molten material contacts skin, cool area immediately in water. DO NOT attempt to remove material from the skin. Treat as a burn, and seek medical attention.

INGESTION: Not a normal route of exposure. However, if swallowed and symptoms develop, seek medical attention.

INHALATION: If respiratory symptoms or other symptoms of exposure develop, move victim to fresh air. If symptoms persist, seek medical attention. If breathing difficulties develop, qualified personnel should administer oxygen. Seek immediate medical attention. If victim is not breathing, immediately begin artificial respiration. Keep victim warm and quiet; seek immediate medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASHPOINT: Not applicable METHOD USED: Not applicable

FLAMMABLE LIMITS

UPPER FLAMMABILITY LIMIT (% BY VOLUME): Not applicable LOWER FLAMMABILITY LIMIT (% BY VOLUME): Not applicable

AUTOIGNITION TEMPERATURE: Not applicable

SUITABLE EXTINGUISHING MEDIA:

Use carbon dioxide, water, dry chemical or foam. Selection of extinguishing media should be based upon the size of the fire, the firefighting training/experience of the individual attempting to extinguish or control the fire, and the packaging materials exposed to the fire.

SPECIAL FIRE FIGHTING PROCEDURES & PROTECTIVE EQUIPMENT:

Firefighters should wear self-contained breathing apparatus with a full-face piece operated in the positive pressure demand mode when fighting fires. Use water spray to keep fire-exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Toxic fumes may be given off in a fire. See also sections on Thermal Degradation and Combustion Byproducts and Other Precautions.

SPECIFIC HAZARDS IN CASE OF FIRE:

NONE

HAZARDOUS COMBUSTION PRODUCTS:

In common with most organic materials, thermal degradation and combustion byproducts may be toxic and should not be inhaled. Thermal degradation is not significant at temperatures achieved during proper installation, as directed by product installation guides. At temperatures higher than those recommended for proper installation, most significantly if the product burns, the thermal degradation and combustion byproducts will depend on the base polymer used and additives, if any, may include but are not limited to carbon monoxide, carbon dioxide, organic acids, aldehydes (including formaldehyde), acetic acid, low molecular weight hydrocarbons, silicon dioxide, hydrogen chloride, hydrogen fluoride, hydrogen bromide, vinyl acetate, ammonia, hydrogen cyanide, antimony, fluoro-olefins, phosphine and oxides of nitrogen, phosphorus and sulfur.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

See Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENVIRONMENTAL PRECAUTIONS:

Prevent spilled material from entering sewers and waterways.

SPILL CONTAINMENT & CLEANUP METHODS/MATERIALS:

Sweep up and collect in a suitable container for disposal or reuse.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING AND STORAGE:

HANDLING: For products containing a thermochromic temperature indicator, discontinue heating after the color changes from red to colorless. Avoid any vapors given off if the product is heated to decomposition, as shown by a darkening and browning of the sleeve. Avoid contact with molten material. Heat-resistant gloves are required if hot products are handled after installation. Do not consume food, beverages, or tobacco in the immediate work area. Wash hands before eating, drinking or smoking.

INSTALLATION: Follow the appropriate installation instructions and application guides to ensure that installation is performed properly. Ensure that any local requirements/legislation concerning the use of hand-held electrical equipment are observed. When using IR (infrared) heating devices, observe specific instructions. Do not touch hot surfaces on installation equipment.

STORAGE: This product is stable under normal conditions.

OTHER PRECAUTIONS (e.g.: Incompatibilities):

Avoid heating products beyond temperatures required for normal installation. See installation instructions for proper installation procedures. If product chars or burns, immediately stop heating.

Avoid inhaling any fumes, which may be given off under such circumstances. Allow any vapors to disperse and ventilate before continuing work in the area.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS/SYSTEM DESIGN INFORMATION:

None

VENTILATION:

Provide general or local exhaust ventilation systems.

RESPIRATORY PROTECTION:

If installation occurs in a confined, unventilated area, NIOSH/MSHA-approved respirators are recommended.

EYE PROTECTION: Use safety glasses with side shield or goggles to prevent contact with eyes, as appropriate to the given operation.

<u>SKIN PROTECTION</u>: Avoid contact with skin. Use heat resistant rated gloves to prevent skin contact; as appropriate to the given operation. If it is necessary to handle grossly overheated or fire-damaged products, wear natural rubber gloves to prevent possible contact with potentially corrosive acid residues.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

EXPOSURE GUIDELINES & LIMITS:

There are no established exposure limits for polymer mixtures.

OSHA	Permissible Exposure Limit (PEL/TWA)	NE
ACGIH	Threshold Limit Value (TLV)	NE
Quebec	Permissible Exposure Value (PEV)	NE
Ontario	Occupational Exposure Level (OEL)	NE
Germany	Maximale Arbeitsplatzkonzentrationen (MAK)	NE
United Kingdom	Occupational Exposure Standard (OES)	NE

TWA – 8-Hour Time Weighted Average NE - Not Established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Plastic tubing % molded parts in a variety of shapes, sizes & colors

ODOR: No odor

ODOR THRESHOLD: Not applicable

PHYSICAL STATE: Solid

pH: Not applicable
BOILING POINT: Not applicable
MELTING POINT: Not Determined
FREEZING POINT: Not applicable
VAPOR PRESSURE (mmHg@20 degrees C): Not applicable
VAPOR DENSITY (AIR = 1): Not applicable
SPECIFIC GRAVITY (H20 = 1): Not applicable

EVAPORATION RATE (Butyl acetate = 1): Not applicable

SOLUBILITY IN WATER: Insoluble

FLASH POINT:

AUTO-IGNITION TEMPERATURE:

LOWER EXPLOSIVE LIMIT (LEL):

UPPER EXPLOSIVE LIMIT (UEL)

PARTITION COEFFICIENT:

VISCOSITY (centipoises @ 25 degrees C):

DECOMPOSITION TEMPERATURE:

Not applicable

Not applicable

FLAMMABILITY/HMIS HAZARD CLASSIFICATIONS (US/EN/EU):

HEALTH: FLAMMABILITY: REACTIVITY:

SECTION 10: STABILITY AND REACTIVITY

STABILITY: This product is stable under normal conditions, at ambient temperature.

INCOMPATIBILITY (MATERIAL TO AVOID):

None known.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

See Section 5: FIRE FIGHTING MEASURES (Hazardous Combustion Products).

HAZARDOUS POLYMERIZATION:

Will not occur. No known polymerization conditions to avoid.

CONDITIONS TO AVOID:

Avoid overheating of product.

SECTION 11: TOXICOLOGICAL INFORMATION

ACUTE TOXICITY (Text Results Basis and Comments):

LD₅₀ (Oral, Rat): Not determined

LC₅₀ (Inhalation, Rat): Not determined

ROUTES OF ENTRY/EFFECTS OF ACUTE OVEREXPOSURE

EYE CONTACT: Contact with the molten material may cause thermal burns.

SKIN CONTACT: This product is not expected to be a skin irritant. Contact with the molten

material may cause thermal burns. No harmful effects are expected from skin

absorption of this product.

INGESTION (Swallowing): Ingestion of this product is highly unlikely. There is insufficient information

available on this material to predict the effects from ingestion.

INHALATION (Breathing): In common with most organic materials, thermal degradation and combustion

byproducts may be toxic and should not be inhaled. (See the Thermal

Degradation and Combustion Byproducts Section for more specific information).

SUBCHRONIC/CHRONIC TOXICITY (TEST RESULTS AND COMMENTS):

IRRITANCY OF PRODUCT: See above SENSITIZATION TO MATERIAL: Not known

CARCINOGENICITY: None of the ingredients to which users may be exposed

and which are present at equal to or greater that 0.1%

of the product, are listed by OSHA, NTP, or IARC as carcinogens.

REPRODUCTIVE TOXICITY: None known.

TERATOGENICITY: None known.

MUTAGENICITY: None known.

TOXICOLOGICALLY SYNERGISTIC PRODUCTS: None known.

SECTION 12: ECOLOGICAL INFORMATION

PERSISTENCE & DEGRADABILITY:

No data available on biodegradation.

BIO-ACCUMULATIVE POTENTIAL (Including Mobility):

No date available on bioaccumulation.

AQUATIC TOXICITY (Test Results & Comments):

No data available on aquatic toxicity.

ADDITIONAL INFORMATION:

- No known effects on stratospheric ozone depletion.
- Water Endangering Class (WGK): NA

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Treatment, storage, and disposal must be in accordance with applicable,

federal, state, provincial, and local regulations.

HAZARDOUS WASTE Class/Code:

US – Not applicable to material as manufactured for distribution into commerce.

CN – Not applicable to material as manufactured for distribution into commerce.

EWC – Not applicable to material as manufactured for distribution into commerce.

ADDITIONAL INFORMATION:

Not Included – Dispose/Recycle as allowed by local jurisdiction for the end-of-life characteristics as-disposed.

SECTION 14: TRANSPORT INFORMATION

GROUND – US-DOT/CAN-TDG/EU-ADR/APEC-ADR:

Proper Shipping Name Not Subject to HMR

Hazard Class	NA	ID Number	NA
Packing Group	NA	Labels	NA

<u>AIRCRAFT – ICAO-IATA:</u>

Proper Shipping Name Not Subject to DGR

Hazard Class NA ID Number NA
Packing Group NA Labels NA

VESSEL – IMO-IMDG:

Proper Shipping Name Not Subject to IMDG

Hazard Class NA ID Number NA Packing Group NA Labels NA

Additional Information:

- Transportation must be in accordance with applicable, federal, state, provincial, and local regulations.
- Transport requires proper packaging and paperwork, including the Nature and Quantity of goods, per applicable origin/destination/customs points as shipped. Statement of Jurisdictional/Modal Special Provision(s) required.
- Not restricted for any mode of international transport as finished goods.
- Not a Marine Pollutant as-shipped per IMO/IMDG.

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS:

All components are listed on the TSCA; EINECS/ELINCS; and DSL, unless noted otherwise below.

U.S. FEDERAL REGULATIONS:

TSCA Section 8b – Inventory Status: All chemicals comprising this product are either exempt or listed on the TSCA Inventory.

TSCA Section 12b – Export Notification: If the product contains chemicals subject to TSCA Section 12b export notification they are listed below:

Chemical CAS #
None NA

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT)

Chemicals present in the product which could require reporting under the statute:

<u>Chemical</u> <u>CAS #</u> None NA

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

If the product contains chemicals subject to the reporting requirements of Section 313 of SARA Title III, they are listed below.

<u>Chemical</u>	<u>CAS #</u>	<u>% wt</u>
None	NA	NA

CERCLA SECTION 311/312 HAZARD CATEGORIES: Note that this product is exempt from these regulations.

Fire Hazard	No
Pressure Hazard	No
Reactivity Hazard	No
Immediate Hazard	No
Delayed Hazard	No

STATE REGULATIONS (US):

California Proposition 65

The following chemicals identified to exist in the product as distributed into commerce are known to the State of California to cause cancer; birth defects, or other reproductive harm:

<u>Chemical</u> <u>CAS #</u> <u>% wt</u> SbO₃ Antinomy trioxide 1309-64-4 up to 7.5%

INTERNATIONAL REGULATIONS (Non-US):

Canadian Domestic Substance List (DSL)

Not applicable.

WHMS Classifications:

Not applicable.

This product has been classified in accordance with the hazard criteria of the "Controlled Products Regulations", and the MSDS contains all of the information required by the "Controlled Products Regulations".

NPRI and Ontario Regulation 127/01:

This product contains the following chemicals subject to the reporting requirements of Canada NPRI and/or Ontario Regulation 127/01:

<u>Chemical</u> <u>CAS #</u> <u>% wt</u> None

European Inventory of Existing Commercial Chemical Substances (EINECS):

All ingredients remaining in the product as distributed into commerce are exempt from, or included on, the European Inventory of Existing Commercial Chemical Substances.

Registration and Authorization of Chemicals (EU REACH)

This product is an article without release under REACH. It contains no substances restricted by REACH, and no substances on the Candidate List.

European Communities (EC) Hazard Classification according to directives 67/548/EEC and 1999/45/EC.

R-Phrases
None
None

Additional Information

This product may be regulated under additional regulations and laws not identified above, such as for uses other than described or as-designed/as-intended by the manufacturer, or for distribution into specific domestic destinations.

SECTION 16: OTHER INFORMATION

OTHER INFORMATION:

Distribution into Quebec to follow Canadian Controlled Product Regulations (CPR) 24 (1) and 24 (2). Distribution into the EU to follow applicable Directives to the Use, Import/Export of the product as-sold.

LIABILITY DISCLAIMER

The information in this MSDS was obtained from sources which we believe are reliable. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS CORRECTNESS.

The conditions of methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF, OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.