

MATERIAL SAFETY DATA SHEET

U.S. CHEMICAL & PLASTICS
An Alco Industries Company
600 NOVA DRIVE SE
MASSILLON, OH 44646
PHONE: 330 830-6000
FAX: 330 830-6005

Product Code: 60075, 60095

DATE REVIEWED: January 27, 2011
DATE REVISED: July 9, 2002
REVISION: Format

TRADE NAMEIdeal Tack Cloth - Magnum Blue
SYNONYM/CROSS REF..... No known synonym
SCHEDULE B#:N/Av

HAZARDOUS INGREDIENTS

<u>Materials or Components</u>	<u>% (w/w)</u>	<u>CAS No.</u>	<u>Hazard data</u>
Bisphenol A Diglycidyl Ether Polymer	20-25%	25068-38-6	N/E

PHYSICAL PROPERTIES

BOILING POINT	>200	MELTING POINT	N/A
VAPOR PRESSURE	Unknown	SPECIFIC GRAVITY (Water = 1)	N/A
VAPOR DENSITY (Air = 1)	N/E	VOLATILE BY VOLUME	Nil
WATER SOLUBILITY	Insoluble	EVAPORATION RATE (Ethyl Ether = 1)	Unknown
APPEARANCE	Blue cloth	V.O.C.....	N/A

FIRE AND EXPLOSION DATA

FLASH POINT °F	490°F Seta Closed Cup
FIRE EXTINGUISHING MEDIA	CO ₂ , Dry Chemicals, Foam.
SPECIAL FIRE FIGHTING PROCEDURES	Firefighters wear self-contained breathing apparatus.
UNUSUAL FIRE AND EXPLOSION HAZARD	May form toxic vapors.
FLAMMABLE LIMITS	N/E

HEALTH HAZARD INFORMATION

THRESHOLD LIMIT VALUE TLV for product is not established.
HEALTH HAZARDS Prolonged contact may cause skin irritation. Eye irritant.

CALIFORNIA PROPOSITION 65:

Trace amounts of some chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be present in this product.

FIRST AID PROCEDURES:

SKIN CONTACT Wash with soap and excess water. Obtain medical attention if irritation occurs.
EYE CONTACT Flush promptly with excess water for 15 minutes. Call a physician.
IF SWALLOWED Do not induce vomiting. Call a physician. If conscious, give a glass of water to person.
INHALATION Remove from contaminated areas, apply artificial respiration if necessary, call a physician.

TOXICITY

ORAL (acute) (rats) N/E ACUTE INTRAPERITONEAL (mice) N/E
INHALATION (acute) (rats) N/E CHRONIC, SUBCHRONIC, ETC: N/E

REACTIVITY DATA

STABILITY Stable
INCOMPATIBILITY Strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS Thermal decomposition will yield carbon monoxide and carbon dioxide and aldehydes
HAZARDOUS POLYMERIZATION Will not occur
CONDITIONS TO AVOID Strong acids or alkalis

SPILL AND DISPOSAL METHOD

STEPS TO BE TAKEN IF MATERIAL IS..... Spills should be swept up and collected in a container for
RELEASED OR SPILLED disposal.
WASTE DISPOSAL METHOD Disposal method must comply with local, state, and federal regulations.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE EXPOSURE, OR ACCIDENT
CALL DAY OR NIGHT, IN THE USA OR CANADA
Chemtrec (USA) 1-800-424-9300 Canutec (Canada) 1-613-996-6666 (collect)

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION	With general room ventilation does not require any respiratory protection. If room ventilation is lacking, use NIOSH approved respirator.
VENTILATION REQUIREMENTS	Local or Mechanical recommended
LOCAL	Recommended
MECHANICAL	Recommended
SPECIAL	N/E
EYE	Not normally required, but Safety Glasses recommended
HAND	Impervious gloves required.
OTHER PROTECTIVE EQUIPMENT	Eye wash fountain and safety shower should be available

HANDLING AND STORAGE PRECAUTIONS

OTHER STORAGE AND HANDLING CONDITIONS.....	Avoid contact with eyes, skin or clothing. Avoid breathing concentrated vapors.
MISCELLANEOUS	Material should be stored at ambient temperatures in closed containers.
	HMIS RATING: Health = 1
	Flammability = 1
	Reactivity = 1
	CODE: Least Hazardous = 0 Greatest Hazard = 4

Do not flame cut, weld, or melt empty containers.

PREPARED BY:	ADDRESS:	PHONE: 330 830-6000
U.S. Chemical & Plastics	600 Nova Drive SE	FAX: 330 830-6005
<i>An Alco Industries Company</i>	Massillon, OH 44646	

NOTES: N/E = Not Established N/D = Not Determined N/A = Not Applicable

The information in this Material Safety Data Sheet has been compiled from our experience and data presented in various technical publications. It is the users responsibility to determine the suitability of this information for the adoption of safety precautions as necessary. We reserve the right to revise Material Safety Data Sheets from time to time as new technical information becomes available. The user has the responsibility to contact the Company to make sure that the sheet is the latest one issued.