

# SAFETY DATA SHEET

## 1. Identification

|   |  |                     |
|---|--|---------------------|
| Product identifier  | H20 TRANS YELLOW   |                     |
| Other means of identification                                 | <b>Product Code</b><br>MST-278-18  |                     |
| Recommended use   | Automotive Refinish Toner  |                     |
| <b>Manufacturer/Importer/Supplier/Distributor information</b> |  |                     |
| Manufacturer  |  |                     |
| <b>Company name</b>   | Pro-Spray Automotive Finishes Limited  |                     |
| <b>Address</b>  | Unit H, Normandy Lane, Stratton Business Park<br>Biggleswade, Bedfordshire SG18 8QB United Kingdom<br>United Kingdom |                     |
| <b>Telephone</b>  | General Information  | +44 (0) 1767 314320 |
| <b>Website</b>  | prosprayfinishes.com   |                     |
| <b>E-mail</b>   | colour@pro-spray.co.uk   |                     |
| <b>Emergency phone number</b>                                 | Office hours only  | +44 (0) 1767 314320 |

## 2. Hazard(s) identification

|  |  |             |
|--|--|-------------|
| <b>Physical hazards</b>                          | Flammable liquids  | Category 4  |
| <b>Health hazards</b>                            | Acute toxicity, inhalation   | Category 3  |
|  | Skin corrosion/irritation  | Category 2  |
|  | Serious eye damage/eye irritation  | Category 2A |
|  | Sensitization, skin  | Category 1  |
|  | Carcinogenicity  | Category 1  |
| <b>Environmental hazards</b>                     | Not classified.  |             |
| <b>OSHA defined hazards</b>                      | Not classified.  |             |
| <b>Label elements</b>                            |  |             |
| <b>Signal word</b>                               | Danger   |             |
| <b>Hazard statement</b>                          | Combustible liquid. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic if inhaled. May cause cancer.  |             |
| <b>Precautionary statement</b>                   |  |             |
| <b>Prevention</b>                                | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.  |             |
| <b>Response</b>                                  | If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. |             |
| <b>Storage</b>                                   | Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.   |             |
| <b>Disposal</b>                                  | Dispose of contents/container in accordance with local/regional/national/international regulations.  |             |
| <b>Hazard(s) not otherwise classified (HNOC)</b> | None known.  |             |

**Supplemental information**

14.98% of the mixture consists of component(s) of unknown acute inhalation toxicity.

**3. Composition/information on ingredients****Mixtures**

| Chemical name                            | Common name and synonyms | CAS number | %          |
|--|--------------------------|------------|------------|
| 2-Butoxyethanol                          |                          | 111-76-2   | 5 to <10   |
| 2-methyl-4-isothiazolin-3-one            |                          | 2682-20-4  | 0.1 to <1  |
| CI Pigment Yellow 150                    |                          | 68511-62-6 | 0.1 to <1  |
| Other components below reportable levels |                          |            | 90 to <100 |

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

**4. First-aid measures****Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.

**Skin contact**

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

**Eye contact**

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur.

**Ingestion**

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

**Indication of immediate medical attention and special treatment needed**

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information**

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

**5. Fire-fighting measures****Suitable extinguishing media**

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

**Unsuitable extinguishing media**

Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical**

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters**

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Fire fighting equipment/instructions**

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

**Specific methods**

Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards**

Combustible liquid.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

**Large Spills:** Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

**Small Spills:** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

**7. Handling and storage****Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Do not get in eyes, on skin, or on clothing. Avoid inhalation of vapors and spray mists. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities**

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components                             | Type | Value                         |
|--|------|-------------------------------|
| 2-Butoxyethanol (CAS 111-76-2)         | PEL  | 240 mg/m <sup>3</sup>         |
| CI Pigment Yellow 150 (CAS 68511-62-6) | PEL  | 50 ppm<br>1 mg/m <sup>3</sup> |

**US. ACGIH Threshold Limit Values**

| Components                             | Type | Value  |
|--|------|--|
| 2-Butoxyethanol (CAS 111-76-2)         | TWA  | 20 ppm   |
| CI Pigment Yellow 150 (CAS 68511-62-6) | TWA  | 24 mg/m <sup>3</sup><br>5 ppm<br>0.015 mg/m <sup>3</sup> |

**Biological limit values****ACGIH Biological Exposure Indices**

| Components                     | Value    | Determinant                              | Specimen            | Sampling Time |
|--------------------------------|----------|--|---------------------|---------------|
| 2-Butoxyethanol (CAS 111-76-2) | 200 mg/g | Butoxyacetic acid (BAA), with hydrolysis | Creatinine in urine | *             |

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

**US - Tennessee OELs: Skin designation**

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

**US NIOSH Pocket Guide to Chemical Hazards: Skin designation**

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

**Appearance****Physical state**

Liquid.

**Form**

Liquid.

**Color**

Yellow

**Odor**

Slight. Solvent.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

Not available.

**Initial boiling point and boiling range**

212 °F (100 °C) estimated

**Flash point**

143.0 °F (61.7 °C) estimated

**Evaporation rate**

Not available.

**Flammability (solid, gas)**

Not applicable.

**Upper/lower flammability or explosive limits****Flammability limit - lower (%)**

Not available.

**Flammability limit - upper (%)**

Not available.

**Explosive limit - lower (%)**

Not available.

**Explosive limit - upper (%)**

Not available.

**Vapor pressure**

0.07 hPa estimated

**Vapor density**

Not available.

**Relative density**

Not available.

**Solubility(ies)****Solubility (water)**

Not available.

**Partition coefficient (n-octanol/water)**

Not available.

**Auto-ignition temperature**

460.4 °F (238 °C) estimated

|                                  |   |
|----------------------------------|---|
| <b>Decomposition temperature</b> | Not available.  |
| <b>Viscosity</b>                 | Not available.  |
| <b>Other information</b>         |   |
| <b>Density</b>                   | 8.45 lbs/gal  |
| <b>Flammability class</b>        | Combustible IIIA estimated  |
| <b>Percent volatile</b>          | 84 % estimated  |
| <b>Specific gravity</b>          | 1.01  |
| <b>VOC</b>                       | 0.5 lbs/gal Material<br>3.1 lbs/gal Coating<br>62 g/l Material<br>365 g/l Coating |

## 10. Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport.  |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.  |
| <b>Possibility of hazardous reactions</b> | No dangerous reaction known under conditions of normal use.  |
| <b>Conditions to avoid</b>                | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| <b>Incompatible materials</b>             | Strong oxidizing agents.   |
| <b>Hazardous decomposition products</b>   | No hazardous decomposition products are known.   |

## 11. Toxicological information

### Information on likely routes of exposure

|   |   |
|---|---|
| <b>Inhalation</b>   | Toxic if inhaled.   |
| <b>Skin contact</b>   | Causes skin irritation. May cause an allergic skin reaction.  |
|   | 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.  |
| <b>Eye contact</b>  | Causes serious eye irritation.  |
| <b>Ingestion</b>  | Expected to be a low ingestion hazard.  |
| <b>Symptoms related to the physical, chemical and toxicological characteristics</b> | Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. |

### Information on toxicological effects

|                       |  |
|-----------------------|--|
| <b>Acute toxicity</b> | Toxic if inhaled. May cause an allergic skin reaction. |
|-----------------------|--|

| <b>Components</b> | <b>Species</b> | <b>Test Results</b> |
|-------------------|----------------|---------------------|
|-------------------|----------------|---------------------|

2-Butoxyethanol (CAS 111-76-2)

| <b>Acute</b>      |            |                  |           |
|-------------------|------------|------------------|-----------|
| <b>Dermal</b>     |            |                  |           |
| LD50              | Rabbit     |                  | 400 mg/kg |
| <b>Inhalation</b> |            |                  |           |
| LC50              | Mouse      | 700 ppm, 7 Hours |           |
|                   | Rat        | 450 ppm, 4 Hours |           |
| <b>Oral</b>       |            |                  |           |
| LD50              | Guinea pig | 1.2 g/kg         |           |
|                   | Mouse      | 1.2 g/kg         |           |
|                   | Rabbit     | 0.32 g/kg        |           |
|                   | Rat        | 560 mg/kg        |           |

\* Estimates for product may be based on additional component data not shown.

|                                  |                         |
|----------------------------------|-------------------------|
| <b>Skin corrosion/irritation</b> | Causes skin irritation. |
|----------------------------------|-------------------------|

|  |  |
|--|--|
| <b>Serious eye damage/eye irritation</b> | Causes serious eye irritation.   |
| <b>Respiratory or skin sensitization</b> |  |
| <b>Respiratory sensitization</b>         | Not a respiratory sensitizer.  |
| <b>Skin sensitization</b>                | May cause an allergic skin reaction.   |
| <b>Germ cell mutagenicity</b>            | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| <b>Carcinogenicity</b>                   | May cause cancer.  |

#### IARC Monographs. Overall Evaluation of Carcinogenicity

|  |   |
|--|---|
| 2-Butoxyethanol (CAS 111-76-2)         | 3 Not classifiable as to carcinogenicity to humans. |
| CI Pigment Yellow 150 (CAS 68511-62-6) | 1 Carcinogenic to humans.                           |

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

#### US. National Toxicology Program (NTP) Report on Carcinogens

|  |                               |
|--|-------------------------------|
| CI Pigment Yellow 150 (CAS 68511-62-6) | Known To Be Human Carcinogen. |
|--|-------------------------------|

|   |   |
|---|---|
| <b>Reproductive toxicity</b>                              | This product is not expected to cause reproductive or developmental effects.  |
| <b>Specific target organ toxicity - single exposure</b>   | Not classified.   |
| <b>Specific target organ toxicity - repeated exposure</b> | Not classified.   |
| <b>Aspiration hazard</b>                                  | Not an aspiration hazard.   |
| <b>Chronic effects</b>                                    | <p>May be harmful if absorbed through skin. Prolonged inhalation may be harmful.</p> <p>2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.</p> <p>Prolonged exposure may cause chronic effects.</p> |

## 12. Ecological information

|                    |  |
|--------------------|--|
| <b>Ecotoxicity</b> | The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. |
|--------------------|--|

| Components                     | Species | Test Results |
|--------------------------------|---------|--------------|
| 2-Butoxyethanol (CAS 111-76-2) |         |              |
| <b>Aquatic</b>                 |         |              |

|      |      |                                       |                     |
|------|------|---------------------------------------|---------------------|
| Fish | LC50 | Inland silverside (Menidia beryllina) | 1250 mg/l, 96 hours |
|------|------|---------------------------------------|---------------------|

\* Estimates for product may be based on additional component data not shown.

|                                      |  |
|--------------------------------------|--|
| <b>Persistence and degradability</b> | No data is available on the degradability of this product. |
|--------------------------------------|--|

#### Bioaccumulative potential

##### Partition coefficient n-octanol / water (log Kow)

|                 |      |
|-----------------|------|
| 2-Butoxyethanol | 0.83 |
|-----------------|------|

|                         |                    |
|-------------------------|--------------------|
| <b>Mobility in soil</b> | No data available. |
|-------------------------|--------------------|

|                              |   |
|------------------------------|---|
| <b>Other adverse effects</b> | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |
|------------------------------|---|

## 13. Disposal considerations

|  |  |
|--|--|
| <b>Disposal instructions</b>                 | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.                         |
| <b>Local disposal regulations</b>            | Dispose in accordance with all applicable regulations.   |
| <b>Hazardous waste code</b>                  | The waste code should be assigned in discussion between the user, the producer and the waste disposal company.   |
| <b>Waste from residues / unused products</b> | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| <b>Contaminated packaging</b>                | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.       |

## 14. Transport information

### DOT

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-methyl-4-isothiazolin-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

### CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethanol (CAS 111-76-2) Listed.  
CI Pigment Yellow 150 (CAS 68511-62-6) Listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

|                   |                        |
|-------------------|------------------------|
| Hazard categories | Immediate Hazard - Yes |
|                   | Delayed Hazard - Yes   |
|                   | Fire Hazard - Yes      |
|                   | Pressure Hazard - No   |
|                   | Reactivity Hazard - No |

### SARA 302 Extremely hazardous substance

Not listed.

### SARA 311/312 Hazardous chemical

No

### SARA 313 (TRI reporting)

| Chemical name         | CAS number | % by wt.  |
|-----------------------|------------|-----------|
| 2-Butoxyethanol       | 111-76-2   | 5 to <10  |
| CI Pigment Yellow 150 | 68511-62-6 | 0.1 to <1 |

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

CI Pigment Yellow 150 (CAS 68511-62-6)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

#### Safe Drinking Water Act (SDWA)

Not regulated.

### US state regulations

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-Butoxyethanol (CAS 111-76-2)  
CI Pigment Yellow 150 (CAS 68511-62-6)

#### US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2)

#### US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)  
CI Pigment Yellow 150 (CAS 68511-62-6)

**US. Pennsylvania Worker and Community Right-to-Know Law**

2-Butoxyethanol (CAS 111-76-2)

**US. Rhode Island RTK**

2-Butoxyethanol (CAS 111-76-2)

CI Pigment Yellow 150 (CAS 68511-62-6)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Carbon Black (CAS 1333-86-4)

Listed: February 21, 2003

CI Pigment Yellow 150 (CAS 68511-62-6)

Listed: May 7, 2004

**International Inventories**

| Country(s) or region        | Inventory name   | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Canada                      | Domestic Substances List (DSL)   | Yes                    |
| Canada                      | Non-Domestic Substances List (NDSL)                                    | Yes                    |
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes                    |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | Yes                    |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision****Issue date** 04-10-2015**Version #** 01**HMIS® ratings**  
Health: 3\*  
Flammability: 2  
Physical hazard: 0**NFPA ratings**  
Health: 3  
Flammability: 2  
Instability: 0**Disclaimer**  
The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.