

## 1. Identification

|   |   |                |
|---|---|----------------|
| <b>Product identifier</b>                                     | <b>MONASTRAL RED</b>                                      |                |
| <b>Other means of identification</b>                          |   |                |
| <b>Product Code</b>   | MT-92-QT  |                |
| <b>Recommended use</b>  | Automotive Refinish Toner                                 |                |
| <b>Manufacturer/Importer/Supplier/Distributor information</b> |   |                |
| <b>Manufacturer</b>   |   |                |
| <b>Company name</b>   | VALSPAR Automotive  |                |
| <b>Address</b>  | 600 Nova Drive SE<br>Massillon, OH 44646<br>United States |                |
| <b>Telephone</b>  | General Assistance  | (330) 299-8879 |
| <b>E-mail</b>   | RON.ANDRUS@valspar.com                                    |                |
| <b>Contact person</b>   | Ron Andrus  |                |
| <b>Emergency phone number</b>                                 | CHEMTREC  | (800) 424-9300 |

## 2. Hazard(s) identification

|                              |  |                             |
|------------------------------|--|-----------------------------|
| <b>Physical hazards</b>      | Flammable liquids                                      | Category 2                  |
| <b>Health hazards</b>        | Acute toxicity, dermal                                 | Category 4                  |
|                              | Acute toxicity, inhalation                             | Category 3                  |
|                              | Skin corrosion/irritation                              | Category 2                  |
|                              | Serious eye damage/eye irritation                      | Category 2A                 |
|                              | Sensitization, skin                                    | Category 1                  |
|                              | Specific target organ toxicity, single exposure        | Category 3 narcotic effects |
| <b>Environmental hazards</b> | Hazardous to the aquatic environment, acute hazard     | Category 3                  |
|                              | Hazardous to the aquatic environment, long-term hazard | Category 3                  |
| <b>OSHA defined hazards</b>  | Not classified.  |                             |

### Label elements



|                                |   |
|--------------------------------|---|
| <b>Signal word</b>             | Danger  |
| <b>Hazard statement</b>        | Highly flammable liquid and vapor. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic if inhaled. May cause drowsiness or dizziness. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.   |
| <b>Precautionary statement</b> |   |
| <b>Prevention</b>              | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing. Wear protective gloves/eye protection/face protection. |

|  |   |
|--|---|
| <b>Response</b>                                  | If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. |
| <b>Storage</b>                                   | Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.  |
| <b>Disposal</b>                                  | Dispose of contents/container in accordance with local/regional/national/international regulations.   |
| <b>Hazard(s) not otherwise classified (HNOC)</b> | Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.   |
| <b>Supplemental information</b>                  | 96.65% of the mixture consists of component(s) of unknown acute dermal toxicity. 83.14% of the mixture consists of component(s) of unknown acute inhalation toxicity. 85.92% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 85.73% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.   |

### 3. Composition/information on ingredients

#### Mixtures

| Chemical name                            | Common name and synonyms | CAS number | %         |
|--|--------------------------|------------|-----------|
| Methyl acetate                           |                          | 79-20-9    | 10 to <20 |
| n-butyl acetate                          |                          | 123-86-4   | 10 to <20 |
| 1-Methoxy-2-propyl acetate               |                          | 108-65-6   | 1 to <5   |
| 2-Butoxyethyl acetate                    |                          | 112-07-2   | 1 to <5   |
| liquid HALS                              |                          | 41556-26-7 | 0.1 to <1 |
| Other components below reportable levels |                          |            | 60 to <70 |

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

#### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.

#### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

#### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

#### Ingestion

Rinse mouth. Get medical advice/attention if you feel unwell.

#### Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

#### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

#### General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

#### Suitable extinguishing media

Alcohol resistant foam. Water fog. Carbon dioxide (CO<sub>2</sub>). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

#### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

|  |  |
|--|--|
| <b>Specific hazards arising from the chemical</b>                    | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed. |
| <b>Special protective equipment and precautions for firefighters</b> | Self-contained breathing apparatus and full protective clothing must be worn in case of fire.  |
| <b>Fire fighting equipment/instructions</b>                          | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.   |
| <b>Specific methods</b>  | Use standard firefighting procedures and consider the hazards of other involved materials.   |
| <b>General fire hazards</b>  | Highly flammable liquid and vapor.   |

## 6. Accidental release measures

|  |  |
|--|--|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| <b>Methods and materials for containment and cleaning up</b>               | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.  |

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

|                                  |  |
|----------------------------------|--|
| <b>Environmental precautions</b> | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination. |
|----------------------------------|--|

## 7. Handling and storage

|                                      |   |
|--------------------------------------|---|
| <b>Precautions for safe handling</b> | Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. |
|--------------------------------------|---|

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

**Conditions for safe storage, including any incompatibilities**

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components                     | Type | Value                           |
|--------------------------------|------|---------------------------------|
| Methyl acetate (CAS 79-20-9)   | PEL  | 610 mg/m3                       |
| n-butyl acetate (CAS 123-86-4) | PEL  | 200 ppm<br>710 mg/m3<br>150 ppm |

**US. ACGIH Threshold Limit Values**

| Components                           | Type | Value   |
|--------------------------------------|------|---------|
| 2-Butoxyethyl acetate (CAS 112-07-2) | TWA  | 20 ppm  |
| Methyl acetate (CAS 79-20-9)         | STEL | 250 ppm |
| n-butyl acetate (CAS 123-86-4)       | TWA  | 200 ppm |
|                                      | STEL | 200 ppm |
|                                      | TWA  | 150 ppm |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components                           | Type | Value                           |
|--------------------------------------|------|---------------------------------|
| 2-Butoxyethyl acetate (CAS 112-07-2) | TWA  | 33 mg/m3                        |
| Methyl acetate (CAS 79-20-9)         | STEL | 5 ppm<br>760 mg/m3              |
|                                      | TWA  | 250 ppm<br>610 mg/m3<br>200 ppm |
|                                      | STEL | 950 mg/m3                       |
| n-butyl acetate (CAS 123-86-4)       | TWA  | 200 ppm<br>710 mg/m3<br>150 ppm |

**US. Workplace Environmental Exposure Level (WEEL) Guides**

| Components                                | Type | Value  |
|---|------|--------|
| 1-Methoxy-2-propyl acetate (CAS 108-65-6) | TWA  | 50 ppm |

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines****US - California OELs: Skin designation**

1-Methoxy-2-propyl acetate (CAS 108-65-6)

Can be absorbed through the skin.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

|                                       |   |
|---------------------------------------|---|
| <b>Skin protection</b>                |   |
| <b>Hand protection</b>                | Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.   |
| <b>Other</b>                          | Wear appropriate chemical resistant clothing.   |
| <b>Respiratory protection</b>         | If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.   |
| <b>Thermal hazards</b>                | Wear appropriate thermal protective clothing, when necessary.   |
| <b>General hygiene considerations</b> | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. |

## 9. Physical and chemical properties

### Appearance

|   |  |
|---|--|
| <b>Physical state</b>                               | Liquid.  |
| <b>Form</b>   | Liquid.  |
| <b>Color</b>  | Blue Red.  |
| <b>Odor</b>   | Solvent.   |
| <b>Odor threshold</b>                               | Not available.   |
| <b>pH</b>   | Not available.   |
| <b>Melting point/freezing point</b>                 | -144.4 °F (-98 °C) estimated   |
| <b>Initial boiling point and boiling range</b>      | 134.24 °F (56.8 °C) estimated  |
| <b>Flash point</b>                                  | 14.0 °F (-10.0 °C) estimated   |
| <b>Evaporation rate</b>                             | Not available.   |
| <b>Flammability (solid, gas)</b>                    | Not applicable.  |
| <b>Upper/lower flammability or explosive limits</b> |  |
| <b>Flammability limit - lower (%)</b>               | 1.4 % estimated  |
| <b>Flammability limit - upper (%)</b>               | 16 % estimated   |
| <b>Explosive limit - lower (%)</b>                  | Not available.   |
| <b>Explosive limit - upper (%)</b>                  | Not available.   |
| <b>Vapor pressure</b>                               | 96.48 hPa estimated  |
| <b>Vapor density</b>                                | Not available.   |
| <b>Relative density</b>                             | Not available.   |
| <b>Solubility(ies)</b>                              |  |
| <b>Solubility (water)</b>                           | Not available.   |
| <b>Partition coefficient (n-octanol/water)</b>      | Not available.   |
| <b>Auto-ignition temperature</b>                    | 797 °F (425 °C) estimated  |
| <b>Decomposition temperature</b>                    | Not available.   |
| <b>Viscosity</b>                                    | Not available.   |
| <b>Other information</b>                            |  |
| <b>Density</b>                                      | 9.21 lbs/gal   |
| <b>Flammability class</b>                           | Flammable IB estimated   |
| <b>Percent volatile</b>                             | 70.27 %  |
| <b>Specific gravity</b>                             | 1.11   |
| <b>VOC</b>  | 1.7 lbs/gal Material<br>3.4 lbs/gal Regulatory<br>203 g/l Material<br>410 g/l Regulatory |

## 10. Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport.  |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.  |
| <b>Possibility of hazardous reactions</b> | Hazardous polymerization does not occur.   |
| <b>Conditions to avoid</b>                | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| <b>Incompatible materials</b>             | Nitrates.  |
| <b>Hazardous decomposition products</b>   | No hazardous decomposition products are known.   |

## 11. Toxicological information

### Information on likely routes of exposure

|                     |  |
|---------------------|--|
| <b>Inhalation</b>   | Toxic if inhaled. May cause drowsiness and dizziness. Headache. Nausea, vomiting.          |
| <b>Skin contact</b> | Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. |
| <b>Eye contact</b>  | Causes serious eye irritation.   |
| <b>Ingestion</b>    | Expected to be a low ingestion hazard.   |

**Symptoms related to the physical, chemical and toxicological characteristics** Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

### Information on toxicological effects

**Acute toxicity** Toxic if inhaled. Harmful in contact with skin. Narcotic effects. May cause an allergic skin reaction.

| <b>Components</b>                    | <b>Species</b> | <b>Test Results</b> |
|--------------------------------------|----------------|---------------------|
| 2-Butoxyethyl acetate (CAS 112-07-2) |                |                     |
| <b>Acute</b>                         |                |                     |
| <b>Dermal</b>                        |                |                     |
| LD50                                 | Rabbit         | 1500 mg/kg          |
| <b>Oral</b>                          |                |                     |
| LD50                                 | Rat            | 2400 mg/kg          |
| Methyl acetate (CAS 79-20-9)         |                |                     |
| <b>Acute</b>                         |                |                     |
| <b>Oral</b>                          |                |                     |
| LD50                                 | Rabbit         | 3.7 g/kg            |
| n-butyl acetate (CAS 123-86-4)       |                |                     |
| <b>Acute</b>                         |                |                     |
| <b>Inhalation</b>                    |                |                     |
| LC50                                 | Wistar rat     | 160 mg/l, 4 Hours   |
| <b>Oral</b>                          |                |                     |
| LD50                                 | Rat            | 14000 mg/kg         |

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

|   |                                      |
|---|--------------------------------------|
| <b>Specific target organ toxicity - single exposure</b>   | May cause drowsiness and dizziness.  |
| <b>Specific target organ toxicity - repeated exposure</b> | Not classified.                      |
| <b>Aspiration hazard</b>                                  | Not an aspiration hazard.            |
| <b>Chronic effects</b>                                    | Prolonged inhalation may be harmful. |

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

| Components                     | Species | Test Results   |
|--------------------------------|---------|--|
| Methyl acetate (CAS 79-20-9)   |         |  |
| <b>Aquatic</b>                 |         |  |
| Fish                           | LC50    | Fathead minnow ( <i>Pimephales promelas</i> ) 295 - 348 mg/l, 96 hours |
| n-butyl acetate (CAS 123-86-4) |         |  |
| <b>Aquatic</b>                 |         |  |
| Fish                           | LC50    | Fathead minnow ( <i>Pimephales promelas</i> ) 17 - 19 mg/l, 96 hours   |

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

### Bioaccumulative potential

#### Partition coefficient n-octanol / water (log Kow)

|                 |      |
|-----------------|------|
| Methyl acetate  | 0.18 |
| n-butyl acetate | 1.78 |

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

### DOT

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1263  |
| <b>UN proper shipping name</b>      | Paint, Paint Related Material   |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 3   |
| <b>Subsidiary risk</b>              | -   |
| <b>Label(s)</b>                     | 3   |
| <b>Packing group</b>                | II  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Special provisions</b>           | IB2, T7, TP1, TP8, TP28   |
| <b>Packaging exceptions</b>         | 150   |
| <b>Packaging non bulk</b>           | 202   |
| <b>Packaging bulk</b>               | 242   |

### IATA

|                  |        |
|------------------|--------|
| <b>UN number</b> | UN1263 |
|------------------|--------|

**UN proper shipping name** Paint, Paint Related Material  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Packing group** II  
**Environmental hazards** No.  
**ERG Code** 3H  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Other information**  
**Passenger and cargo aircraft** Allowed with restrictions.  
**Cargo aircraft only** Allowed with restrictions.

**IMDG**

**UN number** UN1263  
**UN proper shipping name** Paint, Paint Related Material  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Packing group** II  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** F-E, S-E  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**DOT**



**IATA; IMDG**



**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

|                                      |         |
|--------------------------------------|---------|
| 2-Butoxyethyl acetate (CAS 112-07-2) | Listed. |
| Methyl acetate (CAS 79-20-9)         | Listed. |
| n-butyl acetate (CAS 123-86-4)       | Listed. |





| Country(s) or region        | Inventory name   | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| China                       | Inventory of Existing Chemical Substances in China (IECSC)             | No                     |
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)  | No                     |
| New Zealand                 | New Zealand Inventory  | No                     |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | No                     |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

|                      |   |
|----------------------|---|
| <b>Issue date</b>    | 08-31-2015  |
| <b>Version #</b>     | 01  |
| <b>HMIS® ratings</b> | Health: 3<br>Flammability: 3<br>Physical hazard: 0<br>Personal protection: H  |
| <b>NFPA ratings</b>  | Health: 3<br>Flammability: 3<br>Instability: 0  |
| <b>Disclaimer</b>    | The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses. |