Version No. 01.1/EN
Revision N.A.
Printing date 11 Mar. 2019

(according to Regulation EC 1907/2006)

1. IDENTIFICATION OF SUBSTANCE / MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name MagTorch Butane 5.6 oz or 1.42 oz

Registration no. N.A

1.2 Relevant identified uses of substance or mixture and uses advised against

Identified uses Fuel etc.

1.3 Details of the supplier of the safety data sheet

Company M.I.T. LIMITED

Telephone +82-2-711-9160

E-mail mgchoi@mit21.net

1.4 Emergency telephone number +82-10-3723-7861

(This number is serviced during office hours only.)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008 [CLP]

Flammable gases Cat. 1

Gases under pressure (Liquefied gas)

2.1.2. Classification according to Directive 1999/45/EC

Extremely flammable.

2.2 Label elements

2.2.1 Labelling according Regulation (EC) No 1272/2008 [CLP]

Symbol



Signal word DANGER

Hazard Statement H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Precautionary statement P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

2.2.2 According to European Directive 67/548/EEC as amended

Hazard symbol(s)



R-phrase(s) R12 Extremely flammable.

S-phrase(s) S 9 Keep container in a well-ventilated place.

S16 Keep away from sources of ignition - No smoking.

2.3. Other hazards

CERCLA Index (0~3) Health=1, Fire=3, Reactivity=0, Durability=0

NFPA Index (0~4) Health=1, Fire=4, Reactivity=0

Version No. 01.1/EN
Revision N.A.
Printing date 11 Mar. 2019

(according to Regulation EC 1907/2006)

3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Mixture

Components	%	Classification		
Iso-Butane CAS No. 75-28-5	28.0	Classification according to Regulation (EC) No 1272/2008 [EU-GHS/CLP] - Flammable gases Cat. 1 - Gases under pressure (Liquefied gas) According to European Directive 67/548/EEC as amended. - Extremely flammable.		
Propane CAS No. 74-98-6	25.0	Classification according to Regulation (EC) No 1272/2008 [EU-GHS/CLP] - Flammable gases Cat. 1 - Gases under pressure (Liquefied gas) According to European Directive 67/548/EEC as amended. - Extremely flammable.		
N-Butane CAS No. 106-97-8	46.5	Classification according to Regulation (EC) No 1272/2008 [EU-GHS/CLP] - Flammable gases Cat. 1 - Gases under pressure (Liquefied gas) According to European Directive 67/548/EEC as amended. - Extremely flammable.		
Pentane CAS No. 109-66-0	0.5	Classification according to Regulation (EC) No 1272/2008 [EU-GHS/CLP] - Flammable Liquid Cat. 2 - Gases under pressure (Liquefied gas) According to European Directive 67/548/EEC as amended. - Extremely flammable.		

Version No. 01.1/EN
Revision N.A.
Printing date 11 Mar. 2019

(according to Regulation EC 1907/2006)

4. FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation Move from the exposed areas immediately. Artificial respiration if needed.

Secure the airway, maintain blood pressure, and inhale oxygen if possible.

Keep a patient in a warm and comfortable condition.

Treat appropriately depending on the symptoms. Take a proper medical action.

Skin contact Thoroughly wash off with soft detergent and much water (15~20 minutes).

If there are symptoms such as frostbite and freezing, take the following process.

Warm the affected part with warm water of 107 °F (41.7 °C). Gently wrap the affected

part in blanket. Take an immediate medical action.

Eye contact Wash eyes immediately with much water or saline solution until no chemicals remain.

Take an immediate medical action.

Ingestion Treat properly based on the symptoms.

Take an immediate medical action.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Powder fire extinguisher, carbon dioxide (Use water or fog in case of a blaze)

5.2 Special hazards arising from the substance or mixture

May burst or explode if exposed to heat or spark.

Heavier than the air, and there is a possibility of ignition and backfire.

Container may explode by heat or fire.

Mixture of gas & air may explode.

Low electrical conduction may cause static electricity, and ignited by a spark.

5.3 Advice for firefighters

If not dangerous, remove from a fire area.

After putting out a fire, sprinkle cooling water in the side of the container which is exposed by heat.

Escape from the end of tank.

Use a fire hose or monitor nozzle if a blaze occurs in the stored area, and leave it burned if difficult.

Immediately remove if the size of blaze grows bigger or the tank is discolored by heat.

Leave it burned and isolate by more than 1 mile if we cannot stop the spills from gas tank, and tank lorry.

Extinguish it if the gas spills can be stopped. Use much water in a form of fog from a long distance.

Keep away outside a 8.045 km radius if fire is out of control or the container is exposed to a flame.

Don't inhale the smoke from the burning materials with one's back against the wind.

5.4 Special Information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Version No. 01.1/EN
Revision N.A.
Printing date 11 Mar. 2019

(according to Regulation EC 1907/2006)

Avoid heat, flame, spark and other source of ignition.

Do not touch a spilled material.

Do it if you can stop a spilled material with safety.

Sprinkle water in order to reduce vapour.

Isolate the area until the gas disperses.

Prohibit smoke, flame or fire at the dangerous area.

No entry to unauthorized persons, and isolate the dangerous and restricted area.

Ventilate the closed place before entering.

6.2 Environmental precautions

No data available

6.3 Methods and material for containment and cleaning up

No data available

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Store and handle in accordance with the regulations of a central government and local autonomous entity.

Recommend a practical training against static electricity.

7.2 Conditions for safe storage, including any incompatibilities

Please isolate and store the materials separated from other materials which shall not be put together at the same time.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Occupational exposure limits

Exposure standard: Industry safety & health law

Components	OSHA TWA	ACGIH TWA	NIOSH TWA
Iso-Butane	No data	800 ppm (1900 mg/m³)	800 ppm (1900 mg/m³)
Propane	1000 ppm (1800 mg/m³)	2500 ppm	1000 ppm (1800 mg/m³)
N-Butane	800 ppm (1900 mg/m³)	800 ppm	800 ppm (1900 mg/m³)
Pentane	1000 ppm (2950 mg/m³)	600 ppm	610 ppm 1800 mg/m ³

8.2 Appropriate engineering controls

Set up a partial ventilation or general diluted ventilation equipment.

Install explosion-screening facilities for the relevant ventilation equipment if there is a possibility of explosion for the material.

Employer shall install a washing equipment and shower stall near the work place because possibly employee's eye can be exposed to foreign materials

8.3 Personal protection equipment

Eye protection For the gas, eye protection not required, but recommended.

For the liquid, spray or dust protective goggles are needed to avoid a direct contact with

foreign materials. Contact lense shall not be used

Protection clothes For gas, protective clothing is not necessary.

In case of possible contact with liquid, employee must wear proper protection clothes and

equipment in order to prevent a skin from freezing.

Version No. Revision Printing date 01.1/EN N.A.

11 Mar. 2019

(according to Regulation EC 1907/2006)

Protection gloves

Respiratory protection

Wear insulated gloves and gloves against the cold.

Below respirator and maximum use concentration is recommended by NISOH guide or allowance standard report about chemical hazard established by America Health and Human Services Department.

Specifically-selected respirator shall be based on pollutant density in a work place, and does not exceed the operation limit of respirator, and finally approved by NIOSH and NSHA at the same time.

Version No. 01.1/EN
Revision N.A.
Printing date 11 Mar. 2019

(according to Regulation EC 1907/2006)

9. PHYSICAL & CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Properties	roperties Iso-Butane		N-Butane	Pentane
Appearance	liquid & vapor	liquid & vapor	liquid & vapor	Colorless liquid
Odor	odorless	odorless	odorless	gasoline-like odor
Odor threshold	No data	No data	No data	No data
рН	Not applicable	Not applicable	Not applicable	Not applicable
Melting point/Freezing point	-160°C	-187.7°C	-138.3°C	-130 °C
Boiling point and range	-11.5°C	-42.1°C	-0.5°C	36 ℃
Flash point	-88.0°C	-104.4°C	-73.3℃	-49.4°C
Evaporation rate	100%	100%	100%	> 1 (Ehyl Ether = 1.0)
Flammability (solid, gas)	no way to know			
Upper/lower flammability	8.4 vol%	9.5 vol%	8.4 vol%	1.5% vol%
or explosive limits	1.8 vol%	2.2 vol%	1.9 vol%	7.8% vol%
Vapor pressure	0.304MPa @20°C	0.75MPa @20℃	0.214MPa @21.1°C	26.98 psi @55℃
Vapor density	2.595(air=1)	1.55(air=1)	2.1(air=1)	0.626 g/mL @ 25 °C(lit.)
Relative density	0.549 @ 20°C	0.501 @ 20°C	0.549 @ 20°C	0.6262 g @ 20°C
Solubility	no way to know	0.007 g/100mL @ 20°C	3.25 mL/100mL @ 20°C	0.0385 g/L @ 20℃
Partition coefficient: n-octanol/water	2.8 as log POW	2.36 as log POW	2.89 as log POW	3.45 as log POW
Auto-ignition temperature	460°C	466.1°C	287°C	260°C
Decomposition temperature	no way to know			
Viscosity	No data	No data	No data	No data
Explosive properties	No data	No data	No data	No data
Oxidizing properties	No data	No data	No data	No data

10. STABILITY AND REACTIVITY

10.1 Reactivity
10.2 Chemical stability
10.3 Possibility of hazardous reactions

Stable at a normal temperature and pressure No data available.

No dangerous reactions known.

Avoid a contact with heat, flame, spark and other sources of ignition.

Vapor has a explosiveness.

Do not contact with a skin.

May cause frostbite.

Because of a pressure, containers may be burst if exposed to

heat, and thus could move to a long distance. Strong oxidizer: Hazard of fire, explosion

Nitric acid, chlorine dioxide : Material to be avoided Carbonyl nickel & acid: Explode at (20~40) °C

10.4 Conditions to avoid

10.5 Incompatible materials

Version No. Revision 01.1/EN N.A.

Printing date 11 Mar. 2019

(according to Regulation EC 1907/2006)

10.6 Hazardous decomposition products

Pyrolysis product may contain poisonous carbon oxidized substance

11. TOXICOLOGICAL INFORMATION

11.1 Routes of exposure

No data available

11.2 Information on toxicological effects

Acute toxicity No toxicity by inhalation.

Skin corrosion/irritation

Contact with liquid may cause frostbite, ache, and water

blister.

Not irritating (Rabbit)

Serious eye damage/irritation Contact with liquid may cause frostbite, ache, and eyesight

loss.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity No data available

This product is or contains a component that is probably not

Carcinogenicity carcinogenic based on its IARC, ACGIH, NTP, or EPA

classification.

Reproductive toxicity

No data available

STOT-single exposure Simple asphyxiant, and central nervous system suppressant.

STOT-repeated exposure

Aspiration hazard

No data available

No data available

12. ECOLOGICAL INFORMATION

12.1 EcotoxicityNo data available.12.2 Persistence and degradabilityNo data available.12.3 Bioaccumulative potentialNo data available.12.4 Mobility in soilNo data available.12.5 Other adverse effectsNo data available.

13. DISPOSAL CONSIDERATIONS

Comply with a central government and local autonomous

entity regulations.

13.1 Disposal instructions Disposal shall be executed by a standard of 40 CFR 262

applied for hazardous waste generator.

EPA hazardous waste No. D001.

13.2 Waste from residues / unused

products

No data available.

13.3 Contaminated packaging

No data available.

Version No. Revision 01.1/EN N.A.

Printing date 11 Mar. 2019

(according to Regulation EC 1907/2006)

14. TRANSPORT INFORMATION

14.1 UN number UN 2037

RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES)

14.2 UN proper shipping name without a release device, non-refillable

LQ2 2.1

14.3 Transport hazard class(es)
14.4. Packing group

N.A.

14.5. Environmental hazards

14.6. Special precautions for user

N.A.
Passenger plane or train: Prohibited

Cargo plane: 150 kg

15. REGULATORY INFORMATION

15.1 Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical Safety Assessment:

No data available

15.3 Inventory status

No data available

16. OTHER INFORMATION

The contents and format of this MSDS/SDS are in accordance with Regulation (EC) No 1907/2006.

References

Other MSDS (TAEYANG Corporation, GS Caltex Corporation, Korea Petro Chemical Ind. Co., Ltd., Aldirch, Shell Trading International Limited etc.)

KOSHA – Chemical information database system

ESIS (European chemical Substances Information System) (http://ecb.jrc.ec.europa.eu/)

International Uniform Chemical Information Database (IUCLID) (http://ecb.jrc.it/esis)

· Abbreviation and acronyms

ACGIH - American Conference of Industrial Hygienists

CAS - Chemical Abstracts Service

CLP - Regulation on classification, labeling and packaging of substances and mixtures. (Directive 67/548/EEC)

EC - European Community

EEC - The European Economic Community

EPA - Environmental Protection Agency

GHS - Global Harmonized System

IARC - International Agency for Research on Cancer

NIOSH - National Institute for Occupational Safety and Health

NTP - The National Toxicology Program

OSHA - Occupational Safety and Health Administration

STOT - Specific Target Organ Toxicity

• Disclaimer of Liability

Version No. 01.1/EN
Revision N.A.
Printing date 11 Mar. 2019

(according to Regulation EC 1907/2006)

The information in this MSDS/SDS was obtained from source which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reason, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of component in another product, this MSDS/SDS information may not be applicable.