

Safety Data Sheet

MasterSeal NP 150 stn

Revision date : 2016/04/18
Version: 4.0

Page: 1/10
(30605765/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

MasterSeal NP 150 stn

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Canada Inc.
100 Milverton Drive
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

CANUTEC (reverse charges): (613) 996-6666
BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: sealant

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
Repr.	1B (fertility)	Reproductive toxicity
Repr.	1B (unborn child)	Reproductive toxicity
STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Safety Data Sheet

MasterSeal NP 150 stn

Revision date : 2016/04/18

Version: 4.0

Page: 2/10

(30605765/SDS_GEN_CA/EN)

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H373 May cause damage to organs (Liver, Kidney) through prolonged or repeated exposure.
H360 May damage fertility. May damage the unborn child.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P260 Do not breathe dust/gas/mist/vapours.
P273 Avoid release to the environment.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P272 Contaminated work clothing should not be allowed out of the workplace.
P264 Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/attention if you feel unwell.
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P308 + P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

Precautionary Statements (Storage):

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

CAS Number

Weight %

Chemical name

Safety Data Sheet

MasterSeal NP 150 stn

Revision date : 2016/04/18

Version: 4.0

Page: 3/10

(30605765/SDS_GEN_CA/EN)

471-34-1	>= 20.0 - < 50.0%	Calcium carbonate
1317-65-3	>= 3.0 - < 7.0%	Limestone
13463-67-7	>= 3.0 - < 5.0%	Titanium dioxide
57-11-4	>= 0.3 - < 3.0%	stearic acid
1760-24-3	>= 0.3 - < 1.0%	1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-
22673-19-4	>= 0.1 - < 0.2%	Tin, dibutylbis(2,4-pentanedionato-.kappa.O2,.kappa.O4)-, (OC-6-11)-
25973-55-1	>= 0.2 - <= 1.0%	2-(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol
52829-07-9	>= 0.2 - <= 1.0%	bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

No applicable information available.

If on skin:

Wash thoroughly with soap and water. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
foam, water spray, dry powder, carbon dioxide

Safety Data Sheet

MasterSeal NP 150 stn

Revision date : 2016/04/18

Version: 4.0

Page: 4/10

(30605765/SDS_GEN_CA/EN)

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Advice for fire-fighters

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.
For large amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling

Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Keep away from sources of ignition - No smoking. The relevant fire protection measures should be noted.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: tinned carbon steel (Tinplate)

Further information on storage conditions: Keep only in the original container in a cool, well-ventilated place. Protect from direct sunlight. Store protected against freezing.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

stearic acid

ACGIH TLV TWA value 10 mg/m³ ;

Safety Data Sheet

MasterSeal NP 150 stn

Revision date : 2016/04/18

Version: 4.0

Page: 5/10

(30605765/SDS_GEN_CA/EN)

Calcium carbonate	OSHA PEL	PEL 5 mg/m ³ Respirable fraction ; PEL 15 mg/m ³ Total dust ; TWA value 15 mg/m ³ Total dust ; TWA value 5 mg/m ³ Respirable fraction ;
Limestone	OSHA PEL	PEL 5 mg/m ³ Respirable fraction ; PEL 15 mg/m ³ Total dust ; TWA value 15 mg/m ³ Total dust ; TWA value 5 mg/m ³ Respirable fraction ;
Titanium dioxide	OSHA PEL	PEL 15 mg/m ³ Total dust ; TWA value 10 mg/m ³ Total dust ;
	ACGIH TLV	TWA value 10 mg/m ³ ;
Tin, dibutylbis(2,4-pentanedionato-.kappa.O ₂ ,.kappa.O ₄)-, (OC-6-11)-	OSHA PEL	PEL 0.1 mg/m ³ (tin (Sn)); TWA value 0.1 mg/m ³ (tin (Sn)); SKIN_FINAL (tin (Sn)); The substance can be absorbed through the skin.
	ACGIH TLV	TWA value 0.1 mg/m ³ (tin (Sn)); STEL value 0.2 mg/m ³ (tin (Sn)); Skin Designation (tin (Sn)); The substance can be absorbed through the skin.

Advice on system design:

No applicable information available.

Personal protective equipment

Respiratory protection:

Wear appropriate certified respirator when exposure limits may be exceeded.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. No special measures necessary if stored and handled correctly. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	paste
Odour:	odourless
Odour threshold:	No applicable information available.
Colour:	pigmented

Safety Data Sheet

MasterSeal NP 150 stn

Revision date : 2016/04/18

Version: 4.0

Page: 6/10

(30605765/SDS_GEN_CA/EN)

pH value:	neutral to slightly alkaline
Melting temperature:	The product has not been tested.
Sublimation point:	No applicable information available.
Flash point:	Non-flammable.
Flammability:	not determined
Lower explosion limit:	No applicable information available.
Upper explosion limit:	No applicable information available.
Autoignition:	No data available.
Vapour pressure:	No applicable information available.
Density:	12.2 lb/USg (73 - 77 °C)
Relative density:	No applicable information available.
Bulk density:	1,800 - 2,400 kg/m ³
Vapour density:	Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):	No data available.
Self-ignition temperature:	not self-igniting
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	No applicable information available.
Solubility in water:	slightly soluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

Safety Data Sheet

MasterSeal NP 150 stn

Revision date : 2016/04/18

Version: 4.0

Page: 7/10
(30605765/SDS_GEN_CA/EN)

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Based on available Data, the classification criteria are not met.

Oral

No applicable information available.

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

No applicable information available.

Irritation / corrosion

Assessment of irritating effects: Irritating to eyes. The product has not been tested. The statement has been derived from the properties of the individual components.

Sensitization

Assessment of sensitization: Contains a known or suspected skin sensitizer.

Information on: 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-

Guinea pig maximization test

Species: guinea pig

Result: Caused skin sensitization in animal studies.

Method: Directive 84/449/EEC, B.6

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No reliable data was available concerning repeated dose toxicity. Based on available Data, the classification criteria are not met.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Information on: Titanium dioxide

Safety Data Sheet

MasterSeal NP 150 stn

Revision date : 2016/04/18

Version: 4.0

Page: 8/10

(30605765/SDS_GEN_CA/EN)

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Reproductive toxicity

Assessment of reproduction toxicity: Contains a reproductive toxin.

Information on: Tin, dibutylbis(2,4-pentanedionato-.kappa.O2,.kappa.O4)-, (OC-6-11)-

Assessment of reproduction toxicity: Causes impairment of fertility in laboratory animals. The results were determined in a Screening test (OECD 421/422). The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Inherently biodegradable. The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

The polymer component of the product is poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential

Discharge into the environment must be avoided.

Mobility in soil

Safety Data Sheet

MasterSeal NP 150 stn

Revision date : 2016/04/18

Version: 4.0

Page: 9/10

(30605765/SDS_GEN_CA/EN)

Assessment transport between environmental compartments
No data available.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater.

14. Transport Information

Land transport

TDG

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released / listed

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2016/04/18

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our

Safety Data Sheet

MasterSeal NP 150 stn

Revision date : 2016/04/18

Version: 4.0

Page: 10/10

(30605765/SDS_GEN_CA/EN)

operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET