

Safety Data Sheet

Copyright,2015,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	28-7829-6	Version Number:	4.00
Issue Date:	03/31/15	Supercedes Date:	05/02/11

SECTION 1: Identification

1.1. Product identifier

3MTM Wind Blade Bonding Adhesive W1101 Part A

Product Identification Numbers 41-9110-0401-2, 41-9110-0402-0, 70-0066-6833-2, 70-0066-6835-7

1.2. Recommended use and restrictions on use

Recommended use Adhesive

3M
Renewable Energy Division
3M Center, St. Paul, MN 55144-1000, USA
1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1. Skin Corrosion/Irritation: Category 1C. Skin Sensitizer: Category 1A. Specific Target Organ Toxicity (respiratory irritation): Category 3.

2.2. Label elements Signal word Danger

Symbols Corrosion | Exclamation mark |

Pictograms



Hazard Statements Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation.

Precautionary Statements

Prevention:

Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, and eye/face protection. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

1% of the mixture consists of ingredients of unknown acute oral toxicity.1% of the mixture consists of ingredients of unknown acute dermal toxicity.58% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Poly(oxypropylene)Diamine	9046-10-0	15 - 40 Trade Secret *
CALCIUM CARBONATE	471-34-1	10 - 30
Amine-Terminated Butadiene-Acrylonitrile Polymer	68683-29-4	5 - 15
Hydrophobic Fumed Silica	67762-90-7	7 - 13
Triethylenetetramine	112-24-3	1 - 5 Trade Secret *
Fused Silica	60676-86-0	1 - 5
Titanium Dioxide	13463-67-7	1 - 5 Trade Secret *
Filler Coating	Trade Secret*	< 1.5

tris(2,4,6-Dimethylaminomonomethyl)Phenol	90-72-2	1 - 5 Trade Secret *
N-AMINOETHYLPIPERAZINE	140-31-8	0.1 - 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Carbon monoxide Carbon dioxide Irritant Vapors or Gases Oxides of Nitrogen

Condition During Combustion

During Combustion During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition

source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. For industrial or professional use only. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

	CAC No.	A	T insid down o	Additional Commonts
Ingredient		Agency	Limit type	Additional Comments
Triethylenetetramine	112-24-3	AIHA	TWA:6 mg/m3(1 ppm)	Skin Notation
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human
				carcin
Titanium Dioxide	13463-67-7	CMRG	TWA(as respirable dust):5	
			mg/m3	
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
Limestone	471-34-1	OSHA	TWA(as total dust):15	
			mg/m3;TWA(respirable	
			fraction):5 mg/m3	
CALCIUM CARBONATE	471-34-1	CMRG	TWA:10 mg/m3;STEL:20	
			mg/m3	
SILICA, AMORPHOUS	60676-86-0	OSHA	TWA concentration:0.8	
			mg/m3;TWA:20 millions of	
			particles/cu. ft.	
Hydrophobic Fumed Silica	67762-90-7	CMRG	CEIL:5 mg/m3	
SILICA, AMORPHOUS	67762-90-7	OSHA	TWA concentration:0.8	
			mg/m3;TWA:20 millions of	
			particles/cu. ft.	
tris(2,4,6-	90-72-2	CMRG	TWA:5 ppm	
Dimethylaminomonomethyl)Phen				

ol			
ACGIH · American Conference of Governm	ental Industrial I	Avgienists	

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full Face Shield Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Paste
Odor, Color, Grade:	Off-white with amine odor
Odor threshold	No Data Available
рН	Not Applicable
Melting point	Not Applicable
Boiling Point	>=121 °C
Flash Point	>=250 °F [<i>Test Method:</i> Closed Cup]
Evaporation rate	Not Applicable
L'uporation rate	1.011.1pp1100.010

Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	No Data Available
Vapor Density	Not Applicable
Density	1.29 g/ml
Specific Gravity	1.29 [<i>Ref Std:</i> WATER=1]
Solubility in Water	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	>=1,000,000 centipoise [@ 73.4 °F]
Volatile Organic Compounds	Not Applicable
Percent volatile	<=1 %
VOC Less H2O & Exempt Solvents	Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous reactions Hazardous polymerization will not occur.

10.4. Conditions to avoid None known.

10.5. Incompatible materials

Strong acids Strong bases Strong oxidizing agents Amines

10.6. Hazardous decomposition products <u>Substance</u>

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

May be harmful in contact with skin.

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000
			mg/kg
Overall product	Inhalation-		No data available; calculated ATE > 12.5 mg/l
	Dust/Mist(4		
	hr)		
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Poly(oxypropylene)Diamine	Dermal	Rabbit	LD50 > 1,000 mg/kg
Poly(oxypropylene)Diamine	Ingestion	Rat	LD50 >= 475 mg/kg
CALCIUM CARBONATE	Dermal	Rat	LD50 > 2,000 mg/kg
CALCIUM CARBONATE	Inhalation-	Rat	LC50 3.0 mg/l
	Dust/Mist		
	(4 hours)		
CALCIUM CARBONATE	Ingestion	Rat	LD50 6,450 mg/kg
Amine-Terminated Butadiene-Acrylonitrile Polymer	Dermal	Rabbit	LD50 > 3,000 mg/kg
Amine-Terminated Butadiene-Acrylonitrile Polymer	Ingestion	Rat	LD50 > 15,300 mg/kg
Hydrophobic Fumed Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrophobic Fumed Silica	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
Hydrophobic Fumed Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Triethylenetetramine	Dermal	Rabbit	LD50 550 mg/kg
Triethylenetetramine	Ingestion	Rat	LD50 2,500 mg/kg
Fused Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Fused Silica	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		

Fused Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-	Rat	LC50 > 6.82 mg/l
	Dust/Mist		-
	(4 hours)		
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
tris(2,4,6-Dimethylaminomonomethyl)Phenol	Dermal	Rat	LD50 1,280 mg/kg
tris(2,4,6-Dimethylaminomonomethyl)Phenol	Ingestion	Rat	LD50 1,000 mg/kg
N-AMINOETHYLPIPERAZINE	Dermal	Rabbit	LD50 865 mg/kg
N-AMINOETHYLPIPERAZINE	Ingestion	Rat	LD50 1,470 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Poly(oxypropylene)Diamine	Rabbit	Corrosive
CALCIUM CARBONATE	Rabbit	No significant irritation
Hydrophobic Fumed Silica	Rabbit	No significant irritation
Triethylenetetramine	Rabbit	Corrosive
Fused Silica	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
tris(2,4,6-Dimethylaminomonomethyl)Phenol	Rabbit	Corrosive
N-AMINOETHYLPIPERAZINE	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Poly(oxypropylene)Diamine	Rabbit	Corrosive
CALCIUM CARBONATE	Rabbit	No significant irritation
Hydrophobic Fumed Silica	Rabbit	No significant irritation
Triethylenetetramine	Rabbit	Corrosive
Fused Silica	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
tris(2,4,6-Dimethylaminomonomethyl)Phenol	Rabbit	Corrosive
N-AMINOETHYLPIPERAZINE	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Poly(oxypropylene)Diamine	Guinea	Not sensitizing
	pig	
Amine-Terminated Butadiene-Acrylonitrile Polymer	Guinea	Some positive data exist, but the data are not
	pig	sufficient for classification
Hydrophobic Fumed Silica	Human	Not sensitizing
	and	
	animal	
Triethylenetetramine	Guinea	Sensitizing
	pig	
Fused Silica	Human	Not sensitizing
	and	
	animal	
Titanium Dioxide	Human	Not sensitizing
	and	
	animal	
tris(2,4,6-Dimethylaminomonomethyl)Phenol	Guinea	Some positive data exist, but the data are not
	pig	sufficient for classification
N-AMINOETHYLPIPERAZINE	Guinea	Sensitizing
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value

Poly(oxypropylene)Diamine	In Vitro	Not mutagenic
Poly(oxypropylene)Diamine	In vivo	Not mutagenic
Hydrophobic Fumed Silica	In Vitro	Not mutagenic
Fused Silica	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
tris(2,4,6-Dimethylaminomonomethyl)Phenol	In Vitro	Not mutagenic
N-AMINOETHYLPIPERAZINE	In vivo	Not mutagenic
N-AMINOETHYLPIPERAZINE	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Hydrophobic Fumed Silica	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification
Fused Silica	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification
Titanium Dioxide	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Poly(oxypropylene)Diamine	Dermal	Not toxic to female reproduction	Rat	NOAEL 30 mg/kg/day	premating & during gestation
Poly(oxypropylene)Diamine	Dermal	Not toxic to male reproduction	Rat	NOAEL 30 mg/kg/day	premating & during gestation
Poly(oxypropylene)Diamine	Dermal	Not toxic to development	Rat	NOAEL 30 mg/kg/day	premating & during gestation
CALCIUM CARBONATE	Ingestion	Not toxic to development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Hydrophobic Fumed Silica	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Hydrophobic Fumed Silica	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Hydrophobic Fumed Silica	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
Fused Silica	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fused Silica	Inhalation	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fused Silica	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
N-AMINOETHYLPIPERAZINE	Ingestion	Not toxic to female reproduction	Rat	NOAEL 598 mg/kg/day	premating & during gestation
N-AMINOETHYLPIPERAZINE	Ingestion	Not toxic to male reproduction	Rat	NOAEL 409 mg/kg/day	32 days
N-AMINOETHYLPIPERAZINE	Ingestion	Not toxic to development	Rat	NOAEL 899 mg/kg/day	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Poly(oxypropylene)Diamin e	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not available	
CALCIUM CARBONATE	Inhalation	respiratory system	All data are negative	Rat	NOAEL 0.812 mg/l	90 minutes
tris(2,4,6- Dimethylaminomonomethy l)Phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
N- AMINOETHYLPIPERAZI NE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
CALCIUM CARBONATE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Hydrophobic Fumed Silica	Inhalation	respiratory system silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
Fused Silica	Inhalation	respiratory system silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.010 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	All data are negative	Human	NOAEL Not available	occupational exposure
tris(2,4,6- Dimethylaminomonometh yl)Phenol	Dermal	skin liver nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 125 mg/kg/day	28 days
tris(2,4,6- Dimethylaminomonometh yl)Phenol	Dermal	auditory system hematopoietic system eyes	All data are negative	Rat	NOAEL 125 mg/kg/day	28 days
N- AMINOETHYLPIPERAZ INE	Ingestion	heart endocrine system hematopoietic system liver nervous system kidney and/or bladder	All data are negative	Rat	NOAEL 598 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Poly(oxypropylene)Diamine	Some positive data exist, but the data are not sufficient for
	classification

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <u>http://3M.com/Transportinfo</u> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	28-7829-6	Version Number:	4.00
Issue Date:	03/31/15	Supercedes Date:	05/02/11

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com