



## Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 30-3679-5  
**Issue Date:** 02/20/15

**Version Number:** 2.00  
**Supercedes Date:** 01/30/12

**Product identifier**  
3M™ Aerospace Sealant AC-251 Black B-1

**ID Number(s):**

70-0052-0176-2, 70-0052-0575-5

**Recommended use**  
Sealant

### Supplier's details

**MANUFACTURER:** 3M  
**DIVISION:** Aerospace and Commercial Transportation Division  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

**Emergency telephone number**  
1-800-364-3577 or (651) 737-6501 (24 hours)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:**

30-3448-5, 30-3197-8

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M™ Aerospace Sealant AC-251 Black B-1 02/20/15**

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**



## Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 30-3448-5  
**Issue Date:** 02/20/15

**Version Number:** 2.00  
**Supercedes Date:** 09/07/12

## SECTION 1: Identification

### 1.1. Product identifier

3M™ Aerospace Sealant AC-251 B-1/2, B-1, and B-2 Black Base

### Product Identification Numbers

LC-B100-1135-5, LC-B100-1135-6, LC-B100-1135-7, LC-B100-1135-8, LC-B100-1135-9, LC-B100-1136-0, LC-B100-1136-1, 42-0044-2103-0, 42-0044-2104-8, 42-0044-2105-5, 70-0052-1972-3

### 1.2. Recommended use and restrictions on use

#### Recommended use

For industrial or professional use only., Sealant

### 1.3. Supplier's details

**MANUFACTURER:** 3M  
**DIVISION:** Aerospace and Commercial Transportation Division  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## SECTION 2: Hazard identification

### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### 2.2. Label elements

#### Signal word

Not applicable.

#### Symbols

Not applicable.

#### Pictograms

Not applicable.

### Precautionary Statements

**Response:**

Call a POISON CENTER or doctor/physician if you feel unwell.

**2.3. Hazards not otherwise classified**

None.

## SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
POLYSULFIDE RUBBER	68611-50-7	55 - 65
CALCIUM CARBONATE	471-34-1	30 - 40
CARBON BLACK	1333-86-4	0.1 - 0.5 Trade Secret *
QUARTZ SILICA	14808-60-7	0 - 0.5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

No need for first aid is anticipated.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## SECTION 5: Fire-fighting measures

**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
CARBON BLACK	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m <sup>3</sup>	A3: Confirmed animal carcin.
CARBON BLACK	1333-86-4	CMRG	TWA:0.5 mg/m <sup>3</sup>	
CARBON BLACK	1333-86-4	OSHA	TWA:3.5 mg/m <sup>3</sup>	
QUARTZ SILICA	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m <sup>3</sup>	A2: Suspected human carcin.
QUARTZ SILICA	14808-60-7	OSHA	TWA concentration(as total dust):0.3 mg/m <sup>3</sup> ;TWA concentration(respirable):0.1 mg/m <sup>3</sup> (2.4 millions of particles/cu. ft.)	
CALCIUM CARBONATE	471-34-1	CMRG	TWA:10 mg/m <sup>3</sup> ;STEL:20 mg/m <sup>3</sup>	
Limestone	471-34-1	OSHA	TWA(as total dust):15	

			mg/m <sup>3</sup> ;TWA(respirable fraction):5 mg/m <sup>3</sup>	
--	--	--	---	--

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Paste
Odor, Color, Grade:	Sulphurpus odor; Black paste
Odor threshold	<i>No Data Available</i>
pH	<i>No Data Available</i>
Melting point	<i>Not Applicable</i>
Boiling Point	<i>Not Applicable</i>
Flash Point	>=200 °F [ <i>Test Method: Closed Cup</i> ]
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<i>No Data Available</i>

<b>Vapor Density</b>	<i>No Data Available</i>
<b>Specific Gravity</b>	1.61 [Ref Std: WATER=1]
<b>Solubility in Water</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	<i>No Data Available</i>
<b>Volatile Organic Compounds</b>	2.1 g/l
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	2.1 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Reducing agents

Strong acids

Strong bases

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose

and throat pain.

**Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

**Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Carcinogenicity:**

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTAL AIRRESP	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens
CARBON BLACK	1333-86-4	Grp. 2B: Possible human carcinogen	International Agency for Research on Cancer
QUARTZ SILICA	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
POLYSULFIDE RUBBER	Dermal	Rat	LD50 > 7,800 mg/kg
POLYSULFIDE RUBBER	Ingestion	Rat	LD50 > 5,000 mg/kg
CALCIUM CARBONATE	Dermal	Rat	LD50 > 2,000 mg/kg
CALCIUM CARBONATE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3.0 mg/l
CALCIUM CARBONATE	Ingestion	Rat	LD50 6,450 mg/kg
CARBON BLACK	Dermal	Rabbit	LD50 > 3,000 mg/kg
CARBON BLACK	Ingestion	Rat	LD50 > 8,000 mg/kg
QUARTZ SILICA	Dermal		LD50 estimated to be > 5,000 mg/kg
QUARTZ SILICA	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
POLYSULFIDE RUBBER	Rabbit	No significant irritation
CALCIUM CARBONATE	Rabbit	No significant irritation
CARBON BLACK	Rabbit	No significant irritation
QUARTZ SILICA	Professional judgement	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
POLYSULFIDE RUBBER	Rabbit	No significant irritation
CALCIUM CARBONATE	Rabbit	No significant irritation
CARBON BLACK	Rabbit	No significant irritation

**Skin Sensitization**

Name	Species	Value
POLYSULFIDE RUBBER		Not sensitizing

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### Germ Cell Mutagenicity

Name	Route	Value
CARBON BLACK	In Vitro	Not mutagenic
CARBON BLACK	In vivo	Some positive data exist, but the data are not sufficient for classification
QUARTZ SILICA	In Vitro	Some positive data exist, but the data are not sufficient for classification
QUARTZ SILICA	In vivo	Some positive data exist, but the data are not sufficient for classification

#### Carcinogenicity

Name	Route	Species	Value
CARBON BLACK	Dermal	Mouse	Not carcinogenic
CARBON BLACK	Ingestion	Mouse	Not carcinogenic
CARBON BLACK	Inhalation	Rat	Carcinogenic
QUARTZ SILICA	Inhalation	Human and animal	Carcinogenic

#### Reproductive Toxicity

##### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
CALCIUM CARBONATE	Ingestion	Not toxic to development	Rat	NOAEL 625 mg/kg/day	pre mating & during gestation

#### Target Organ(s)

##### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
CALCIUM CARBONATE	Inhalation	respiratory system	All data are negative	Rat	NOAEL 0.812 mg/l	90 minutes

##### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
CALCIUM CARBONATE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
CARBON BLACK	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
QUARTZ SILICA	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

#### Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

#### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## **SECTION 13: Disposal considerations**

### **13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

**EPA Hazardous Waste Number (RCRA):** Not regulated

## **SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: Regulatory information**

### **15.1. US Federal Regulations**

Contact 3M for more information.

#### **311/312 Hazard Categories:**

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

### **15.2. State Regulations**

Contact 3M for more information.

### **15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### **15.4. International Regulations**

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## **SECTION 16: Other information**

#### **NFPA Hazard Classification**

**Health: 2 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	30-3448-5	<b>Version Number:</b>	2.00
<b>Issue Date:</b>	02/20/15	<b>Supercedes Date:</b>	09/07/12

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**



## Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:**

30-3197-8

**Issue Date:**

02/20/15

**Version Number:**

3.00

**Supercedes Date:**

05/22/13

## SECTION 1: Identification

### 1.1. Product identifier

3M™ Aerospace Sealant AC-251 B-1 Black Catalyst

### Product Identification Numbers

LC-B100-1121-5, LC-B100-1121-6, LC-B100-1205-8, 42-0044-2026-3, 70-0052-1988-9

### 1.2. Recommended use and restrictions on use

#### Recommended use

Hardener, For industrial or professional use only.

### 1.3. Supplier's details

**MANUFACTURER:**

3M

**DIVISION:**

Aerospace and Commercial Transportation Division

**ADDRESS:**

3M Center, St. Paul, MN 55144-1000, USA

**Telephone:**

1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## SECTION 2: Hazard identification

### 2.1. Hazard classification

Reproductive Toxicity: Lactation.

Specific Target Organ Toxicity (repeated exposure): Category 1.

### 2.2. Label elements

#### Signal word

Danger

#### Symbols

Health Hazard |

#### Pictograms



### Hazard Statements

May cause harm to breast-fed children.

Causes damage to organs through prolonged or repeated exposure:

nervous system |

respiratory system |

### Precautionary Statements

#### Prevention:

Obtain special instructions before use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid contact during pregnancy/while nursing.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

#### Response:

IF exposed or concerned: Get medical advice/attention.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### 2.3. Hazards not otherwise classified

None.

8% of the mixture consists of ingredients of unknown acute oral toxicity.

8% of the mixture consists of ingredients of unknown acute dermal toxicity.

## SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
MANGANESE DIOXIDE	1313-13-9	30 - 50 Trade Secret *
HYDROGENATED TERPHENYL	61788-32-7	30 - 45 Trade Secret *
PARTIALLY HYDROGENATED POLYPHENYLS	68956-74-1	0 - 10
ALUMINUM OXIDE	1344-28-1	0 - 5
TERPHENYL	26140-60-3	1 - 5 Trade Secret *
WATER	7732-18-5	0.1 - 3
IRON OXIDE (FE2O3)	1309-37-1	0 - 3
QUARTZ SILICA	14808-60-7	0.1 - 3 Trade Secret *
CARBON BLACK	1333-86-4	1 - 3 Trade Secret *
FERBAM	14484-64-1	0.1 - 1 Trade Secret *
SODIUM HYDROXIDE	1310-73-2	0 - 1 Trade Secret *
LEAD	7439-92-1	<= 0.06 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

##### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

##### **Eye Contact:**

No need for first aid is anticipated.

##### **If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion
Oxides of Sulfur	During Combustion

#### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent

material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Avoid contact during pregnancy/while nursing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
IRON OXIDE (FE2O3)	1309-37-1	ACGIH	TWA(respirable fraction):5 mg/m <sup>3</sup>	A4: Not class. as human carcin
IRON OXIDE (FE2O3)	1309-37-1	OSHA	TWA(as fume):10 mg/m <sup>3</sup>	
ROUGE	1309-37-1	OSHA	TWA(as total dust):15 mg/m <sup>3</sup> ;TWA(respirable fraction):5 mg/m <sup>3</sup>	
SODIUM HYDROXIDE	1310-73-2	ACGIH	CEIL:2 mg/m <sup>3</sup>	
SODIUM HYDROXIDE	1310-73-2	CMRG	TWA:2 mg/m <sup>3</sup>	
SODIUM HYDROXIDE	1310-73-2	OSHA	TWA:2 mg/m <sup>3</sup>	
MANGANESE COMPOUNDS	1313-13-9	OSHA	CEIL(as Mn):5 mg/m <sup>3</sup>	
MANGANESE, INORGANIC COMPOUNDS	1313-13-9	ACGIH	TWA(as Mn, inhalable fraction):0.1 mg/m <sup>3</sup> ;TWA(as Mn, respirable fraction):0.02 mg/m <sup>3</sup>	A4: Not class. as human carcin
CARBON BLACK	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m <sup>3</sup>	A3: Confirmed animal carcin.
CARBON BLACK	1333-86-4	CMRG	TWA:0.5 mg/m <sup>3</sup>	
CARBON BLACK	1333-86-4	OSHA	TWA:3.5 mg/m <sup>3</sup>	
ALUMINUM OXIDE	1344-28-1	CMRG	TWA:1 fiber/cc	
ALUMINUM OXIDE	1344-28-1	OSHA	TWA(as total dust):15 mg/m <sup>3</sup> ;TWA(respirable fraction):5 mg/m <sup>3</sup>	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m <sup>3</sup>	A4: Not class. as human carcin
FERBAM	14484-64-1	ACGIH	TWA(inhalable fraction):5 mg/m <sup>3</sup>	A4: Not class. as human carcin
FERBAM	14484-64-1	OSHA	TWA(as total dust):15 mg/m <sup>3</sup>	
QUARTZ SILICA	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m <sup>3</sup>	A2: Suspected human carcin.
QUARTZ SILICA	14808-60-7	OSHA	TWA concentration(as total dust):0.3 mg/m <sup>3</sup> ;TWA	

			concentration(respirable):0.1 mg/m <sup>3</sup> (2.4 millions of particles/cu. ft.)	
TERPHENYL	26140-60-3	ACGIH	CEIL:5 mg/m <sup>3</sup>	
TERPHENYL	26140-60-3	OSHA	CEIL:9 mg/m <sup>3</sup> (1 ppm)	
HYDROGENATED TERPHENYL	61788-32-7	ACGIH	TWA:0.5 ppm	
LEAD	7439-92-1	ACGIH	TWA(as Pb):0.05 mg/m <sup>3</sup>	A3: Confirmed animal carcin.
LEAD	7439-92-1	OSHA	TWA:0.05 mg/m <sup>3</sup>	29 CFR 1910.1025

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

None required.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**General Physical Form:**

Liquid

**Odor, Color, Grade:**

Slight odor; Black, viscous liquid

**Odor threshold**

*No Data Available*

**pH**

*Not Applicable*

**Melting point**

*Not Applicable*

**Boiling Point**

*No Data Available*

**Flash Point**

>=200 °F [Test Method: Closed Cup]

<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Vapor Density</b>	$\geq 1$ [Ref Std: AIR=1]
<b>Specific Gravity</b>	1.59 [Ref Std: WATER=1]
<b>Solubility in Water</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	<i>No Data Available</i>
<b>Volatile Organic Compounds</b>	0.9 g/l [Test Method: calculated SCAQMD rule 443.1]
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	0.9 g/l [Test Method: calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Reducing agents

Strong acids

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

May be harmful in contact with skin.

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

**Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Prolonged or repeated exposure may cause target organ effects:**

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which may interfere with lactation or be harmful to breastfed children.

**Carcinogenicity:**

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTAL AIRRESP	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens
CARBON BLACK	1333-86-4	Grp. 2B: Possible human carcinogen	International Agency for Research on Cancer
LEAD	7439-92-1	Grp. 2B: Possible human carcinogen	International Agency for Research on Cancer
LEAD	7439-92-1	Anticipated human carcinogen	National Toxicology Program Carcinogens
QUARTZ SILICA	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
MANGANESE DIOXIDE	Dermal	Rat	LD50 2,000 mg/kg
MANGANESE DIOXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.5 mg/l
MANGANESE DIOXIDE	Ingestion	Rat	LD50 > 2,197 mg/kg
HYDROGENATED TERPHENYL	Dermal	Rabbit	LD50 6,800 mg/kg
HYDROGENATED TERPHENYL	Inhalation-	Rat	LC50 > 11.1 mg/l

	Dust/Mist (4 hours)		
HYDROGENATED TERPHENYL	Ingestion	Rat	LD50 > 10,000 mg/kg
TERPHENYL	Dermal	Rabbit	LD50 > 5,000 mg/kg
TERPHENYL	Inhalation-Dust/Mist (4 hours)	Rat	LD50 > 3.8 mg/l
TERPHENYL	Ingestion	Rat	LD50 2,304 mg/kg
ALUMINUM OXIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
ALUMINUM OXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
ALUMINUM OXIDE	Ingestion	Rat	LD50 > 5,000 mg/kg
QUARTZ SILICA	Dermal		LD50 estimated to be > 5,000 mg/kg
QUARTZ SILICA	Ingestion		LD50 estimated to be > 5,000 mg/kg
IRON OXIDE (FE2O3)	Dermal	Not available	LD50 3,100 mg/kg
IRON OXIDE (FE2O3)	Ingestion	Not available	LD50 3,700 mg/kg
CARBON BLACK	Dermal	Rabbit	LD50 > 3,000 mg/kg
CARBON BLACK	Ingestion	Rat	LD50 > 8,000 mg/kg
FERBAM	Dermal	Rabbit	LD50 > 4,000 mg/kg
FERBAM	Ingestion	Rat	LD50 1,130 mg/kg
LEAD	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
LEAD	Ingestion		LD50 estimated to be 50 - 300 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
HYDROGENATED TERPHENYL	Rabbit	No significant irritation
TERPHENYL	Rabbit	No significant irritation
ALUMINUM OXIDE	Rabbit	No significant irritation
IRON OXIDE (FE2O3)	Rabbit	No significant irritation
QUARTZ SILICA	Professional judgement	No significant irritation
CARBON BLACK	Rabbit	No significant irritation
SODIUM HYDROXIDE	Rabbit	Corrosive
FERBAM	Rabbit	No significant irritation
LEAD	similar compounds	No significant irritation

#### Serious Eye Damage/Irritation

Name	Species	Value
HYDROGENATED TERPHENYL	Rabbit	No significant irritation
TERPHENYL	Rabbit	No significant irritation
ALUMINUM OXIDE	Rabbit	No significant irritation
IRON OXIDE (FE2O3)	Rabbit	No significant irritation
CARBON BLACK	Rabbit	No significant irritation
SODIUM HYDROXIDE	Rabbit	Corrosive
FERBAM	Rabbit	Severe irritant
LEAD	similar compounds	Mild irritant

#### Skin Sensitization

Name	Species	Value
HYDROGENATED TERPHENYL	Human	Not sensitizing
IRON OXIDE (FE2O3)	Human	Some positive data exist, but the data are not sufficient for classification
SODIUM HYDROXIDE	Human	Not sensitizing

FERBAM	Guinea pig	Not sensitizing
--------	------------	-----------------

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
HYDROGENATED TERPHENYL	In vivo	Not mutagenic
TERPHENYL	In Vitro	Not mutagenic
TERPHENYL	In vivo	Not mutagenic
ALUMINUM OXIDE	In Vitro	Not mutagenic
IRON OXIDE (FE2O3)	In Vitro	Not mutagenic
QUARTZ SILICA	In Vitro	Some positive data exist, but the data are not sufficient for classification
QUARTZ SILICA	In vivo	Some positive data exist, but the data are not sufficient for classification
CARBON BLACK	In Vitro	Not mutagenic
CARBON BLACK	In vivo	Some positive data exist, but the data are not sufficient for classification
SODIUM HYDROXIDE	In Vitro	Not mutagenic
LEAD	In vivo	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
ALUMINUM OXIDE	Inhalation	Rat	Not carcinogenic
IRON OXIDE (FE2O3)	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
QUARTZ SILICA	Inhalation	Human and animal	Carcinogenic
CARBON BLACK	Dermal	Mouse	Not carcinogenic
CARBON BLACK	Ingestion	Mouse	Not carcinogenic
CARBON BLACK	Inhalation	Rat	Carcinogenic
FERBAM	Ingestion	Rat	Not carcinogenic
LEAD	Not Specified	official classification	Carcinogenic

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
HYDROGENATED TERPHENYL	Ingestion	Not toxic to female reproduction	Rat	NOAEL 81 mg/kg/day	2 generation
HYDROGENATED TERPHENYL	Ingestion	Not toxic to male reproduction	Rat	NOAEL 62 mg/kg/day	2 generation
HYDROGENATED TERPHENYL	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 500 mg/kg/day	2 generation
FERBAM	Ingestion	Not toxic to female reproduction	Rat	NOAEL 25 mg/kg/day	3 generation
FERBAM	Ingestion	Not toxic to male reproduction	Rat	NOAEL 25 mg/kg/day	3 generation
FERBAM	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 11 mg/kg/day	during organogenesis
LEAD	Not Specified	Toxic to female reproduction	Human	LOAEL 10 ug/dl blood	
LEAD	Not Specified	Toxic to male reproduction	Human	LOAEL 37 ug/dl blood	
LEAD	Not	Toxic to development	Human	NOAEL Not	

	Specified			available	
--	-----------	--	--	-----------	--

## Lactation

Name	Route	Species	Value
FERBAM	Ingestion	Rat	Causes effects on or via lactation

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SODIUM HYDROXIDE	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	
LEAD	Ingestion	nervous system	May cause damage to organs	Human	LOAEL 90 ug/dl blood	poisoning and/or abuse
LEAD	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	poisoning and/or abuse

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROGENATED TERPHENYL	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	90 days
HYDROGENATED TERPHENYL	Ingestion	endocrine system   blood   liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 144 mg/kg/day	14 weeks
ALUMINUM OXIDE	Inhalation	pneumoconiosis   pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
IRON OXIDE (FE2O3)	Inhalation	pulmonary fibrosis   pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
QUARTZ SILICA	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
CARBON BLACK	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
LEAD	Inhalation	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 60 ug/dl blood	occupational exposure
LEAD	Inhalation	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 50 ug/dl blood	occupational exposure
LEAD	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	occupational exposure
LEAD	Inhalation	heart   endocrine system   immune system   vascular system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
LEAD	Ingestion	bone, teeth, nails, and/or hair	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 20 ug/dl blood	3 months
LEAD	Ingestion	eyes	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL .5 mg/kg/day	20 days
LEAD	Ingestion	hematopoietic system   kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	environmental exposure
LEAD	Ingestion	nervous system	May cause damage to organs though prolonged or repeated	Human	LOAEL 11 ug/dl blood	environmental exposure

			exposure			
LEAD	Ingestion	auditory system   heart   endocrine system   vascular system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	environmental exposure

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

## **SECTION 12: Ecological information**

#### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## **SECTION 13: Disposal considerations**

#### **13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA): D008 (Lead)**

## **SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: Regulatory information**

#### **15.1. US Federal Regulations**

Contact 3M for more information.

#### **311/312 Hazard Categories:**

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
MANGANESE DIOXIDE (MANGANESE COMPOUNDS)	1313-13-9	30 - 50
ALUMINUM OXIDE	1344-28-1	0 - 5
ALUMINUM OXIDE (ALUMINUM OXIDE (FIBROUS FORMS ONLY))	1344-28-1	0 - 5

## 15.2. State Regulations

Contact 3M for more information.

### California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
LEAD	7439-92-1	Female reproductive toxin
LEAD	7439-92-1	Male reproductive toxin
LEAD	7439-92-1	Carcinogen
LEAD	7439-92-1	Developmental Toxin

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

WARNING: This product contains a chemical known to the State of California to cause cancer.

## 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 1 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Document Group:**  
**Issue Date:**

30-3197-8  
02/20/15

**Version Number:**  
**Supercedes Date:**

3.00  
05/22/13

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to

determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**