



## Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	29-3591-4	<b>Version Number:</b>	3.00
<b>Issue Date:</b>	12/30/15	<b>Supersedes Date:</b>	07/30/14

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Roll Coat Color 4980C Transparent Dark Red

#### Product Identification Numbers

42-0023-8405-7, 75-0301-8814-0

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Roll Coat

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Traffic Safety and Security Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Liquid: Category 3.  
Serious Eye Damage/Irritation: Category 2A.  
Skin Corrosion/Irritation: Category 2.  
Skin Sensitizer: Category 1A.  
Reproductive Toxicity: Category 2.  
Carcinogenicity: Category 1A.  
Specific Target Organ Toxicity (single exposure): Category 1.  
Specific Target Organ Toxicity (central nervous system): Category 3.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

## Symbols

Flame | Exclamation mark | Health Hazard |

## Pictograms



## Hazard Statements

Flammable liquid and vapor.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

May cause cancer.

Causes damage to organs:  
sensory organs |

Causes damage to organs through prolonged or repeated exposure:  
nervous system |

May cause damage to organs through prolonged or repeated exposure:  
sensory organs |

## Precautionary Statements

### Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.  
 Keep cool.  
 Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

May cause an allergic respiratory reaction in sensitive people.

37% of the mixture consists of ingredients of unknown acute oral toxicity.

37% of the mixture consists of ingredients of unknown acute dermal toxicity.

68% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>% by Wt</b>
Oligomer 17171	Trade Secret*	15 - 40
Heavy aromatic solvent naphtha (Petroleum)	64742-94-5	10 - 30 Trade Secret *
1-Methoxy-2-propyl acetate	108-65-6	7 - 13
Cyclohexanone	108-94-1	7 - 13 Trade Secret *
Light aromatic solvent naphtha (petroleum)	64742-95-6	5 - 13 Trade Secret *
Alkyl amine polymer (New Jersey Trade Secret Registry # 04499600-5252P)	Trade Secret*	7 - 13
1,2,4-Trimethylbenzene	95-63-6	1 - 5 Trade Secret *
Butyl alcohol	71-36-3	1 - 5 Trade Secret *
Diethylene glycol butyl ether	112-34-5	1 - 5 Trade Secret *
Xylene	1330-20-7	1 - 5 Trade Secret *
Organic pigment (NJ TSR # 04499600-5232P)	Trade Secret*	1 - 5
Organic pigment (NJ TSR # 04499600-5245P)	Trade Secret*	1 - 5
Vinyl polymer (New Jersey Trade Secret Registry # 04499600-5238P)	Trade Secret*	1 - 5
Diethylaminoethanol	100-37-8	0.1 - 1.0 Trade Secret *
2,3-Epoxypropyl neodecanoate	26761-45-5	< 0.5 Trade Secret *
Ethylbenzene	100-41-4	< 0.4 Trade Secret *
Naphthenic Acid	1338-24-5	< 0.4 Trade Secret *
Nickel salts of naphthenic acids	61788-71-4	< 0.4 Trade Secret *
Naphthalene	91-20-3	< 0.3 Trade Secret *
Formaldehyde	50-00-0	< 0.2 Trade Secret *
Methyl alcohol	67-56-1	< 0.2 Trade Secret *
Benzene	71-43-2	< 0.03 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

#### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Oxides of Nitrogen	During Combustion

#### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Diethylaminoethanol	100-37-8	ACGIH	TWA:2 ppm	Skin Notation
Diethylaminoethanol	100-37-8	OSHA	TWA:50 mg/m3(10 ppm)	Skin Notation
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
Ethylbenzene	100-41-4	OSHA	TWA:435 mg/m3(100 ppm)	
Ethylbenzene	100-41-4	CMRG	TWA:25 ppm;STEL:75 ppm	
1-Methoxy-2-propyl acetate	108-65-6	AIHA	TWA:50 ppm	
1-Methoxy-2-propyl acetate	108-65-6	CMRG	TWA:10 mg/m3;STEL:90 ppm	
Cyclohexanone	108-94-1	ACGIH	TWA:20 ppm;STEL:50 ppm	A3: Confirmed animal carcin., Skin Notation
Cyclohexanone	108-94-1	OSHA	TWA:200 mg/m3(50 ppm)	
Diethylene glycol butyl ether	112-34-5	CMRG	TWA:35 ppm	
Diethylene glycol butyl ether	112-34-5	ACGIH	TWA(inhalable fraction and vapor):10 ppm	
Xylene	1330-20-7	ACGIH	TWA:100 ppm;STEL:150 ppm	A4: Not class. as human carcin
Xylene	1330-20-7	CMRG	TWA:50 ppm;STEL:75 ppm	

Xylene	1330-20-7	OSHA	TWA:435 mg/m3(100 ppm)	
Formaldehyde	50-00-0	CMRG	TWA:0.5 ppm	
Formaldehyde	50-00-0	ACGIH	CEIL:0.3 ppm	A2: Suspected human carcin., Dermal/Respiratory Sensitizer
Formaldehyde	50-00-0	OSHA	TWA:0.75 ppm;STEL:2 ppm	29 CFR 1910.1048
NICKEL, SOLUBLE COMPOUNDS	61788-71-4	OSHA	TWA(as Ni):1 mg/m3	
Heavy aromatic solvent naphtha (Petroleum)	64742-94-5	CMRG	TWA:17 ppm(100 mg/m3)	
Kerosine (petroleum)	64742-94-5	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., Skin Notation
Naphtha	64742-94-5	OSHA	TWA:400 mg/m3(100 ppm)	
Light aromatic solvent naphtha (petroleum)	64742-95-6	CMRG	TWA:50 ppm(245 mg/m3)	
Methyl alcohol	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	Skin Notation
Methyl alcohol	67-56-1	OSHA	TWA:260 mg/m3(200 ppm)	
Butyl alcohol	71-36-3	OSHA	TWA:300 mg/m3(100 ppm)	
Butyl alcohol	71-36-3	ACGIH	TWA:20 ppm	
Benzene	71-43-2	OSHA	TWA:1 ppm;TWA:10 ppm;STEL:5 ppm;CEIL:25 ppm	29 CFR 1910.1028
Benzene	71-43-2	ACGIH	TWA:0.5 ppm;STEL:2.5 ppm	Skin Notation, A1: Confirmed human carcin.
Naphthalene	91-20-3	OSHA	TWA:50 mg/m3(10 ppm)	
Naphthalene	91-20-3	ACGIH	TWA:10 ppm	A3: Confirmed animal carcin., Skin Notation
Benzene, trimethyl-	95-63-6	ACGIH	TWA:25 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the

results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for formaldehyde

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Liquid
<b>Odor, Color, Grade:</b>	Solvent odor, red, liquid
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	>=243 °F
<b>Flash Point</b>	105 °F [ <i>Test Method:</i> Tagliabue Closed Cup]
<b>Evaporation rate</b>	0.23 - 1 [ <i>Ref Std:</i> BUOAC=1]
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	0.9 %
<b>Flammable Limits(UEL)</b>	11.7 %
<b>Vapor Pressure</b>	<=5.1 mmHg [@ 68 °F]
<b>Vapor Density</b>	2.6 - 4.8 [ <i>Ref Std:</i> AIR=1]
<b>Density</b>	0.87 - 0.9 g/ml [@ 20 °C]
<b>Specific Gravity</b>	0.87 - 0.9 [ <i>Ref Std:</i> WATER=1]
<b>Solubility in Water</b>	Negligible
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	670 - 870 °F
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	2,000 - 3,000 centipoise
<b>Volatile Organic Compounds</b>	600 - 700 g/l
<b>Percent volatile</b>	60.00 % weight

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Sparks and/or flames

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction in sensitive people: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

#### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

#### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:**

**Single exposure may cause target organ effects:**

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Prolonged or repeated exposure may cause target organ effects:**

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
NICKEL COMPOUNDS	61788-71-4	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Benzene	71-43-2	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Formaldehyde	50-00-0	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Naphthalene	91-20-3	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
NI CMPDS NOT ALLOYS	61788-71-4	Known human carcinogen	National Toxicology Program Carcinogens
Benzene	71-43-2	Known human carcinogen	National Toxicology Program Carcinogens
Formaldehyde	50-00-0	Known human carcinogen	National Toxicology Program Carcinogens
Naphthalene	91-20-3	Anticipated human carcinogen	National Toxicology Program Carcinogens
Benzene	71-43-2	Cancer hazard	OSHA Carcinogens
Formaldehyde	50-00-0	Cancer hazard	OSHA Carcinogens

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE 20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Heavy aromatic solvent naphtha (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
Heavy aromatic solvent naphtha (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
1-Methoxy-2-propyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
1-Methoxy-2-propyl acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 28.8 mg/l
1-Methoxy-2-propyl acetate	Ingestion	Rat	LD50 8,532 mg/kg
Light aromatic solvent naphtha (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
Light aromatic solvent naphtha (petroleum)	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
Light aromatic solvent naphtha (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Cyclohexanone	Dermal	Rabbit	LD50 >794, <3160 mg/kg
Cyclohexanone	Inhalation-Vapor (4	Rat	LC50 > 6.2 mg/l

	hours)		
Cyclohexanone	Ingestion	Rat	LD50 1,296 mg/kg
Vinyl polymer (New Jersey Trade Secret Registry # 04499600-5238P)	Dermal	Rabbit	LD50 > 8,000 mg/kg
Vinyl polymer (New Jersey Trade Secret Registry # 04499600-5238P)	Ingestion	Rat	LD50 > 8,000 mg/kg
Organic pigment (NJ TSR # 04499600-5232P)	Dermal		LD50 estimated to be > 5,000 mg/kg
Organic pigment (NJ TSR # 04499600-5232P)	Inhalation-Dust/Mist		LC50 estimated to be > 12.5 mg/l
Organic pigment (NJ TSR # 04499600-5232P)	Ingestion		LD50 estimated to be > 5,000 mg/kg
Diethylene glycol butyl ether	Dermal	Rabbit	LD50 2,764 mg/kg
Diethylene glycol butyl ether	Ingestion	Rat	LD50 7,292 mg/kg
Butyl alcohol	Dermal	Rabbit	LD50 3,402 mg/kg
Butyl alcohol	Inhalation-Vapor (4 hours)	Rat	LC50 24 mg/l
Butyl alcohol	Ingestion	Rat	LD50 2,290 mg/kg
Organic pigment (NJ TSR # 04499600-5245P)	Dermal		LD50 estimated to be > 5,000 mg/kg
Organic pigment (NJ TSR # 04499600-5245P)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
1,2,4-Trimethylbenzene	Dermal	Rabbit	LD50 > 3,160 mg/kg
1,2,4-Trimethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 18 mg/l
1,2,4-Trimethylbenzene	Ingestion	Rat	LD50 3,400 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-Vapor (4 hours)	Rat	LC50 29 mg/l
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Diethylaminoethanol	Dermal	Rabbit	LD50 880 mg/kg
Diethylaminoethanol	Inhalation-Vapor (4 hours)	Rat	LC50 4.5 mg/l
Diethylaminoethanol	Ingestion	Rat	LD50 1,300 mg/kg
2,3-Epoxypropyl neodecanoate	Dermal	Rat	LD50 > 2,000 mg/kg
2,3-Epoxypropyl neodecanoate	Ingestion	Rat	LD50 > 2,000 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Nickel salts of naphthenic acids	Ingestion		LD50 estimated to be 50 - 300 mg/kg
Naphthalene	Dermal	Human	LD50 estimated to be 2,000 - 5,000 mg/kg
Naphthalene	Inhalation-Vapor	Human	LC50 estimated to be 20 - 50 mg/l
Naphthalene	Ingestion	Human	LD50 estimated to be 300 - 2,000 mg/kg
Methyl alcohol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
Methyl alcohol	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
Methyl alcohol	Ingestion		LD50 estimated to be 50 - 300 mg/kg
Formaldehyde	Dermal	Rabbit	LD50 270 mg/kg
Formaldehyde	Inhalation-Gas (4 hours)	Rat	LC50 470 ppm
Formaldehyde	Ingestion	Rat	LD50 800 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Heavy aromatic solvent naphtha (Petroleum)	Rabbit	Irritant
1-Methoxy-2-propyl acetate	Rabbit	No significant irritation
Light aromatic solvent naphtha (petroleum)	Rabbit	Irritant
Cyclohexanone	Rabbit	Irritant

Vinyl polymer (New Jersey Trade Secret Registry # 04499600-5238P)	Professional judgement	No significant irritation
Organic pigment (NJ TSR # 04499600-5232P)	Professional judgement	No significant irritation
Diethylene glycol butyl ether	Rabbit	Minimal irritation
Butyl alcohol	Rabbit	Mild irritant
1,2,4-Trimethylbenzene	Rabbit	Irritant
Xylene	Rabbit	Mild irritant
Diethylaminoethanol	Rabbit	Corrosive
2,3-Epoxypropyl neodecanoate	Rabbit	No significant irritation
Ethylbenzene	Rabbit	Mild irritant
Nickel salts of naphthenic acids	Professional judgement	Minimal irritation
Naphthalene	Rabbit	Minimal irritation
Methyl alcohol	Rabbit	Mild irritant
Formaldehyde	official classification	Corrosive

**Serious Eye Damage/Irritation**

Name	Species	Value
Heavy aromatic solvent naphtha (Petroleum)	Rabbit	Mild irritant
1-Methoxy-2-propyl acetate	Rabbit	Mild irritant
Light aromatic solvent naphtha (petroleum)	Rabbit	Mild irritant
Cyclohexanone	Rabbit	Severe irritant
Vinyl polymer (New Jersey Trade Secret Registry # 04499600-5238P)	Professional judgement	No significant irritation
Organic pigment (NJ TSR # 04499600-5232P)	Professional judgement	No significant irritation
Diethylene glycol butyl ether	Rabbit	Corrosive
Butyl alcohol	Rabbit	Severe irritant
1,2,4-Trimethylbenzene	Rabbit	Mild irritant
Xylene	Rabbit	Mild irritant
Diethylaminoethanol	Rabbit	Corrosive
2,3-Epoxypropyl neodecanoate	Rabbit	No significant irritation
Ethylbenzene	Rabbit	Moderate irritant
Nickel salts of naphthenic acids	Professional judgement	Mild irritant
Naphthalene	Rabbit	No significant irritation
Methyl alcohol	Rabbit	Moderate irritant
Formaldehyde	official classification	Corrosive

**Skin Sensitization**

Name	Species	Value
Heavy aromatic solvent naphtha (Petroleum)	Guinea pig	Not sensitizing
1-Methoxy-2-propyl acetate	Guinea pig	Not sensitizing
Light aromatic solvent naphtha (petroleum)	Guinea pig	Not sensitizing
Cyclohexanone	Guinea	Not sensitizing

	pig	
Butyl alcohol	Human	Not sensitizing
1,2,4-Trimethylbenzene	Guinea pig	Not sensitizing
Diethylaminoethanol	Guinea pig	Not sensitizing
2,3-Epoxypropyl neodecanoate	Guinea pig	Sensitizing
Ethylbenzene	Human	Not sensitizing
Nickel salts of naphthenic acids	similar compounds	Sensitizing
Methyl alcohol	Guinea pig	Not sensitizing
Formaldehyde	Guinea pig	Sensitizing

### Respiratory Sensitization

Name	Species	Value
Formaldehyde	Human	Some positive data exist, but the data are not sufficient for classification

### Germ Cell Mutagenicity

Name	Route	Value
1-Methoxy-2-propyl acetate	In Vitro	Not mutagenic
Cyclohexanone	In vivo	Not mutagenic
Cyclohexanone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Butyl alcohol	In vivo	Not mutagenic
Butyl alcohol	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,2,4-Trimethylbenzene	In Vitro	Not mutagenic
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Diethylaminoethanol	In Vitro	Not mutagenic
Diethylaminoethanol	In vivo	Not mutagenic
2,3-Epoxypropyl neodecanoate	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,3-Epoxypropyl neodecanoate	In vivo	Mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl alcohol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl alcohol	In vivo	Some positive data exist, but the data are not sufficient for classification
Formaldehyde	In Vitro	Some positive data exist, but the data are not sufficient for classification
Formaldehyde	In vivo	Mutagenic

### Carcinogenicity

Name	Route	Species	Value
Heavy aromatic solvent naphtha (Petroleum)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Light aromatic solvent naphtha (petroleum)	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Cyclohexanone	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic

Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic
Nickel salts of naphthenic acids	Not Specified	similar compounds	Carcinogenic
Naphthalene	Inhalation	Multiple animal species	Carcinogenic
Methyl alcohol	Inhalation	Multiple animal species	Not carcinogenic
Formaldehyde	Not Specified	Human and animal	Carcinogenic

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
1-Methoxy-2-propyl acetate	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
1-Methoxy-2-propyl acetate	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
1-Methoxy-2-propyl acetate	Ingestion	Not toxic to development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
1-Methoxy-2-propyl acetate	Inhalation	Not toxic to development	Rat	NOAEL 21.6 mg/l	during organogenesis
Light aromatic solvent naphtha (petroleum)	Inhalation	Not toxic to female reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not toxic to male reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 500 ppm	2 generation
Cyclohexanone	Inhalation	Not toxic to female reproduction	Rat	NOAEL 4 mg/l	2 generation
Cyclohexanone	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 2 mg/l	2 generation
Cyclohexanone	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	LOAEL 1,100 mg/kg/day	during organogenesis
Cyclohexanone	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 2 mg/l	2 generation
Butyl alcohol	Ingestion	Not toxic to female reproduction	Rat	NOAEL 5,000 mg/kg/day	prematuring & during gestation
Butyl alcohol	Inhalation	Not toxic to male reproduction	Rat	NOAEL 18 mg/l	6 weeks
Butyl alcohol	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 10.6 mg/l	during gestation
1,2,4-Trimethylbenzene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months

1,2,4-Trimethylbenzene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 1.5 mg/l	during gestation
Xylene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	during organogenesis
Xylene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	during gestation
Diethylaminoethanol	Inhalation	Not toxic to development	Rat	NOAEL 0.49 mg/l	during organogenesis
Diethylaminoethanol	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	LOAEL 11 mg/kg/day	2 years
Diethylaminoethanol	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	during gestation
Ethylbenzene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 4.3 mg/l	prematuring & during gestation
Methyl alcohol	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,600 mg/kg/day	21 days
Methyl alcohol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesis
Methyl alcohol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesis
Formaldehyde	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg	not applicable
Formaldehyde	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 10 ppm	during gestation

**Lactation**

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Does not cause effects on or via lactation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Heavy aromatic solvent naphtha (Petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Heavy aromatic solvent naphtha (Petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL Not available	
Heavy aromatic solvent naphtha (Petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
1-Methoxy-2-propyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional	NOAEL Not available	

				judgement		
Light aromatic solvent naphtha (petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Cyclohexanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Guinea pig	LOAEL 16.1 mg/l	6 hours
Cyclohexanone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Cyclohexanone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Butyl alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Butyl alcohol	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Butyl alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
1,2,4-Trimethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
1,2,4-Trimethylbenzene	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
1,2,4-Trimethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg	not applicable
Diethylaminoethanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Diethylaminoethanol	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	NOAEL 0.05 mg/l	14 weeks
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Naphthalene	Ingestion	blood	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Methyl alcohol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
Methyl alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Methyl alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
Methyl alcohol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Methyl alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Formaldehyde	Inhalation	respiratory system	Causes damage to organs	Rat	LOAEL 128 ppm	6 hours
Formaldehyde	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
1-Methoxy-2-propyl acetate	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 16.2 mg/l	9 days
1-Methoxy-2-propyl acetate	Inhalation	olfactory system	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 1.62 mg/l	9 days
1-Methoxy-2-propyl acetate	Inhalation	blood	All data are negative	Multiple animal species	NOAEL 16.2 mg/l	9 days
1-Methoxy-2-propyl acetate	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	44 days
Cyclohexanone	Inhalation	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 0.76 mg/l	50 days
Cyclohexanone	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 4,800 mg/kg/day	90 days
Butyl alcohol	Inhalation	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.3 mg/l	3 months
Butyl alcohol	Inhalation	auditory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Butyl alcohol	Inhalation	liver   kidney and/or bladder   respiratory system	Some positive data exist, but the data are not sufficient for classification	Guinea pig	NOAEL Not available	3 months
Butyl alcohol	Inhalation	nervous system	All data are negative	Rat	NOAEL 9.09 mg/l	13 weeks
Butyl alcohol	Ingestion	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 500 mg/kg/day	13 weeks
1,2,4-Trimethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.1 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
1,2,4-Trimethylbenzene	Inhalation	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	heart   endocrine	All data are negative	Rat	NOAEL 1.2	3 months

		system   immune system			mg/l	
1,2,4-Trimethylbenzene	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	14 days
1,2,4-Trimethylbenzene	Ingestion	liver   immune system   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	28 days
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart   endocrine system   hematopoietic system   muscles   kidney and/or bladder   respiratory system	All data are negative	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	All data are negative	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Diethylaminoethanol	Inhalation	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.36 mg/l	14 weeks
Diethylaminoethanol	Inhalation	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	All data are negative	Rat	NOAEL 0.36 mg/l	14 weeks
Diethylaminoethanol	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 20 mg/kg/day	1 years
Diethylaminoethanol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 400 mg/kg/day	6 months
Diethylaminoethanol	Ingestion	heart   endocrine system   hematopoietic system   liver   respiratory system	All data are negative	Rat	NOAEL 400 mg/kg/day	2 years
Diethylaminoethanol	Ocular	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.36 mg/l	14 weeks
2,3-Epoxypropyl neodecanoate	Ingestion	hematopoietic system   liver	Some positive data exist, but the data are not sufficient for	Rat	NOAEL 400 mg/kg/day	5 weeks

			classification			
2,3-Epoxypropyl neodecanoate	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 40 mg/kg/day	5 weeks
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair   muscles	All data are negative	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart   immune system   respiratory system	All data are negative	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 680 mg/kg/day	6 months
Naphthalene	Dermal	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Dermal	eyes	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Naphthalene	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.01 mg/l	13 weeks
Naphthalene	Inhalation	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Inhalation	eyes	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Naphthalene	Ingestion	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Ingestion	eyes	May cause damage to organs though prolonged or repeated exposure	Rabbit	LOAEL 500 mg/kg/day	15 days
Methyl alcohol	Inhalation	liver	All data are negative	Rat	NOAEL 6.55 mg/l	4 weeks
Methyl alcohol	Inhalation	respiratory system	All data are negative	Rat	NOAEL 13.1 mg/l	6 weeks
Methyl alcohol	Ingestion	liver   nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	90 days
Formaldehyde	Dermal	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 80 mg/kg/day	60 weeks
Formaldehyde	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.3 ppm	28 months
Formaldehyde	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 20 ppm	13 weeks
Formaldehyde	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 15 ppm	3 weeks
Formaldehyde	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 10 ppm	13 weeks
Formaldehyde	Inhalation	endocrine system   immune system	All data are negative	Rat	NOAEL 15 ppm	28 months

		muscles   kidney and/or bladder				
Formaldehyde	Inhalation	eyes   vascular system	All data are negative	Rat	NOAEL 14.3 ppm	2 years
Formaldehyde	Inhalation	heart	All data are negative	Mouse	NOAEL 14.3 ppm	2 years
Formaldehyde	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	2 years
Formaldehyde	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 20 mg/kg/day	4 weeks
Formaldehyde	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 15 mg/kg/day	24 months
Formaldehyde	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 109 mg/kg/day	2 years
Formaldehyde	Ingestion	heart   endocrine system   hematopoietic system   respiratory system   vascular system	All data are negative	Rat	NOAEL 300 mg/kg/day	2 years
Formaldehyde	Ingestion	skin   muscles   eyes	All data are negative	Rat	NOAEL 109 mg/kg/day	2 years

### Aspiration Hazard

Name	Value
Heavy aromatic solvent naphtha (Petroleum)	Aspiration hazard
Light aromatic solvent naphtha (petroleum)	Aspiration hazard
Butyl alcohol	Some positive data exist, but the data are not sufficient for classification
1,2,4-Trimethylbenzene	Aspiration hazard
Xylene	Aspiration hazard
Ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective

regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D018 (Benzene)

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

#### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Diethylene glycol butyl ether (GLYCOL ETHERS)	112-34-5	1 - 5
Butyl alcohol	71-36-3	Trade Secret 1 - 5
1,2,4-Trimethylbenzene	95-63-6	Trade Secret 1 - 5
Xylene	1330-20-7	Trade Secret 1 - 5
Nickel salts of naphthenic acids (NICKEL COMPOUNDS)	61788-71-4	< 0.4
Ethylbenzene	100-41-4	Trade Secret < 0.4
Naphthalene	91-20-3	Trade Secret < 0.3
Formaldehyde	50-00-0	Trade Secret < 0.2

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

Health: 2 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include

the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	29-3591-4	<b>Version Number:</b>	3.00
<b>Issue Date:</b>	12/30/15	<b>Supersedes Date:</b>	07/30/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**