

Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 29-8286-6
 Version Number:
 3.01

 Issue Date:
 01/18/18
 Supercedes Date:
 02/25/16

SECTION 1: Identification

1.1. Product identifier

3MTM ESPETM ScotchbondTM Universal Etchant

Product Identification Numbers

ID Number UPC ID Number UPC
LE-F100-1014-5 LE-F100-1040-4
70-2011-3906-3 70-2011-4006-1
70-2011-4007-9

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Etching gel

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Corrosive to metal: Category 1.

Serious Eye Damage/Irritation: Category 1. Skin Corrosion/Irritation: Category 1.

- 1 · · ·

2.2. Label elements

Signal word

Danger

Symbols

Corrosion |

Pictograms



Hazard Statements

May be corrosive to metals.

Causes severe skin burns and eye damage.

Precautionary Statements

Prevention:

Keep only in original container.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves, protective clothing, and eye/face protection.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Absorb spillage to prevent material damage.

Storage:

Store in a corrosive resistant container with a resistant inner liner.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
WATER	7732-18-5	50 - 65 Trade Secret *
PHOSPHORIC ACID	7664-38-2	30 - 40 Trade Secret *
SYNTHETIC AMORPHOUS SILICA, FUMED,	112945-52-5	5 - 10 Trade Secret *
CRYSTALLINE FREE		
POLYETHYLENE GLYCOL	25322-68-3	1 - 5 Trade Secret *

Page 2 of 10

ATTE OF THE COURSE	1244 20 1	. A. T. 1 C
ALUMINUM OXIDE		
IALOWINOW CAUSE	11344-20-1	1< 2 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eve Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance
Carbon monoxide
Carbon dioxide

Condition

During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Page 3 **of** 10

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ALUMINUM OXIDE	1344-28-1	OSHA	TWA(as total dust):15	
			mg/m3;TWA(respirable	
			fraction):5 mg/m3	
POLYETHYLENE GLYCOL	25322-68-3	AIHA	TWA(as particulate):10	
			mg/m3	
PHOSPHORIC ACID	7664-38-2	ACGIH	TWA:1 mg/m3;STEL:3	
			mg/m3	
PHOSPHORIC ACID	7664-38-2	OSHA	TWA:1 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

n 1 e 10

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:Specific Physical Form:
Gel

Odor, Color, Grade: Slight characteristic odor, Blue

Odor threshold No Data Available

pH < 1

Melting pointNot ApplicableBoiling PointNo Data Available

Flash Point > 100 °C [Test Method:Closed Cup]

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapor PressureNo Data AvailableVapor DensityNo Data AvailableDensity1.1 g/ml - 1.2 g/ml

Specific Gravity 1.1 - 1.2 [Ref Std:WATER=1]

Solubility in Water Complete

Solubility- non-water No Data Available Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available Viscosity No Data Available Molecular weight No Data Available **Volatile Organic Compounds** No Data Available Percent volatile No Data Available **VOC Less H2O & Exempt Solvents** No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong bases

Page 5 of 10

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eve Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Route	Species	Value
Dermal		No data available; calculated ATE >5,000 mg/kg
Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Dermal	Rabbit	LD50 2,740 mg/kg
Ingestion	Rat	LD50 1,530 mg/kg
Dermal	Rabbit	LD50 > 5,000 mg/kg
	Dermal Ingestion Dermal Ingestion	Dermal Ingestion Dermal Rabbit Ingestion Rat

Page 6 **of** 10

3M TM ESPE TM Scotchbond TM Universal Etchant 0	01/18/18
--	----------

SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Rat	LD50 > 5,110 mg/kg
POLYETHYLENE GLYCOL	Dermal	Rabbit	LD50 > 20,000 mg/kg
POLYETHYLENE GLYCOL	Ingestion	Rat	LD50 32,770 mg/kg
ALUMINUM OXIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
ALUMINUM OXIDE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
ALUMINUM OXIDE	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
PHOSPHORIC ACID	Rabbit	Corrosive
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Rabbit	No significant irritation
POLYETHYLENE GLYCOL	Rabbit	Minimal irritation
ALUMINUM OXIDE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
PHOSPHORIC ACID	official	Corrosive
	classifica	
	tion	
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Rabbit	No significant irritation
POLYETHYLENE GLYCOL	Rabbit	Mild irritant
ALUMINUM OXIDE	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
PHOSPHORIC ACID	Human	Not classified
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Human	Not classified
	and	
	animal	
POLYETHYLENE GLYCOL	Guinea	Not classified
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
PHOSPHORIC ACID	In Vitro	Not mutagenic
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	In Vitro	Not mutagenic
POLYETHYLENE GLYCOL	In Vitro	Not mutagenic
POLYETHYLENE GLYCOL	In vivo	Not mutagenic
ALUMINUM OXIDE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE	Not	Mouse	Some positive data exist, but the data are not
FREE	Specified		sufficient for classification
POLYETHYLENE GLYCOL	Ingestion	Rat	Not carcinogenic
ALUMINUM OXIDE	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity

Page 7 **of** 10

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
PHOSPHORIC ACID	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
PHOSPHORIC ACID	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
PHOSPHORIC ACID	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
POLYETHYLENE GLYCOL	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,125 mg/kg/day	during gestation
POLYETHYLENE GLYCOL	Ingestion	Not classified for male reproduction	Rat	NOAEL 5699 +/- 1341 mg/kg/day	5 days
POLYETHYLENE GLYCOL	Not Specified	Not classified for reproduction and/or development		NOEL N/A	
POLYETHYLENE GLYCOL	Ingestion	Not classified for development	Mouse	NOAEL 562 mg/animal/da y	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
PHOSPHORIC ACID	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
POLYETHYLENE GLYCOL	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
POLYETHYLENE GLYCOL	Inhalation	respiratory system	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks
POLYETHYLENE GLYCOL	Ingestion	kidney and/or bladder heart endocrine system hematopoietic system liver nervous system	Not classified	Rat	NOAEL 5,640 mg/kg/day	13 weeks
ALUMINUM OXIDE	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
ALUMINUM OXIDE	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

Page 8 of 10

01/18/18

on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA): D002 (Corrosive)

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Corrosive to metal

Health Hazards

Hazard Not Otherwise Classified (HNOC)

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

% by Wt

Ingredient C.A.S. No

ALUMINUM OXIDE 1344-28-1 Trade Secret < 2

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

<u>Ingredient</u> <u>C.A.S. No.</u> <u>Listing</u>

Page 9 **of** 10

ETHYLENE OXIDE	75-21-8	Female reproductive toxin
ETHYLENE OXIDE	75-21-8	Male reproductive toxin
ETHYLENE OXIDE	75-21-8	Carcinogen
ETHYLENE OXIDE	75-21-8	Developmental Toxin

15.3. Chemical Inventories

3MTM ESPETM ScotchbondTM Universal Etchant

The components of this product are in compliance with the new substance notification requirements of CEPA.

01/18/18

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

Corrosive: Yes

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 29-8286-6
 Version Number:
 3.01

 Issue Date:
 01/18/18
 Supercedes Date:
 02/25/16

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com

Page 10 of 10