



## Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 33-2643-6 | <b>Version Number:</b>  | 1.01     |
| <b>Issue Date:</b>     | 08/13/14  | <b>Supersedes Date:</b> | 06/23/14 |

### SECTION 1: Identification

#### 1.1. Product identifier

3M(TM) Scotch-Weld(TM) Low Odor Acrylic Adhesive DP8825NS Green and Low Odor Acrylic Adhesive 8825NS Green, Part B

#### Product Identification Numbers

62-2866-8530-0, 62-2866-9530-9

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Structural adhesive

#### 1.3. Supplier's details

|                      |   |
|----------------------|---|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Industrial Adhesives and Tapes Division |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark |

##### Pictograms



**Hazard Statements**

Causes serious eye irritation.  
Causes skin irritation.  
May cause an allergic skin reaction.

**Precautionary Statements**

**Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wear protective gloves and eye/face protection.  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

None.

6% of the mixture consists of ingredients of unknown acute oral toxicity.  
59% of the mixture consists of ingredients of unknown acute dermal toxicity.

**SECTION 3: Composition/information on ingredients**

| Ingredient   | C.A.S. No.    | % by Wt                 |
|--|---------------|-------------------------|
| Tetrahydrofurfuryl Methacrylate                                  | 2455-24-5     | 20 - 50 Trade Secret *  |
| Hydroxyethyl Methacrylate  | 868-77-9      | 1 - 30 Trade Secret *   |
| Isobornyl Methacrylate   | 7534-94-3     | 1 - 20 Trade Secret *   |
| Butadiene-Acrylonitrile Polymer                                  | 9003-18-3     | 1 - 20 Trade Secret *   |
| Fillers (NJTS Reg No 04499600-6923)                              | Trade Secret* | 1 - 20 Trade Secret *   |
| Phosphate Esters of PPG Methacrylate (NJTS Reg No 04499600-6924) | Trade Secret* | 0.1 - 10 Trade Secret * |
| Bisphenol A Polyethylene Glycol Diether Dimethacrylate           | 41637-38-1    | 0.1 - 10 Trade Secret * |
| Benzyltributylammonium Chloride                                  | 23616-79-7    | 1 - 5 Trade Secret *    |
| Non-Hazardous Additive (NJTS Reg. No. 04499600-7174)             | Trade Secret* | 1 - 5 Trade Secret *    |

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### **If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

| <u>Substance</u>   | <u>Condition</u>  |
|--------------------|-------------------|
| Carbon monoxide    | During Combustion |
| Carbon dioxide     | During Combustion |
| Oxides of Nitrogen | During Combustion |

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

## 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

## 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### Occupational exposure limits

| Ingredient             | C.A.S. No. | Agency | Limit type             | Additional Comments |
|------------------------|------------|--------|------------------------|---------------------|
| Isobornyl Methacrylate | 7534-94-3  | CMRG   | TWA:25 ppm;STEL:35 ppm |                     |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|  |   |
|--|---|
| <b>General Physical Form:</b>                  | Liquid  |
| <b>Specific Physical Form:</b>                 | Paste   |
| <b>Odor, Color, Grade:</b>                     | White, acrylate odor  |
| <b>Odor threshold</b>                          | <i>No Data Available</i>                                      |
| <b>pH</b>                                      | <i>Not Applicable</i>   |
| <b>Melting point</b>                           | <i>Not Applicable</i>   |
| <b>Boiling Point</b>                           | >=100 °F  |
| <b>Flash Point</b>                             | > 200 °F [ <i>Test Method: Closed Cup</i> ]                   |
| <b>Evaporation rate</b>                        | <i>No Data Available</i>                                      |
| <b>Flammability (solid, gas)</b>               | Not Applicable  |
| <b>Flammable Limits(LEL)</b>                   | <i>No Data Available</i>                                      |
| <b>Flammable Limits(UEL)</b>                   | <i>No Data Available</i>                                      |
| <b>Vapor Pressure</b>                          | <i>No Data Available</i>                                      |
| <b>Density</b>                                 | 1.14 g/ml   |
| <b>Specific Gravity</b>                        | 1.14 [ <i>Ref Std: WATER=1</i> ]                              |
| <b>Solubility in Water</b>                     | Nil   |
| <b>Solubility- non-water</b>                   | <i>No Data Available</i>                                      |
| <b>Partition coefficient: n-octanol/ water</b> | <i>No Data Available</i>                                      |
| <b>Autoignition temperature</b>                | <i>No Data Available</i>                                      |
| <b>Decomposition temperature</b>               | <i>No Data Available</i>                                      |
| <b>Viscosity</b>                               | 125,000 centipoise  |
| <b>Hazardous Air Pollutants</b>                | 0 % weight  |
| <b>VOC Less H2O &amp; Exempt Solvents</b>      | 0.5 % [ <i>Details: when used as intended with Part A</i> ]   |
| <b>VOC Less H2O &amp; Exempt Solvents</b>      | 4.8 g/l [ <i>Details: when used as intended with Part A</i> ] |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat  
Sparks and/or flames

#### 10.5. Incompatible materials

Amines  
Strong acids  
Strong bases  
Strong oxidizing agents

#### 10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known.      |                  |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

##### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

##### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.  
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

##### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

##### Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

**3M(TM) Scotch-Weld(TM) Low Odor Acrylic Adhesive DP8825NS Green and Low Odor Acrylic Adhesive 8825NS Green, Part B**  
**08/13/14**

| Name   | Route     | Species | Value   |
|--|-----------|---------|---|
| Overall product  | Dermal    |         | No data available; calculated ATE > 5,000 mg/kg       |
| Overall product  | Ingestion |         | No data available; calculated ATE 2,000 - 5,000 mg/kg |
| Tetrahydrofurfuryl Methacrylate                        | Ingestion |         | LD50 estimated to be 2,000 - 5,000 mg/kg              |
| Hydroxyethyl Methacrylate                              | Dermal    | Rabbit  | LD50 > 5,000 mg/kg                                    |
| Hydroxyethyl Methacrylate                              | Ingestion | Rat     | LD50 5,564 mg/kg                                      |
| Fillers (NJTS Reg No 04499600-6923)                    | Ingestion | Rat     | LD50 > 2,000 mg/kg                                    |
| Isobornyl Methacrylate                                 | Dermal    | Rabbit  | LD50 > 3,000 mg/kg                                    |
| Isobornyl Methacrylate                                 | Ingestion | Rat     | LD50 > 2,000 mg/kg                                    |
| Butadiene-Acrylonitrile Polymer                        | Dermal    | Rabbit  | LD50 > 15,000 mg/kg                                   |
| Butadiene-Acrylonitrile Polymer                        | Ingestion | Rat     | LD50 > 30,000 mg/kg                                   |
| Bisphenol A Polyethylene Glycol Diether Dimethacrylate | Ingestion | Rat     | LD50 > 2,000 mg/kg                                    |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name                            | Species           | Value                     |
|---------------------------------|-------------------|---------------------------|
| Tetrahydrofurfuryl Methacrylate | similar compounds | Irritant                  |
| Hydroxyethyl Methacrylate       | Rabbit            | Minimal irritation        |
| Isobornyl Methacrylate          | Rabbit            | Mild irritant             |
| Butadiene-Acrylonitrile Polymer |                   | No significant irritation |

**Serious Eye Damage/Irritation**

| Name                            | Species           | Value                     |
|---------------------------------|-------------------|---------------------------|
| Tetrahydrofurfuryl Methacrylate | similar compounds | Severe irritant           |
| Hydroxyethyl Methacrylate       | Rabbit            | Moderate irritant         |
| Isobornyl Methacrylate          | Rabbit            | Mild irritant             |
| Butadiene-Acrylonitrile Polymer |                   | No significant irritation |

**Skin Sensitization**

| Name   | Species          | Value  |
|--|------------------|--|
| Tetrahydrofurfuryl Methacrylate                        | Human            | Some positive data exist, but the data are not sufficient for classification |
| Hydroxyethyl Methacrylate                              | Human and animal | Sensitizing  |
| Isobornyl Methacrylate                                 | Guinea pig       | Not sensitizing  |
| Bisphenol A Polyethylene Glycol Diether Dimethacrylate | Guinea pig       | Not sensitizing  |

**Respiratory Sensitization**

| Name | Species | Value |
|------|---------|-------|
|------|---------|-------|

**Germ Cell Mutagenicity**

| Name   | Route    | Value  |
|--|----------|--|
| Hydroxyethyl Methacrylate                              | In vivo  | Not mutagenic  |
| Hydroxyethyl Methacrylate                              | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Bisphenol A Polyethylene Glycol Diether Dimethacrylate | In Vitro | Not mutagenic  |

**Carcinogenicity**

| Name | Route | Species | Value |
|------|-------|---------|-------|
|------|-------|---------|-------|

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure |
|------|-------|-------|---------|-------------|----------|
|------|-------|-------|---------|-------------|----------|

**3M(TM) Scotch-Weld(TM) Low Odor Acrylic Adhesive DP8825NS Green and Low Odor Acrylic Adhesive 8825NS Green, Part B  
08/13/14**

|                           |           |                                  |     |                             | <b>Duration</b>                     |
|---------------------------|-----------|----------------------------------|-----|-----------------------------|-------------------------------------|
| Hydroxyethyl Methacrylate | Ingestion | Not toxic to female reproduction | Rat | NOAEL<br>1,000<br>mg/kg/day | pre mating &<br>during<br>gestation |
| Hydroxyethyl Methacrylate | Ingestion | Not toxic to male reproduction   | Rat | NOAEL<br>1,000<br>mg/kg/day | 49 days                             |
| Hydroxyethyl Methacrylate | Ingestion | Not toxic to development         | Rat | NOAEL<br>1,000<br>mg/kg/day | pre mating &<br>during<br>gestation |

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

| Name                            | Route      | Target Organ(s)        | Value  | Species | Test Result         | Exposure Duration |
|---------------------------------|------------|------------------------|--|---------|---------------------|-------------------|
| Tetrahydrofurfuryl Methacrylate | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification |         | NOAEL Not available |                   |

**Specific Target Organ Toxicity - repeated exposure**

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|------|-------|-----------------|-------|---------|-------------|-------------------|
|      |       |                 |       |         |             |                   |

**Aspiration Hazard**

| Name | Value |
|------|-------|
|      |       |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No    Pressure Hazard - No    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - No

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### NFPA Hazard Classification

**Health: 2 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 33-2643-6 | <b>Version Number:</b>  | 1.01     |
| <b>Issue Date:</b>     | 08/13/14  | <b>Supersedes Date:</b> | 06/23/14 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to

determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**