Revision Date: 02/24/2020

SAFETY DATA SHEET

1. Identification

Product identifier: NAPA Mac's 1397 Belt Dressing

Other means of identification

SDS number: RE1000036034

Recommended restrictions
Product use: Lubricant

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: NAPA BALKAMP Address: 1601 Whitaker Rd

INDIANAPOLIS, IN 46168

Telephone: 317-837-2800

Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Skin sensitizer Category 1
Specific Target Organ Toxicity - Category 3¹

Single Exposure

Aspiration Hazard Category 1

Target Organs

Narcotic effect.

Environmental Hazards

Acute hazards to the aquatic Category 2

environment

Chronic hazards to the aquatic Category 3

environment

Label Elements

Hazard Symbol:



Signal Word: Danger

Revision Date: 02/24/2020

Hazard Statement: Extremely flammable aerosol.

Causes skin irritation.

Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors

or in a well-ventilated area. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water If skin irritation or rash occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

| Chemical Identity | CAS number | Content in percent (%)* |
|---|-------------|-------------------------|
| 2-Propanone | 67-64-1 | 20 - <50% |
| Propane | 74-98-6 | 10 - <20% |
| Butane | 106-97-8 | 10 - <20% |
| Solvent naphtha (petroleum), light aliph. | 64742-89-8 | 10 - <20% |
| Heptane | 142-82-5 | 5 - <10% |
| Heptane, branched, cyclic and linear | 426260-76-6 | 5 - <10% |
| Naphtha (petroleum), hydrotreated light | 64742-49-0 | 5 - <10% |
| Naphtha (petroleum), heavy alkylate | 64741-65-7 | 5 - <10% |
| Maleic Anhydride Modified Liquid Polyisoprene | 841251-34-1 | 1 - <5% |

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so

that stomach content doesn't get into the lungs.

Revision Date: 02/24/2020

Inhalation: Move to fresh air.

Skin Contact: Get medical attention. Destroy or thoroughly clean contaminated shoes.

Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction

develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning

up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop

the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you

can do so without risk.

Revision Date: 02/24/2020

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin. Avoid contact with

eyes, skin, and clothing.

Conditions for safe storage, including any incompatibilities:

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 3

400.7.0.000. 2010

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | Туре | Exposure Limit Values | Source |
|--|-----------|-----------------------|---|
| 2-Propanone | STEL | 1,000 ppm 2,400 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| · | PEL | 1,000 ppm 2,400 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 |
| | | | CFR 1910.1000) (02 2006) |
| | TWA | 250 ppm | US. ACGIH Threshold Limit Values (03 2015) |
| | TWA | 750 ppm 1,800 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | STEL | 500 ppm | US. ACGIH Threshold Limit Values (03 2015) |
| | REL | 250 ppm 590 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| Propane | REL | 1,000 ppm 1,800 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | PEL | 1,000 ppm 1,800 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | TWA | 1,000 ppm 1,800 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Butane | REL | 800 ppm 1,900 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | STEL | 1,000 ppm | US. ACGIH Threshold Limit Values (03 2018) |
| | TWA | 800 ppm 1,900 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Solvent naphtha (petroleum), light aliph. | REL | 100 ppm 400 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| <u> </u> | TWA | 100 ppm 400 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | PEL | 100 ppm 400 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 |
| | | | CFR 1910.1000) (03 2016) |
| Naphtha (petroleum), hydrotreated light | PEL | 100 ppm 400 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016) |
| | REL | 100 ppm 400 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | TWA | 100 ppm 400 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Heptane | TWA | 400 ppm 1,600 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| • | REL | 85 ppm 350 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | PEL | 500 ppm 2,000 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | STEL | 500 ppm 2,000 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 400 ppm | US. ACGIH Threshold Limit Values (02 2012) |
| | STEL | 500 ppm | US. ACGIH Threshold Limit Values (02 2012) |
| | Ceil Time | 440 ppm 1,800 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| Naphtha (petroleum), heavy alkylate | PEL | 100 ppm 400 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| • | TWA | 100 ppm 400 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | REL | 100 ppm 400 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| Distillates (petroleum), hydrotreated heavy naphthenic | TWA | 400 ppm 1,600 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | PEL | 500 ppm 2,000 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Distillates (petroleum), hydrotreated heavy naphthenic - Mist. | REL | 5 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | STEL | 10 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | TWA | 5 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Distillates (petroleum), | Ceil_Time | 1,800 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |

Revision Date: 02/24/2020

| hydrotreated heavy | | | | |
|---------------------------|---------|-----------|-------------|--|
| naphthenic | | | | |
| Distillates (petroleum), | TWA | | 5 mg/m3 | US. ACGIH Threshold Limit Values (03 2014) |
| hydrotreated heavy | | | | |
| naphthenic - Inhalable | | | | |
| fraction. | | | | |
| Distillates (petroleum), | REL | | 350 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| hydrotreated heavy | | | | |
| naphthenic | | | | |
| Benzene, methyl- | STEL | 150 ppm | 560 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | REL | 100 ppm | 375 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | TWA | 100 ppm | 375 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | Ceiling | 300 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | TWA | 20 ppm | | US. ACGIH Threshold Limit Values (2008) |
| | TWA | 200 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | MAX. | 500 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | CONC | | | (1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 |
| | STEL | 150 ppm | 560 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| Benzene | REL | 0.1 ppm | | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | TWA | 1 ppm | | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | Ceiling | 25 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | TWA | 0.5 ppm | | US. ACGIH Threshold Limit Values (2008) |
| | STEL | 2.5 ppm | | US. ACGIH Threshold Limit Values (2008) |
| | STEL | 5 ppm | | US. OSHA Specifically Regulated Substances (29 |
| | SILL | 3 рріп | | CFR 1910.1001-1053) (02 2006) |
| | OSHA_AC | 0.5 ppm | | US. OSHA Specifically Regulated Substances (29 |
| | T T | 0.5 ppiii | | CFR 1910.1001-1053) (02 2006) |
| | TWA | 10 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | MAX. | 50 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | CONC | 30 ррпі | | 05. OSHA Table 2-2 (29 CH 1910.1000) (02 2000) |
| | STEL | 5 ppm | | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 1 ppm | | US. OSHA Specifically Regulated Substances (29 |
| | | | | CFR 1910.1001-1053) (02 2006) |
| | STEL | 1 ppm | | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| Benzene, (1-methylethyl)- | REL | 50 ppm | 245 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| , , | TWA | 50 ppm | | US. ACGIH Threshold Limit Values (2008) |
| | PEL | 50 ppm | 245 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 |
| | | оо ррии | 2 10 mg/mo | CFR 1910.1000) (02 2006) |
| | TWA | 50 ppm | 245 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 1 ppm | 240 mg/mo | US. ACGIH Notice of Intended Changes (NIC) to |
| | 1 7 7 7 | i ppiii | | Threshold Limit Values (03 2018) |
| Benzene, ethyl- | STEL | 125 ppm | 545 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| Benzene, emyr | REL | 100 ppm | 435 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | PEL | 100 ppm | 435 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 |
| | FLL | 100 ppill | 433 mg/m3 | CFR 1910.1000) (02 2006) |
| | STEL | 125 nnm | 545 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | | 125 ppm | | |
| | TWA | 100 ppm | 435 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Havena | TWA | 20 ppm | 400 | US. ACGIH Threshold Limit Values (12 2010) |
| Hexane | TWA | 50 ppm | 180 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | PEL | 500 ppm | 1,800 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 |
| | DEI | FC | 400 | CFR 1910.1000) (02 2006) |
| | REL | 50 ppm | 180 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | TWA | 50 ppm | | US. ACGIH Threshold Limit Values (2008) |
| Cyclohexane | TWA | 100 ppm | | US. ACGIH Threshold Limit Values (2008) |
| | TWA | 300 ppm | 1,050 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | REL | 300 ppm | 1,050 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | PEL | 300 ppm | 1,050 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 |
| | | | | CFR 1910.1000) (02 2006) |

Biological Limit Values

| Chemical Identity | Exposure Limit Values | Source |
|---|--------------------------------|---------------------|
| 2-Propanone (acetone: Sampling time: End of shift.) | 25 mg/l (Urine) | ACGIH BEL (03 2015) |
| Benzene, methyl- (toluene: Sampling time: End of shift.) | 0.03 mg/l (Urine) | ACGIH BEL (03 2013) |
| Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.) | 0.3 mg/g (Creatinine in urine) | ACGIH BEL (03 2013) |
| Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.) | 0.02 mg/l (Blood) | ACGIH BEL (03 2013) |
| Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.) | 25 μg/g (Creatinine in urine) | ACGIH BEL (03 2013) |
| Benzene (t,t-Muconic acid: Sampling time: End of shift.) | 500 μg/g (Creatinine in urine) | ACGIH BEL (03 2013) |
| Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.) | 0.15 g/g (Creatinine in urine) | ACGIH BEL (02 2014) |
| Hexane (2,5-Hexanedion, without hydrolysis: Sampling time: End of shift.) | 0.5 mg/l (Urine) | ACGIH BEL (03 2018) |

Revision Date: 02/24/2020

Appropriate Engineering

Controls

No data available.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable

level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear,

and protective clothing appropriate for the risk of exposure. Contact health

and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Avoid contact with eyes. When

using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed

out of the workplace.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol Color: No data available. Odor: No data available. Odor threshold: No data available. :Ha No data available. Melting point/freezing point: No data available. Initial boiling point and boiling range: No data available. Flash Point: Estimated -104.44 °C **Evaporation rate:** No data available. Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): Estimated 9.5 %(V)
Flammability limit - lower (%): Estimated 1.9 %(V)
Explosive limit - upper (%): No data available.
Explosive limit - lower (%): No data available.

Vapor pressure: Estimated 2,068 - 3,447 hPa (20 °C)

Vapor density:

Density:

No data available.

No data available.

No data available.

No data available.

Solubility(ies)

Solubility in water: No data available.

Revision Date: 02/24/2020

Solubility (other): No data available. Partition coefficient (n-octanol/water): No data available. Auto-ignition temperature: No data available. **Decomposition temperature:** No data available. Viscosity: No data available.

10. Stability and reactivity

No data available. Reactivity:

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

2-Propanone LD 50 (Rat): 5,800 mg/kg

Solvent naphtha

(petroleum), light aliph.

LD 50 (Rat): > 5,000 mg/kg

LD 50 (Rat): > 5,000 mg/kgHeptane

Heptane, branched,

cyclic and linear

LD 50: > 2,000 mg/kg

Naphtha (petroleum), hydrotreated light

LD 50 (Rat): > 5,000 mg/kg

Revision Date: 02/24/2020

Naphtha (petroleum),

heavy alkylate

LD 50: > 2,000 mg/kg

Maleic Anhydride **Modified Liquid** Polyisoprene

LD 50: > 2,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

2-Propanone

LD 50 (Rabbit): > 7,426 mg/kg

Solvent naphtha

(petroleum), light aliph.

LD 50 (Rabbit): > 2,000 mg/kg

Heptane LD 50 (Rabbit): > 2,000 mg/kg

Heptane, branched. cyclic and linear

LD 50: > 2,000 mg/kg

Naphtha (petroleum), hydrotreated light

LD 50 (Rabbit): > 3,750 mg/kg

Naphtha (petroleum),

heavy alkylate

LD 50: > 2,000 mg/kg

Maleic Anhydride **Modified Liquid** Polyisoprene

LD 50: > 2,000 mg/kg

Inhalation

Product: ATEmix: 65.21 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):

2-Propanone NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental

result, Key study

Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

Butane LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result. Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

Solvent naphtha (petroleum), light aliph. NOAEL (Mouse, Rat(Female, Male), Inhalation, 107 - 113 Weeks): 1,402

mg/m3 Inhalation Experimental result, Key study

NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal

Experimental result, Key study

NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal

Experimental result, Supporting study

Heptane NOAEL (Rat(Male), Inhalation): 12,470 mg/m3 Inhalation Experimental

result, Key study

Naphtha (petroleum), hydrotreated light

LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Readacross based on grouping of substances (category approach), Key study

NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal

Experimental result, Supporting study

NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m3 Inhalation

Experimental result, Key study

Revision Date: 02/24/2020

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

2-Propanone in vivo (Rabbit): Not irritant Experimental result, Supporting study

Solvent naphtha Assessment Non-Irritating

(petroleum), light aliph. in vivo (Rabbit): Irritating Experimental result, Key study

Heptane in vivo (Rabbit): Irritating Read-across based on grouping of substances

(category approach), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

2-Propanone Irritating.

Rabbit, 24 hrs: Minimum grade of severe eye irritant

Solvent naphtha

(petroleum), light aliph.

Rabbit: Not irritating

Heptane Rabbit, 24 - 72 hrs: Not irritating

Naphtha (petroleum),

hydrotreated light

Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

2-Propanone Skin sensitization:, in vivo (Guinea pig): Non sensitising Solvent naphtha Skin sensitization:, in vivo (Guinea pig): Non sensitising

(petroleum), light aliph.

Heptane Skin sensitization:, in vivo (Guinea pig): Non sensitising Naphtha (petroleum), Skin sensitization:, in vivo (Guinea pig): Non sensitising

hydrotreated light

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Revision Date: 02/24/2020

Specified substance(s):

2-Propanone Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Heptane Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: No data available.

Specified substance(s):

Solvent naphtha May be fatal if swallowed and enters airways.

(petroleum), light aliph.

Heptane May be fatal if swallowed and enters airways. Heptane, branched, cyclic May be fatal if swallowed and enters airways.

and linear

Naphtha (petroleum), May be fatal if swallowed and enters airways.

hydrotreated light

Naphtha (petroleum), May be fatal if swallowed and enters airways.

heavy alkylate

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

2-Propanone LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key

study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Solvent naphtha

(petroleum), light aliph.

LL 50 (Pimephales promelas, 96 h): 8.2 mg/l Experimental result, Key study

Heptane LC 50 (Mozambique tilapia (Tilapia mossambica), 96 h): 375 mg/l Mortality

Naphtha (petroleum),

hydrotreated light

LC 50 (96 h): 8.41 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

2-Propanone LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Solvent naphtha EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study (petroleum), light aliph. NOAEL (Daphnia magna, 48 h): 0.5 mg/l Experimental result, Key study

Heptane EC 50 (Daphnia magna, 48 h): 1.5 mg/l Experimental result, Key study

SDS_US - RE1000036034

Revision Date: 02/24/2020

Naphtha (petroleum), hydrotreated light

EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Solvent naphtha (petroleum), light aliph.

NOAEL (Daphnia magna): 2.6 mg/l Other, Key study

Heptane NOAEL (Oncorhynchus mykiss): 1.284 mg/l QSAR QSAR, Key study

Naphtha (petroleum), hydrotreated light

EC 50 (Daphnia magna): 10 mg/l Other, Key study NOAEL (Daphnia magna): 2.6 mg/l Other, Key study

Aquatic Invertebrates

Product:

No data available.

Specified substance(s):

2-Propanone LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

Solvent naphtha (petroleum), light aliph.

EC 50 (Daphnia magna): > 40 mg/l Experimental result, Key study

Heptane NOAEL (Daphnia magna): 0.17 mg/l Read-across based on grouping of

substances (category approach), Key study

EC 50 (Daphnia magna): 0.23 mg/l Read-across based on grouping of

substances (category approach), Key study

Heptane, branched, cyclic and linear

NOEC: < 1 mg/l estimation

Naphtha (petroleum), hydrotreated light

EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product:

No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

2-Propanone 90.9 % (28 d) Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

Solvent naphtha (petroleum), light aliph.

90.35 % (28 d) Detected in water. Experimental result, Supporting study 77.05 % Detected in water. Experimental result, Supporting study

Heptane 70 % Detected in water. Experimental result, Key study

Naphtha (petroleum), hydrotreated light

90.35 % (28 d) Detected in water. Experimental result, Supporting study

Revision Date: 02/24/2020

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

2-Propanone Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment

Experimental result, Not specified

Solvent naphtha Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by

(petroleum), light aliph. calculation, Key study

Heptane Bioconcentration Factor (BCF): 552 Aquatic sediment Estimated by

calculation, Key study

Naphtha (petroleum), Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by

hydrotreated light calculation, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Naphtha (petroleum), Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study hydrotreated light Log Kow: 2.2 - 5.2 23 °C Yes Experimental result, Key study

Log Kow: 2.2 - 6.1 23 °C Yes Experimental result, Key study

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

2-Propanone No data available. Propane No data available. Butane No data available. Solvent naphtha (petroleum), light aliph. No data available. Heptane No data available. Heptane, branched, cyclic and linear No data available. Naphtha (petroleum), hydrotreated light No data available. Naphtha (petroleum), heavy alkylate No data available. Maleic Anhydride Modified Liquid Polyisoprene No data available.

Other adverse effects: Toxic to aquatic organisms. Harmful to aquatic life with long lasting effects.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): –
Packing Group: II
Marine Pollutant: No

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

Revision Date: 02/24/2020

IMDG

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2 Label(s): EmS No.:

Packing Group:

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):

2.1 Class: Label(s): Packing Group:

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity OSHA hazard(s) Benzene Flammability

> Cancer Aspiration Eye Blood Skin

respiratory tract irritation Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

| Chemical Identity | Reportable quantity |
|---------------------------|---------------------|
| 2-Propanone | lbs. 5000 |
| Propane | lbs. 100 |
| Butane | lbs. 100 |
| Heptane | lbs. 100 |
| Benzene, methyl- | lbs. 1000 |
| Benzene | lbs. 10 |
| Benzene, (1-methylethyl)- | lbs. 5000 |
| Benzene, ethyl- | lbs. 1000 |
| Hexane | lbs. 5000 |
| Cyclohexane | lbs. 1000 |

Revision Date: 02/24/2020

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Immediate (Acute) Health Hazards

Flammable aerosol Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Skin sensitizer

Specific Target Organ Toxicity - Single Exposure

Aspiration Hazard

SARA 302 Extremely Hazardous Substance

<u>Reportable</u>

<u>Chemical Identity</u> <u>quantity</u> <u>Threshold Planning Quantity</u> 2-Propanone

Hexane

SARA 304 Emergency Release Notification

| Chemical identity | Reportable quantity |
|---------------------------|---------------------|
| 2-Propanone | lbs. 5000 |
| Propane | lbs. 100 |
| Butane | lbs. 100 |
| Heptane | lbs. 100 |
| Benzene, methyl- | lbs. 1000 |
| Benzene | lbs. 10 |
| Benzene, (1-methylethyl)- | lbs. 5000 |
| Benzene, ethyl- | lbs. 1000 |
| Hexane | lbs. 5000 |
| Cyclohexane | lbs. 1000 |
| | |

SARA 311/312 Hazardous Chemical

| <u>Chemical Identity</u> | Threshold Planning Quantity |
|--|------------------------------------|
| 2-Propanone | 10000 lbs |
| Propane | 10000 lbs |
| Butane | 10000 lbs |
| Solvent naphtha (petroleum), light aliph. | 10000 lbs |
| Heptane | 10000 lbs |
| Heptane, branched, cyclic and linear | 10000 lbs |
| Naphtha (petroleum), hydrotreated light | 10000 lbs |
| Naphtha (petroleum), heavy alkylate | 10000 lbs |
| Maleic Anhydride Modified Liquid Polyisoprene | 10000 lbs |
| Distillates (petroleum), hydrotreated heavy naphthenic | 10000 lbs |
| Benzene, methyl- | 10000 lbs |
| Benzene | 10000 lbs |
| Benzene, (1-methylethyl)- | 10000 lbs |
| Benzene, ethyl- | 10000 lbs |
| Hexane | 10000 lbs |
| Cyclohexane | 10000 lbs |

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) US State Regulations

Revision Date: 02/24/2020

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Benzene, methylBenzene

Developmental toxin. 03 2008
Developmental toxin. 03 2008

Benzene Carcinogenic. 05 2011

Benzene Male reproductive toxin. 03 2008

Benzene, (1-methylethyl)- Carcinogenic. 05 2011 Benzene, ethyl- Carcinogenic. 05 2011

Hexane Male reproductive toxin. 12 2017

US. New Jersey Worker and Community Right-to-Know Act Chemical Identity

2-Propanone Propane Butane

Solvent naphtha (petroleum), light aliph. Naphtha (petroleum), hydrotreated light

Heptane

Naphtha (petroleum), heavy alkylate

Distillates (petroleum), hydrotreated heavy naphthenic

US. Massachusetts RTK - Substance List Chemical Identity

Benzene

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

2-Propanone

Propane

Butane

Solvent naphtha (petroleum), light aliph. Naphtha (petroleum), hydrotreated light

Heptane

Naphtha (petroleum), heavy alkylate

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

2-Propanone

Stockholm convention

2-Propanone

Rotterdam convention

2-Propanone

Kyoto protocol

Revision Date: 02/24/2020

Inventory Status:

Australia AICS: Not in compliance with the inventory.

Canada DSL Inventory List: On or in compliance with the inventory

Canada NDSL Inventory: Not in compliance with the inventory.

Ontario Inventory: Not in compliance with the inventory.

China Inv. Existing Chemical Substances:

On or in compliance with the inventory

Japan (ENCS) List: Not in compliance with the inventory.

Japan ISHL Listing: Not in compliance with the inventory.

Japan Pharmacopoeia Listing: Not in compliance with the inventory.

Korea Existing Chemicals Inv. (KECI): Not in compliance with the inventory.

Mexico INSQ: Not in compliance with the inventory.

New Zealand Inventory of Chemicals: Not in compliance with the inventory.

Philippines PICCS: Not in compliance with the inventory.

Taiwan Chemical Substance Inventory: Not in compliance with the inventory.

US TSCA Inventory: On or in compliance with the inventory

EINECS, ELINCS or NLP: Not in compliance with the inventory.

16.Other information, including date of preparation or last revision

Issue Date: 02/24/2020

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.