

MATERIAL SAFETY DATA SHEET

Page 1 of 4

1. PRODUCT AND COMPANY IDENTIFICATION

NAME: NEXUS SYSTEM BUILT LAUNDRY DETERGENT EC

USE: LAUNDRY DETERGENT LABEL BRAND: U S CHEMICAL

MSDS # 5577693N CODE # 5577714

USCHEMICAL, 316 HART STREET, WATERTOWN, WI 53094 USA

MEDICAL EMERGENCY #: 1-866-923-4913 USA SPILL EMERGENCY #: 1-800-424-9300 USA

PRODUCT INFORMATION #: 1-800-558-9566 (8 A.M. TO 5 P.M. CST MONDAY TO FRIDAY)

INTERNET ADDRESS: www.uschemical.com

REVIEWED 1-6-12 REVISED 1-6-12 SECTION REVISED: 1

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING! COMBUSTIBLE LIQUID. MAY BE SEVERELY IRRITATING TO EYES AND SKIN.

PRINCIPLE ROUTES OF EXPOSURE: EYES, SKIN, INGESTION, INHALATION.

POTENTIAL ACUTE HEALTH EFFECTS

EYES: MAY BE SEVERELY IRRITATING TO EYES.

SKIN: MAY BE SEVERELY IRRITATING TO SKIN.

INHALATION: MAY BE IRRITATING TO NOSE, THROAT AND RESPIRATORY TRACT.

INGESTION: MAY BE IRRITATING TO MOUTH, THROAT AND STOMACH. MAY CAUSE ABDOMINAL

DISCOMFORT, NAUSEA, VOMITING AND DIARRHEA.

MEDICAL CONDITIONS AGGRAVATED: PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE

MORE SUSCEPTABLE TO IRRITATING EFFECTS.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| HAZARDOUS INGREDIENT | CAS# | % BY WT | LC50/LD50 |
|----------------------|------------|------------|-----------|
| | | | |
| ALCOHOL ETHOXYLATES | 68439-46-3 | 7.0 – 13.0 | N.AV. |
| ETHYL ALCOHOL | 64-17-5 | 1.0 – 5.0 | N.AV. |
| SODIUM CARBONATE | 497-19-8 | 5.0 – 10.0 | |
| | | | |

STATE RIGHT TO KNOW: THIS PRODUCT CONTAINS:

WATER/7732-18-5. ALCOHOL ETHOXYLATES/68439-46-3. SODIUM LAURETH SULFATE/9004-82-4.

SODIUM CARBONATE/497-19-8, SODIUM XYLENE SULFONATE/1300-72-7,

ETHYL ALCOHOL/64-17-5

4. FIRST AID MEASURES

Page 2 of 4

EYES: IMMEDIATELY FLUSH EYES WITH RUNNING WATER FOR AT LEAST 15 MINUTES, KEEPING EYELIDS OPEN. **SKIN:** IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. REMOVE AND WASH CONTAMINATED CLOTHING AND FOOTWEAR BEFORE RE-USE.

IF SWALLOWED: GIVE A CUPFUL OF WATER OR MILK. THEN IMMEDIATELY CONTACT A PHYSICIAN OR POISON CENTER. DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

INHALATION: IF BREATHING IS AFFECTED, REMOVE TO FRESH AIR.

ADMINISTER FIRST AID TREATMENT AS STATED ABOVE, THEN CALL 1-866-923-4913 OR CONTACT PHYSICIAN FOR FURTHER MEDICAL INSTRUCTIONS.

NOTE TO PHYSICIAN: CALL 1-866-923-4913 FOR ASSISTANCE WITH THE MANAGEMENT OF EXPOSURES.

5. FIRE-FIGHTING MEASURES

FLAMMABILITY: ALTHOUGH THIS PRODUCT HAS A FLASH POINT BELOW 200°F, IT IS AN AQUEOUS SOLUTION WHICH HAS BEEN TESTED AND SHOWN NOT TO SUSTAIN COMBUSTION.

FLASH POINT: 58.9°C, 138°F SETAFLASH CC PRODUCTS OF COMBUSTION: SEE SECTION 10.

HANDLE CAREFULLY TO AVOID DAMAGING CONTAINER.

SUITABLE EXTINGUISHING MEDIA: FOR FIRES IN AREA, USE APPROPRIATE MEDIA. FOR EXAMPLE: WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE, OR ALCOHOL FOAM.

SPECIFIC HAZARDS: A VAPOR ACCUMULATION MAY FLASH IF IGNITED. **SPECIFIC METHODS:** NORMAL FIRE-FIGHTING PROCEDURES MAY BE USED.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: SEE SECTION 8. PUT ON APPROPRIATE PPE. SPILL RESPONSE: ELIMINATE ALL IGNITION SOURCES. EVACUATE UNPROTECTED PERSONNEL FROM AREA. WEAR PROPER PROTECTIVE EQUIPMENT INCLUDING RUBBER BOOTS. VENTILATE AREA IF NEEDED. STOP LEAK IF YOU CAN DO SO WITHOUT RISK. DIKE OR DAM LARGE SPILLS. AVOID DIRECT DISCHARGE TO SEWER AND SURFACE WATERS. PUMP TO CONTAINER OR SOAK UP WITH NON-COMBUSTIBLE INERT ABSORBENT MATERIALS. AFTER SPILL COLLECTION, FLUSH AREA WITH WATER AND FOLLOW WITH NORMAL CLEAN-UP PROCEDURES. WASH CONTAMINATED CLOTHING AND FOOTWEAR BEFORE RE-USE. BE CAREFUL AS SPILLS ARE SLIPPERY.

7. HANDLING AND STORAGE

HANDLING: FOLLOW ALL LABEL DIRECTIONS. INSTRUCT PERSONNEL ABOUT PROPER USE, HAZARDS, PRECAUTIONS, AND FIRST AID MEASURES. USE IN WELL-VENTILATED AREAS. AVOID BREATHING VAPORS OR MISTS. AVOID INGESTION AND CONTACT WITH EYES. DO NOT TASTE OR SWALLOW. REMOVE AND WASH CONTAMINATED CLOTHING AND FOOTWEAR BEFORE RE-USE. PRODUCT RESIDUE MAY REMAIN ON OR IN EMPTY CONTAINERS.

STORAGE: ROTATE STOCK REGULARLY. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID TEMPERATURES BELOW 35°F OR ABOVE 120°F. KEEP AWAY FROM HEAT, SPARK AND FLAME. PROTECT FROM FREEZING. STORAGE AT AMBIENT TEMPERATURES IN A DRY AREA OUT OF DIRECT SUNLIGHT IS RECOMMENDED. KEEP AWAY FROM FOOD AND DRINK. KEEP OUT OF CHILDREN'S REACH.

Page 3 of 4

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS: ETHYL ALCOHOL = 1000 PPM TWA (ACGIH/OSHA)

ENGINEERING CONTROLS: NONE REQUIRED. GENERAL ROOM VENTILATION IS ADEQUATE.

PERSONAL PROTECTION

EYES: SAFETY GLASSES WITH SIDE SHIELDS RECOMMENDED IF SPRAYING.

HANDS: FOR PROLONGED OR REPEATED CONTACT WITH SKIN: RUBBER GLOVES.

RESPIRATORY: N.AP.

FEET: N.AP. BODY: N.AP.

9. PHYSICAL AND CHEMICAL PROPERTIES

COLOR: BLUE FLASH POINT: 49°C, 120°F TCC

ODOR: FRESH UEL: N.AV. ph concentrate: 11.0 Lel: N.AV.

pH CONCENTRATE: 11.0 LEL: N.AV.
pH @ 2500 PPM SOLUTION: N.AP. EVAPORATION RATE: N.AP.

pH @ USE DILUTION: N.AP.

PHYSICAL STATE: LIQUID

SPECIFIC GRAVITY: 1.115

VISCOSITY: SLIGHTLY VISCOUS

ODOR THRESHOLD: N.AP

VAPOR PRESSURE: N.AP

VAPOR DENSITY: N. AP.

COEFF. OIL/WATER: N.AP.

BOILING POINT: N.AP.

COEFF. OIL/WATER: N.AP.

WATER SOLUBILITY: COMPLETE

MELTING POINT: N.AP. OTHER: N.AP.

10. STABILITY AND REACTIVITY

STABLE: YES

CONDITIONS TO AVOID: AVOID TEMPERATURES BELOW 35°F. AVOID HEAT, SPARKS AND FLAME.

MATERIALS TO AVOID: AVOID MIXING DIRECTLY WITH ANY OTHER CLEANING PRODUCT. AVOID OXIDIZING AGENTS INCLUDING BLEACH. MIX ONLY WITH WATER.

DECOMPOSITION PRODUCTS: FIRE OR MIXING WITH INCOMPATIBLE MATERIALS MAY PRODUCE OXIDES OF CARBON AND OTHER TOXIC OR IRRITATING FUMES.

POSSIBILITY OF HAZARDOUS REACTIONS: N.AP.

11. TOXICOLOGICAL INFORMATION

ACUTE EFFECTS: SEE SECTION 2.

CHRONIC EFFECTS: NONE KNOWN. NO REPORTABLE CARCINOGENS, MUTAGENS, SENSITIZERS, SYNERGISTIC MATERIALS, TERATOGENS, OR REPRODUCTIVE TOXINS.

LC50/LD50: N.AV.

TARGET ORGANS: EYES, SKIN, RESPIRATORY SYSTEM.

OTHER TOXIC EFFECTS: NONE KNOWN.

12. ECOLOGICAL INFORMATION

Page 4 of 4

NOT AVAILABLE.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: UNDILUTED PRODUCT WITH FLASH POINT BELOW 140 F IS REGULATED UNDER ENVIRONMENTAL AND TRANSPORTATION LAWS AS AN IGNITABLE WASTE (RCRA CLASS D001). COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS. CONSULT STATE AND LOCAL AUTHORITIES FOR RESTRICTIONS ON DISPOSAL OF CHEMICAL WASTE. MANAGE CHEMICAL WASTES THROUGH AN APPROVED WASTE TREATMENT FACILITY. DO NOT REUSE EMPTY CONTAINER. RINSE EMPTY CONTAINER THOROUGHLY WITH WATER BEFORE DISCARDING CONTAINER IN ACCORDANCE WITH CURRENT LOCAL COMMUNITY CODES. PLEASE RECYCLE EMPTY CONTAINER WHENEVER POSSIBLE.

14. TRANSPORT INFORMATION

DOT/TDG: NOT REGULATED

DOT RQ: N.AP.
DOT ERG #: N.AP.

15. REGULATORY INFORMATION

EPA CERCLA RQ: N.AP. EPA REGISTERED: NO OSHA HAZARDOUS: YES

PHOSPHORUS CONTENT: 0.00%

PROPOSITION 65: N.AP.

SARA 311/312 HAZARDS: ACUTE, FIRE

SARA 313 CHEMICALS: N.AP.

STATE RIGHT TO KNOW: SEE SECTION 3 FOR STATE RTK CHEMICAL NAMES.

TSCA INVENTORY STATUS: ALL COMPONENTS ARE LISTED ON THE INVENTORY.

VOC: 2.25% CALCULATION METHOD USED IS BASED ON CALIFORNIA ARB STANDARD.

WHMIS CLASS: D-2B, B-3

16. OTHER INFORMATION

NFPA RATING: HEALTH-2/FLAMMABILITY-1/REACTIVITY-0/SPECIAL HAZARD-N.AP.

HMIS RATING: HEALTH-2/FLAMMABILITY-1/REACTIVITY-0/PERSONAL PROTECTION-SEE 8.0

N.AV. = NOT AVAILABLE N.AP. = NOT APPLICABLE PREPARED BY: HEALTH AND SAFETY

NOTICE TO READER

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. IT DOES NOT CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION CONTAINED WITHIN. ACTUAL CONDITIONS OF USE AND HANDLING ARE BEYOND SELLER'S CONTROL. USER IS RESPONSIBLE FOR EVALUATING ALL AVAILABLE INFORMATION WHEN USING PRODUCT FOR ANY PARTICULAR USE AND TO COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.