



SAFETY DATA SHEET

Creation Date 29-May-2015

Revision Date 29-May-2017

Version 3

1. IDENTIFICATION

Product Name Coated Veils

Synonyms VL 3589, VL 3590, VL 3591, VL NF ACBM GOLD

Product Code OCCM00026

Recommended Use Building applications

Manufacturer Address Owens Corning Composite Materials, LLC
One Owens Corning Parkway
Toledo, Ohio 43659

Company Phone Number 1-800-GET-PINK or 1-800-438-7465
24 Hour Emergency Phone Number Chemtrec 1-800-424-9300
Emergency Telephone 1-419-248-5330 (after 5 pm ET and weekends)

E-mail address productcompliance@owenscorning.com
Company Website <http://www.owenscorning.com/>

2. HAZARDS IDENTIFICATION

OSHA Regulatory Status This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).
This product is considered an article. 29 CFR 1910.1200(c) definition of an article is as follows: "Article" means a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical (as determined under paragraph (d) of this section), and does not pose a physical hazard or health risk to employees

WHMIS Regulatory Status This product is not considered hazardous by the Canadian Hazardous Products Regulation SOR/2015-17
Continuous Filament Glass Fiber (CFGF) Products are manufactured articles. The definition of manufactured article given by the Canadian Hazardous Products Act R.S.C., 1985, c. H-3 is: any article that is formed to a specific shape or design during manufacture, the intended use of which when in that form is dependent in whole or in part on its shape or design, and that, when being installed, if the intended use of the article requires it to be installed, and under normal conditions of use, will not release or otherwise cause an individual to be exposed to a hazardous product

Label elements

The product contains no substances which at their given concentration, are considered to be hazardous to health

Hazards not otherwise classified (HNOC) Not applicable

Other Information

As manufactured continuous filament glass fibers are non-respirable. May cause temporary skin and mucous membranes itching due to mechanical abrasion effect of fibers. Under normal conditions of use, these products may release dust and non-respirable fibers (Particles Not Otherwise Regulated). Under severe process conditions (e.g. shredding, crushing), these products may release very small amount of respirable particulate, some of which may be fiber-like in terms of l/d ratio (so-called "shards"). See Section 8 for Exposure Limit Data

Under severe processing conditions (e.g. cutting or grinding), these products may release trace amount of airborne crystalline silica dust, part of which may be respirable. See Section 8 for Exposure Limit Data.

Unknown acute toxicity • 67.1% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components

Continuous filament glass fiber 15 - 45 %

Mineral filler 40 - 70 %

Cured acrylic polymer 5 - 25%

Chemical Name	CAS No.	Weight-%	Trade Secret
Continuous filament glass fiber, non-respirable	65997-17-3	15 - 45	*
Ground Calcium Carbonate containing traces of quartz	1317-65-3	20 - 35	*
Aluminum hydrous silicate: Kaolin Clay	1332-58-7	20 - 35	*
Mica (Al, Si)	12001-26-2	0 - 1	*
Sodium Polyacrylate	9003-04-7	0 - 0.3	*
Lauryl sulfate, sodium salt	73296-89-6	0 - 0.01	*

• *The exact percentage (concentration) of composition has been withheld as a trade secret or for covering a group of substantially similar products

Comments The remaining components of this product are non-hazardous or are in a small enough quantity as to not meet regulatory thresholds for disclosure. These components contain no substances or impurities which would influence the classification of this product

4. FIRST AID MEASURES

Description of First Aid Measures

Eye contact

- DO NOT rub or scratch eyes
- Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes
- If eye irritation persists: Get medical advice/attention

Skin contact

- DO NOT rub or scratch affected area
- DO NOT use warm water because this will open up the pores of the skin, which will cause further penetration of the fibers
- Wash skin with soap and water
- Use a wash cloth to help remove fibers
- If fibers are seen penetrating from the skin, the fibers can be removed by applying and removing adhesive tape so that the fibers adhere to the tape and are pulled out of the skin

Inhalation

- Move victim to fresh air
- If symptoms persist, call a physician

Ingestion

- Accidental ingestion of this material is unlikely
- Rinse mouth with water and drink water to remove fibers from the throat

- If symptoms persist, call a physician

Note to physicians

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable properties

- Not flammable. Only the organic part of the product is combustible and could release small quantities of undetermined hazardous compounds in case of major and prolonged heat or fire

Suitable extinguishing media

- Use CO2, dry chemical, or foam
- Water spray or fog

Unsuitable extinguishing media

- None

Specific hazards arising from the chemical

- No information available

Explosion data**Sensitivity to Mechanical Impact** • None**Sensitivity to Static Discharge** • None**Protective equipment and precautions for firefighters**

- As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal precautions**

- Avoid contact with eyes and skin

Environmental precautions

- See Section 12 for ecotoxicology additional information

Methods and material for containment and cleaning up**Methods for containment**

- Prevent further leakage or spillage if safe to do so

Methods for cleaning up

- Use personal protective equipment as required
- Avoid creating dust
- Take up mechanically, placing in appropriate containers for disposal
- Use an industrial vacuum cleaner with a high efficiency filter to clean up dust and fiber contamination

7. HANDLING AND STORAGE

Precautions for safe handling

- Prevent and/or minimize dust formation

Conditions for safe storage, including any incompatibilities**Storage Conditions**

- Store in a manner which will minimize dust generation and accumulation
- Keep product in packaging until use to minimize potential dust generation

Incompatible materials

- None known

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH REL
Continuous filament glass fiber, non-respirable 65997-17-3	TWA: 1 fiber/cm ³ respirable fibers: length >5 µm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m ³ inhalable particulate matter	-	-
Ground Calcium Carbonate containing traces of quartz 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Aluminum hydrous silicate: Kaolin Clay 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Mica (Al, Si) 12001-26-2	TWA: 3 mg/m ³ respirable particulate matter	(vacated) TWA: 3 mg/m ³ respirable dust <1% Crystalline silica TWA: 20 mppcf <1% Crystalline silica	IDLH: 1500 mg/m ³ TWA: 3 mg/m ³ containing <1% Quartz respirable dust
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	(vacated) TWA: 0.1 mg/m ³ respirable dust : (30)/(%SiO ₂ + 2) mg/m ³ TWA total dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

NIOSH REL Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Engineering Controls

Provide local exhaust and/or general ventilation to maintain exposure below regulatory and recommended limits
Local exhaust ventilation should be provided at areas of cutting, milling or other similar processing to remove airborne dust and fibers

Individual protection measures, such as personal protective equipment

Eye/face protection

- Wear safety glasses with side shields (or goggles)

Skin and body protection

- Wear protective gloves
- Wear long-sleeved shirt and long pants

Respiratory protection

- If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations

General Hygiene Considerations

- Wash hands before breaks and immediately after handling products
- Remove and wash contaminated clothing before re-use

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State @20°C

Solid - fiber with diameter larger than 6 micron

Appearance

Coated glass fiber veil

Odor

Organic

Color

Gold

pH value

not applicable

Melting point / freezing point	not applicable
Boiling point / boiling range	not applicable
Flash point	not applicable
Vapor pressure @20 °C (kPa)	not applicable mm Hg @ 20°C
Density VALUE	not applicable
Water solubility	No information available
Autoignition temperature	No information available not applicable
Explosive properties	Not an explosive
Oxidizing properties	Not an oxidizer
Specific Gravity	not applicable
Softening point	> 800°C
Density VALUE	not applicable

10. STABILITY AND REACTIVITY

Reactivity	• No known reactivity
Chemical stability	• Stable under recommended storage conditions
Possibility of Hazardous Reactions	• None under normal processing
Conditions to avoid	• None known
Incompatible materials	• None known
Hazardous Decomposition Products	• Thermal decomposition can lead to release undetermined compounds in small quantities

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

- Continuous filament glass fibers are not respirable according to the World Health Organization (WHO) definition. Respirable fibers have a diameter (d) smaller than 3µm, a length (l) larger than 5µm and a l/d-ratio larger than or equal to 3. Fibers with diameters greater than 3 microns, which is the case for continuous filament glass fiber, do not reach the lower respiratory tract and, therefore have no possibility of causing serious pulmonary disease. Continuous filament glass fibers do not possess cleavage planes which would allow them to split length-wise into fibers with smaller diameters, rather they break across the fiber, resulting in fibers which are of the same diameter as the original fiber with a shorter length and a small amount of dust. Microscopic examination of dust from highly chopped and pulverised glass demonstrated the presence of small amounts of respirable dust particles. Among these respirable particles, some were fiber-like in terms of l/d ratio (so-called "shards"). It can be clearly observed however that they are not regular shaped fibers but irregular shaped particles with fiber-like dimensions. To the best of our knowledge, the exposure levels of these fiber-like dust particles measured at our manufacturing plants are of the order of magnitude between 50 to 1000 below existing applicable limits
- The International Agency for Research on Cancer (IARC) in June, 1987, and in October, 2001 (see IARC Monographs on the Evaluation of Carcinogenic risks to humans – Man-made Vitreous Fibers – Volume 81), categorized continuous filament fiber glass as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify continuous filament fiber glass as a confirmed, probable or even possible cancer causing material

Component Information

Chemical Name	Oral LD50	LD50/dermal/rat - NO UNITS (Wizards mg/kg)	Inhalation LC50
Sodium Polyacrylate	> 40 g/kg (Rat)	-	-

9003-04-7			
Lauryl sulfate, sodium salt 73296-89-6	= 1783 mg/kg (Rat)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization
Germ cell mutagenicity
Carcinogenicity

None known.
None known.
The table below indicates whether each agency has listed any ingredient as a carcinogen. This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
Continuous filament glass fiber, non-respirable 65997-17-3	-	Group 3	-	-
Quartz 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Target Organ Effects
Aspiration hazard

This product does not contain any known or suspected reproductive hazards.
No known effects under normal use conditions.
None under normal use conditions.
No known effects under normal use conditions.
Not applicable.

12. ECOLOGICAL INFORMATION

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Lauryl sulfate, sodium salt 73296-89-6	42: 96 h Desmodemus subspicatus mg/L EC50	-	-

Persistence and degradability • No information available

Bioaccumulation • No information available

Other adverse effects • No information available

13. DISPOSAL CONSIDERATIONS

Disposal of wastes • Disposal should be in accordance with applicable regional, national and local laws and regulations

Contaminated packaging • Do not reuse container

US EPA Waste Number • No EPA Waste Number are applicable
• U122

14. TRANSPORT INFORMATION

DOT	Not regulated
TDG	Not regulated
MEX	Not regulated
ICAO (air)	Not regulated
IATA	Not regulated
IMDG	Not regulated
RID	Not regulated
ADR	Not regulated
ADN	Not regulated

15. REGULATORY INFORMATION

Continuous filament glass fiber products are articles. Articles are exempted from registration or listing under chemicals inventories like TSCA (USA), DSL/NDL (CAN), REACH (EU), ENCS (JP), IECSC (CN), KECL (KR), PICCS (PH), AICS (AUS).

International Inventories

Chemical Name	TSCA	DSL	NDL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Continuous filament glass fiber, non-respirable 65997-17-3	X	X		X		X	X	X	X	X
Ground Calcium Carbonate containing traces of quartz 1317-65-3	X		X	X		X	X	X	X	X
Aluminum hydrous silicate: Kaolin Clay 1332-58-7	X	X		X		X	X	X	X	X
Mica (Al, Si) 12001-26-2	Ex.	X					X	X	X	X
Sodium Polyacrylate 9003-04-7	X	X				X	X	X	X	X
Lauryl sulfate, sodium salt 73296-89-6	X	X		X		X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any

chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Quartz 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ground Calcium Carbonate containing traces of quartz 1317-65-3	X	X	X
Aluminum hydrous silicate: Kaolin Clay 1332-58-7	X	X	X
Mica (Al, Si) 12001-26-2	X	X	X
Quartz 14808-60-7	X	X	X

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

Prepared By	FCs
Creation Date	29-May-2015
Revision Date	29-May-2017
Revision Note	Review of Section 2 and 15

Disclaimer

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use

End of Safety Data Sheet